



W.O.  
Code No.  
13463

. 57  
Vocabulary  
3695

**RESTRICTED**

The information given in this document is not to be communicated, either directly or indirectly to the Press, or to any person not authorized to receive it.

# Vocabulary of Army Ordnance Stores

## SECTION Y1

### Signal Stores—Line, Visual and Sound Reproduction Equipment

**1962**

(Supersedes W.O. Code No. 12611)

By Command of the Army Council,

A handwritten signature in black ink, appearing to be 'R. G. W. J.', written over a horizontal line.

THE WAR OFFICE,  
July, 1962.



V.A.O.S. SECTION Y1

N.A.T.O. INDEX

Item	NATO Class	Page	Item	NATO Class	Page
Adaptor			Bell - continued		
2 point	5850	152	Battery	5805	51
Electrical plug to plug	5935	173	Magneto	5805	51
Transmitter, inset, No.1	5835	50	No. 56 A	5805	51
Valve, No.2	5935	173	Bell, electrical	6350	232
Adaptor assembly, ball-socket L.S.D.S.R.			Bell gong	6350	233
lightweight	5850	152	Bell set	5805	51
Adjuster, spring	5835	50	Bell unit	5805	52
Ammeter	6625	230	Belt		
Amplifier			Driving	5835	135
A.F.	5805	50	Endless	5835	135
Apparatus, L.S.	5830	126	Lineman, safety	4240	32
Ardenite type 615	5830	126	Reel, cable	5465	298
Comolete, apparatus, L.S.	5830	127	Binder	5995	252
Field telephone	5805	51	Block		
Portable, public address	5830	127	Bearing, A.C.L.	3920	13
Amplifier and loudspeaker	5830	127	Bearing, chain wheel	3920	16
Apparatus			Connection	5835	135
Aerial signalling	8345	297	Telephone, protector	5920	164
Cable laying	3920	16	Terminal	5940	185
L.S.	5830	127	Board, terminal	5940	136
Arm			Bobbin	6350	233
4 Way	5975	243	Bolt	5305	35
Bracket, support	3920	17	Arm	5335	35
Iron	5975	242	Tie	5335	36
Lazy tong, No.1	5835	51	Box		
Multi-air line	5975	242	Cable laying equipment	3920	18
Pickup	5835	135	Generator CN	5835	52
Sound reproducer	5835	135	Index, field	7520	292
Stay, complete, A.C.L., No.11	3920	17	Junction	5975	243
Steel channel	5975	242	No.1, telephone set F.	5835	52
Swinging	5835	135	Spore battery	6140	277
Switch	5835	135	Spare cell, large	6140	277
Traverse, cutter head	6940	291	Spare parts	5850	153
Wood	5975	242	Terminal, signal office	5940	187
Armature			Brace, bracket	5975	243
Bell	5805	51	Bracket		
Buzzer	6350	281	Extension	5975	243
Microphone	5965	204	G.P.O. type	5975	243
Pickup	5835	135	Mounting	5835	52
Relay, No.A 12/3	5945	190	No. 15	5305	53
Assembly, for pillars, distribution	6110	275	Telephone	5835	53
Attenuator	5905	161	Brake action, complete	5835	135
Bags, Waterproof			Brake assembly	5835	100
Carbon protector	5910	243	Brake, complete	5835	135
Connectors	5935	173	Brake, relay assembly	5835	130
Band, brake	2530	13	Bridge, metal, No.1, neckband	5965	204
Bar			Brush	5977	251
Carrying	3920	17	Bush		
Controlling, rocking arm, A.C.L.	3920	17	Cable ring	5975	243
Diagng	5120	32	Oillite, special	5835	170
Finger, pressel switch	5835	51	Screwed, No.1	5935	173
Barrow, drum, W.D.	3920	17	Button		
Battery-unit	6140	277	Buzzer switch, telephone sets, F	5930	130
Bearing, detachable	3920	13	Re-wind lever	5930	107
Bearing unit	3130	13	Start/stop	5930	107
Bell			Buzzer	6350	293
3-5 ohms. No.1	5820	125	Buzzer housing	6350	284
			Cable, Bowden type	5835	106
			Cable layer, underground	3995	15
			Can, storage	3335	136

## V.A.O.S. SECTION Y1

## N.A.T.O. INDEX - continued

Item	NATO Class	Page	Item	NATO Class	Page
Cap			Coil - continued		
Brush-holder	5805	53	Induction	5950	199
Electrical	5965	205	1/SCO/278	5805	56
Lamp	6250	280	Repeating	5950	201
Lampholder	6250	280	Telephone induction	5950	201
Rubber sealing	5805	53	Collar		
Capacitor	5910	163	Spindle	3920	18
Capping	5805	53	Steel	5835	137
Capsules, microphone	5965	205	Collet	5340	46
Carbon protector	5975	244	Concentrator	5805	56
Carrier			Condenser	5910	163
Armature, B'	5805	53	Cone, loudspeaker	5965	205
Cable pack	5975	244	Connector	5995	252
Cartridge, sound reproducer	5835	137	Superposing unit	5935	173
Case			Connector, assembly	5935	173
Accessory, filled, test equipment, CB exchange	5805	53	Connector and terminal assembly	5995	252
Amplifier, complete	5830	128	Console, control	5830	128
Carrying	5820	126	Contact		
Coil and condenser	5805	54	Fixed, switch,		
Distribution	5805	54	transmitter, breast	5805	56
Metal, spare bulb, No.1	6250	280	Plunger switch	5850	153
Metal, spare fuse, No.1	5920	104	Side spring, micro.	5965	206
Microphone, hand	5965	205	Contact assembly	5965	206
Moulded, microphone, hand	5965	205	Container, empty, No.1 Wire recording	5835	137
Nos. 30, 31 and 54	5805	54	Control, sound, recorder, reproducer	5835	137
Parts	5805	54	Control unit	5830	129
Receiver, I.T.E.	5965	205	Cord	5995	262
Receiver, watch	5805	55	Cord assembly electrical	5995	274
Rubber, microphone	5965	205	Cordage, instrument	6145	278
Spare parts	5835	137	Core, coil	6350	284
Telephone	5805	55	Counter	5999	275
Telephone attachment headgear	5805	55	Counter, electrical	6680	290
Test D8352	6625	286	Coupling, brake	3920	19
Wood	5805	55	Cover		
Chain	5975	245	Assembly, Vibrator	5805	57
Chair, ringing	5985	251	Back, receivers, watch	5965	206
Choke			Battery	6135	277
A.F.	5950	199	Bell	5805	57
Minifon recorder	5835	137	Buzzer, No.18	6350	285
R.F.	5999	275	Cord, moulded	5995	275
Circlip DIN799	5835	137	Dial	5805	57
Clamp	5975	245	Dustproof, relay	5945	190
Climber, pole	8465	298	Electrical relay	5945	191
Climber, tree	8465	299	Erase, head	5835	137
Clip			Finger, pressel switch	5805	57
Bonding	5975	245	For blocks, terminal	5940	187
Disc, retaining	5835	137	For socket mouthpiece	5805	57
Microphone, hand	5965	205	Front	5805	57
No. 7	5975	245		5830	129
Pad, receiver, Watch J	5965	205		5965	206
Pole	5975	245		5920	164
Retaining	5340	46	Fuse-mounting		
Securing cover	5965	205	Holder, No.1. spare bulb	6250	281
Wire leader	5835	137	Housing	5835	138
Clocks	6645	289	Inner	5830	129
Clutch	5835	137	Insulator	5970	239
Coil			Jack	5805	57
Bridging	5805	55	Label, celestoid	5805	57
Heat	5805	55	Lamp	5805	57
Hum, recording unit	5835	137	Latex	5965	206
			Microphone	5965	206



## V.A.O.S. SECTION Y1

## N.A.T.O. INDEX - continued

Item	NATO Class	Page	Item	NATO Class	Page
Cover - continued			Extractor	5805	61
Moulded, telephone sets	5805	58	Eye-bolt, microphone, hand	5965	209
No's. 1, 2 and 8	5965	207	Eye-piece, rubber	5850	153
Plug	5935	173			
Potentiometer	5905	162	Fanning strip	5805	61
Recording head, mu-metal	5835	138	Fasteners		
Relay	5945	191	Cord	5975	246
Rubber	5935	174	Jack	5935	174
Stile, bar	5805	58	File, switchboard, Visible index	7520	292
Switch, loudspeakers, telehone	5930	167	Filter	5850	153
Switch, S.P.	5930	167	Flask	7510	291
Terminal box	5940	188	Floor bar assembly	5805	61
Terminal case, transmitter breast	5805	58	Follower, wire guide steel	5835	139
Cradle	5805	58	Foot control	5805	61
Cross-piece, frame	3920	19	Frame		
Crutch, stay	5975	246	A.C.L.	3920	20
Cup			Adapting, A.C.L.	3920	20
Lock	5805	58	Cover, finger, pressel switch	5805	62
Metal	5805	59	D. and P.	5835	63
Deflector, sound L.S.	5830	129	I.D.400 line, equipped	5835	62
Demagnetiser	5950	201	M.D.400 line equipped	5835	62
Desk, stand, microphone	5305	59	Notice	5835	62
Dial, automatic	5805	59	Supporting	3920	21
Diaphragm	5805	59	Frame assemblies		
	5965	207	Microphone and receiver	5965	209
Disc			No. 1 telephone, hand	5835	62
Amber	5850	153	Front, projector	5850	153
Baseboard	5805	59	Fullerphone	5805	63
Green	5850	153	Fuse	5335	139
Identification	5930	167		5920	164
Insulating	5965	207	Fuse mounting	5920	165
	6250	281	Fuse unit assembly	5835	139
Lampholder	6250	281			
Recording	5835	138	Gasket	5330	45
Ruby	5850	153	Gauge, arm	5210	35
Door	5805	59	Gear, steel spur	3920	21
Dowel, brass	5805	60	Gear wheel	3920	21
Drawer, metal, boxes, battery-test	5805	60	Generator	5835	63
Drive assembly, timing unit	5835	136	Gimbal	5965	209
Drum	3920	19	Gland, rubber	5835	64
Dynamometer	6695	290	Glass, front	5850	154
			Gloves	8415	298
Ear-cushion	5965	208	Gong, bell	6350	295
Earphone	5965	208	Governor, brush assembly	5835	139
Earphone element	5965	208	Grip		
Ear-piece	5965	209	Cord	5935	174
Earth bar	5835	60	Handle	3920	21
Elderpith	5975	246	Grommet	5325	45
End bar			Guard, gauze	5965	210
Frame MD.	5805	60	Guide, cable	3920	21
No. 1	3920	19	Guide, wire	5835	139
End panel assembly	5805	60	Guy, telegraph pole	5975	246
Equaliser	5835	61			
Equipment cable laying, Variables (30 cwt)	3920	19	Hammer		
Equipment multiphone	5835	61	Bell, magneto	6530	295
Erase head assembly	5835	138	Telegraph sledge	5120	32
Eraser, magnetic	5835	139	Handle		
Extension handle	5965	209	A.C.L.	3920	22
			Bar, carrying, reel cable	3920	22
			Carrying	5835	139
			Chest	6525	210

## V.A.O.S. SECTION Y1

## N.A.T.O. INDEX - continued

Item	NATO Class	Page	Item	NATO Class	Page
Handle - continued			Jack box assembly	5935	175
Chest, No. 1	5805	64	Jack-fastener, driver	5935	175
Cranked	3920	22	Jack plug	5835	139
Flush type	5805	64	Jack, Socket assembly	5835	139
Generator	5805	64	Jumper	5975	247
Key	5930	167	Key		
Lamp, with S.P. switch	5850	154	Draw Vice	5805	69
Lever, brake	3920	22	Mouthpiece	5805	69
Lifter, pole	3920	22	No.	5805	69
Microphone	5965	210	Rectangular	3920	23
Stamp, dating	7520	292	S.C.	5805	72
Telephone	5805	65	Signalling	5805	72
Winding	3920	23	Tension ratchet	5805	72
Handle assemblies			Keyboard end piece	5805	67
Bar, carrying, lightweight	3920	21	Key-mountings	5805	66
No. 8	5805	64	Key-plate, filler	5805	69
Handset	5965	210	Keysender	5805	73
Head			Knob		
Cutter, B B C type A	5835	139	Clutch operating	3920	23
Tripod, threaded	5850	154	Control, No.1	5805	73
Head-band	5965	211	Painton type K20	5805	73
Headset	5965	212	Switch, telephone No.1	5805	73
Hellograph	5850	154	Telephone key switch	5930	166
Hinge	5805	66	Wood	3920	23
Holder			Knuckle	3920	24
Bulb	5850	155			
Label	5805	66	Label	5805	73
Lamp, 4 way, No. 1	6250	281	Lacer	5120	32
Loudspeaker	5965	213	Ladder	5440	47
Microphone	5965	213	Lamp, signalling	5850	156
No. 1 spare bulb	6250	281	Lampholder	6250	281
Sling	3920	23	Latch, retaining, spool		
Strip, designation	5805	67	assembly	5835	139
Testing, No.1, line			Lead	5835	140
units	6625	286	Lead, battery connection	5995	275
Transmitter	5805	67	Leg	5850	157
Hood, canvas, battery clip	5850	155	Base, stand	5965	210
Hook			Lens, indicator light	6210	279
Anchoring	5850	155	Lever		
Cord	5805	67	Brake	3920	24
Guide, large	5805	67		5835	140
No. 1	5965	213	Microphone pressel		
No. 1A	5965	213	switch	5965	216
No. 8	5805	67	Switch	5965	216
Swivel loop	5965	213	Lid		
Hook bolt	5805	67	Battery box	6140	277
Horn	5965	213	Battery compartment	6135	277
Housing, Buzzer	6350	285	Box, terminal and inset	5805	76
Howler	5805	67	Case, amplifier	5830	129
Indicator			Case, test frame	6625	286
Signal, red and green, C.D	5850	155	Case, unit, LS	5830	129
Insert, microphone	5835	139	Front, case, D	5805	76
Inset	5965	215	Microphone compartment		
Installation kit,			control unit	5965	216
electronic	5820	126	No. 3	5805	76
Instructions, Working	7610	293	Projector compartment	5850	157
Insulator	5970	239	Telephone unit, L.S.	5830	129
Iron			Lifter, pole	3920	24
Chimney corner	5805	67	Light indicator	6210	279
Soldering, electric	3439	14	Lighting attachment	5850	157
Terminal	5975	247	Lining, brake band	3920	24
Jack	5935	175			

## V.A.O.S. SECTION Y1

## N.A.T.O. INDEX - continued

Item	NATO Class	Page	Item	NATO Class	Page
Link			Pad		
Connection	5805	76	Ear	5965	227
Sling, carrying	5820	126	Headgear, receivers	5965	227
U	5805	76	Inking	7510	291
Waist belt	5850	157	Valve	5805	81
Wire	5805	76	Panel		
Lock	5805	77	Amplifier, line	6940	291
Loop	5805	77	Component, No.1	5830	130
Loudspeaker	5965	217	Component, No.2	5805	81
Loudspeaker assembly	5965	220	Connection	5850	158
Lug	5940	188	Exchange line	5805	81
			Front	5830	130
Machine, ringing	5805	77	Fuse	5805	81
Main drive assembly, recording unit	5835	140	Indicator	5805	82
Marker, No.12	5805	77	Link and resistor	5805	82
Mattock, telegraph equipment	5120	33	Mains tapping	5830	130
Megaphone	8465	299	Perforated M.S.	5975	247
Megaphone, power	5830	130	Plug	5805	82
Meter	6625	286	Relay mounting, control unit	5830	130
Mica, No. 2	5975	247	Socket	5805	82
Microphone	5965	221	Superposing unit	5805	82
Microphone and receiver headgear assemblies	5965	220	Switch and lamp control unit	5830	130
Microphone element	5965	226	Tag	5805	83
Microphone matching unit	5965	226		5830	131
Miniature reproducer	5835	140	Terminal	5805	83
Motor	5835	140		5830	131
Mounting	5805	77	Pannier, signalling	5895	161
Mouthpiece	5805	79	Partition	5805	83
Mouthpiece, microphone	5965	226	Paster	7690	295
Neckband	5965	227	Peg	5805	83
Needle, playback	5835	140	Pegwood	5975	247
Nuts			Picket, guy	5975	247
Adjusting, brake, band	2530	13	Pick-up	5835	141
Anchoring, hook	5850	157	Pike-Pole	5120	33
Brass, special B.S.W.	5850	157	Pillar		
B.S.F., Wing special	3920	24	Distribution	6110	275
Captive	5850	157	Support, lid	5805	84
Gland	5805	80	Pin		
Hexagon, bell set	5805	80	Brake coupling	3920	25
Knurled	5835	141	Buffer	5965	227
Lock Hexagon	5835	141	Collar	5850	158
Locking	3965	227	Complete with chain	3920	25
Plunger	5805	80	Earth	5975	247
Round, special	5805	81	Hinge	5850	158
Special	5805	81	Locking	3920	25
	5850	157	Plug	5935	180
	5935	180	Positioning wheels	7520	292
Support lid	5805	81	Retaining	3920	25
Whit, B.S. wing, special	3920	24	Securing knob, wood	3920	25
Wing, special	3920	25	Securing wheel	7520	292
Wing, special tapped	5850	157	Steel	5975	247
			Taper	3920	25
Oscillator	5805	81	Toggle	3895	15
			Plate		
Packer			Back, deflector, sound	5965	228
Frame, front	5850	158	Backing	5805	85
Metal	5850	158	Base	5805	85
Wood, spare battery box	5850	158	Battery instruction	5805	85
			Bearing	3920	26
			Buzzer fixing	5805	85
			Cableguard	5805	85

## V.A.O.S. SECTION Y1

## N.A.T.O. INDEX - continued

Item	NATO Class	Page	Item	NATO Class	Page
Plate - continued			Rack	5805	94
Circuit diagram	5805	85		5830	132
Clamp	5965	223		6625	287
Connection	5805	85	Rack, Cable, interior	5975	248
Contact, buzzer	6350	285	Rail		
Cover	5805	86	Foot C.B.exchange	5805	95
Designation	5805	86	Guard	5805	95
Diagram	5805	87	Ratchet, stainless steel	5835	143
Door assembly	5805	88	Ratchet and tongs	5805	95
Dowel	5805	88	Receiver		
Earth	5805	88	Bell, No. 1A, 60 ohms	5805	96
	5975	247	Headgear	5965	228
Engraved	5805	88	Inset	5965	232
	5830	131	Watch	5965	233
	5940	188	Recorder	5835	143
Escutcheon	5805	89	Recorder-reproducer set		
Flush, No. 1	5805	89	sound	5835	144
Front, fixing	5965	223	Recording head assembly		
Instruction	5805	89	No. 1	5835	146
	5850	158	Rectifier	6130	276
Insulating	5805	90	Reel, sound recording tape	5835	146
Lid corners	5805	91	Reeling machine, cable, hand	3895	15
Lock	5805	91	Reflector, projector	5850	159
Modification record	5905	301	Relay	5945	191
Moulded	5975	247	Relay set	5945	199
Mounting	5805	91	Resistance assembly 4		
	5965	228	ohms, No. 1	5905	162
Mounting, relay	5945	191	Resistor	5905	162
Name, No. 31	5805	92	Rheostat, T	5905	163
Nos. 6 and 96	5805	92	Ring		
Protection	5805	92	Cable	5985	251
Retaining	3920	26	Clamping, cover, switch	5965	233
	5805	92	Inner, microphone, M.C	5830	132
Securing	5805	92	Insulator	5970	241
Spring, retaining	3920	26	Jumper	5975	248
Stile cover	5805	92	Locking, receiver	5965	234
Terminal	5805	93	Rubber	5805	96
Plate and cleat assembly	5805	84	Securing, lampholder, No. 1	6250	281
Pliers	5120	33	Ringer, telephone	5805	96
Plug	5935	180	Rod		
Plunger			Earthing	5975	249
Clutch	3920	26	Handle, projector, No. 1	5850	159
Microphone, pressel switch	5965	228	Pruning	3750	14
Mk. 1	5805	93	Restoring assembly, No. 1	5805	96
Spindle	3920	26	Retaining	5850	159
Pointer and bush assembly	5835	141	Screwed	5805	96
Pointer and knob assembly	5835	141	Stay	5805	97
Pole	5510	47	Runway	5805	97
Post, picket, multi-airline	5975	248	Runway assembly	5805	97
Potentiometer, No. 1	5905	162	Saddle	5975	249
Pouch web	3920	27	Satchel	5805	97
Power Unit	6625	287		5830	132
Probe	6625	287	Screen	5850	159
Protector			Screws	5305	37
H.C. and T.	5805	94	Screwdriver	5120	33
Reflector	5850	159	Screw-eye	5305	36
Rubber	5965	228	Section	5805	92
Protector and fuse	5805	94	Shock absorber	5830	132
Public address set	5830	131	Shoe, clutch release	3920	27
Pulley	5835	142	Shrouds, metal, No. 1	5965	234
Pulley and bush assembly	5835	142	Silk	8310	297
Pulley-weight	5805	94	Sleeve, rubber	5970	241
Push Rod	5835	143	Sleeve, set, identification	5340	46

## V.A.O.S. SECTION Y1

## N.A.T.O. INDEX - continued

Item	NATO Class	Page	Item	NATO Class	Page
Slide-rule,stay	7520	292	Spring		
Sling			Contact - continued		
Box, spare battery	5850	159	Upper	5805	100
Carrying	3920	27	Fixed	5805	100
Case, carrying	5850	159	Flap, unit C	5805	101
Socket			Flat	5935	185
1 SSO/14	5935	184	For sockets, mouthpiece	5805	101
4 point	5935	134	For spindle, bracket, plunger	3920	29
10 point	5935	184	Helical, extension	5340	46
12 point	5935	184	Leaf	5805	101
Auto-dial, No.1	5805	99		6625	237
Coupling	5965	234	Lever, micro	5965	236
Electrical	5935	184	Microphone	5965	236
Key, signalling	5850	159	Moving, tele, hand	5805	101
Moulded, switchboard, magneto, 10 line (W.D)	5805	99	Phos. br.	5835	147
Mouthpiece	5805	99	Plunger	3920	29
Plunger	3920	27	Recording headguide	5835	148
Socket assembly, No. 1, link, U	5805	98	Reflector	5850	160
Spacer, brass	5835	146	Restoring	3920	30
Spade, rabbiting	5120	33		5805	101
Spanner	5120	33	Retaining, front	5850	160
Spike	5850	160	Steel	5835	148
Spindle			Top	5805	101
A.C.L.	3920	27	Spring assembly	5835	149
Brake-coupling	3920	28	Sprocket	3920	30
Complete with brake housing, No.2	3920	28	Stamp	7520	292
Complete with handle, winding	3920	28	Stand		
Drum	3920	28	Lamp or heliograph, A. Mk. 3	5850	161
Handle	3920	29	Microphone	5965	237
Insulator	5975	249	Stay block, medium	5510	49
Spindle and idler assembly	5835	147	Step, pole	5975	250
Spindle assembly	5835	146	Stethophone	5835	149
Splicer, tape, sound recording	5835	147	Sticks, crook	5120	34
Spool	5835	147	Stiffener	5965	237
Spoon, digging	5120	34	Stile casing	5805	101
Spring			Stile cover assembly	5805	101
Battery box	5805	99	Stirrup		
Bottom	5805	99	Climber tree, lightweight	8465	299
Brake release	3920	20	Headband, web	5965	237
Buffer, capsule case	5805	99	Stop clutch release	3920	30
Capsule, centre contact	5805	99	Stop, Finger S.S.	5835	149
Centre contact	5965	235	Strainer, multi-airline	5975	250
Clamping	5835	147	Strap		
Contact			Arm, multi-airline	5975	251
Bulb-holder	5850	160	Bracing	3920	30
Capsule case	5805	99	Carrying	8465	299
	5965	235	Chin	8405	297
Double, microphone, hand	5965	235	Climber's pole	8465	300
Fixed	5805	100	Connection	5805	102
	5965	235	Double climber, tree, lightweight	8465	300
LH, microphone hand	5965	235	Headgear, retaining control units	5830	132
Lower	5965	235	Metal	5805	102
Moving	5805	100	Microphone, hand, power, No. 1A	5965	237
	5965	235	Retaining	3920	31
Nickel silver	5835	147	Shoulder	3920	31
R.H., microphone, hand	5965	235		5850	161
Side, microphone, hand	5965	236	Single, climber, tree, lightweight	8465	301
Single, microphone, hand	5965	236			

## V.A.J.S. SECTION Y1

## V.A.T.O. INDEX - continued

Item	NATO Class	Page	Item	NATO Class	Page
Strap - continued			Test frame	6625	289
Spindle, retaining	3920	31	Thimble	5805	119
Waist	3920	31	Tie-bar, mountings, runway, frames 1.D	5805	120
Strip			Tightener	5805	120
Bottom, A, front, No.1	5805	102	Timing assembly, recording unit	5835	151
Connection	5805	102	Tongs	5805	120
Contact, buzzer	5805	105	Tools, stay splicing	5120	35
Designation	5805	105	Training set, interference	6940	291
Fanning	5805	106	Transformer	5950	201
Gauze, M.C.	5965	237	Transmitter	5805	120
Jack, 70A	5805	106	Tube	5805	120
Metal, slotted	6625	237	Uniselecto	5805	122
Terminal	5805	106	Units		
Stud, locating, brake	3920	31	Access jack	5805	122
Stud, plain	5307	43	Alarm	5805	122
Stylus	5835	149	Amplifier and loudspeaker	5830	134
Superposing unit	5805	107	Amplifying, No.23D	5805	123
Support			Energising, L.S. telephone	5830	134
Bearing block	3920	31	Generator, answering 20 circuit	5805	123
Cable	6625	287	Line	5805	123
Rail, guard	5805	108	Loudspeaker	5830	134
Switch	5930	169	Microphone, throat, low level	5965	238
Switchboards	5805	108	Multiple, 400 line	5805	124
Table, telegraph, Mk.1	5805	111	Receiver, watch J	5965	238
Tablet, Test, E.C. 1144	6625	288	Switchboard, magneto, multiple 360 line	5805	124
Tag			Telephone	5805	125
For cords, telephone headgear	5965	237	Transfer, intercom	5830	134
Strain, cord	5965	237	Transformer, microphone	5950	204
Tail, insulated	5805	111	Transformer, Rectifier	5950	204
Tape			Vibrator, ringing	5805	125
Driving, spring steel	5835	150	Vice, draw, No.2	5805	125
Magnet recording	5835	150	Volume control	5835	151
Rubber	9320	301	Washers	5310	43
Sound recording	5835	150	Web	8305	290
Telegraph	5805	111	Wheel		
Telephone	5805	111	Gear	5835	151
Hand	5805	113	Phos.Br. rubbered tyred	5835	151
Head and breast	5805	117	Type	7520	293
Intercom	5805	118	Worm	5835	151
Loudspeaking	5830	132	Wiper	5805	125
Tracker	5805	118	Wire, recording, $\frac{1}{2}$ lb spools	5835	151
Telephone attachment, headgear, double	5965	238	Worm, stainless steel	5835	152
Telephone set	5805	118			
Telephone units, L.S.	5830	134			
Terminal	5940	188			
Terminal board	5940	189			
Terminal box	5940	190			
Terminal strip	5940	190			
Tester	6625	288			

## ABBREVIATIONS

A.C.L.	Apparatus, cable laying	L.S.	Loudspeaker/loudspeaking
A.F.	Audio frequency	L.S.D.S.R.	Lamp, signalling, daylight, short range
Al.	Aluminium	mA	Milliamperes(s)
ampfr.	Amplifier	maq.	Magneto
App.	Apparatus	M.C.	Moving coil
assy.	Assembly	M.D.	Main distribution
aux.	Auxiliary	M.E.S.	Miniature Edison screw
B.A.	British Association	Met.C.	Metal case/cased
B.P.	Breast plate	M.I.	Malleable iron
Br.	Brass	Mic.	Microphone
B.S.	Bright steel	M.R.	Mechanically restored
B.S.F.	British Standard Fine	M.S.	Mild steel
B.S.P.	British Standard Pipe	mtg.	mounting
B.S.W.	British Standard Whitworth	Ni.Sil.	Nickel silver
cap.	Capstan	N.P.	Nickel plated
C.B.	Central battery	N.P.D.	Nickel plated, dull
C.B.S.	Central battery signalling	O.D.	Outside diameter
cct.	Circuit	P.A.	Public address
C.D.	Coast defence	P.A.B.X.	Private automatic branch exchange
ch.hd.	cheese head	P.B.X.	Private branch exchange
C.I.	Cast iron	P.M.	Permanent magnet
C.L.	Cable laying	P.M.B.X.	Private manual branch exchange
con.	Connector	porc.	Porcelain
cpr.	Copper	P.V.C.	Polyvinyl Chloride
c/s	Cycles per second	resis.	Resistance
C.T.	Carrier telephone	R.F.	Radio frequency
D.and P.	Distribution and protection	R.T.	Radio telephony
db.	Decibel	S.C.	Single current
diag.	Diagram	Secy.	Secondary
enam.	Enamelled	S.I.	Standard inset
exch.	exchange	sig.	signal/signalling
F.and F.	Field and fortress	Sound P	Sound powered
F.S.	Flash spotting	S.P.	Single pole
fil.	filister	S.R.B.P.	Synthetic resin bonded paper
Gen.	Generator	S.S.C.	Single silk covered
Galv.I.	Galvanized iron	S.U.R.	Supply units rectifier
H.C.	Heat coil	S.W.G.	Standard wire gauge
H.C.and T.	Heat coil and test	tel.	telephone
hdgr.	Headgear	teleg.	telegraph
helio.	Heliograph	t.p.i.	threads per inch
H.R.	High resistance	T.R.S.	Tough rubber sheathed
I.D.	Inside diameter or Intermediate distributor	U.C.	Universal call
I.D.F.	Intermediate distribution frame	V.F.	Voice frequency
inst.	Instrument	V.R.	Vulcanized rubber
I.R.	India rubber	Whit.	Whitworth
I.T.B.A.	Inset, telephone, balanced armature	W.S.	Wireless station
I.T.E.	Inset, telephone, equalized	W.T.	Wireless telegraphy/tele- phony
K.c/s	Kilowatt cycles per second	xform.	transformer
L.B.	Local battery	ohm	ohm
L.P.	Long playing	μF	micro-farad
L.R.	Low resistance		

VOCABULARY OF ARMY ORDNANCE STORES-SECTION Y1

General instructions; see V.A.O.S. and C.C.N. Preface, 1960 (W.O. Code No. 12862)

Additional Copies

1. Indents (A.B. 222) for additional copies of V.A.O.S. or C.C.N. publications and/or amendments thereto will be addressed, according to the location of the formation or unit (see Cat. of W.O. Publications, Pt. 1, 1957 (W.O. Code No. 12123), para. 6) as follows:-

All commands at home	Officer i/c Stationery Section, R.A.O.C., of respective command.
Abroad	To formation or district R.A.O.C. representative.

(Where no formation or district R.A.O.C. representative exists, and subject to any local instructions, to Army Publications, Kimber Road, Wandsworth, London, S.W.18.)

Amendments

2. Amendments to the V.A.O.S. sections will be published as replacement pages.
3. This revised edition embodies amendments up to and including amendment No. 3
4. Items introduced since the last amendment to previous edition are indicated by an asterisk in column 1.

Obsolescent and obsolete items

5. Obsolescent items are shown in italics.
6. Items declared obsolete since last amendment to previous edition are listed in Appendix A (see page 302).

NATO cataloguing system

7. The NATO system of cataloguing utilizes a four digit coding structure, the first two digits identify the NATO group and the second two digits the class within that group. A 13 digit catalogue number, including these four digits, is utilized to indicate and identify NATO catalogued items and is explained in V.A.O.S. and C.C.N. Preface, 1960 (W.O. Code No. 12862).

INSTRUCTIONS FOR DEMANDING WARLIKE STORES

8. The stores catalogued in this V.A.O.S. section are provided under Vote 7F.
9. Indents for stores will be prepared on AFG 982E (Carbac) (combined demand and issue voucher) and submitted in accordance with Equipment Regulations, Pamphlet No. 2 (W.O. Code No. 13104); not more than one item will be demanded on each set of A.Fs.
10. It is important that the V.A.O.S. section, correct item name, catalogue number, and quantity of item required be clearly stated as the following example shows:-

V.A.O.S. Section Y1	Cat. No.	Quantity required
Item name or designation		
BLOCK, Bearing, A.C.L., No. 11	Y1/YA 7829	12

11. In cases of urgency, stores may be demanded by signal, telegram, or letter, when more than one item may be included in the demand; in such cases a shortened version of the item name may be quoted together with the full catalogue number and the quantity/ies required: Example:-FOLLOWING ITEM URGENTLY REQUIRED STOP BLOCK BEARING Y1/YA 7829 QUANTITY TWELVE



## SECTION Y1

## GROUP 25-VEHICULAR EQUIPMENT COMPONENTS

## CLASS 2530-VEHICULAR BRAKE, STEERING, AXLE, WHEEL, AND TRACK COMPONENTS

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6086	BAND, Brake No. 1	M.S.strip, No.16 S.W.G., with brake lining 1 ft.3 in. x 1/8 in. riveted to it; terminated at one end by M.S.rod 5/16 in. dia., threaded 5/16 in. B.S.F.; used on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 2772	NUT, adjusting, brake band	1. 1/2 in. x 1.3/16 in.; M.I. wing nut, B.S.F., 5/16 in.	single	C 4270
Y1/3130-99-942-1/44	BEARING Unit	<p style="text-align: center;">GROUP 31 - BEARINGS</p> <p style="text-align: center;">CLASS 3130 - BEARINGS MOUNTED</p> Plain flange, housing, self aligning, designed for 1/4 in. dia., shaft, 2 bolt holes 3/4 in. dia., 3/4 in. between centres, top bearing for capstan, rewind and take-up motors; (old cat. No. Y1/YA 8983)	single	

SECTION Y1

GROUP 34--METALWORKING MACHINERY

CLASS 3439--MISCELLANEOUS WELDING, SOLDERING, AND BRAZING SUPPLIES AND ACCESSORIES

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7343	IRON, Soldering, electric, 50V.	G. P. O. patt. weight of cpr. bit 1 oz.	single	C 4270
Y1/YA 1390	Pruning	W. D. threads are 1. 1/32 in. dia., 14 t. p. i. (3/4 in. B. S. P. thread) G. P. O. threads are 31/32 in. dia., t. p. i. (non-standard)	single	C 4270
Y1/YA 1389	Complete	Consisting of 1 holster; 1 hook; 1 line; 4 rods (with couplings); 1 saw; 1 shears	set	A 4770
Y1/YA 1395	Complete, G. P. O.	Consisting of 1 holder and 4 rods G. P. O. patt.	single	C 4270
Y1/YA 1396	Leather	M. S. socket; W. D. thread	single	A 4770
Y1/YA 1391	Hook, G. P. O. patt.	M. S. socket; G. P. O. thread	single	C 4270
Y1/YA 1397	Line	Sash line plaited, 1 in. circumference, 19 ft. 6 in. long, with raw hide thong 5 ft. long	single	A 4770

GROUP 37--AGRICULTURAL MACHINERY AND EQUIPMENT

CLASS 3750--GARDENING IMPLEMENTS

R0D

Y1/YA 1398	Rod Set	Bamboo, length 5 ft. with Gm. couplings Consisting of 1 each, top lengths and No. 1, 2, 3; W.D. thread	set	A 4770
Y1/YA 1399	Set, G.P.O.	Consisting of 1 each, top lengths and No. 1, 2, 3; G.P.O. thread	set	C 4270
Y1/YA 1400	Top length	Top length with male and female sockets and iron strap with eye; W.D. thread	single	A 4770
Y1/YA 1401	No. 1	Second length with male and female sockets; W.D. thread	single	A 4770
Y1/YA 1402	No. 1, G.P.O. patt.	G.P.O. thread	single	C 4270
Y1/YA 1403	No. 2	Third length with male and female sockets; W.D. thread	single	A 4770
Y1/YA 1404	No. 2, G.P.O. patt	G.P.O. thread	single	C 4270
Y1/YA 1405	No. 3, G.P.O. patt	G.P.O. thread	single	C 4270
Y1/YA 1406	Saw	Steel; socket, W.D. thread	single	A 4770
Y1/YA 1407	Shears	Steel; socket, W.D. thread	pair	A 4770

GROUP 38 - CONSTRUCTION, MINING, EXCAVATING, AND HIGHWAY MAINTENANCE EQUIPMENT

CLASS 3895 - MISCELLANEOUS CONSTRUCTION EQUIPMENT

*Y1/3895-99-901-2162	CABLE LAYER, Underground	Reel and dispenser pack type 10 in. max. laying depth, 1 in. min. I.D. of planting tube, two wheel trailer medium	single	
*Y1/3895-99-901-3901	PIN, Taggle, eye	Steel; 3/8 in. dia. shank, 3.25/32 in. grip lg. used on cable layer, underground (Y1/3895-99-901-2162)	single	
*Y1/3895-99-901-1033	REELING MACHINE, cable hand		single	
*Y1/3895-99-901-3232	No. 14	3 ft. 4 in. lg. x 2.1/2 in. w. Removable reels; rigid frame (Old Cat. No. Y1/YA 12367) (I.S.P.L. 13486)	single	

## SECTION Y1

 GROUP 39-MATERIALS HANDLING EQUIPMENT  
 CLASS 3920-MATERIALS HANDLING EQUIPMENT, NON-SELF-PROPELLED

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5807	APPARATUS, Cable laying No. 2, Mk. 2	(IL 2526)	single	C 4270
Y1/YA 6003	No. 3 Mk. 2	3 ft.6 in.x 2 ft.x 1 ft.5 in.M.S.rectangular box-shaped frame; fitted with geared chain-driving device; brake gear; detachable bearing, handle, sleeve and spindle; issued with frame, supporting Mk. 2; 1 guide, cable; for use with drum, cable No. 5 (Sec.Y3) and reel, cable, No.1, Mk.2 (Sec.Y3); for laying and reeling up cable, elec. for components, see C.I.E.M.E. list E.S.340 (IL 11354)	single	C 4270
* Y1/YA 12580 Y1/YA 5244	Mk. 3 No. 6A	18 in.x 16 in.x 13 in.; port. 1 man cable-laying app. M.S. frame-work with shoulder and bracing straps (IL 2541)	single	C 4270
Y1/YA 7037	No. 9	For use on Scout cars; holds one reel, cable, No.1, Mk.2 (Sec.Y3)	single	C 5687

Y1/YA 7475	No. 10	For use by assault troops and carried on the arm; holds 1 reel, cable, No.4(Sec.Y3) (IL 2862)	single	C 5687
Y1/YA 7682	No. 11	3 ft.4in.x 3 ft.x 7 in. when closed; 2 M.S. tubular frames, "H" shaped, hinged together, collapsible for transit purposes; fitted with spindle, winding handle, brake ass., blocks bearing; issued with 2 slings carrying A.C.L. No. 11 (IL 2930)	single	C 4270
Y1/YA 7834	ARM			
Y1/YA 7832	Bracket, support Stay, complete, A.C.L.No.11	8 in.x 3/4 in.x 9/16 in. M.S.; used on A.C.L.No.11 Fabricated steel arm; one end fitted with hook and spring, the other end forked; used on A.C.L. No. 11	single single	C 4270 C 4270
Y1/YA 9695	BARROW, Drum, W.D., Mk.4	M.S. frame with pneumatic tyred wheels; braking gear, hand-controlled chain drive and free wheel device. For components, see I.E.M.E. list E.S. 2526 I.L.	single	C 6816
Y1/YA 0125	BAR Carrying Drum, cable, No.5 and No.8	Steel tubular; with 2 suspending links, spring pin, chain with 2 S.hooks and winding handle; includes spindle	single	A 5926, B 4802
Y1/YA 3064	Spindle	18.21/32 in.x 1 in.dia.; M.S. with 2 collars	single	B 4111, B 4802
Y1/YA 3347	Collar	M.S., with set screw	single	B 4802
Y1/YA 7532	Lightweight, drum, cable, No.5	3 ft.6 in.x 1 ft.8 in.x 5.1/2 in.; M.A. tubular framework with handle at each end; fitted with spindle assy.; crank assy.; bearing assy. and straps	single	C 4270
Y1/YA 6900	Reel, cable, No.1, Mk.2	16.1/4 in.x 1 in.dia.; consisting of handled stem sleeve and loose handle	single	C 4270
Y1/YA 6928	Controlling, rocking arm, A.C.L., No.8	22 in. x 1.1/4 in. x 1/4 in. M.S., with slot 4.1/2 in. x 7/16 in.	single	C 4270

## SECTION Y1

## CLASS 3920-MATERIALS HANDLING EQUIPMENT, NON-SELF-PROPELLED - continued

Cat No.	Item name or designation	Item description or detail	Unit of Issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0053	BEARING, Detachable	M.S.strip 1/4 in.x 1.1/2 in.shaped square,fitted	single	B 2812 C 4270
Y1/YA 6102	Outer	2 M.S. dowel pins and G.M. bush; used on A.C.L.,No.3 19.1/2 in.x 13.1/2 in.x 1.1/2 in.M.S.bracket; "U" shaped, fitted with 2 M.S.pins and G.M.bush; used on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 7829	BLOCK Bearing, A.C.L.,No.11	M.I. becomes bearing spindle drum bolted to frame with two - 3/8 in.x2.1/4. whit bolts and nuts. Pin and chain attached to retain spindle in bearing	single	C 4270
Y1/YA 3945	Bearing,chain wheel	2 in.x 1.1/4 in.Ø.M.S.fitted with G.M.bush 5/8 in. I.D. used on A.C.L.,No.3, Mk.2	single	C 4270
Y1/YA 2710	BOX,Cable-laying equipment	Used in M.T.vehicles for transporting miscellaneous stores used in connection with cable-laying	single	B 2911
Y1/YA 2711	A	2 ft.3 in.x 1 ft.3 in.x 11.1/2 in.wood;with hinged lid in two parts;fitted with 2 carrying handles; includes 1 tray	single	B 2911
Y1/YA 2343	B	2 ft.1.3/8 in.x 6.1/2 in.wide x 3 in.deep 1 ft.6 in.long x 6 in.wide x 1 ft.deep;wood; lidless,fitted with 2 M.S.supports for hooking on to side of lorry	single	B 2911
Y1/YA 2513	COLLAR, Spindle,No.2	2.1/4 in.dia.x 7/8 in.Ø.M.S.,1 in.square hole,fitted with pin,tapered, 5/16 in.x 2.1/2 in.Mk.4	single	B 3252 C 4270

Y1/YA 6088	COUPLING, Brake	M.S.; used on A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 5891	CROSS-PIECE, Frame	9. 1/4 in. x 2. 1/8 in. x 3/4. ; ash fused on A.C.L., No. 2, Mk. 2	single	C 4270
Y1/YA 7492	DRUM Brake, A.C.L., No. 8	9 in. dia. x 1. 3/8 in. hardwood disc centre hole 13/16 in. dia.; part of spindle, assy; used on A.C.L., No. 8	single	C 4270
Y1/YA 6089	Brake/clutch	5. 1/2 in. dia. x 1. 27/32 in.; C.I. fused on A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 6090	Plunger	6 in. x 1. 1/8 in.; C.I. fused on A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 6142	END-BAR, No. 1	1 in. dia. x 14 in. long; M.S. tube with a M.S. lug driven in one end and a wooden plug driven in flush the other end fused on bars, carrying drums, cable, No. 5, collapsible patt.	single	C 4270
Y1/YA 2511	EQUIPMENT, Cable-laying vehicles (30 cwt.)	Comprising the undermentioned fittings for vehicles (30 cwt.) when utilised for cable-laying	single	B 3341
Y1/YA 2548	Block	Wood; 13 in. x 5 in. overall; for housing spare helves; one per set	single	
Y1/YA 2549	Bracket, Digging bar	3. 3/8 in. x 2. 1/4 in. x in.; metal; to carry one bar, digging; one per set	single	
Y1/YA 2551	Carrier Front, near	For pole, teleg., wood Metal; 36 in. high, with cowl; 23 in. rubber strap and 7 in. rubber buckling pieces; 1 per set	single	
Y1/YA 2552	Front, off	Similar to front, near, but opposite hand; 1 per set	single	
Y1/YA 2553	Intermediate	Metal, 25 1/2 in. high; 2 per set	single	
Y1/YA 2554	Rear	Metal, 36 in. high; with 23 in. rubber strap and 7 in. buckling pieces; 2 per set	single	
Y1/YA 2555	Plate, strap	Metal, 2. 1/4 in. x 1. 1/4 in. for fixing strap, 12 in.; 3 per set	single	

## SECTION Y1

## CLASS 3920-MATERIALS HANDLING EQUIPMENT, NON-SELF-PROPELLED - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 2556	EQUIPMENT, Cable-laying vehicles (30 cwt.) Carrier - continued Rack	Metal plate, 9.3/8 in. x 2.1/4 in. fitted with three clips (1 large, 2 small); 2 per set	single	
Y1/YA 2557	Sticks, crook	Wood block, 12 in. x 3 in. with 14 in. rubber strap and 10 in. rubber buckling piece; 1 per set	single	
Y1/YA 2558	Ring, cable guide	Metal, 1.1/2 in. long, with 2.1/4 in. dia. hole; 1 per set	single	
Y1/YA 2559	Strap, 12 in.	Reinforced rubber, with buckle; 3 per set	single	
Y1/YA 5858	FRAME Adapting, A.C.L., No. 8	17.3/4 in. x 14.5/8 in. x 4.1/8 in. rectangular metal framework (1 in. x 1 in. x 1/8 in. angle); for use with A.C.L., No. 8, when used in lorry or sledge	single	C 4270
Y1/YA 6355	A.C.L., No. 3, Mk. 2	19 in. x 13 in. x 14.1/4 in. rectangular M.S. framework; includes 1 G.M. bush, used on A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 7465	A.C.L., No. 9	11 in. x 8 in. x 9 in. M.S. plate, 11.3/4 in. x 8.1/2 in. x 1/4 in. with 2 triangular M.S. plates, 8.1/2 in. x 9 in. x 1/4 in. welded to it at right angles	single	C 4270



Y1/YA 0058	Supporting, Mk.2	19 in. x 13.1/2 in. x 16.1/2 in. M.S. angle-iron framework; used with A.C.L., No.3, Mk.2	single	B 1081, C 4270
Y1/YA 0059	GEAR, Steel spur, straight, 2.2 in. dia. 12 teeth, No.1	2.2 in. dia. x 1.3/16 in.; M.S. with G.M. bush; to suit roller-chain 1/2 in. pitch x 5/16 in.; used on A.C.L., No.3 and No.3, Mk.2	single	C 4270
Y1/YA 0060	GEARWHEEL	7.3/16 in. O.D. x 2.7/16 in.; M.S., 47 teeth; spindle dia. .624 in.; used on A.C.L., No.3 and No.3, Mk.2	single	C 4270
Y1/YA 6160	GRIP, handle, No.5	4 in. x 1.1/2 in. O.D. x 1/2 in. I.D.; hardwood; used on A.C.L., No.6A, handles	single	C 4270
Y1/YA 0061	GUIDE, Cable	16 in. x 12.7/8 in. x 4.1/2 in.; fabricated from 1.1/2 in. x 1/8 in. M.S. strip; 1 in. x 1 in. x 1/8 in. M.S. angle, and 3/8 in. dia. M.S. rod, to form a triangular-shaped framework that clips to the frame of A.C.L., No.3 and No.3, Mk.2	single	C 4270
Y1/YA 5290	A.C.L., No.6A	7.3/4 in. x 6.1/2 in.; M.S. 5/16 in. dia. rod; bent to fit into clips on the frame, guides the cable on to the drum	single	C 4270
Y1/YA 7458	A.C.L., No. 9	7.1/4 in. x 4 in. x 2.1/4 in.; M.S., consists of an "L" shaped bracket, to which is welded, at one end, a plate 2.1/4 in. dia. x 1/4 in. which has two indentations, and at the other end, one complete helix 3/4 in. dia. of No.6, S.W.G. M.S. rod	single	C 4270
Y1/YA 5894	No.2	Hardwood; otherwise similar to guide, cable, No.1; used on A.C.L., No.2, Mk.2	single	C 4270
Y1/YA 7861	HANDLE ASSEMBLY, Bars, carrying, lightweight	M.S. tube 5/8 in. O.D. x No.12 S.W.G. x 5.13/16 in. long, to which is welded at one end a M.S. collar and boss, and at the other end a M.S. bracket, to this is riveted a spindle complete with hardwood handle which can be moved to horizontal or vertical position	single	C 4270

## SECTION Y1

## CLASS 3920-MATERIALS HANDLING EQUIPMENT, NON-SELF-PROPELLED - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5919	HANDLE A.C.L., No. 6A	Complete assy. consisting of M.S. flat bar 1 in. x 3/16 in. x 5.1/2 in. with tube, 4.1/2 in. long, welded to it at right angles over which is fitted grip, handle, No. 5	single	C 4270
Y1/YA 6941	Bar, carrying, reel, cable, No. 1, Mk. 2	4.1/2 in. x 1 in. O.D. x .425 in. I.D. includes 3 in. of 1/4 in. jack chain, solid link, iron, and 1 split pin 1.1/2 in. x 1/8 in. part of bar, carrying, reel, cable, No. 1	single	C 4270
Y1/YA 0062	Cranked, adjustable, No. 1	9.1/8 in. long when closed; 13.3/8 in. extended; consists of 2 M.S. channels; M.S. spindle and hardwood handle; used on A.C.L., No. 3	single	C 4270
Y1/YA 5021	Levers, brake Horizontal	2 in. long x 1.1/2 in. O.D. x 17/32 in. I.D.; hardwood; used on A.C.L. No. 3 and No. 3, Mk. 2	single	C 4270
Y1/YA 5020	Vertical	1.1/4 in. long x 3 in. dia.; hardwood; centre hole 11/32 in. dia.; used on A.C.L., No. 3 and No. 3, Mk. 2	single	C 4270
Y1/YA 8358	Lifter, pole	G.P.O. patt.	single	C 4270

Y1/YA 7633	Winding A.C.L., No.11	M.S.bar 10.3/4 in. long x 1 in. x 1/4 in., with a M.S. spindle, 4.7/16 in. long x 1/2 in. dia with a hardwood handgrip, to the other end of the bar is welded 2 M.S. square collars and a length of 3/8 in. chain terminated by a split pin	single	C 4270
Y1/YA 5274	No. 1	M.S. bar 8.1/4 in. x 1.1/4 in. x 1/4 in., with wooden handle 5 in. long x 1.3/8 in. dia. used on spindles, special, drum, cable, No.5	single	C 4270
Y1/YA 7404	No. 2	M.S. bar 6 in. x 1 in. x 1/4 in., to one end is welded a M.S. socket 3/4 in. long, at the other end is a hardwood handle 4 in. long x 1.1/4 in. dia. used on bar, carrying, drum, cable, No.5, collapsible patt. and A.C.L., No.8	single	C 4270
Y1/YA 5896	HOLDER, Sling, No.2	Br. clip to which sling carrying can be attached, used on A.C.L., No.2, Mk.2	single	C 4270
Y1/YA 5068	KEY Rectangular, 1/4 in. sq. x 1 in. long	Steel key, engaging with sprockets, driven on barrow, drum, W.D., Mk.4	single	C 4270
Y1/YA 6091	KNOB Clutch operating	3/4 in. O.D. x 1.9/64 in. M.S., 1 end threaded 5/16 in. B.S.F., used on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 5897	Wood, No. 1	1.3/8 in. dia. x 1.9/16 in. beech, with hole drilled through centre to suit 1/4 in. carriage bolt, used on A.C.L., No.2, Mk.2	single	C 4270
Y1/YA 5898	Wood, No.2	2 in. dia. x 2.1/2 in. hardwood, with 25/64 in. dia. hole through centre, used on A.C.L., No.2, Mk.2	single	C 4270

## SECTION Y1

## CLASS 3920-MATERIALS HANDLING EQUIPMENT, NON-SELF-PROPELLED - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7827	KNUCKLE Female, A.C.L., No.11	1. 7/16 in. dia. x 3.3/4 in. long; G.M. ; part of knuckle-joint frame assy.	single	C 4270
Y1/YA 7826	Male, A.C.L., No.11	G.M. ; part of knuckle-joint frame assy.	single	C 4270
Y1/YA 6092	LEVER Brake, horizontal, No.2	11 in. x 1 in. x 3/16 in. W.S. ; slightly cranked ; 3/8 in. dia. hole at one end, at the other rectangular hole 5/8 in. x .438 in. used on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 5017	Brake, vertical	9. 1/2 in. x 1 in. x 3/16 in. W.S. fitted with hardwood handle ; used on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 7619	LIFTER, Pole 12 ft.	G.P.O. patt. ; unhandled	single	C 4270
Y1/YA 6354	LINING, Brake band, No.2	1 ft. 3 in. x 7/8 in. x 1/8 in. ; brake lining includes 9 cpr. rivets ; used on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 7824	NUT B.S.F. Wing, special, 1/4 in.	M.I. wing nut for adjusting spring tension on brake band of A.C.L., No. 11	single	C 4270
Y1/YA 7825	Whit, B.S., wing, special, 5/16 in.	M.I. wing nut for special screw for clamp, tube, tapped 5/16 in Whit.	single	C 4270

Y1/YA 6929	Wing, special, B.S.W., 3/8 in., No.1	M.S.; used on A.C.L., No.8	single	C 4270
Y1/YA 6157	PIN Brake-coupling No. 1	1. 1/8 in. long x 5/8 in. dia.; .323 in. dia. hole 9/16 in. from the end; M.S.; used on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 6158	No. 2	1 in. long x 5/16 in. dia.; 3/32 in. dia. hole 1/2 in. from the end; M.S.; used on A.C.L., No.2 and No.3, Mk.2	single	C 4270
Y1/YA 6938	C/w chain, securing handle A.C.L., No.8	Pin, keep, split, 3/16 in. x 1. 1/2 in. connected to chain 6 in. long; used on A.C.L., No.8	single	C 4270
Y1/YA 7822	C/w chain, securing handle, A.C.L., No.11	Pin split, 2. 1/2 in. long 5/32 in. dia. C/w 3/8 in. oval chain 16 S.W.G. comprising of 12 links approx. 5 in. long	single	C 4270
Y1/YA 7820	C/w chain, securing spindle drum	3. 3/8 in. x 3/8 in. dia. connected to a split pin by chain; used on A.C.L., No.11	single	C 4270
Y1/YA 6937	Locking bearing, with chain, A.C.L., No.8	3/16 in. x 2. 1/2 in.; M.S. pin with key, joined to chain	single	C 4270
Y1/YA 7459	Locking spindle with chain, A.C.L., No.9	6 in. long; used on A.C.L., No.8	single	C 4270
Y1/YA 5920	Retaining, spindle (c/w chain)	5/16 in. x 2. 9/16 in.; M.S. pin with key, joined to 6 in. of chain M.S. rod 1/4 in. dia.; one end bent at right angles 3/4 in. long the other end bent into a circle to which is joined 4 in. of suitable chain; used on A.C.L., No. 6A	single	C 4270
Y1/YA 5899	Securing knob, wood, No.2	3/8 in. dia. x 2. 7/8 in.; used on A.C.L., No.2, Mk.2	single	C 4270
Y1/YA 5040	Taper, 5/32 in. x 1. 1/2 in. long	M.S.; used on A.C.L., No.3 and No.3, Mk.2	single	C 4270

## SECTION Y1

## CLASS 3920-MATERIALS HANDLING EQUIPMENT, NON-SELF-PROPELLED - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0041	PLATE Bearing, No.3	2-3/4 in.O.D.x 7/16 in.I.D.x No.10 S.W.G.; 2 semi-circular M.S.plates riveted together at one end and held in the closed position by means of spring steel clip; used on A.C.L., No.2, Mk.2	single	C 4270
Y1/YA 7823	Retaining Bracket-support	2 in.x 1 in.x 1/4 in.; M.S.; with central hole 21/64 in. dia.; used on A.C.L., No.11	single	C 4270
Y1/YA 7821	Spring, retaining	1.33/64 in.x 3/4 in.x 3/16 in.; M.S.; with ends turned down to 3/16 in. dia.; with central slotted hole 17/64 in.dia.; part of brake assy. on A.C.L., No.11	single	C 4270
Y1/YA 6095	PLUNGER Clutch, No.1	5/8 in.dia. x 1.5/8 in.; M.S.; 3/8 in. dia.fitted with M.S. knob, 5/8 in.dia. x 13/32 in. used on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 3269	Spindle Bracket	4.3/4 in.long x 1/2 in.dia.M.S.rod with end bent over to form a handle; for securing spindle to frame; used on barrow, drum, W.D., Mk.4	single	C 4270

Y1/YA 3265	Control Driving	2 in.dia.x 4.5/6 in.long M.S. 1 in.dia. shaft with 2 in. dia. knurled head; connection between driving mechanisms and spindle on barrow, drum, W.D., Mk. 4	single	C 4270
Y1/YA 3266	Locking	2 in.dia.x 3 in.long M.S. shaft 1/2 in.dia. with 2 in. dia. knurled handle; with flat cut on shaft; used on barrow, drum, W.D. Mk. 4	single	C 4270
Y1/YA 2328	POUCH, Web, No. 1	3.1/4 in. x 2.7/8 in. x 1.3/4 in.; webbing; flap closed by means of 1/2 in. br. buckle; used on A.C.L., No. 2, Mk. 1 or Mk. 2	single	B 3901, C 4270
Y1/YA 6096	SHOE, Clutch release	4 in. x 3/8 in. x 3/4 in.; centre hole tapped 5/16 in. B.S.W.; G.M., curved, wedge-shaped and slotted; used on A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 7836	SLING, Carrying A.C.L., No. 11	4 ft. 5 in. x 2 in.; web, drab, thick; fitted each end with swivel hooks, spring locking and a buckle; used on A.C.L., No. 11	single	C 4270
Y1/YA 0043	No. 2	4 ft. 6 in. x 2 in.; web, drab, thick; with 2 br. loops and buckle for adjusting length; used on A.C.L., No. 2	single	C 4270
Y1/YA 6097	SOCKET, Plunger	M.S. .56 in. O.D. x 23/32 in. long threaded 1/4 in. gas; one end slotted, the other drilled .378 in. dia. x 19/32 in.; used on A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 0064	SPINDLE A.C.L., No. 3, Mk. 1	M.S.; 0.65 in. square in centre, ends 0.624 in. dia. fitted with M.S. flange 5 in. dia. x 3/8 in. thick, overall length 15.1/4 in.	single	B 2812, C 4270
Y1/YA 6107	A.C.L., No. 3, Mk. 2	1 in. square x 16.15/64 in.; M.S. ends turned down to .624 in. with M.S. collar and taper pin 5/32 in. dia. x 1.1/2 in. used on A.C.L., No. 3, Mk. 2	single	C 4270

## SECTION Y1

## CLASS 3920-MATERIALS HANDLING EQUIPMENT, NON-SELF-PROPELLED - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5921	SPINDLE - continued A.C.L., No.6A	M.S.tube 1/2 in.O.D.x 12.1/2 in.overall,with square bar,2 in.dia.discs and threaded bar, brazed in position;used on A.C.L.,No.6A	single	C 4270
Y1/YA 7460	A.C.L., No.9	5/8 in.square x 11.1/4 in.; M.S.bar; one end turned down to 1/2 in.dia.,the other threaded 3/8 in.B.S.W.; 2.1/2 in.dia.and 1.1/2 in.dia. discs welded in position; used on A.C.L.,No.9	single	C 4270
Y1/YA 6098	Brake-coupling	3/8 in.dia.x 3.13/16 in.; M.S.; one end threaded 3/8 in.B.S.W.with M.S.collar 3/4 in.dia.x 15/32 in.; used on A.C.L.,No.3,Mk.2	single	C 4270
Y1/YA 6528	C/w brake housing,No.2	1 in. square x 15.1/4 in.; M.S.; ends turned down to 5/8 in.dia.with 5 in.dia.plate secured in position; includes brake cover plate; used on A.C.L.,No.3,Mk.1	single	C 4270
Y1/YA 0044	C/w handle,winding	3/4 in.dia.x 11.1/4 in.; M.S. screwed and brazed to handle 5.3/4 in.x 3/4 in. x 1/4 in.; with hardwood knob at one end and a No. 0 B.A.terminal at other; used on A.C.L., No. 2, Mk.2	single	C 4270
Y1/YA 7835	Drum A.C.L.,No.11	1 in.square x 2 ft.6 in.; M.S.; reduced to 3/4 in. dia.for 2.5/32 in.starting at 3.11/16 in. from each end; used on A.C.L.,No.11	single	C 4270



Y1/YA 7860	Bar, Carrying, Lightweight	5/8 in. O.D. x No. 12 S.W.G. x 12.3/4 in. M.S.; one end tapped 1/2 in. B.S.W., on other end is welded key 5/16 in. dia. x 4 in. and 3 collars; used on bar carrying, lightweight, drum, cable, No. 5	single	C 4270
Y1/YA 2517	Cable	1 in. square x 17.13/16 in.; M.S.; ends turned down to 1 in. dia. for 1.1/2 in. fitted with 2 M.S. collars 2.1/4 in. dia. x 7/8 in.; one secured by 3/8 in. B.S.F. screw, the other by 5/16 in. dia. x 2.1/2 in. taper pin; used on barrows, drum, W.D., Mk. 4	single	B 3252, C 4270
Y1/YA 5023	Handle	Head 3/4 in. dia., shaft 1/2 in. dia. x 2.5/16 in.; M.S.; used on A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 7862	Bar, Carrying, Lightweight	5.1/4 in. long; M.S.; used on bar, carrying, lightweight, drum, cable, No. 5	single	C 4270
Y1/YA 6357	No. 2	1/2 in. dia. x 6.1/32 in. M.S.; one end threaded 3/8 in. B.S.W., other end 5/16 in. B.S.W.; used on A.C.L., No. 3 Mk. 2	single	C 4270
Y1/YA 3259	SPRING Brake release, No. 2	2 in. free length x 21/64 in. I.D.; 12 complete turns of No. 14 S.W.G.; used on barrows, drum, W.D., Mk. 4 and A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 3270	For spindle, bracket, plunger	2.1/2 in. free length x 9/16 in. I.D.; spring steel wire No. 15 S.W.G.; 12 turns; used on barrows; drum, W.D., Mk. 4	single	C 4270
Y1/YA 6099	Plunger, No. 2	5/8 in. free length x 9/32 in. I.D.; spring steel wire No. 20 S.W.G.; 4 turns; used on A.C.L., No. 3, Mk. 2	single	C 4270

## SECTION Y1

## CLASS 3920-MATERIALS HANDLING EQUIPMENT, NON-SELF-PROPELLED - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0067	SPRING - continued Restoring Brake arm	Spring steel wire, No. 14 S.W.G.; 18 turns; 1/2 in. dia.; ends bent to form eyes 7/32 in. dia. x 2.3/4 in. between eye centres; used on A.C.L., No. 3 and No. 3, Mk. 2	single	C 4270
Y1/YA 7818	Brake Lever	1.5/8 in. free length x 5/16 in. I.D.; spring steel wire, No. 18 S.W.G.; 10 turns; ends closed; used on A.C.L., No. 11	single	C 4270
Y1/YA 7461	Catch, locking, guide, cable, A.C.L., No. 9	Spring steel wire, No. 14 S.W.G.; 14 turns; 35/64 in. dia.; ends bent to form eyes 3/8 in. dia., 1.9/16 in. between eye centres; used on A.C.L., No. 9	single	C 4270
Y1/YA 3271	SPROCKET, Driven	18 teeth; fits 1 in. dia. shaft; used on barrows, drum, W.D., Mk. 4	single	C 4270
Y1/YA 6100	STOP, Clutch release	5/8 in. dia. x 1.9/64 in.; M.S. one end threaded 5/16 in. B.S.F. for 7/16 in.; used on A.C.L., No. 3, Mk. 2	single	C 4270
Y1/YA 5922	STRAP Bracing No. 2	1 ft. 10 in. x 1/8 in.; chrome leather; used on A.C.L., No. 6A	single	C 4270

Y1/YA 5923	No. 3	1 ft. 6.3/4 in.x 2.1/2 in.x 1/8 in.; chrome leather; used on A.C.L., No. 6A	single	C 4270
Y1/YA 5924	Retaining No. 12	Chrome leather 6.1/4 in.x 3/4 in.x 1/8 in., with one buckle,roller,3/4 in.; used on A.C.L., No.6A	single	C 4270
Y1/YA 5925	No. 13	Chrome leather 5.1/2 in.x 7/8 in.x 1/8 in.; with one buckle,roller,1 in.; used on A.C.L., No. 6A	single	C 4270
Y1/YA 5926	Shoulder L.H.	Chrome leather; 31 in.x 2 in.wide,tapering to 7/8 in.x 1/8 in.thick; used on A.C.L.,No.6A	single	C 4270
Y1/YA 5927	R.H.	Chrome leather; 31 in.x 2 in.wide,tapering to 7/8 in.x 1/8 in.thick; used on A.C.L.,No.6A	single	C 4270
Y1/YA 7863	Spindle, retaining Bar,Carrying, Lightweight	Webbing; 1/2 in.wide x 15 in.; with buckle and tip; used on bar,carrying,lightweight,drum, cable, No. 5	single	C 4270
Y1/YA 5928	Waist, No. 2	4 ft.10 in.x 7/8 in.x 1/8 in.; chrome leather, with 1 in. buckle; used on A.C.L., No. 6A	single	C 4270
Y1/YA 7830	STUD,Locating,brake	1.1/16 in.x 9/16 in.,dia.; M.S.; one end threaded 5/16 in.B.S.W.; used on A.C.L.,No.11	single	C 4270
Y1/YA 5028	SUPPORT,Bearing block	22 in.x 13.1/2 in.; M.S.; "A" shaped support, fabricated from 1.1/2 in.x 1/4 in.; used on A.C.L., No.3, Mks. 1 and 2	single	C 4270

## SECTION Y1

## GROUP 42-FIRE FIGHTING, RESCUE AND SAFETY EQUIPMENT

## CLASS 4240-SAFETY AND RESCUE EQUIPMENT

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0176	BELT Lineman, safety	With runner; not G.P.O. patt.	single	12425, 13998
Y1/YA 0177	Runner,brass		single	A 3
GROUP 51-HAND TOOLS				
CLASS 5120-HAND TOOLS, NON-EDGED, NON-POWERED				
Y1/YA 0133	BAR, Digging	7 ft.long; G.P.O.patt.; steel; chisel and punner ended; used with spoon, digging	single	A 6418
Y1/YA 0686	HAMMER,Telegraph,sledge	Helved, for jumpers	single	8292
Y1/YA 0687	Head	Steel; 16 lb. round faced at both ends	single	25713
Y1/YA 0688	Helves	Ash or white hickory,with 2 wedges; length 3 ft.	single	C 4270
Y1/YA 0689	Wedge		single	C 4270
Y1/YA 8359	LACER	G.P.O. patt.	single	C 4270
Y1/YA 8360	No. 1	10 in. long; used for lacing cable	single	C 4270
Y1/YA 8366	No. 2	18 in. long; used for lacing cable	single	C 4270
Y1/YA 8366	No. 3	Needle type, for general wiring	single	C 4270

Y1/YA 1061	MATTOCK, Telegraph equipment	Helved; without case	single	12049
Y1/YA 1063	Head	Steel	single	
Y1/YA 1064	Helves	Wood, steel shod	single	
*Y1/5120-99-901-3332	PIKE, Pole	Wool handle w/MS. hook	single	
*Y1/5120-99-901-1279	7 ft. 6.1/2 in.	w/hook;	single	
	12 ft. 6.1/2 in.lg.			
Y1/YA 4002	PLIERS	G.P.O. patt.	pair	C 4270
Y1/YA 5639	Adjusting, No.3	Duckbill, straight, 5.1/2 in.long,insulated	pair	
Y1/YA 5640	Cord repair	Tool No. 83; for binding cord	pair	
	No. 1	Tool No. 213; for tagging cord		
	No. 2			
Y1/YA 7345	SCREWDRIIVER	24 in.x 1/4 in.; G.P.O.patt.,No.7; used on exch.C.B.,	single	C 4270
Y1/YA 7346	Inst., No. 7	multiple, W.D.,unit type,maintenance tool kit		
	Offset, No. 1	5 in.x 5/16 in.; G.P.O.patt.; used on exch.,	single	C 4270
		C.B.,multiple, W.D.,unit type,maintenance		
		tool kit		
Y1/YA 8364	SPADE, Rabbiting	G.P.O. patt.; approx. 7 ft. long	single	C 4270
*Y1/YA 11321	SPANNER	Minifon recorder,model 54	single	
*Y1/YA 11322	Ring nut	Minifon recorder, model 54	single	
	Ring nut and screwdriver			
Y1/YA 7355	SPANNER, Box	3.7/16 in.x 7/16 in.x 3/8 in.; steel,double	single	C 4270
	Cranked, No.2	ended,flat, 8 B.A.for 600 type relay spring		
		set screws; used on exch. C.B.,multiple,		
		W.D.,unit type(maintenance tool kit)		
Y1/YA 7668	No.3	G.P.O.patt.; 3/8 in.x 13/32 in.x 6.1/2 in.long;	single	C 4270
		used with spike,capstan,No.1 on swbd.,C.B.		
		multiple, W.D.,unit type(tool kit)		

## SECTION Y1

## CLASS 5120-HAND TOOLS, NON-EDGED, NON-POWERED - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 1468	SPOON, digging	G.P.O.patt.; steel scoop with wood handle, overall length 8ft.; used with bar, digging, for poles, tel., wood	single	A 6418
Y1/YA 1524	STICK, Crook 14 ft.	Teleg. equip. In two lengths, top length M.S.tube covered with spruce and cane; width across flats 1 in. to 9/16 in. fitted with brass tube and plug one end and M.S.galv.crook at the other; bottom length green-heart, dia. 1.1/4 in. to 1.3/32 in. fitted with brass cup ferrule one end and brass socket tube at the other end; used in the erection of poled cable	single	A 693
Y1/YA 1525	Bottom Length	Three 3 ft. lengths and one 2 ft. 8 in. length, without straps	single	C 4270
Y1/YA 1526	Top Length		single	C 4270
Y1/YA 1514	Jointed, Mk.2		single	19478, B 4213
Y1/YA 1516	Intermediate Length		single	C 4270
Y1/YA 1515	Lower Length		single	C 4270
Y1/YA 1517	Top Length		single	C 4270
Y1/YA 1518	Strap		single	25713
Y1/YA 1519	Long	2 ft. 4 in. x 3/4 in. with sliding loop Cast steel crook fitted in wood stock; 7 ft. 6.1/2 in. for dismounted work	single	A 6421, B 4213
Y1/YA 1522	Short, dismounted services	M.S. crook fitted in wood stock; 3 ft. 1.1/2 in long; for dismounted work	single	19788, A 6421

Y1/YA 2176 Y1/YA 2177	TOOL, Stay splicing Large Small	G.P.O. patt. ; steel for attaching stay wire 13 in. 7 in.	single single	12087, 24621
Y1/YA 0659	GAUGE, Arm	GROUP 52—MEASURING TOOLS CLASS 5210—MEASURING TOOLS, CRAFTSMEN'S G.P.O. patt. ; steel for spacing position of slots for arms on pole	single	C 4270
Y1/YA 5599 Y1/YA 3456 Y1/YA 9127 Y1/YA 9128 Y1/YA 9129 Y1/YA 2387	BOLT No. 1 No. 6 No. 8 No. 21 No. 25 No. 26	GROUP 53—HARDWARE AND ABRASIVES CLASS 5305—BOLTS AND SCREWS G.P.O. patt. 3.1/2 in. x 5/8 in. 4.1/2 in. x 5/8 in. 16.7/8 in. x 5/8 in. 2 in. x 3/8 in. 2.3/4 in. x 5/8 in. 3.1/2 in. x 3/8 in.	single single single single single single	C 5687
Y1/YA 3330 Y1/YA 2358	BOLT, Arm No. 8 No. 9	G.P.O. patt. 8.1/2 in. x 5/8 in. ; fitted with 1 nut and 1 washer, galv., No.4 9.1/2 in. x 5/8 in. ; fitted with 1 nut and 1 washer, galv., No.4	single single	C 4270 C 4270

## SECTION Y1

## CLASS 5305-BOLTS AND SCREWS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
		2		
		3		
		4		
		5		
Y1/YA 3331	BOLT, Arm - continued	10. 1/2 in. x 5/8 in. † fitted with 1 nut and 1 washer, galv., No. 4	single	C 4270
Y1/YA 3455	No. 11	11. 1/2 in. x 5/8 in.	single	C 5687
Y1/YA 5291	No. 12	12. 1/2 in. x 5/8 in.	single	C 5687
Y1/YA 6436	No. 13	13. 1/2 in. x 5/8 in.	single	C 5687
Y1/YA 6324	No. 14	14. 1/2 in. x 5/8 in.	single	C 5687
Y1/YA 9130	No. 15	15. 1/2 in. x 5/8 in.	single	C 5687
Y1/YA 9131	No. 16	16. 1/2 in. x 5/8 in.	single	C 5687
Y1/YA 9132	No. 17	17. 1/2 in. x 5/8 in.	single	C 5687
Y1/YA 3712	No. 19	19. 1/2 in. x 5/8 in.	single	C 5687
Y1/YA 11341	No. 21	21. 1/2 in. x 5/8 in.	single	C 8635
Y1/YA 2386	No. 22	22. 1/2 in. x 5/8 in.	single	C 5687
	BOLT, tie	G.P.O. patt. † fitted with 1 sq. nut		
Y1/YA 10982	No. 1	24 in. x 3/4 in.	single	C 8423
Y1/YA 10976	No. 2	30 in. x 3/4 in.	single	C 8423
Y1/YA 10977	No. 3	36 in. x 3/4 in.	single	C 8423
Y1/YA 10978	No. 4	45 in. x 3/4 in.	single	C 8423
Y1/YA 8349	No. 5	54 in. x 3/4 in. † used on overhead work	single	C 4270
Y1/YA 10980	No. 6	63 in. x 3/4 in.	single	C 8423
	SCREW-EYE	G.P.O. patt.		
Y1/YA 7472	Spiral, 1/2 in.		single	C 4270



Y1/YA 6919	Spiral, 3/4 in.	single
Y1/YA 6362	Spiral, 1 in.	single
<b>SCREW</b>		
*Y1/YA 11316	Adjusting	single
*Y1/YA 11317	Brush plate	single
*Y1/YA 12114	Cheese-head	single
	Coach	
Y1/YA 1413	2 in.	
Y1/YA 1414	2.1/2 in.	
Y1/YA 4823	Insulated, Relay, No. 1	
Y1/YA 4824	Relay, No. 1	
Y1/YA 0228	<b>Contact B</b>	
	Mk. 1	
*Y1/YA 12115	Countersunk head	
*Y1/YA 12120	Governor contact	
Y1/ZA 12598	Insulating, No. 4, B.A.	
*Y1/YA 11320	Lock	
Y1/YA 6023	Lock, No. 6, special	
*Y1/YA 11318	Motor securing	
<b>SCREW, Special</b>		
	26 t.p.i., Whit. form,	
	steel, knurled head	
Y1/YA 6706	3/8 in. x 1.3/16 in. #No. 1	
Y1/YA 6708	3/8 in. x 1.11/16 in.,	
	No. 1	
	Forward/changover brake; minifon recorder, model 54	
	Minifon recorder, model 54	
	Minifon recorder, model 54	
	M.S. galv. § 3/16 in. dia. square head	A 5530
	For insulator, bobbin, No. 1	
	For insulator, Bobbin, No. 2	
	5/32 in. dia. x 60 t.p.i. 17/32 in. long; Br. cap. hd.	C 4270
	with ivoryine stud inserted in the end; used	
	on swbd., U.C., 10 line	
	5/32 in. dia. x 60 t.p.i., 17/32 in. long;	
	Br. cap. hd. with platinum contact; used on swbd.,	C 4270
	U.C. and relays line	
	With knurled edge knob and fixed contact	
	point; used with buzzer, F.Mk. 2 and T. Mk. 1	B 2342,
	Minifon recorder, model 54	B 6339
	Minifon recorder, model 54	
	Used on panel, mains tapping, No. 4	C 4270
	Minifon recorder, model 54	
	O B.A. x 1.1/4 in. long; threaded 3/8 in. esk. hd. §	C 4270
	M.S. § used on swbd., teleprinter, 15 line	
	Minifon recorder, model 54	
	Ch. hd., straight knurled, threaded 3/8 in. §	
	used on test frames, 20 pr., Mk. 2 and 40 pr., Mk. 2	C 4270
	Ch. hd., straight knurled, threaded 7/8 in., used on	
	test frames, 20 pr., Mk. 2 and 40 pr., Mk. 2	C 4270

## SECTION Y1

## CLASS 5305-BOLTS AND SCREWS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6709	SCREW, Special. 26 t.p.i., White. form, steel, knurled head - continued 3/8 in. x 1.29/32 in., No. 1	Ch. hd., straight knurled, threaded 5/16 in., "C" stamped on head used on test frames, 20 pr., Mk. 2 and 40 pr., Mk. 2	single	C 4270
Y1/YA 7950 Y1/YA 7949	B.A., brass Binding hd. No. 5 x 3/16 in., No. 1 No. 5 x 3/8 in., No. 1	Head 7/32 in. dia. x 5/64 in. used on tel. set, J Head 7/32 in. dia. x 5/64 in., threaded 5/32 in. used on tel. set, J	single single	C 4270 C 4270
Y1/YA 7539	Button hd. No. 2 x 1/4 in., No. 1	G.P.O. patt., used on box, battery, test, No. 1	single	C 4270
Y1/YA 5502 Y1/YA 8254	Cheese hd. No. 2 x 5/16 in., No. 1 No. 2 x 5/8 in., No. 1	Secures gong on bells, mag., T Head .343 in. dia., shank 1/4 in. dia. x 1/2 in. long, tapped No. 2 B.A. x 1/2 in. deep, used on training set, No. 4A	single single	C 4270 C 4270
Y1/YA 7541	No. 4 x 5/16 in., No. 1	Head 3/8 in. dia. x 1/8 in. used on units, gen. answering, 20 cct. of swbd., C.B., multiple W.D., unit type	single	C 4270
Y1/YA 5950	No. 4 x 7/16 in., No. 1	Threaded 1/8 in., mounts indicator jacks on units A/J and C on swbd. F. and F.	single	C 4270

Y1YA 6065	No.4 x 9/16 in.,No.1	Threaded 1/8 in. for indicator and jack strips on swbd.,F. and F., unit C	single	C 4270
Y1YA 5141	No.6 x 3/16 in.,No.1	Standard screw with head reduced to .06 in. thick for connections of pressel switch on tel. band	single	C 4270
Y1YA 5503	Fillister hd. No.2 x 2 in.,No.1	Threaded 1/4 in., shank dia. 9/64 in. secures bottom cover of case on tel. set, L. tel. set, H, Mk.2 and tel. set, J	single	C 4270
Y1YA 3923	No.8 x .093 in.,No.1	G.P.O. patt. No.8 BC threaded 1/16 in. fused on plugs No. 201,301,316	single	C 4270
Y1YA 7433	Knurled hd. No.0 x 1.7/32 in.,No.1	Threaded 7/16 in., head dia. 5/8 in., coarse diamond knurled and slotted fused on swbd., mag., 10 line, W.D.	single	C 4270
Y1YA 7441	No.2 x 3/4 in.,No.1	Threaded 3/16 in., head 7/16 in. dia. x 9/32 in. long diamond knurled with coin slot fused on swbd., mag., 10 line, W.D.	single	C 4270
Y1YA 7440	No.2 x 1.3/16 in.,No.1	Threaded 5/16 in., head 7/16 in. dia. x 3/8 in. long diamond knurled with coin slot; used on swbd., mag. 10 line W.D.	single	C 4270
Y1YA 3232	Knurled Fillister hd., No.2 x 1.5/32 in.,No.1	Threaded 3/8 in., head diamond knurled with shoulder 5/32 in. long fused on tel. set, F, Mk.1, Mk.1/1 and Mk.2	single	C 4270
Y1YA 8296	Round hd., No.2 x.675 in.,	Shouldered, with 2 B.A. tapped br. washer 3/8 in. dia. x .032 in. secures covers No.8 on protectors and fuze, No.1, 2/2	single	C 4270
Y1YA 1640	Wing hd., No.2 x 1.5/32	Threaded 11/32 in. head 1/2 in. dia. x 3/32 in. with centre rib 1/8 in. thick x 1/4 in., forming a winghead; used on swbd., U.C., box, accessories	single	B 4807, C 4270
Y1YA 5607	B.A., steel Button hd., No.4 x 1/4 in., No.1	Hd. 5/16 in. dia. x 5/64 in. fused on swbd., command, 200 line and swbd., F. and F.	single	C 4270

## SECTION Y1

## CLASS 5305--BOLTS AND SCREWS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7574	SCREW, Special B.A., steel - continued Cheese hd. No.0 x 15/16 in.,No.1	Threaded 7/32 in.,head 1/2 in.,dia.x 1/8 in.; used on case, line test	single	C 4270
Y1/YA 5022	No.2 x 19/32 in.,No.1	Head 19/64 in.,dia.x 1/8 in.,shoulder 7/32 in.,dia. x 11/64 in.; slotted; secures clutch lever on A.C.L., No.3, Mk.2	single	C 4270
Y1/YA 7431	No.2 x 1. 1/8 in.,No.1	Threaded 1/16 in.,shoulder .34 in.,dia.x .281 in.; used on swbd., mag., 10 line, W.D.	single	C 4270
Y1/YA 7551	No.2 x 1.11/16 in., No.1	Head 5/16 in.,dia.x 5/16 in.,long,slotted and centrally tapped No.4 B.A.to depth of 3/16 in.; used on case,line test	single	C 4270
Y1/YA 4816	No.2 x 3.1/16 in., No.1	Threaded 1/4 in.,head 3/4 in.,dia.x 3/16 in.,thick; slotted and centrally tapped No.2 B.A.x 3/8 in. deep,shoulder 9/32 in.,dia.x 3/8 in.,long,remainder of shank reduced to 9/64 in.,dia.;used on swbd., U.C.	single	C 4270
Y1/YA 7555	No.3 x 3/8 in.,No.1	Head 1/2 in.,dia.x 1/16 in.,slotted,shoulder .187 in.,dia.x 1/8 in.; undercut between shoulder and thread; used on junction,relay test set	single	C 4270
Y1/YA 5572	No.4 x 7/16 in.,No.1	Threaded 3/16 in.,head 1/4 in.,dia.x 7/64 in.; used on gen.,C on tel.set, L	single	C 4270

Y1/YA 8113	No.4 x 1/2 in.,No.1	Threaded 3/16 in.,shank .1 in.dia. used on ampfr., field tel.,No.1	single	C 4270
Y1/YA 7733	No.4 x 5/8 in.,No.1	Head 25/64 in.dia.x 9/64 in.,shoulder 3/16 in.dia. x 1/4 in.long	single	C 4270
Y1/YA 8114	No.4 x 1.7/16 in.,No.1	Threaded 1/2 in. used on ampfr.,field tel.,No.1	single	C 4270
Y1/YA 4667	Connector hd.,No.4 x 9/32 in.,No.1	Head 3/8 in.dia.x 3/32 in. used on tel.set,F, Mk.1, 1/1 and 2	single	C 4270
Y1/YA 5541	Countersunk hd. No.4 x 2.3/16 in.,No.1	Threaded 5/8 in. used on handle, gen.,No.3	single	C 4270
Y1/YA 5379	Knurled hd. No.0 x 9/32 in.,No.1	Threaded 7/32 in.,straight knurled; used on bracket,special,No.2	single	C 4270
Y1/YA 6675	No.2 x 23/32 in.,No.1	Threaded 1/4 in.,head 7/16 in.dia.,straight knurled; used on test frames,20 pr.,Mk.3 and 40 pr.,Mk.2	single	C 4270
Y1/YA 7535	No.2 x 1 in.,No.1	Threaded 1/4 in.,head 5/16 in.dia.x 1/4 in.long, slotted and knurled; used on box,battery,test No.1	single	C 4270
Y1/YA 8275	No.2 x 1.1/8 in.,No.1	Threaded 3/8 in.,fil.hd.1/2 in.dia.x 5/16 in.long, diamond knurled; used on panel,fuze,No.7,units, access jack,No.1 and rack,cable, No.1	single	C 4270
Y1/YA 6442	No.4 x 1.7/16 in.,No.1	Threaded 11/16 in.,head 5/16 in.dia.x 5/16 in.long, straight knurled; used on tel.,L.S.,No.2,sets, Mk.2/1 control units	single	C 4270
Y1/YA 6175	B.S W.,steel Binding hd. 1/4 in.x 7/16 in.,No.1	Threaded 3/16 in.,head 7/16 in.dia.x 5/32 in., shank 3/16 in.dia. used on swbd.,F.and F.,20 and 40 line, Mk.2	single	C 4270
Y1/YA 6030	1/4 in.x 1.1/4 in., No.1	Threaded 31/32 in.,head 3/4 in.dia.x 1/4 in., shoulder 15/32 in.dia.x 1/32 in.,shank reduced to core dia.,secures lid of case,swbd.,F.and F., unit D	single	C 4270

## SECTION Y1

## CLASS 5305-BOLTS AND SCREWS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5011	SCREW, Special B.S.W., steel-continued Cheese hd. 1/4 in. x 3/4 in., No. 1	Threaded 7/16 in., head 3/4 in. dia. x 3/32 in., slotted, shoulder .31 in. dia. x 7/32 in.; used on A.C.L., No. 3 and No. 3, Mk. 2	single	C 4270
Y1/YA 6125	1/4 in. x 1.7/8 in., No. 1	Threaded 17/32 in., head 5/8 in. dia. x 5/16 in., hole through shank 17/32 in. from the end; used on boxes, terminal, sig. office, Mk. 2 and Mk. 3	single	C 4270
Y1/YA 7462	5/16 in. x 1 in., No. 1	Threaded 11/32 in., head 9/16 in. dia. x 1/8 in., shoulder 3/8 in. dia. x 19/32 in.; used on A.C.L., No. 9	single	C 4270
Y1/YA 7463	3/8 in. x 1 1/16 in., No. 1	Threaded 19/64 in., head 3/4 in. dia. x 1/8 in., shoulder 1/2 in. dia. x 17/64 in.; used on A.C.L., No. 9	single	C 4270
Y1/YA 6707	Connector hd., 5/16 in. x 13/16 in., No. 1	Threaded 1/2 in., head 5/8 in. dia. x 3/16 in., hole 3/16 in. dia. x 1/16 in. drilled in end of screw; used on test frames, 20 pr., Mk. 2 and 40 pr., Mk. 2	single	C 4270
Y1/YA 6126	Hexagon hd. 1/4 in. x 1.17/32 in., No. 1	Threaded 1/2 in., hole .07 in. dia. 17/32 in. from end, pin 1/8 in. dia. x 1.3/16 in. through head used on boxes, terminal, sig. office, Mk. 2 and Mk. 3	single	C 4270
Y1/YA 5037	5/16 in. x 1 in., No. 1	Standard screw modified by reducing width to 3/8 in. across 2 of the flats and drilling hole 5/64 in. dia. 1/8 in. from the end; used on A.C.L., No. 3, Mk. 1 and Mk. 2	single	C 4270

Y1/5307-99-910-2150	STUD, Plain	CLASS 5307-STUDS	single
Y1/YA 8118	WASHER Felt 15/32 in.O.D.x 7/32 in. I.D.,No.1	Br.2 BA; 0.906 in.lg. O/A. used on recorder, magnetic tape with playback	single
Y1/YA 4985	Fibre	CLASS 5310-NUTS AND WASHERS	C 4270
Y1/YA 7953	Gland Rubber,5/32 in.x 5/16 in.x 1/16 in. thick	7/32 in.thick,impregnated with anti-freeze used on ampfr.,field tel.,No.1	single
Y1/YA 7952	Special, No.1	1.5/8 in.O.D.x 1.1/16 in.I.D.x 3/16 thick; hard red fibrefused on barrows,drum,W.D.,Mk.4	C 4270
Y1/ZA 4165	Microphone, No.3A	Rubber,soft tpl. grade, used on tel. set, J 7/16 in.O.D.x 7/32 in.I.D.x 1/32 in.thick; M.S.fused on tel.set,J	C 4270
Y1/YA 4901	Retaining,plunger,spring	2. 1/4 in.O.D.x 2.1/32 in.I.D.x 1/8 in.; ebonite fused on mic.,hand,No.3	single
Y1/ZA 25229	Rubber 1.3/4 in.I.D.x 1.15/16 in.O.D.x 1/16 in.	27/32 in.O.D.x 17/32 in.I.D.x 1/16 in.thick; M.S.fused on barrows,drum,W.D.,Mk.4	C 4270
Y1/ZA 23883	3.1/4 in.x 2.3/4 in., M.C.,No.1	Used on mic., M.C., No. 1	doz
			single
			C 4270

## SECTION Y1

## CLASS 5310-NUTS AND WASHERS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZA 23884	WASHER Rubber - continued 3.1/4 in. x 3 in., M.C., No. 1	1/16 in. thick; used on mic., M.C., No. 1	single	C 4270
Y1/YA 6908	I.T.E.	1.7/64 in. O.D. x 3/4 in. I.D. x .06 in. thick; used on recvr., watch, I.E., No. 1 and mic., hand (I.T.E.), No. 17	single	C 4270
Y1/YA 4987	Special, D.hole	1.3/8 in. O.D., with D shape hole 3/4 in. dia. and 6 holes 1/8 in. dia; used on barrows, drum, Mk. 4	single	C 4270
Y1/YA 5139	Spring, insets, No. 1	2.3 in. O.D. x 1.625 in. I.D. x .0148 in. ; hard br., spring tempered; used on tel., hand (sound P), No. 2	single	C 4270
Y1/YA 7480	Steel, special 17/32 in. hole	1 in. O.D. x 17/32 in. I.D. x .064 in. thick; used on frame, I.D., swbd., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 7481	3/8 in. hole	1 in. O.D. x 3/8 in. I.D. x .064 in. thick; used on frame, I.D., swbd., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 8278	1.11/32 in. O.D. x 1.072 in. I.D., No. 1	.048 in. thick, zinc plated; used on units, alarm No. 1	single	C 4270



Y1/YA 7941	GROMMET, rubber, No.30	CLASS 5325-FASTENING DEVICES	single	C 4270
	.580 in.x .580 in.O.D.x .30 in.I.D.; oil resisting; used on tel.set., J			
Y1/ZA 25367	GASKET Loudspeaker, No.5A	CLASS 5330-PACKING AND GASKET MATERIALS	single	C 4270
Y1/YA 8292	Rubber 1.9/32 in.x 29/32 in., No.1	8.5/8 in.dia.x 1/16 in. compressed cork; includes disc of oiled silk; 6.1/2 in.dia.	single	C 4270
Y1/ZB/M94 0009	4 in.dia.x 1/16 in.	For sealing keys; used on rack, tel.terminal, No.1	single	C 4270
Y1/5330-99-943-9360	5.1/8 in.x 5.1/8 in.x 1/16 in.thick	Used on L.S., re-entrant, 15 ohm, No. 1	single	C 4270
Y1/YA 7705	6.1/4 in.x 5.3/32 in., No. 1	Used on unit, line, 3 cct.; units alarm and units common apps., No.2 (equipt., tel.terminal, No.1) (old Cat.No.Y1/YA 8082)	single	C 4270
Y1/YA 7706	6.9/32 in.x 3.5/16 in., No. 1	1/16 in.thick; used on L.S.D. S.R., lightweight	single	C 4270
Y1/ZB/M 94 0008	6.3/4 in.dia.x 1/6 in.	1/4 in.wide x 1/8 in.thick; used on L.S.D. S.R. lightweight	single	C 4270
Y1/5330-99-943-9359	8.3/8 in.x 5.1/4 in.x 3/32 in thick	Used on L.S., re-entrant, 15 ohm, No.1 (old Cat.No. Y1/YA 8081)	single	C 4270
Y1/YA 7439	12.7/16 in.x 3.7/8 in., No. 1	Used on units, line relay, rack, tel.terminal, No.1	single	C 4270
Y1/YA 8099	17 in.x 6.1/2 in.x 7/16 in.	3/8 in.sq.section; used on front and back covers of swbds., mag, 10 line, W.D. Used on rack, tel.terminal, No.1 equipped	single	C 4270

## SECTION Y1

## CLASS 5330-PACKING AND GASKET MATERIALS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	GASKET - continued			
Y1/YA 7972	Sealing 3.5/16 in.x 1.7/8 in.	1/2 in. wide x .062 in. thick rubber used on tel. set, J	single	C 4270
Y1/YA 7973	10.3/16 in.x 4.5/8 in.	.180 in. wide x .12 in. thick used on tel. set, J	single	C 4270
*Y1/5340-99-943-8227	CLIP, retaining	CLASS 5340-MISCELLANEOUS HARDWARE 2.128 in. long O/A, 3 in. wide. 064 in. dia. T.M.C. type S49347	single	
*Y1/YA 11309	COLLET	Minifon recorder, model 54	single	
*Y1/YA 12235	COLLETS, Pair 1/54 sets	G.P.O. patt.	set	
*Y1/YA 12236	55/100 sets	G.P.O. patt.	set	
*Y1/YA 12238	101/200 sets	G.P.O. patt.	set	
*Y1/5340-99-901-2415	SLEEVE SET, Identification 1/50	G.P.O. patt.	set	
*Y1/5340-99-901-2416	51/100	G.P.O. patt.	set	
*Y1/5340-99-120-0363	SPRING, Helical extension	T.M.C. type S. 55377	single	

GROUP 54--PREFABRICATED STRUCTURES AND SCAFFOLDING  
 CLASS 5440--SCAFFOLDING EQUIPMENT AND CONCRETE FORMS

Y1/YA 7623	LADDER Extension, No.1	14 ft. closed, 25 ft. extended; G.P.O. patt. ; 2 sections	single	C 4270
Y1/YA 7624	Extension, No.2	18 ft. closed, 33 ft. extended; G.P.O. patt. ; wood; 2 sections	single	C 4270
Y1/YA 9252	Lightweight, extending 11/20 ft. with cradle rung	Al. alloy 11 ft. 3 in. closed, 20 ft. 3 in. extended	single	C 5687
Y1/YA 0931	Multi-airline	9 ft. 6 in. long; octagonal wood pole, fitted with 7 M.S. steps; M.S. foot; and M.S. clip with chain and hook	single	25653, A 1424
Y1/YA 0934	Step	M.S. ; galv.	single	16196, A 1424
Y1/YA 6655	Stout, 16 ft. 2 in.	G.P.O. patt. ; 18 rungs	single	C 4270

GROUP 55--LUMBER, MILLWORK, PLYWOOD AND VENEER

CLASS 5510--LUMBER AND RELATED WOOD MATERIALS

Y1/HH 0700	POLE Flag, multi-airline	Fir; 5 ft. 6 in. long, tapered from 1 in. at butt to 1/2 in. at top; steel shod	single	C 3899, C 6496
Y1/HH 0701	Shoe Light	G.P.O. patt. ; wood; marked with one crown on the butt; scarfed; bored for arm belts and provided with roof slopes	single	C 4270
Y1/YA 5251	18 ft.		single	
Y1/YA 3334	22 ft.		single	

## SECTION Y1

## CLASS 5510-LUMBER AND RELATED WOOD MATERIALS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 1185	POLF - continued Multi-airline	16 ft. long; wt. 10 lb.; wood; tapered in two directions; dia. where taper commences 2.3/4 in.; dia. at top 2.1/8 in.; round hollow spar type; solid bottom, top plugged and fitted with M.S. band	single	25654, A 7875
Y1/YA 1201	Telegraph, wood 16 ft., octagonal, Mk. 1/1	<i>Pointed and tapered at butt; dia. at butt before tapering 2.5/8 in.; dia. at tip 1.7/8 in.</i>	single	25465, C 8181
Y1/5510-99-942-7935	Line construction, wood 17 ft.	To I.E.M.E. dwg. No. S 4115B (Old Cat. No. Y1/YA 1202)	single	14739, C 8635
Y1/5510-99-942-7936	17 ft., bottom piece	To I.E.M.E. dwg. No. S 4115B (Old Cat. No. Y1/YA 1203)	single	14709, C 8635
Y1/5510-99-942-7937	17 ft., top piece	To I.E.M.E. dwg. No. S 4115B (Old Cat. No. Y1/YA 1204)	single	14709, C 8635
Y1/5510-99-942-7938	21 ft.	To I.E.M.E. dwg. No. S 4116A (Old Cat. No. Y1/YA 1205)	single	A 6695, C 8635
Y1/5510-99-942-7939	21 ft., bottom piece	To I.E.M.E. dwg. No. S 4116A (Old Cat. No. Y1/YA 1206)	single	A 6695, C 8635
Y1/5510-99-942-7940	21 ft., top piece	To I.E.M.E. dwg. No. S 4116A (Old Cat. No. Y1/YA 1207)	single	A 6695, C 8635
Y1/5510-99-942-7761	Light, 20 ft.	Pressure creosoted (Old Cat. No. Y1/YA 5875)	single	C 4270
Y1/5510-99-942-7762	Light, 24 ft.	Pressure creosoted (Old Cat. No. Y1/YA 3465)	single	C 4270, C. 8635

Y1/5510-99-942-7763	Light, 26 ft..	Pressure creosoted (Old Cat.No.Y1/YA 3805)	single	C 4270, C 8635
Y1/5510-99-942-7764	Light, 28 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3466)	single	C 4270, C 8635
Y1/5510-99-942-7765	Light, 30 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3467)	single	C 4270, C 8635
Y1/5510-99-942-7766	Light, 32 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3335)	single	C 4270, C 8635
Y1/5510-99-942-7767	Light, 34 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3468)	single	C 4270, C 8635
Y1/5510-99-942-7768	Light, 36 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3469)	single	C 4270, C 8635
Y1/5510-99-942-7769	Medium, 24 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3470)	single	C 4270, C 8635
Y1/5510-99-942-7770	Medium, 26 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3471)	single	C 4270, C 8635
Y1/5510-99-942-7771	Medium, 28 ft.	Pressure creosoted (Old Cat.No.Y1/YA 5785)	single	C 4270, C 8635
Y1/5510-99-942-7772	Medium, 30 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3472)	single	C 4270, C 8635
Y1/5510-99-942-7773	Medium, 32 ft.	Pressure creosoted (Old Cat.No.Y1/YA 5786)	single	C 4270, C 8635
Y1/5510-99-942-7774	Medium, 34 ft.	Pressure creosoted (Old Cat.No.Y1/YA 5787)	single	C 4270, C 8635
Y1/5510-99-942-7775	Medium, 36 ft.	Pressure creosoted (Old Cat.No.Y1/YA 5788)	single	C 4270, C 8635
Y1/5510-99-942-7776	Stout, 26 ft.	Pressure creosoted (Old Cat.No.Y1/YA 5789)	single	C 4270, C 8635
Y1/5510-99-942-7777	Stout, 28 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3473)	single	C 4270, C 8635
Y1/5510-99-942-7781	Stout, 36 ft.	Pressure creosoted (Old Cat.No.Y1/YA 3477)	single	C 4270, C 8635
Y1/YA 3807	STAYBLOCK, Medium	G.P.O. Patt. j rупingized; scots pine or other suitable timber; 2 ft.10 in.x 10 in.x 5 in. j bored with 7/8 in. hole	single	C 4270

SECTION Y1  
GROUP 58—COMMUNICATION EQUIPMENT  
CLASS 5805—TELEPHONE AND TELEGRAPH EQUIPMENT

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5134	ADAPTOR, Transmitter, inset, No. 1	Plastic; to house transmitter, inset, No.1	single	C 4270
Y1/YA 9466	ADJUSTER, Spring	G.P.O. patt.	single	C 8181
Y1/YA 9467	No. 5	For use with two motion selectors	single	C 8181
Y1/YA 7786	No. 8	For use with two motion selectors remote springs	single	C 4270
Y1/YA 7341	No. 9	For selector wipers all types	single	C 4270
Y1/YA 7342	No. 12	For 500 and 600 type relays	single	C 4270
Y1/YA 9670	No. 13	For protectors, H.C. and T.	single	C 8181
Y1/ZB 0478	AMPLIFIER A.F., 2 watt, sealed, No. 1, 12V, A.F., No. 2	9 in. x 9 in. x 3 in. sealed amplifier with 12V power supply unit Input and output impedances, 10, 100, 600 and 4,000 ohms 2 W. min. output 200/250 V., A.C. 2% harmonic distortion; gain 40 db.	single	C 4270
Y1/YA 11465	A.F., M.I.M.C.O. type 1165C, modified	Amplifier assy., M.I.M.C.O. type 1165C, modified and pre-amp assy., M.I.M.C.O. type 1172C, modified, together with associated connection; mounted in metal case 21.3/8 in. x 19 in. x 13 in.	single	C 9519
Y1/YA 7474	Field telephones, No. 1	10 in. x 5.3/8 in. x 3.7/16 in. weight 8 lb. Single stage A.F. amplifier for use with field tel., fitted in die-cast Al. case. For components see E.M.E.R. Telecom. 0366/1	single	C 4270, C 6816

Y1/YA 10207	Field telephone;No.1, Mk.2	10 in. x 5.1/2 in. x 3.1/2 in. approx. die-cast case; weight approx. 8 lb.; single stage A.F. ampfr. for use with field tel. in canvas carrying case (1L 11681)	single	C 6816
	ARMATURE			
	Bell			
Y1/YA 6193	56A	For bell, battery, No. 56A	single	C 4270
Y1/YA 8053	Magneto, No. 3 (W.D.)	For bell, mag, No. 3 (W.D.)	single	
Y1/YA 5101	Magneto, I	For bell, mag, I	single	
Y1/YA 2801	ARM, Lazy tong, No. 1	M.S., with adjustable mic. clamp; 13 in. long when closed, extending to 30 in.; used with tel. L.S., No. 1	single	B 4106, C 4270
	BAR, Finger, pressel switch			
Y1/YA 6866	No. 6	2.1/2 in. x 1/4 in. x 5/16 in.; plastic; includes 2 screws, No. 8 B.A. x 3/16 in., csk. hd., Br.; used on tel. hand, No. 6	single	C 4270
Y1/YA 7935	No. 7	Bakelite x 5073 (Black); used on tel. set J	single	
	BELL			
	Battery			
Y1/YA 0154	No. 13A. Modified	Consists of bell, battery, No. 13A without base and with the gong secured by csk. hd. screws	single	A 6694, B 3011
Y1/YA 8297	Mk. 1/1	Full tpl version of bell, battery, No. 13A, modified; used on rack, tel. terminal, No. 1	single	C 4270
Y1/YA 0166	Magneto; No. 53A	G.P.O. patt.; 500 ohms + 500 ohms, series or parallel, for alarm circuits	single	A 3395
*Y1/YA 12310	No. 56A	G.P.O. patt.	single	
	BELL-SET			
Y1/YA 9166	No. 20	G.P.O. patt. For one exch. line and 1 Or 2 extensions	single	C 8181

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7409	BELL-SET - continued No.26	Includes 1 bell, No.59A, unmounted; 1 bell gong, No. 2; 1 bell gong, No. 2A; 1 condenser, M.C.,No. 102; used on kits, extension tel.,C.B. exch.	single	C 4270
Y1/YA 3190	No. 31, black	Includes 1 bell, No.59A, unmounted; 1 bell gong, No.2; 1 bell gong, No.2A; 1 coil, induction, No.21; 1 condenser, M.C.,No.102	single	C 4270
Y1/YA 9322	No. 37	For use with tel., No.246	single	C 8181
Y1/YA 8585	No. 39A, black		single	C 5687
Y1/YA 11247	No. 44, black		single	C 8635
Y1/YA 1867	BELL UNIT	500 ohms + 500 ohms; without 2 bell gongs, No.2 complete with 2BA csk.head, br.screws 7/16 in.lg., finish N.P.D. and black enam. head	single	C 4270
Y1/YA 4844	BOX Generator, C.N.	6.1/2 in. x 4.15/16 in. x 3 in.; hardwood; fitted with 2 terminals, inst., single, No.4, modified (Sec. Y3); for use with gen., C.N.	single	B 8029
Y1/YA 1885	Mk.1*, telephone set, F	Teak, metal-bound; without strap carrying, F; for use with tel. sets, F.Mks.1, 1* and 2	single	B 5255
Y1/YA 10763	BRACKET Mounting BU	G.P.O. patt.  M.S.plate bent at right angles; includes fixing screws; for supporting tel., No.246	single	C 8423



Y1/YA 10631	CC	For supporting tel.No.145; includes fixing screws	single	
Y1/YA 10764	CU	For supporting strips, fanning (N.I.V.)	single	
Y1/YA 10762	No. 15		single	
Y1/YA 10765	Telephone, No.12, black	For mtg. tel. without tray	single	
CAP				
Y1/YA 8288	Brush-holder, No.30	Moulded plastic cap with threaded Br.insert; used on machine, ringing, 24V., No.1	single	C 4270
Rubber sealing				
Y1/YA 8295	1.5/16 in. x 15/16 in., No. 1	For sealing keys; used on rack, tel. terminal, No.1	single	C 4270
Y1/YA 8305	Tapped 32 t.p.i., No.1	For sealing toggle switch on unit, alarm, No.1	single	
CAPPING				
Y1/YA 7664	Footrall	3 in. x 2.1/2 in. x 3/4 in.; hardwood; used on swbd., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 8352	Steel, No.3	G.P.O. patt.; in 15 in. lengths	single	
Y1/YA 3928	CARRIER Armature B, No.1	Soft iron plate with edges bent over and centre recessed to accommodate the armature; used on buzzers, F and T; the lugs on this carrier are turned up	single	C 4270
CASE				
Y1/YA 7390	Accessory, filled, test equipment, C.B. exchange	Packing case filled with boxes, battery test, No.1; cases, line test; con, double, No.17; con, test, No.4/60 B and No.4/60E; tel., hand, No.1 or No.5; for use with exch. C.B., multiple, W.D., unit type, "N" positions	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 3420	CASE - continued Coil and condenser, N 1616	G.P.O.patt.; includes 1 bracket, mounting, BH, BQ; 2 clips No.32; 1 coil, inductance, No.3/16; 1 coil, retardation, No.3416; 1 condenser, No.100; 1 condenser, No.102; 1 rectifier element, No.2/2A; 3 resistance coils, No.12, 200 ohms; used on unit, amplifying, No.23B	single	C 4270
Y1/YA 3063	Distribution, 40 wire	15 in. x 14.1/4 in. x 3.3/4 in.; G.P.O.patt.; for 20 pr. in and 20 pr. out	single	C 4270
Y1/YA 3714	Distribution, 80 wire	15.1/4 in. x 20.1/4 in. x 3.7/8 in.; G.P.O.patt.; for 40 pr. in and 40 pr. out	single	C 4270
Y1/YA 4016	Distribution, 160 wire	15.1/2 in. x 33 in. x 5.1/4 in.; G.P.O.patt.; for 80 pr. in and 80 pr. out	single	C 4270
Y1/YC 00646	Distribution, 240 wire	21.5/8 in. x 33 in. x 5 in.; G.P.O.patt.; for 120 pr. in and 120 pr. out	single	C 5687
Y1/YA 10881	No.30	G.P.O. patt.; wood case 4.1/2 in. x 7.1/4 in. x 6.1/4 in.; can accommodate 5 lever keys, vertical type	single	C 8423
Y1/YA 10882	No.31	G.P.O. patt.; wood case 6.1/2 in. x 7.1/4 in. x 8 in.; can accommodate 10 lever keys, vertical type	single	C 8423
Y1/YA 11398	No. 54	G.P.O. store; for gen., No.26 AN, 26 AP and 28 HN	single	C 9519
*Y1/YA 12268	Part No.1/SCA/20 green	G.P.O.patt., tel. case, used on tel., No.332, green	single	
*Y1/YA 12267	Part No.1/SCA/20, red	G.P.O.patt., tel. case, used on tel., No.332, red	single	

Y1/ZA 19010	Receiver, watch, D.L.R. No. 5	2 in. dia. x .885 in.; plastic moulding, fitted with soldering lug, screws, washers and lock-nuts	single	C 4270
Y1/ZA 22497	No. 5, without terminal	2 in. dia. x .885 in.; plastic moulding; used on transmitter, breast, Sound P., No. 2, Mk. 3	single	C 4270
Y1/YA 9057	Telephone, 1/SCA/17	G.P.O. patt.; case for tel., No. 332, black	single	C 5687
Y1/YA 9056	Telephone, 1/SCA/37	G.P.O. patt.; case for tel., No. 162, black	single	C 5687
Y1/YA 1705	Telephone attachment, headgear	8.1/4 in. x 7.1/2 in. x 4.1/2 in.; wood, fitted with webbing handle	single	B 3410
Y1/YA 8154	Telephone attachment, headgear, No. 2	7.1/2 in. x 3.13/16 in. x 6.3/4 in.; metal, with hinged lid; for use with tel. attachment, hdgr., double, No. 1. Mk. 5/1	single	B 4394 C 4270
Y1/YA 2873	Telephone, D, Mk. 5	9.3/4 in. x 4.3/8 in. x 6 in.; metal, with hinged lid and inner compartment	single	B 3410, C 4270
Y1/YA 9118	Wood, 30.1/2 in. x 23 in. x 20 in. deep	Transit case with screw-on lid for carrying R.E.H.I. box, spare parts, filled with mic. etc	single	
COIL				
Y1/YA 2369	Bridging No. 1E, W.D.	2.19/32 in. x 7/8 in. dia.; 300 ohms similar to G.P.O. patt.; No. 1E but with tpl. finish; used on swbds., F. and F., and swbds., U.C., civil line units	single	B 4804, B 4960
Y1/YA 3999	No. 1F	G.P.O. patt.; 500 ohms, tubular, 2.19/32 in. x 7/8 in. dia.	single	C 5687
Y1/YA 8855	No. 1G	G.P.O. patt.; 600 ohms, tubular, 2.19/32 in. x 7/8 in. dia.	single	C 5687
Y1/YA 8637	No. 1H	G.P.O. patt.; 750 ohms, tubular, 2.19/32 in. x 7/8 in. dia.	single	C 5687
Y1/YA 0459	Heat A. Green	G.P.O. patt.; for all teleg. and tel. contracts 0.3 amp. for 3 hrs. Res. 4.5-5.5, striking point 0.5 amp. 15-60 seconds	single	C 5687

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	COIL Heat - continued			
Y1/YA 3020 Y1/YA 7594	BB Dummy B	G.P.O. patt.; used for teleg. and tel. contracts G.P.O. patt.; metal stamping; replaces coils, heat, BB on protectors, H.C. and test, 40B only	single single	C 5687 C 5687
Y1/YA 7194 Y1/YA 7931	H 9A I/SCO/278	Similar to coil, heat, BB but tpl. finish G.P.O. patt.; 12 ohms; used on uniselector, No. 33C	single single	5687 C 4270
	CONCENTRATOR 5 line, C.D.	9 in. x 7.3/8 in. x 8 in.; cordless type switch unit, with grouping facilities; for use with coast defences; hardwood case. For components, see C.I.E.M.E. list E.S. 336	single	B 4105
Y1/YA 2707	6 line, No. 1	Used by Signal Centre Corps in trailer, 2 ton	single	
Y1/YA 10839	CONTACT, Fixed, switch, transmitter, breast (Sound P.), No. 1	Used on transmitter, breast (Sound P.), No. 1	single	C 4270
Y1/YA 4619				

COVER			
Y1/YA 5150	Assembly,vibrator,No.1	8.1/4 in.x 1.3/64 in.x 1.3/8 in.Br.cover with br.hinge and 1 stud,threaded No.6 B.A.fitted on front edge; used on vibrators,ringing, 12 or 24V.	single C 4270
Y1/YA 6205	Bell,No.13B	2 in.x 2 in.x 3/4 in.;metal cover used on bell, elec., No. 56A	single C 4270
Y1/YA 4425	Dial, No.1	Circular metal cover for socket,auto-dial, No.1 when auto-dial is not fitted; used on swbds. F. and F.	single C 4270
Y1/YA 7939	Finger,presel switch, No.1	3 in.x 3/4 in.x 1/32 in.; rubber(soft)black, tpl.grade; used on tel. sets, J	single C 4270
Y1/YA 3177	For socket, mouthpiece	Metal,2 in.dia.; for securing socket,mouthpiece on transmitter, breast	single C 4270
Y1/YA 5998	Front, transmitter, breast, No.23	Plastic moulding cover for terminal block; used on transmitter, No.23	single C 4270
Y1/YA 5093	Jack, No.2	2.5/16 in.x 1.1/16 in.x 9/32 in.; plastic moulding with "HANDSET JACK" moulded on front edge; used on tel.set,H, Mk.3 and tel.set,L	single C 4270
	Label, celestoid	0.16 in.thick; used on swbds.,C.B.,multiple, W.D., unit type	single C 4270
Y1/YA 7234	1 in.x 7/16 in.		single
Y1/YA 7235	1.3/16 in.x 1 in.		single
Y1/YA 7542	5.3/32 in.x 1.3/16 in.		single
Y1/YA 7589	5.5/16 in.x 1.7/32 in.		single
Y1/YA 7253	6.11/16 in.x 7/16 in.		single
Y1/YA 7254	7.1/2 in.x 1.3/16 in.		single
Y1/YA 7556	8.1/8 in. x 3/8 in.		single
Y1/YA 7236	10 in. x 3/8 in.		single
Y1/YA 7255	21.1/16 in.x 7/16 in.		single
Y1/YA 5297	Lamp,4-way,No.1	4.3/16 in.x 1 in.x 3/4 in.; plastic moulding; includes 4 transparent discs engraved 1 to 4, one securing screw	single C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7497	COVER - continued Moulded, telephone set, F, H.P.	Plastic moulding; similar to covers, moulded case but without diag. plate; used on tel, set F, H.P., No.1, Mk.2	single	C 4270
Y1/YA 8065	Stile bar, No.1	6.1/2 in. x 1.343 in. steel, .048 in. thick, with edges turned over and strengthening plate soldered on at each end; used on exch., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 4621	Terminal case, transmitter, breast, (Sound P), No.1	2.7/8 in. x 1.3/4 in. x 3/16 in.; plastic moulding; includes 4 No.6 B.A. screws captive in cover; used on transmitter, breast (Sound P) No.1	single	C 4270
*Y1/YA 12142 Y1/YA 8674	CRADLE Microphone Telephone, 1/SCR/1, black	Vitavox CN 184 G.P.O. patt	single single	C 5687
Y1/YA 5715	CUP, Lock No.4	13/32 in. dia. x 3/16 in.; Br; hole tapped and csk. for No.2 B.A.; part of lock, No.4; used on swbds., F. and F. and concentrators, 5 line, C.D.	single	C 4270
Y1/YA 6031	No.5	1 in. dia. x .064 in. thick; M.S.; centre hole tapped 1/4 in. B.S.W.; with 3 csk. holes for fixing; used with special winged screw for securing lids on units, D. of swbds., F. and F.	single	C 4270

Y1/YA 8835	CUP,Metal 2/SCU/1	G.P.O. patt	single	C 5687
*Y1/YA 12130	DESK,Stand,Microphone	Reslo type; 6.3/8 in.dia.	single	
Y1/YA 7422	DIAL,Automatic Dummy,for No.3,black	G.P.O. patt. Plastic moulding with metal backing plates; 3.1/8 in.dia.recessed for label,No.160;dummy, dials,auto,No.10 etc.; used on privacy equipt.	single	C 4270, C 8424
Y1/YA 1549	Dummy, No.4	Dummy, for dial, auto No.10	single	C 8423
Y1/YA 3154	No.10 F.A.	Fitted with number ring "F" and impulse wheel "A"; for non-director systems	single	C 4270
Y1/YA 10652	No.10 F.A.,chinese red		single	C 8423
Y1/YA 10651	No.10 F.A.,jade green		single	C 8423
Y1/YA 3505	S.S.,No.10 F.A.	Similar to No.10 F.A. but with stainless steel parts	single	C 4270
Y1/YA 2889	S.S.,No.10 L.A.	Fitted with number ring "L" and impulse wheel "A"; for use in director area	single	C 4270
Y1/ZA 28336	DIAPHRAGM,Inset,moving coil	1.3/4 in.dia.x .337 in.; bakelised paper; speech coil wound in 4 layers with No.46 S.W.G.enamelled copper wire	single	C 4270
Y1/YA 6170	DISC,Baseboard,No.1	1.7/32 in,dia.x 1/4 in.; Br.with 3 fixing holes 1/8 in.dia.csk.; used on swbds.,F.and F.	single	C 4270
	DOOR			
Y1/YA 6171	Case, No.1 L.H.	9.5/8 in.x 5.5/8 in.x 1/2 in.; teak; fitted with 1 bush, Br. No.11 and 2 hinges, strap,5 in., No.1; used on swbds.,F. and F.	single	C 4270
Y1/YA 6172	R.H.	9.5/8 in.x 5.5/8 in.x 1/2 in.; teak; fitted with 2 bushes,Br., No.11 and 2 hinges,strap,5 in.,No.1; used on swbds., F. and F.	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5716	DOOR - continued No.3	7.3/4 in.x 7 in.x 1/2 in.; teak; includes 2 brackets, lock, No.5; 2 hinges, br.2 in.x 1.1/4 in., No.1; used on concentrator, 5 line, C.D.	single	C 4270
Y1/YA 6210	DOWELL, Brass, 3/16 in.x 13/32 in., tapped 2 BA	1.1/4 in.x 5/8 in.x 1/8 in.; br.plate with 1/4 in. dia. pin, 7/16 in. long riveted to centre; used on swbds., F. and F.	single	C 4270, C5687
Y1/YA 7540	DRAWER, Metal battery test box	4.7/8 in.x 3.1/4 in.x 1.13/16 in.; M.S., No.22 S.W.G. and 16 S.W.G. less lamps and fuses	single	C 4270
Y1/YA 4198	EARTH BAR	6.1/2 in.x 5/8 in.x 3/16 in.; copper; used on frame, D. and P., 10 wire, Mk.3	single	C 4270
Y1/YA 8357	END BAR, Frame, M.D.	G.P.O. patt.; with 5 bolts and nuts; used on frame, M.D., O/480	single	C 4270
Y1/YA 7782	END PANEL ASSEMBLY, Section I.D.F. and C.T., combined	4 ft.6 in.x 3 ft.5.1/2 in.x 1 ft.3 in.; teak; used on exch., C.B., multiple, W.D., unit type	single	C 4270



Y1/YA 8188	EQUALISER,Type A,No.1	4 in.x 2.5/8 in.x 2 in.; circuit equaliser in metal case, fitted with 4 condensers, .0002 $\mu$ F, 1 condenser, .003 $\mu$ F and 3 resistors, 470K; used on training set, No. 5A	single	C 4270
Y1/YA 8473	EQUIPMENT MULTIPHONE, AD. 1594	G.P.O.patt.; comprises 1 switchboard; 2 units, amplifying; 2 receivers,H.G.; 2 transmitters, breast; 1 transit case; for A.A. use	single	C 5687
Y1/YA 2175	EXTRACTOR No.1	G.P.O. patt. Plier type for extracting coils,heat and caps, lamp; used with swbds.,magneto,multiple,300 line and swbds.,C.B.,multiple W.D.,unit type (maintenance test kits)	single	C 4270
Y1/YA 4000	No.6	For extracting lamp, No.4	single	
Y1/YA 7379	FANNING STRIP,Frames,M.D.	2 ft.11.11/16 in.x 2.1/2 in.x 3/4 in.; teak; with 60 holes,1/4 in.dia.; used on exch, C.B., multiple W.D.,unit type, "N" positions, complete station	single	C 4270
Y1/YA 7368	FLOOR BAR ASSEMBLY,Frames I.D.	Used on exch.,C.B.,multiple W.D.,unit type,"N" position, complete station 2 ft.8 in.x 1 ft.11.1/4 in.x 1.3/4 in.;consists of 4 angle irons 2 ft.8 in. long x 1.1/2 in.x 1.1/2 in.x 1/4 in.,riveted to 3 flat steel bars 1 ft. 11.1/4 in.x 1.1/2 in.x 1/4 in.	single	C 4270
Y1/YA 7380	M.D.	3 ft.7 in.x 1 ft.4 in.x 1.3/4 in.; consists of 7 angle irons,1 ft.4 in.long x 1.1/2 in.x 1.1/2 in. x 1/4 in.,riveted to 3 flat M.S.bars,3 ft.7 in. long x 1.1/2 in.x 1/4 in.	single	C 4270
*Y1/YA 12127	FOOT CONTROL	Without xform; model 2553	single	

## SECTION Y1

## CLASS 5605--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 8181	FRAME ASSEMBLY, No.1, telephone, hand	Spring steel wire (No.13 S.W.G.) approx. 0/A dim, 5.1/2 in. x 2.1/8 in. x .092 in. used on tel. hand, No.11	single	C 4270
Y1/YA 7940	FRAME Cover, finger pressel switch, No.1	3 in. x .75 in. x .25 in.; br. part of finger pressel switch, No.1; used on tel. set J	single	C 4270
Y1/YA 6726	I.D., 400 line, equipped	7 ft. x 2 ft. 8 in. x 1 ft. 11.1/4 in.; M.S. channel iron frame fitted with jumper rings; strips, connection; battery jack and jack strip	single	C 4270
Y1/YA 6725	M.D., 400 line, equipped	7 ft. 11.1/2 in. x 3 ft. 7.1/2 in. x 1 ft. 4 in.; M.S. frame with 7 verticals; fitted with 21 protector strips, 28 fuze mtgs., 1 jack strip, one 120 fuzes 1/2; used on swbd., C.B., multiple W.D., unit type	single	C 4270
Y1/YA 9107	Notice No.1	G.P.O. patt. Oxidized metal, 4.29/32 in. x 3.1/8 in.	single	C 5687
Y1/YA 9104	No.6	Metal, 8.5/8 in. x 3.1/2 in.	single	C 5687

	FRAME,D. and P. 10 wire Mk.1/1	Metal frame fitted with terminals, spring, No.1; incorporates 2 housings fitted with 2 socket contacts, 5 pr., No.1; can be built up horizontally and/or vertically into multiples of any number of frames. Includes 20 carbons, protector, No.14; 10 fuzes, No.28/2; 20 links, wire	single	B 2912, B5064
Y1/YA 2273				
Y1/YA 2275	1/5	Fitted with 2 socket-contacts, 5 pr., No.1, 1/5	single	
Y1/YA 2274	6/10	Fitted with 2 socket-contacts, 5 pr., No.1, 6/10	single	
Y1/YA 5724	Mk.3 6/10	Similar to Mk.1/1 but with welded steel framework	single	C 4270
Y1/YA 5717	Frame, steel	Welded steel framework for frame, D. and P., Mk.3	single	
Y1/YA 6562	Set	Similar to Mk.1/1 set but with welded steel framework (IL2657)	single	
Y1/YA 7717	FULLERPHONE, Mk.6	Tropical	single	C 4270
	GENERATOR			
Y1/YA 0662	B	400 ohms; 3 magnet; without handle, gen., No.1 or handle, gen., No.2	single	B 1782, B 8029
Y1/YA 2878	C	500 ohms; tpl. finish; fixing centres 3.1/8 in. x 1.1/16 in.; fitted with 1 No.4 B.A. screw for securing handle to spindle and 2 brushes, No.1, without handles, gen., Nos.1, 2 or 3	single	B 4389, B 8029
Y1/5805-99-100-1865	C, Mk.2	Bridging; normally open; swbd. mounted; 2.1/4 in. x 3.1/8 in. x 4.5/8 in. overall (Old Cat. No. Y1/YA 8458)	single	C 5687
Y1/YA 10838	CN, Mk.2	Similar to Mk.1 but fitted with gen., C, Mk.2 in place of Mk.1	single	C 8423
Y1/YA 2278	No.26A (W.D.)	500 ohms; similar to G.P.O. patt. No.26A but with tpl. finish; fitted with 2 brushes, No.1; without handle, gen., No.21; fixing hole centres 1.9/32 in. x 2.5/16 in.; wt. 2 lb.; used on swbds., F. and F., units C	single	B 4804, B 8029

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 3654	GENERATOR - continued No.26 AN	G.P.O.patt.; 4.1/4 in.x 7.1/8 in.x 6.3/8 in.; for table or wall fixing; comprises 1 gen., No.26A, 1 handle, gen. No.20	single	C 4270
Y1/YA 7905 *Y1/YA 8498 *Y1/YA 12004	No.26 AN "TPL" No.28 H.N. Hand	Tpl. version of gen., No.26 AN G.P.O. patt. Switchboard type 3.7/8 in. lg. x 2.3/8 in. w. x 3.1/8 in.h.	single single single	C 4270
Y1/YA 8103	GLAND,Rubber,15/32 in. O.D.x 7/32 in., No.1	15/32 in.dia.x 1/4 in.thick; moulded rubber; used on ampfr.,field tel.,No.1	single	C 4270
Y1/YA 8272	HANDLE ASSEMBLY,No.8	3.1/8 in.long;threaded 5/16 in.B.S.F.; wing nut handle; secures cover on supply unit,rectifier, No.19	single	C 4270
Y1/YA 6020	HANDLE Chest, No.1	M.S.; similar to "Bates" 4 in.chest handle; used on swbds.,teleprinter,15 line and 40 line	single	C 4270
Y1/YA 5479	Flush type,No.1	5.1/16 in. x 2.3/4 in. O/A dim.; Br.; used on swbd., F. and F. units C and D	single	C 4270
Y1/YA 0664	Generator No.1	Lever type; bayonet fitting socket; barrel 27/32 in. long; lever 1.11/16 in.long; handle 5/8 in.long; for use with gen., B or C on tel.sets,F.and H.	single	B 1782,B 8029

Y1/YA 0665	No.2	Swivelling lever type with adjustable nut; bayonet fitting socket; barrel 1.3/16 in.long; lever 1.11/16 in.long; handle 1.5/16 in long; for use with gen., B or C on swbds.,U.C.,common apps. unit	single	B 3011
Y1/YA 3719	No.3	Folding handle with securing clip; barrel 2.3/32 in.long; lever 1.5/8 in.long; handle 1 in.long; includes 1 securing screw, csk.hd., 2.3/32 in.long; tapped,No.4 B.A.; for use with gen., C on tel. set, L	single	B 4476
Y1/YA 6809	No.3A	Modified version of handle, gen., No.3; dispenses with sliding clip; used on tel,set, L	single	C 4270
Y1/YA 7875	No.5	Similar to handle,gen.,No.3A, but fitted with waterproof gland washer; used on tel.set,J	single	C 4270
Y1/YA 4675	No.20	G.P.O.patt.; screwed No.0 B.A.; spindle 3/4 in. long; used on gen.,Nos.2A,8A,13F,26A,26AN	single	C 4270
Y1/YA 2279	No.21	G.P.O.patt.; lever type; threaded No.0 B.A.socket; barrel 1.13/32 in.long;lever 1.1/2 in.long; handle 1.5/16 in.long; for use with gen., No.26A W.D.	single	B 4804,B 8029
Y1/YA 2636/3	Telephone,hand B	8.5/8 in.x 2.1/2 in.x 1.1/2 in.; plastic; with metal inserts and con. assy.moulded in position; part of tel.,hand, No.5	single	C 4270
Y1/YA 5131	No.2	9 in.x 2.1/2 in.x 2.1/4 in.; plastic; with metal inserts and con.assy.moulded in position; used on tel.,hand,(Sound P.),No.2	single	C 4270
Y1/YA 5832	No.2A	Plastic;with metal inserts and con.assy. moulded in position,fitted with springs,cover plate and hooks,cord; part of tel.,hand, No.6 and 6A	single	C 4270
Y1/YA 7960	No.10	Plastic; with metal inserts and connections moulded in position; used on tel.set, J	single	C 4270
Y1/YA 6752	Telephone,No.184B,black	Plastic; with metal inserts and connections moulded in; used on tel.,No.184B, black	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6211	HINGE Bar, No.1	15.9/16 in.x 3/8 in.x 3/8 in.;M.S.sq.section bar hinged at one end by hinge flap,1.3/8 in. x 1 in.x .080 in.; used on swbd.,F.and F., unit C	single	C 4270
Y1/YA 5719	Brass,2 un.x 1.1/8 in., No.1	Used on concentrator, 5 line, C.D.	single	
Y1/YA 6040	Piano, 1.1/2 in.x 20 in.,No.1	Br.; used on swbd., F. and F., unit,C	single	
Y1/YA 6755	Strap,4 in.,No.1	M.S.; used on tel. set,F, high powered,No.1,Mk.2	single	
Y1/YA 6069	Strap,5 in.,No.1	M.S.; with special drillings; used on swbd.,F.and F., 20, 40 and 60 line,Mk.2	single	
Y1/YA 6043	Strap,6 in.x 3.1/2 in., No. 1	M.S.6 in.strap hinge with one end shortened to 3.1/2 in.; used on swbd.,F.and F.,unit C	single	
Y1/YA 6034	Strap,10 in.,No.1	M.S.; used on swbd.,F.and F.,unit D	single	
Y1/YA 5151	Vibrator,No.1	Br.piano hinge 3/4 in.wide x 8.5/8 in.long; used on vibrators,ringing,12 and 24V.	single	
Y1/YA 7543	HOLDER Label,10.3/32 in.3/8 in.	Br.;includes label, paper, white and guard label, cellestoid; used on swbd.,C.B.,multiple W.D., unit type	single	C 4270

Y1/YA 7261	Strip, designation, No.1	1 ft.9.1/2 in.x 9/16 in.x 1/8 in.; sheet steel .028 in.thick; used on swbd.,C.B.,multiple W.D., unit type	single	C 4270
Y1/YA 7262	Strip, designation, No.2	6.15/16 in.x 9/16 in.x 1/8 in.;sheet steel .028 in. thick;used on swbd.,C.B.,multiple W.D.,unit type	single	C 4270
Y1/YA 5999	Transmitter, breast, No.23	G.P.O.patt.; plastic; part of transmitter, No.23	single	C 4270
HOOK				
Y1/YA 5138	Cord, No. 1	25/32 in.x 5/16 in.x 5/16 in.;Br. cord anchorage in tel., hand,(Sound P.), No.2	single	C 4270
Y1/YA 0778	Guide, large	Enam. with 1.1/4 in.open eye; threaded No.12 wood screw for 1.1/4 in.; to support and insulate light cables,electric	single	21669,A 205
Y1/YA 3629	No.8	G.P.O.patt.; M.S.; length 1.1/2 in.; I.D. of hook 5/16 in.; used on swbds.,F. and F. and swbd., teleprinter,15 line	single	C 4270
Y1/YA 7483	HOOK,BOLT,Mounting, runway,frame, I.D.	Steel "J" bolt, 5/16 in.dia.x 3.1/4 in.long, threaded 5/16 in.B.S.W.; used on frame,I.D., swbd., C.B.,multiple W.D.	single	C 4270
Y1/YA 9109	HOWLER, No.3	G.P.O.patt.; for C.B. exchanges	single	C 5687
*Y1/YA 12592	IRON,Chimney corner	G.P.O.patt.; for use on overhead tel, and tel. construction	single	
KEYBOARD END PIECE				
Y1/YA 8061	S.C.T.,C.B.exchange	1 ft.5 in.x 3 ft.x 1.1/8 in.x 1 in.; hardwood; cable terminating section,keyboard,end-piece; used on exch, C.B.,multiple W.D.,unit type	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 8064	KEYBOARD END PIECE - continued Sec., I.D.F. and C.T. combined	1 ft.5 in. x 3 ft. x 1.1/8 in. x 1 in. hardwood; keyboard end-piece for sect., cable terminating with I.D.F. and end panel; used on exch., C.B., multiple W.D., unit type	single	
	KEY-MOUNTING			C 4270
Y1/YA 3948	J	G.P.O. patt.; non-standard size; fixing centres 1.625 in.	single	
Y1/YA 8263	K	2.1/8 in. x 3/4 in.; G.P.O. patt.; fixing centres 1.3/4 in.; includes 2 fixing screws	single	
Y1/YA 5799	KAA	4.1/4 in. x 1.1/16 in.; G.P.O. patt.; fixing centres 3.7/8 in.; for 2 keys	single	
Y1/YA 5818	NA	2.1/8 in. x 3/4 in.; G.P.O. patt.; fixing centres 1.3/4 in.; includes two fixing screws	single	
Y1/YA 0857	P	2.1/8 in. x 1 in.; G.P.O. patt.; fixing centres 1.3/4 in.; includes two fixing screws	single	
Y1/YA 5442	P(W.D.), No.2	Key-mounting, P, engraved "CLEAR ALARM" and "OPERATE"; used on swbd., command, 200 line	single	
Y1/YA 4929	Q	2.5/8 in. x 1.1/8 in.; G.P.O. patt.; fixing centres 2.1/4 in.; includes 2 fixing screws	single	



Y1/YA 8126	S	2.5/8 in. x 3/4 in.; G.P.O. patt.; fixing centres 2.1/4 in.; includes 2 fixing screws	single	
Y1/YA 3011	U	2.1/8 in. x 1.1/16 in.; G.P.O. patt.; fixing centres 1.3/4 in.; includes 2 fixing screws	single	
Y1/YA 2462	V	2.1/8 in. x 1.1/8 in.; G.P.O. patt.; fixing centres 1.3/4 in.; includes 2 fixing screws	single	
Y1/YA 5723	KEY-PLATE, Filler, No.1	2.1/8 in. x 3/8 in., key-mounting dummy; used on concentrators	single	C 4270
	KEY			
Y1/YA 0846	Draw vice, No.2	G.P.O. patt.; steel; for vice, draw, No.2	single	5215, B 5064
Y1/YA 1896	Mouthpiece	Metal stud, for removing mouthpiece from tel., hand	single	B 1782, C 4270
	No.	In the detail for keys No. B. signifies Break C. signifies Change-over(B before M) K. signifies Change-over(M before B) L. signifies Locking M. signifies Make N. signifies Non-locking S. signifies stop		
		The first side is that with the springs nearest to the frame		
Y1/YA 2858	No.1 (W.D.)	Lever key, vertical type; 1st side L, 4C; 2nd side L, 4C	single	B 4805, B 5582
Y1/YA 7967	No.5	G.P.O. patt.; plunger type, NL, 1M	single	C 4270
Y1/YB 00933	No.5 (W.D.)	Lever key, vertical type; 1st side L, 4C, 2K; 2nd side L, 4C; used on app., V.F., teleg., 3 channel, Duplex	single	C 4270
Y1/YA 7132	No.8 (W.D.)	Lever, vertical type; 1st side L, 2K; 2nd side NL, 3C; used on swbd., position, magneto, $\frac{10+50}{60}$ , No.1	single	C 4270

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7133	KEY - continued No.9 (W.D.)	Lever,vertical type; 1st side L, 5M; 2nd side NL, 2C,1M; used on swbd.,position magneto, 10+50, No.1 60	single	C 4270
Y1/YB 04605	No.11 (W.D.)	Lever, vertical type; 1st side S; 2nd side L, 2K, L, 2C; used on app.,C.T.(1+1), No. 2W (active)	single	C 4270
Y1/YA 8152	No.12 (W.D.)	Lever, vertical type; with modified cam; 1st side stopped; 2nd side L,4C; used on rack,tel. terminal, No.1	single	C 4270
Y1/YA6337	No.72	G.P.O.patt.; lever,vertical type; 1st side NL, 2C; 2nd side S	single	B 5064,C 4270
Y1/YA 6339	No.73	G.P.O.patt.; lever,vertical type; 1st side S; 2nd side L, 4C	single	A 567,C 4270
<i>Y1/YA 3119</i>	<i>No.171</i>	<i>G.P.O.patt.; lever,vertical type; 1st side N, 2C; 2nd side L,3C</i>	<i>single</i>	<i>B 5882,C 4270</i>
<i>Y1/YA 8204</i>	<i>No.194</i>	<i>G.P.O.patt.; lever,vertical type; 1st side S; 2nd side L, 2K</i>	<i>single</i>	<i>C 4270</i>
Y1/YA 3121	No.198	G.P.O.patt.; lever,vertical type; 1st side L, 4C; 2nd side L,4C	single	B 5064,C 4270
Y1/YA 7139	No.204 (W.D.)	Lever,vertical type; 1st side L, 2M; 2 nd side N, 2C	single	C 4270

Y1/YA 7213	No.206	G.P.O.patt.; lever,vertical type; 1st side N, 3C; 2nd side L, 3C	single	C 4270
Y1/YA 3833	No.208	G.P.O.patt.; lever,vertical type; 1st side L, 2C; 2nd side L, 4C	single	B 5064,C 4270
Y1/YA 7212	No.219	G.P.O.patt.; lever key,vertical type; 1st side N, 2C; 2nd side L, 2K	single	C 4270
Y1/YA 7549	No.232	G.P.O.patt.; lever key,vertical type; 1st side N, 3C; 2nd side L, 2C	single	C 4270
Y1/YA 11082	No.242	G.P.O.patt.; lever type,1st side N, 3C, 2nd side L, 2C, 2M, 2B	single	C 8423
Y1/YA 7252	No.245 (W.D.)	G.P.O. patt.; lever key,vertical type; 1st side N, 2C, 1M; 2nd side N, 2C, 1M	single	C 4270
Y1/YA 7215	No.263	G.P.O.patt.; lever key, vertical type; 1st side L, 2K; 2nd side L, 2K	single	C 4270
Y1/YA 7217	No.265	G.P.O.patt.; lever key,vertical type; 1st side N, 2C; 2nd side N, 2C. 2M	single	C 4270
Y1/YA 0907	No.279	G.P.O. patt.; plunger type, L, 2C	single	B 3011,B 5064
Y1/YA 6056	No.282	G.P.O. patt.; lever key,vertical type; 1st side N, 3C; 2nd side L, 2K, 1C	single	C 4270
Y1/YA 6057	No.286*	Similar to G.P.O. patt.; No.286 but with special spring setting; lever key,vertical type; 1st side N, 2C, 1M; 2nd side L, 4M	single	C 4270
Y1/YA 7219	No.293	G.P.O. patt.; lever key,vertical type; 1st side N, 2C; 2nd side L, 4K	single	C 4270
Y1/YA 7220	No.295	G.P.O. patt.; lever key,vertical type; 1st side N, 4C; 2nd side L, 6C	single	C 4270
Y1/YA 7470	No.297	G.P.O. patt.; lever key,vertical type; 1st side L, 2C; 2nd side L, 6C	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 8285	KEY - continued No.301,modified	Similar to G.P.O. key No.301 but with a modified cam; lever key,vertical type; 1st side N, 3C; 2nd side L, 4C; for use on unit,line, 3 cct.,No.1	single	C 4270
Y1/YA 10031 Y1/YA 11083	No.302A No.307	G.P.O. patt.; plunger type; N, 1K G.P.O. patt.; lever type; 1st side S, 2nd side L, 2C 4B	single single	C 8423 C 8423
Y1/YA 11251	No.317	G.P.O. patt.; lever key,vertical type, 1st side 1K	single	C 8635
Y1/YA 11252	No.318A	G.P.O. patt.; plunger type; 1K	single	C 8635
Y1/YA 11253	No.318B	G.P.O. patt.; plunger type; 1C	single	C 8635
Y1/YA 10953	No.319	G.P.O. patt.; lever type, 1st side S,2nd side L, 8B	single	C 8423
Y1/YB 03461	No.837	Plunger type key, N,2M; includes handle; for use on signalling equip. No.10	single	C 4270
	S.C.	Single current; on wood base		
	Unmounted	Keys, S.C., minus wood base; for baseboard,S.C.	single	B 5580
Y1/YA 0871	W.D.		single	
Y1/YA 0862	G.P.O.		single	
Y1/YA 1860	Signalling,No.1	Double contact sending key,mounted on bakelised fabric base,2.1/8 in.x 1.5/8 in.approx.	single	B 5882,C 4270
Y1/YA 2216	Tension ratchet	G.P.O. patt.; for ratchets and tongs,Nos.2,and 5	single	24567,B 5064

Y1/YA 11084	KEYSENDER, No. 5 FA	G.P.O. patt.; for use in non-directory areas as an alternative to dial, auto., No. 10 at a busy P.B.X.	single	C 8423
	KNOB			
Y1/YA 0630	Control, No. 1	1.3/8 in. dia. x 11/16 in.; plastic; used on fullerphones, Mk. 4, 4/1 and 5	single	B 6339
*Y1/YA 12181	Painton type K20		single	
Y1/YA 5418	Switch, telephone, No. 1	11/16 in. dia. x 23/32 in.; M.S.; engraved "CB" on top surface; used on tel. set, L and tel. set, H, Mk. 3	single	C 4270
	LABEL			
Y1/YA 3000	Enamelled, for frames, D and P 10 wire, Mk. 2	7 in. x 1 in.; metal; stoved enam. white	single	C 4270
Y1/YA 6052	Engraved, "ANSWER"	5/8 in. dia. x 1/8 in.; ivory; engraved "ANS" and filled in black; used on swbd., F. and F.	single	C 4270
Y1/YA 6051	Engraved, "CALL"	Ivory; engraved "CALL" and filled in black; used on swbds., F. and F.	single	C 4270
Y1/YA 6045	Engraved, "COUPLE KEY"	5/8 in. dia. x 1/8 in.; ivory; engraved "COUPLE KEY" and filled in black; used on swbds., F. and F.	single	C 4270
Y1/YA 6044	Engraved, "COUPLE OPER"	5/8 in. dia. x 1/8 in.; ivory; engraved "COUPLE OPER," and filled in black; used on swbds., F. and F.	single	C 4270
Y1/YA 6063	Engraved, "COUPLING"	1.3/4 in. x 1/2 in. x 1/16 in.; S.R.B.P.; engraved "COUPLING" and filled in white; used on swbds., F. and F.	single	C 4270
Y1/YA 6047	Engraved, "DIAL"	5/8 in. dia. x 1/8 in.; ivory; engraved "DIAL" and filled in black; used on swbds., F. and F.	single	C 4270
Y1/YA 6064	Engraved, "GENERATOR JACK"	1.3/4 in. x 1/2 in. x 1/16 in.; S.R.B.P.; engraved "GENERATOR JACK" and filled in white; used on swbds. F. and F.	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6046	LABEL - continued Engraved, "N.A."	5/8 in.dia.x 1/8 in.; ivory; engraved "N.A." and filled in black; used on swbds., F. and F.	single	C 4270
Y1/YA 6062	Engraved, "PHONES AND MIC."	1.3/4 in.x 1/2 in.x 1/16 in.; S.R.B.P.; engraved "PHONES MIC." and filled in white; used on swbds., F. and F.	single	C 4270
Y1/YA 6049	Engraved, "RING"	5/8 in.dia.x 1/8 in.; ivory; engraved "RING" and filled in black; used on swbds., F. and F.	single	C 4270
Y1/YA 6048	Engraved, "RING BACK"	5/8 in.dia.x 1/8 in.; ivory; engraved "RING BACK" and filled in black; used on swbds., F. and F.	single	C 4270
Y1/YA 6050	Engraved, "SPEAK"	5/8 in.dia.x 1/8 in.; ivory; engraved "SPEAK" and filled in black; used on swbds., F and F.	single	C 4270
Y1/YA 6053	Engraved, "TEST"	5/8 in.dia.x 1/8 in.; ivory; engraved "TEST" and filled in black; used on swbds., F. and F.	single	C 4270
Y1/YA 7728	Indicator, No. 1, transparent	21/32 in.x 23/64 in.x .02 in.; plastic; transparent used with indicators, M.R., No. 4A on swbd., mag., 10 line, W.D.	single	C 4270
Y1/YA 5112	Indicator, No. 1, white	21/32 in.x 23/64 in.x .02 in.; celastoid; white, used on indicators, M.R., No. 3 and No. 2	single	C 4270
Y1/YA 6061	Jack, No. 1	12.1/2 in. long x 3/4 in. wide; ivory; engraved with 11 lines 1 in. apart; filled in black; used on swbds., F. and F.	single	C 4270

Y1/YA 0915	Line A	Ash, for identifying field teleg. and tel.lines <i>Indented hex., hole in apex; for Lines of Communication</i>	single <i>single</i>	17915,B 2269
Y1/YA 0916	B	<i>Pointed oblong, hole in base; for G.H.Q.lines</i>	<i>single</i>	
Y1/YA 0920	F	<i>Triangle, hole in apex; for Infantry Battalion lines</i>	<i>single</i>	
Y1/YA 0921	G	<i>Square, hole in centre of one side; for Royal Horse Artillery and Field Artillery Brigade lines</i>	<i>single</i>	
Y1/YA 0922	H	<i>Square, hole in one angle; for Heavy and Medium Artillery Brigade lines</i>	<i>single</i>	
Y1/YA 0923	J	<i>Triangle, hole in centre of base; for A.A.Group lines and Royal Artillery Survey Company</i>	<i>single</i>	
Y1/YA 0924	K	<i>Rhomboid, hole in centre of long side; for Battery lines</i>	<i>single</i>	
Y1/YA 0925	L	<i>Indented oblong, hole in centro of unindented end; for Air M'ormation Sig.</i>	<i>single</i>	B 2269
Y1/YA 9317	Plastic, 3.1/4 in. x 1.5/8 in.	For use in identifying army tel. and teleg. lines	single	C 8181
Y1/YA 7339	No. 55, green	1/2 in. x 3/8 in.; G.P.O. patt.; with 2 fixing pins	single	C 4270
Y1/YA 4221	No. 105, white	5/16 in. x 11/16 in.; G.P.O. patt.; metal frame, with celluloid inset; used with jack, No. 505BR	single	C 4270
Y1/YA 8343	No. 129 Black	G.P.O. patt.; used on key, No. 5	single	C 4270
Y1/YA 8344	Green		single	
Y1/YA 8365	Neutral		single	
Y1/YA 8345	Red		single	
Y1/YA 7198	No. 153	1.1/4 in. x 3/4 in. x 1 in.; G.P.O. patt.; angle type; used with protectors and H.C., 40 B	single	C 4270
Y1/YA 7429	No. 160DA	1.37/64 in. dia.; G.P.O. patt.; paper disc, for dials, auto.	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6423	LID Box,terminal and inset, No.1	6 in.x 4.1/8 in.x 3/8 in.; softwood lid; used on L.S.,tel.,No.4	single	C 4270
Y1/YA 6238	Front,case,D,No.1	21 in.x 18.1/4 in.x 5/8 in.; teak; includes bag, canvas, No.3; plate,No.6; plate,No.96; and strip, felt, No.7; used on swbd., F.and F., units, D	single	C 4270
Y1/YA 5681	No.3	Similar to lid, No.2 but is riveted to the hinge which is secured to the frame; part of frame, Fullerphone, Mk.4/1	single	C 4270
Y1/YA 4779	LINK Connection,No.1	1.1/16 in.x 1/4 in.x 1/2 in.; br.plate,with 2 Br. pins, 1/2 in. long x .115 in.dia.riveted to it; used on swbd., F. and F.	single	C 4270
Y1/YA 8236	U,15/32 in.,No.1	Br., 1/8 in.dia.,15/32 in.centres,1 in.long; used on drive and monitor units,S.S.B.,No.1	single	C 4270
Y1/YA 1057	Wire	G.P.O.patt.; U link,hard drawn copper wire,tinned, 0.092 in. dia.,1/2 in.span; for use in bridging test points on apps. of G.P.O.patt.	single	24851,A 9252



Y1/YA 5123	LOCK No.4	Screw type lock on keyboard,consisting of br. right-angle bracket,tapped,No.2 B.A.; screws, special 2 B.A.,csk.hd.,br., 1.1/4 in. and screw cup, br., 13/32 in.dia.x 3/16 in.,tapped 2 B.A.; used on swbd., F. and F.	single	C 4270
Y1/YA 5726	No.5	Screw type lock; includes bracket,lock,No.5; cup, lock, No.4; screw lock, No.5,special; used on concentrator, 5 line, C.D.	single	C 4270
Y1/YA 3127	LOOP,For band,transmitter, B.P.,slotted hole	G.P.O.patt.;detachable loop for repairs of all types of B.P. transmitters	single	C 4270
Y1/YA 6940	MACHINE,Ringing 2.1/2 watt,type P9/G7	48V.,D.C.input and 75V.17-23 c/s.output; used on swbd.,C.B.,multiple,W.D.,unit type	single	C 4270
Y1/YA 8091	24 volt,No.1	24V.,D.C.input,75V. 17-23 c/s.output; used on rack,tel.,terminal,No.1,equipped	single	C 4270
Y1/YA 5447	MARKER,No.12	G.P.O.patt.; wire guard type,5/8 in.high; used on swbd.,command,200 line	single	C 4270
	MOUNTING			
Y1/YA 1853/5	Condenser No.4	1.3/4 in.x 3/4 in.x 1/4 in.; plastic moulding; used on tel. set,D,Mk.5	single	C 4270
Y1/YA 3658	No.5	Plastic plate fitted with clips to hold and connect tubular type condenser; used on tel. sets, F.Mk.1/1 and Mk.2	single	C 4270
Y1/YA 4220	Dial,automatic No.9	G.P.O.patt.; sloping top; mounted vertically or horizontally as required; includes 5 way pin, socket con. 2 screws for fixing	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	MOUNTING			
Y1/YA 4424	Dial, automatic-continued No.9, incomplete	Similar to No.9 less the socket; used on swbds., F. and F.	single	C 4270
Y1/YA 7141	No.13, with cord	Similar to mtg. dial, auto., No.13, with the addition of cord, inst., No.5/19E, 2.1/2 in.	single	C 4270
Y1/YA 7195	Fuse, tropically finished; No.4001	A mtg. to take fuse, No.1/2; used on frames, M.D., 400 line	single	C 4270
Y1/YA 4168	Fuse clip	5.1/8 in. x 1/2 in. x 1/4 in.; plastic strip for mtg. fuse clips on frames, D. and P., 10 wire	single	C 4270
Y1/YA 6349	Indicator, No.130/10A	10.5/16 in. x 1 in.; G.P.O. patt.; used on swbd., command 200 line	single	C 4270
Y1/YA 4663	Induction coil for tel. set, F	Mtg. for induction coil No.21; comprises M.S. housing, contact plate and cable form	single	C 4270
Y1/YA 7890	No.151/1A	3.11/16 in. x 1.1/2 in.; G.P.O. patt.	single	C 4270
Y1/YA 7193	Protector, H40	Mtg. for carbon, protector, No.14, Mk.2; used on frame, M.D., 400 line	single	C 4270
Y1/YA 3364	Resistor, No.1	1.15/32 in. x 1.7/8 in. x 1/16 in.; plastic board; mounts 8 soldering tags; used on tel., L.S., No.2, set	single	C 4270
	Runway			
Y1/YA 7374	Frame, I.D.	Consists of 2 cable runways 2 ft.2.1/2 in. x 1 ft.3 in. with fittings; used on exch., C.B., multiple, W.D., unit type, "N" positions	single	C 4270

Y1/YA 7384	Frame, M.D.	Consists of 1 cable runway 3 ft.9 in.x 1 ft.3 in. and fittings; used on exch., C.B., multiple, W.D., unit type, "N" positions, complete stations	single	C 4270
Y1/YA 4169	Securing, carbon spring	6.3/8 in.x 1/2 in.x 5/16 in.; plastic strip; part of frames, D and P., 10 wire	single	C 4270
Y1/YA 4170	Terminal Inst. side	6.3/8 in.x 1 in.x 5/16 in.; plastic strip; part of frames, D and P., 10 wire	single	C 4270
Y1/YA 4171	Line side	6.3/8 in.x 1 in.x 5/16 in.; plastic strip; part of frames, D and P., 10 wire	single	C 4270
Y1/YA 1853/6	No.1	2.5/16 in.x 1.3/32 in.x 1/2 in.; plastic moulding; engraved L1 and L2 or E; used on tel.set, D, Mk. 5	single	C 4270
MOUTHPIECE				
Y1/YA 5869	A	Min.dia. .555 in.x max. dia. 1.23/32 in.x .070 in. thick; rubber, horn type; used on transmitters, breast, sound P., No.2, Mks.1 and 2; tel., head and breast, sound P., No.2 and No.2A	single	C 4270
Y1/YA 5132	B	2.11/16 in.dia.x 1.1/4 in.; plastic moulding; face drilled with 21 holes; used on tel., hand, sound P., No.2; tel., hand, No.4, No.5 and No.6; tel. sets, F, high powered, No.1, Mk.2	single	C 4270
Y1/YA 2741	No.6A	Horn-shaped, screwed end; fitted with clip for securing to transmitters, breast, No.1	single	B 3410, B 5882
Y1/YA 3273	Clip	1.3/16 in.x 3/8 in.x .02 in.; Ni.Sil.; used on mouthpieces, No.6A for securing to transmitter, breast, No.1	single	C 4270
*Y1/YA 12263	No.15. green	G.P.O. patt. for handsets.(Tel.No.164,184 etc.)	single	
*Y1/YA 11974	No.15. red	G.P.O. patt. for handsets.(Tel.No.164,184)	single	
Y1/YA 7689	No.16	G.P.O. patt.; used with transmitter, No.22		C 4270

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5982	MOUTHPIECE - continued No.19 Telephone	G.P.O. patt.	single	C 4270
Y1/YA 1897	Hand, No.1	Similar to mouthpiece, "B" but with 8 slots instead of holes; slotted bakelite, used on tel. hand No.1	single	B 1782,C 4270
Y1/YA 4624	Transmitter,breast (sound powered), No.1	2.1/2 in.dia.x 1.3/4 in.with 1.5/16 in.dia centre hole; plastic moulding; used on transmitter, breast (sound P.), No.1	single	C 4270
Y1/YA 8104	NUT Gland, .578 in.long 26 t.p.i., No.1	M.S.hex.; 19/32 in.across flats x .578 in.long; includes 2 glands, rubber fitted in position; used on ampfr.,field tel.,No.1	single	C 4270
Y1/YA 8105	Gland, .578 in.long, 32 t.p.i.,No.1	M.S.hex.; 19/32 in.across flats x .578 in.long; includes 2 glands, rubber fitted in position; used on ampfr., field tel., No.1	single	C 4270
Y1/ZA 10043	Gland,moulded,No.1	Plastic moulding	single	C 4270
Y1/YA 6456	Hexagon,bell set,No.1	G.P.O. patt.; oxidised headnut	single	C 4270
Y1/YA 3236	Plunger	Br., 1/4 in.B.S.F.special locknut; used on tel. sets, F, Mks. 1 and 2	single	C 4270

Y1/YA 6214	Round Special, 2 B.A., No. 2	Br. knurled and tapered; used on swbd., F. and F., units C and units D	single	C 4270
Y1/YA 7432	Special No. 2 B.A., No. 6	9/32 in. dia. x .437 in. Br., round, diamond knurled; used on swbd., mag., 10 line, W.D.	single	C 4270
Y1/YA 5833	No. 8	11/32 in. long x .269 in. dia. slotted csk. hd. x .189 in. shank; tapped No. 5 B.A. x 1/4 in. deep; used on tel., hand, Nos. 2 and 2A	single	C 4270
Y1/YA 4014	Support, lid, No. 1	1/2 in. dia. x 1/4 in. thick; br., No. 1 B.A., knurled	single	C 4270
Y1/YA 10705 *Y1/YA 12209	OSCILLATOR No. 23A No. 61A	G.P.O. patt Portable, 1K c/s. genr. output; continuous or interrupted at 2 or 5 p.p.s. 24V. operating from Batteries Secy. portable No. 14	single single	C 8423
Y1/YA 6743	PAD, Valve, No. 1	3.15/16 in. x 2.15/32 in. x 11/16 in.; metal cover lined with 5/16 in. felt; used on tel. set, F, high powered, No. 1, Mk. 2	single	C 4270
Y1/YA 1853/7	PANEL Component, No. 2	9.5/8 in. x 4.1/8 in. x 1/8 in.; plastic; includes buzzer housing and plug connections; part of tel. set, D, Mk. 5	single	C 4270
Y1/YA 7887	Exchange line	M.S. panel with 5 jacks, M.R., No. 2 and 5 indicators, M.R., No. 3; used on swbd., mag., $\frac{10+50}{60}$	single	C 4270
Y1/YA 7258	Fuse No. 4	6.15/16 in. x 2.5/16 in. x 3/8 in.; ebonite; fitted with earth and bus-bar assy., alarm bar and terminal for mounting 10 fuses 31/2; used on swbd., multiple, W.D., unit type	single	C 4270

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	PANEL			
Y1/YA 8089	Fuse - continued No.7	Ebonite panel with mounting and cover; includes 9 fuses, 31/2	single	C 4270
Y1/YA 7670	Indicator,M.R.,5 way,No.1	9 in.x 2.23/64 in.x No.12 S.W.G.; M.S.; mounts 5 indicators, M.R.,No.1; includes batten assy.and 4 special screws;used on swbd.,F.and F., units A and A/J	single	C 4270
Y1/YA 8106	Link and resistor,No.1	Bakelised Fabric panel 3.1/2 in.x 2.1/4 in.x .062 in.with 6 special tags; used on ampfr., field tel., No. 1 tapped 4BA. and 8 eyelet tags	single	C 4270
Y1/YA 8098	Plug, No.2	18.1/2 in.x 11 in.x No.16 S.W.G.; M.S.; fitted with 22 miniature multi-contact plugs; used on rack, tel. terminal., No.1	single	C 4270
Y1/YA 4780	Socket,No.1	7.7/8 in.x 1.3/8 in.x 1/2 in.; plastic; fitted with cable form, 2 M.S.angle brackets and 43 sockets to accept plugs,jumper,single,No.2; used on swbd.,F and F.,units A/J,Mk.2	single	C 4270
Y1/YA 6690	Superposing unit, 1 transformer	4.1/4 in.x 3.5/8 in.x 1/8 in.; plastic laminated board; drilled and engraved for components; used on superposing units, 1 transformer	single	C 4270

*Y1/YA 12102	Tag	Motor battery,Minifon recorder model 54	single	
Y1/YA 7437	Terminal Engraved "Line-L2 or earth-alarm"	12.3/16 in.x 2.3/16 in.x 1/4 in.; plastic; engraved and drilled; used on swbd.,mag., 10 line W.D.	single	C 4270
Y1/YA 5593	Lamp and switch control unit,No.2,Mk.2	5.5/16 in.x 2.3/4 in.x 3/16 in.; plastic panel fitted with terminals,lampholders and switches	single	C 4270
Y1/YA 4781	No.5	8.1/4 in.x 2.1/4 in.x 5/16 in.; plastic; drilled and engraved; used on swbd.,F.and F., units A/J, Mk.2	single	C 4270
Y1/YA 4782	No.6	8.1/4 in.x 2.1/4 in.x 5/16 in.; plastic; used on swbd., F.and F.,units A/J, Mk.1	single	C 4270
Y1/YA 4946	No.8	3.5/16 in.x 2.1/4 in.x 1/8 in.; ebonite; mounts 8 terminals, inst., slotted,single,No.4,small (Sec.Y3) and 1 ebonite block; used on swbd., U.C.,civil line units, Mk.1/1	single	C 4270
Y1/YA 4664	PARTITION,Moulded case, telephone,F	3.11/16 in.x 3.7/32 in.x .07 in.thick; plastic; drilled with 2 holes,csk.,for No.4 B.A.screws; partition for battery compartment of tel.set, F.and tel.set,F.,high powered,No.1,Mk.2	single	C 4270
Y1/YA 7391	PEG Designation, C.B.exchange	Face 7/16 in.sq.;body dia. .244 in.; length 1.1/4 in.; used on exch.,C.B.,multiple W.D., unit type, "N" posn.,complete stations	single	C 4270
Y1/YA 3492	No.15 Black	G.P.O. patt. For pegging spare jacks; used on swbd; command 200 line	single	C 4270
Y1/YA 8886	Code 16L white,w/red centre		single	C 8423
Y1/YA 8884	Green		single	C 8423
Y1/YA 9770	Matt pink		single	C 8423

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	PEG			
	No.15 - continued			
Y1/YA 11008	Matt white		single	C 8423
Y1/YA 3493	Red	For pegging faulty ccts. on multiple jacks; used on swbd., command, 200 line	single	C 4270
Y1/YA 3494	White	For pegging multiple jacks; used on swbd., command 200 line	single	C 4270
Y1/YA 8887	Yellow		single	C 8423
Y1/YA 9049	No.16 Code, 16L White,w/red centre	G.P.O. patt.	single	C 8423
Y1/YA 9260	Green		single	
Y1/YA 9259	Orange		single	
Y1/YB 01457	Red		single	
Y1/YA 9214	No.63	G.P.O. patt.	single	C 8423
Y1/YA 3230	PILLAR,Support,lid,No.2	Shank 7/32 in.dia.x shoulder 1/2 in.dia.x 25/32 in.long,threaded No.1 B.A.; used on tel. set, D.Mk.5	single	C 4270
Y1/YA 6748	PLATE AND CLEAT ASSEMBLY, Telephone,F,H.P.,No.1,Mk.2	Plastic cleat 2.5/16 in.x .421 in.x .406 in.with plastic plate 3 in.x 2.5/16 in.x .275 in.; terminates cord (6 way) on tel.set,F,No.1,Mk.2	single	C 4270



PLATE				
Y1/YA 8107	Backing 2 in.O.D.x 1/2 in. I.D., No. 1	.064 in.thick; 4 No.4 B.A.special hank bushes; used on ampfr., field tel., No. 1	single	C 4270
Y1/YA 5155	Base,mounting resistor, vibrator,No.1	2.15/16 in.x 1.3/16 in.x 3/32 in.; tufnol, drilled for components; used on vibrators, ringing, 12 and 24V.	single	C 4270
Y1/YA 6756	Battery instruction,tel., F.,H.P.	5.3/4 in.x 4 in.x 1/32 in.; battery connections diagram on S.R.B.P. board; used on tel.set,F., high-powered,No.1,Mk.2	single	C 4270
Y1/YA 4821	Buzzer fixing,No.2	2.13/16 in.x 2.9/32 in.x 1/16 in.; Birmabright; drilled for mtg. buzzer; used on swbd.,U.C., locators, line and cable faults,No.1 (Sec.Z4)	single	C 4270
Y1/YA 6217	Cableguard,No.1	No.16 S.W.G.br.2 in.x 1.1/2 in.x 3/16 in.; 2 holes 5/32 in.dia. at one end,7/8 in,centres; used on swbd.,F. and F.,units C	single	C 4270
Y1/YA 4665	Circuit diagram	3.1/4 in.x 2.1/8 in.x .032 in.; br.; with cct. diag.chemically engraved; used on tel.set F., Mk.2	single	C 4270
Y1/YA 8108	Amplifier,field telephone,No.1	6 in.x 4 in.x 19 S.W.G.; A1.; with cct.diag. chemically engraved	single	C 4270
Y1/YA 8281	Unit,alarm,No.1	4.1/2 in.x 2.5/8 in.x .022 in.;engraved metal	single	C 4270
Y1/YA 1158	Connection No.1	3/4 in.x 5/16 in.x 3/32 in.; G.P.O. patt.; screwed terminal wire connection plate with csk. fixing hole; includes 2 No.5 B.A.x 5/16 in. con.hd.screws	single	B 4105
Y1/YA 2939	No.7	.844 in.x .312 in.x .08 in.; G.P.O.patt.; br.screwed terminal and solder tag connection plate; with csk.fixing hole; includes 1 No.5 B.A.x 3/16 in.con.hd.screw and washer	single	C 4270
Y1/YA 2722	No.11	Consists of 2 plastic plates 12.1/8 in.x 3.7/8 in. x 1/8 in.fitted with 4 cable forms; 40 connection plates; brackets and clips; used on swbd., F. and F., units, B.Mk.1/1 and unit,B/J,Mk.2	single	B 4804,C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	PLATE - continued			
Y1/YA 8293	Cover 1.9/32 in.x 29/32in., No.1	For covering keys; with 4 No.6 B.A.screws tapped into plate and riveted; used on rack, tel. terminal, No.1	single	C 4270
Y1/YA 8294	1.5/16 in.x 15/16 in., No.1	For covering keys; used on rack,tel.terminal No.1	single	C 4270
Y1/YA 5133	Terminal, No.2	1.741 in.dia.x .125 in.; plastic; used on tel., hand, Nos. 1,2, 2A and 3 and tel.,hand (Sound P), No.2	single	C 4270
	Designation			
Y1/YA 7561	Alarm circuit	1 in.x 9/32 in.x .028 in.; M.S.printed "ALARM CIRCUIT" used on case, line test	single	C 4270
Y1/YA 7562	Aux. tele.	1 in.x 9/32 in.x .028 in.; .S. printed "AUX.TELE"; used on case, line test	single	C 4270
Y1/YA 7568	Battery	1 in.x 9/32 in.x .028 in.; M.S. printed "BATTERY"; used on case, line test	single	C 4270
Y1/YA 7567	Fuze alarm	1 in.x 9/32 in.x .028 in.; M.S. printed "FUZE ALARM"; used on case,line test	single	C 4270
Y1/YA 5700	No.4	7/8 in.x 1/4 in.x 1/16 in.; ebonite,engraved "DIAL"; used on swbd., U.C.,civil line unit, Mk.1/1	single	C 4270
Y1/YA 7565	Sounder Circuit	1 in.x 9/32 in.x .028 in.; M.S.printed "SOUNDER CIRCUIT"; used on case, line test	single	C 4270

Y1/YA 7563	Speak Circuit	1 in.x 9/32 in.x .028 in.; M.S. printed "SPEAK CIRCUIT"; used on case, line test	single	C 4270
Y1/YA 5449	Telephone set,L	3 in.x 1 in.x .02 in.; Br. engraved, "TELEPHONE SET L"	single	C 4270
Y1/YA 8029	Telephone set,L,Mk. 1/1	3 in.x 1 in.x .02 in.; Br. engraved, "TELEPHONE SET, L.Mk.1/1"	single	C 4270
Y1/YA 7566	Test Circuit	1 in.x 9/32 in.x .028 in.; M.S.; printed "TEST CIRCUIT"; used on case, line test	single	C 4270
Y1/YA 5156	Vibrator,12 V.	2.1/4 in.x 1.1/4 in.x 1/32 in.; Br. engraved; used on vibrator,ringing,12 V.	single	C 4270
Y1/YA 5157	Vibrator,24 V.	2.1/4 in.x 1.1/4 in.x 1/32 in.; Br. engraved; used on vibrator, ringing, 24 V.	single	C 4270
Y1/YA 7564	Volmeter,constant	1 in.x 9/32 in.x .028 in.; M.S. printed "VOLTMETER CONSTANT"; used on case, line test	single	C 4270
Diagram				
Y1/YA 2873/6	Cell, No.1	3 in.x 1.3/8 in.x 1/32 in.;S.R.B.P. engraved, showing connection of cells; used on tel.set, D. Mk.5	single	C 4270
Y1/YA 2873/5	No.4	7 in.x 3.1/16 in.x .015 in.; metal,engraved with cct.diag.; used on tel.set,D.Mk.5	single	C 4270
Y1/YA 6054	No.5	7 in.x 5 in.; paper paster,cct.diag. of A/J units on swbd.,F. and F.	single	C 4270
Y1/YA 6691	Superposing unit, 1 transformer	4.7/16 in.x 3.7/8 in.x 1/16 in.;plate with cct. diag.engraved	single	C 4270
Y1/YA 7445	Switchboard,Magneto, 10 line	S.R.B.P. on which is reproduced cct.diag.	single	C 4270
Y1/YA 6742	Telephone set,F,H.P.	9.7/8 in.x 4.21/32 in.x 1/32 in.;S.R.B.P. on which is reproduced working instruction cct. diag.	single	C 4270
Y1/YA 7955	Tel.Set, J	8.1/4 in.x 2.1/4 in.x .02 in.;metal; engraved with working instructions	single	C 4270
Y1/YA 5450	Telephone Set, L	8.1/4 in.x 2.1/4 in.x .02 in.;Br.; engraved with diag.	single	C 4270
Y1/YA 7044	Telephone Set,L.Mk.1/1	8.1/4 in.x 2.1/4 in.x .02 in.; Br.; engraved with diag.	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	PLATE			
Y1/YA 5158	Diagram - continued Vibrator, No.1	5 in. x 5 in.; paper paster, cct. diag.; used on vibrator, ringing, 12 and 24 V.	single	C 4270
Y1/YA 6173	Door assembly, rear, No.1	19 in. x 5.3/4 in. x .064 in.; M.S.; with 3 hinges riveted on and fitted with 2 captive screws; used on swbd., F. and F.	single	C 4270
	Dowel			
Y1/YA 6033	L.H., No.1	2 in. x 1.1/2 in. x 3/4 in.; M.S.; "U" shaped bracket with 1/4 in. dia. dowel pin; used on swbd., F. and F.	single	C 4270
Y1/YA 6032	R.H., No.1	2 in. x 1/2 in. x 1/8 in.; M.S. plate to which is riveted a M.S. pin 1/4 in. dia. x 7/16 in.; used on swbd., F. and F.	single	C 4270
Y1/YA 6041	No.2	1.1/4 in. x 5/8 in. x 1/8 in.; Br. with 1/4 in. dia. x 7/16 in. long pin riveted on centrally; used on swbd., F. and F.	single	C 4270
Y1/YA 3450	Earth	2 ft.6 in. x 2 ft.6 in.; G.P.O. patt.; G.I., with 7/16 in. soft copper wire; used on exch., C.B., multiple, W.D., unit type	single	C 4270
	Engraved			
Y1/YA 7552	Dialling to Auto exchanges	2 in. x 2.1/2 in. x .028 in.; M.S.; used on case, line test	single	C 4270

Y1/YA 7550	Main battery supply	4.1/2 in.x 4 in.x .028 in.; M.S.; used on case, line test	single	C 4270
Y1/YA 7553	Resistance test results	6.1/2 in.x 4 in.x .028 in.; M.S.; used on case, line test	single	C 4270
Y1/YA 6221	Escutcheon Generator, No.2	1.1/4 in.O.D.x 3/8 in.I.D., .064 in.; br.with 2 fixing holes 1/8 in.dia.csk.; used on swbd., F. and F.	single	C 4270
Y1/YA 7944	No.64	1.3/8 in.x 21/32 in.x .048 in.; Br.; centre hole 21/64 in.dia.; 2 fixing holes tapped No.4 B.A.; used on tel.set,J	single	C 4270
Y1/YA 6038	Flush, No.1	2 in.x 7/8 in.x 1/8 in.; M.S.; with 4 csk.holes; used on swbd., F. and F.	single	C 4270
Y1/YA 8109	Instruction Amplifier, field telephone, No.1 Battery Box	6 in.x 3 in.x .028 in.; A1.; engraved	single	C 4270
Y1/YA 7945	Tel.set,J	.062 in.synthetic resin impregnated paper board, natural	single	C 4270
Y1/YA 5456	Tel.set,L	3 in.x 1.1/2 in.x 3/64 in.; plastic; white; engraved showing cell connections; used on tel. set, L	single	C 4270
Y1/YA 3172	Buzzer	1.3/4 in.x 1.9/16 in.x .032 in.; Br.engraved "Press for Buzzer Call"; used on tel. set, F., Mk.2	single	C 4270
Y1/YA 5465	Handle, stowage, No.1	3 in.x 1/2 in.x .02 in.; Br.engraved; used on tel. set, L	single	C 4270
Y1/YA 7991	Headgear, No.1	5 in.x 1.7/16 in.x 1/16 in.; plastic on which is reproduced instructions for stowage of hdgr.; used on fullerphone, Mk.5	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cst. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	PLATE			
	Instruction - continued			
Y1/YA 6026	No.36	5 in.x 4.3/8 in.x .048 in.; Br.engraved with instructions for erection of swbd.; used on swbd., F. and F.	single	C 4270
Y1/YA 2879/7	No.37	9.1/8 in.x 3.7/8 in.x .015 in.; metal;engraved with working instructions; used on tel.set,D, Mk.5	single	C 4270
Y1/YA 7444	Switchboard,magneto, 10 line	10.1/2 in.x 2.3/4 in.x 1/16 in.; S.R.B.P. on which is reproduced operation instructions	single	C 4270
Y1/YA 4225	Telephone, F	6.1/4 in.x 5.1/2 in.x .02 in.; Br.photo-etched with working instructions	single	C 4270
Y1/YA 5159	Vibrator,12 volts	8.5/16 in.x 3/4 in.x 1/32 in.; Br.engraved with working instructions; used on vibrator, ringing, 12 V.	single	C 4270
Y1/YA 5160	Vibrator,24 volts	8.5/16 in.x 3/4 in.x 1/32 in.; Br.engraved with working instructions; used on vibrator, ringing, 24 V.	single	C 4270
	Insulating			
Y1/YA 5499	Battery Box,tel.set,L	3.5/32 in.x 1.23/32 in.x 4.37/64 in.deep x 3/64 in.thick; S.R.B.P.; box construction with two 1/4 in.dial holes in one side	single	C 4270
Y1/ZA 20050	No.2	11/16 in.x 1/4 in.x 1/16 in., with 2 holes .12 in.dia.	single	C 4270

Y1/ZA 20051	No.3	11/16 in. x 1/4 in. x .09 in., with 2 holes .12 in. dia.	single	C 4270
Y1/YA 6240	Lid corner, R.H.	Similar to plate, lid, corner, L.H. but holes are csk. on other side of plate; used on swbd., F. and F.	single	C 4270
Y1/YA 6174	Lock, No.2	1/8 in. x 1/2 in. x 1/8 in.; Br. centre hole tapped 1/4 in. B.S.W., 2 outside holes 5/32 in. dia. csk., used on swbd., F. and F.	single	C 4270
Y1/YA 7334	Mounting Condenser No.2	3 in. x 2.1/8 in. x 1/16 in.; S.R.B.P.; with 2 M.S. brackets for mtg., and 3 double-ended solder tags eyeletted to panel; used on tel. set, L. Mk.1/1	single	C 4270
Y1/YA 7449	No.3	2.1/2 in. x 2.3/8 in. x 1/32 in.; S.R.B.P.; with 2 holes 1/8 in. dia.; used on fullerphone, Mk.4/1	single	C 4270
Y1/YA 6164	Finger bar	2.687 in. x .3 in. x .036 in.; Br.; with 2 holes 3/32 in. dia. csk.; used on tel., hand, Nos.2,2A,3 and tel., hand (Sound P.), No.2	single	C 4270
Y1/YA 6222	Indicator, M.R., No.2, 12 way	14 in. x 1.5/16 in. x 3/32 in.; M.S.; drilled and slotted for mounting 12 indicators, M.R., No.2; used on swbd., F. and F.	single	C 4270
Y1/YA 5451	Indicator, M.R., No.2, 15 way	17 in. x 1.1/4 in. x .092 in.; M.S.; complete with supporting plate and bell alarm contacts; for mounting 15 indicators, M.R.	single	C 4270
Y1/YA 6223	Jack, M.R., No.1A, 12 way	14 in. x 5.1/8 in. x 3/4 in.; M.S. right-angle mtg. plate for mounting 12 jacks, M.R., No.1; used on swbd., F. and F.	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	PLATE			
	Mounting - continued			
*Y1/YA 12136	No.5	G.P.O. patt.	single	
*Y1/YA 12135	No.9	G.P.O. patt.	single	
Y1/YA 5829	Switch, pressel	3.27/64 in.x 19/64 in.x .064 in.; Br.,mtg.plate for pressel switch; used on tel.,hand	single	C 4270
Y1/YA 6224	Name, No.31	2 in.x 1.1/2 in.x 1/16 in.; S.R.B.P.; engraved; used on swbd., F. and F., units C	single	C 4270
Y1/YA 6029	No.6	2 in.x 5/8 in.x 3/16 in.; M.S.; with 2 holes 5/32 in.dia.csk.; used on swbd.,F.and F.	single	C 4270
Y1/YA 6241	No.96	1.3/4 in.x 5/8 in.x 1/8 in.; M.S.; with 2 holes 5/32 in.dia. csk.; used on swbd., F. and F.	single	C 4270
Y1/ZA 26426	Protection, No.1	1.1/8 in.dia.x .203 in.; br.For I.T.E., No.1 in mic., hand, No.18	single	C 4270
Y1/YA 5143	Retaining Bar, pressel, No.1	. 523 in.x 19/64 in.x 1/32 in.; Br.; with 1 hole .14 in.dia. csk.; retaining plate for pressel switch, used on tel., hand	single	C 4270
Y1/ZA 15129	Securing No. 2	Used on unit, sig., V.F.,No.3, Mk.3	single	C 4270
Y1/YA 7663	Stile cover	9 in.x 11/16 in.x 1/8 in.; M.S.; with 2 holes 5/32 in.dia.; used on swbd.,C.B.,multiple,W.D., unit type	single	C 4270



Y1/YA 5953	Terminal No.2	1 in. x 5/16 in. x 1/8 in.; Br.; with centre hole tapped No.4 B.A. and 2 side holes tapped No.6 B.A.; captive screw in centre hole; used on swbd., F. and F.	single	C 4270
Y1/YA 6757	3 way, H.T., L.T., No.1	4 in. x 3/4 in. x .178 in.; S.R.B.P. with 3 holes .166 in. dia. and 2 holes .156 in.; engraved; used on tel. set, F, high power, No.1, Mk.2	single	C 4270
Y1/YA 6754	3 way, No.1	3.3/8 in. x 1.1/8 in. x .15 in.; S.R.B.P. with 3 holes .166 in. dia. and 4 holes .120 in. dia. csk., for fixing; used on tel. set, F, high power, No. 1, Mk.2	single	C 4270
Y1/YA 7946	7 way, No.1	3.3/8 in. x 1.1/2 in. x 3/32 in.; S.R.B.P.; fitted with 9 tags; 9 No.5 B.A. ch.hd.screws 3/16 in. long; 2 hard Br. links; 1 rectifier, selenium; panel engraved; used on tel. set, J	single	C 4270
Y1/YA 5094	Line, No.3	2.3/4 in. x 29/32 in. x 1/2 in.; plastic; fitted with 2 terminals, inst., slotted, single, No.4, large (Sec. Y3)	single	C 4270
Y1/YA 5161	Vibrator 12 V.	7.13/16 in. x 1.1/16 in. x 1/8 in.; ebonite; engraved; used on vibrator, ringing 12 V.	single	C 4270
Y1/YA 5162	24 V.	Similar to plates, terminal, vibrator, 12 V., but voltage engraved on panel is 24 V.; used on vibrator, ringing, 24 V.	single	C 4270
Y1/YA 1877	PLUNGER, Mk.1	3/4 in. dia. x 1 23/64 in.; Br; binding hd.; threaded 1/4 in. B.S.F. fitted with escutcheon plate and 2 locknuts; for operating cradle switch on tel. set, F, Mk.1/1 and Mk.2	single	B 5255, C 4270
Y1/YA 2874	PROTECTOR, H.C. and T., No.40, B.	G.P.O. patt.; fitted with external springs for plug, No.222 to be inserted without removing H.C.; mtg.; plate length 11 in.; includes 80 carbons, protector, No.14; 40 coils, heat, B.B.	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5940	PROTECTOR AND FUZE, No. 1.2/2	4 in. x 1.1/2 in. x 1.3/4 in.; G.P.O. patt.; plastic; part of kits, extension tel., C.B. exchange	single	C 4270
Y1/YA 7134	PULLEY-WEIGHT No. 14A	4.1/2 in. x 7.23/64 in. x 7/16 in.; G.P.O. patt.; wt. 24 oz.; double; 1 pulley above the other; used on swbd. position, mag. $\frac{10+50}{60}$ , No. 1	single	C 4270
Y1/YA 1244	No. 16	4 in. x 2 in. x 7/16 in.; G.P.O. patt.; wt. 9 oz.; single pulley; for cords on swbd.	single	19258
Y1/YA 8097	RACK Cable, No. 1, complete	19.1/2 in. x 8.1/8 in. x 5.1/2 in.; M.S. cable rack fabricated from 1 in. x 1 in. x 3/16 in. angle end 3/4 in. x 3/16 in. strip and fitted with 4 jumper rings 1.1/2 in. I.D. and M.S. cover on the rear, size 17.3/8 in. x 7.5/8 in. x 3.1/2 in.	single	C 4270
Y1/YA 6729	Junction, relay set, C.B. exch. (W.D.)	7 ft. x 3 ft. 8 in. x 1 ft. 6 in.; M.S. rack framework equipped for 40 junctions; does not include relay sets; completely enclosed by cabinet assy.; used on exch., C.B., multiple W.D., unit type	single	C 4270

Y1/YA 6728	L.and C.O.relays 300 line equipped C.B.exch. (W.D.)	7 ft.x 3 ft.8 in.x 1 ft.6 in.; M.S.rack framework equipped for 300 lines; includes 300"L" relays and 300 "CO" relays; completely enclosed by cabinet assy.; used on exch., C.B.,multiple W.D., unit type	single	C 4270
Y1/YA 6731	Meter,200 line,equipped	7 ft.x 1 ft.9 in.x 1 ft.6 in.; M.S.rack framework; fully equipped,includes 200 meters and meter test eqipt.; used on exch.,C.B., multiple W.D., unit type	single	C 4270
Y1/YA 8665	Telephone terminal,No.1, Mk.2	Channel iron rack 5 ft.3 in. high; provides terminal eqipt.for external tel.lines working on mag.sig. Used as part of eqipt, fire control, A.A. or control room, mobile, A.A.	single	C 5687
RAIL				
Y1/YA 7392	Foot, C.B.,exchange	1 ft.11.1/4 in.x 2.1/2 in.x 2 in.; teak; used on swbd.,C.B., multiple W.D., unit type	single	C 4270
Guard				
Y1/YA 7369	Frame, I.D.	1 ft.9.3/8 in.x 1.1/2 in.x 5/8 in.; convex iron; with 2 holes 11/32 in.dia. csk.; used on exch., C.B.,multiple W.D.,unit type	single	C 4270
Y1/YA 7381	Frame, M.D.	3 ft.5.5/8 in.x 1.1/2 in.x 5/8 in.; convex iron; with 3 holes 11/32 in.dia. csk.; used on exch., C.B.,multiple W.D.,unit type, "N" position	single	C 4270
RATCHET AND TONGS				
Y1/YA 4864	No.1	G.P.O.patt.; without keys,tension ratchet; with tension inducator; for 300,400,600 and 800 lb.wire; includes 4 screws,for ratchet and tongs, No.1	single	C 4270
Y1/YA 1246	No.2	With tension indicator; for 100,150 and 200 lb. wire	single	25467
Y1/YA 1247	No.3	With tension indicator; for 40 and 70 lb. bronze wire	single	25467

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5914	RATCHET AND TONGS-continued No.4	Without tension indicator; for 100,150 and 200 lb. wire	single	C 4270
Y1/YA 1248	No.5	Without tension indicator; for 40 and 70 lb. bronze wire	single	C 4270
Y1/YA 7691	RECEIVER, Bell, No.1A 60 ohms	G.P.O.pat. ; 60 ohms; used on kits extension tel., C.B. exch.	single	C 4270
Y1/YA 8112	RING Rubber, 9/16 in. O.D. x 13/32 in. I.D., No.1	Circular cross section 5/64 in. dia.; used on ampfr., field tel., No.1	single	C 4270
Y1/5805-99-901-1252- Y1/5805-99-943-0570	RINGER TELEPHONE G.P.O. type 59A 2 in. x 2.1/4 in. x 1 in. dia. O/A.	Without gong 24 V, AC.500 ohms + 500 ohms (old cat.No.Y1/YA 3143) 24 V, AC.500 ohms + 500 ohms (old cat.No.Y1/YA 8054)	single single	
Y1/YA 6068	ROD Restoring, assembly, No.1	13.1/8 in. x 1/4 in. x 1/4 in.; Br.; fitted with lever, blocks and springs for mechanically restoring indicators; used on swbd., F. and F.	single	C 4270
Y1/YA 7476	Screwed, 11.1/4 in. x 1/2 in. dia.	11.1/4 in. long x 1/2 in. dia.; M.S.; screwed 1/2 in. B.S.W. at both ends; used on frame, M.D., swbd., C.B., multiple, W.D., unit type	single	C 4270

Y1/YA 7482	Screwed, 24.1/4 in. x 1/2 in. dia.	24.1/4 in. long x 1/2 in. dia.; M.S.; screwed 1/2 in. B.S.W. at both ends for a distance of 3 in.; used on frame, I.D., swbd., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 3441	Stay No. 1	6 ft. x 5/8 in.; G.P.O. patt.; fitted with washer bow, thimble and ratchet-nut	single	C 4270
Y1/YA 3336	No. 2	8 ft. x 3/4 in.; G.P.O. patt.; fitted with washer, No. 9; bow; thimble No. 2 and ratchet-nut	single	C 4270
Y1/YA 3485	No. 5	4 ft. 6 in. x 1/2 in.; G.P.O. patt.; fitted with washer, No. 21; bow; thimble, No. 1 and ratchet-nut	single	C 4270
RUNWAY ASSEMBLY				
Y1/YA 7486	Frame, I.D.	2 ft. 2.1/2 in. x 1 ft. 3 in.; M.S. cable rack fabricated from 1.1/2 in. x 1/4 in. M.S.; used on frame, I.D., swbd., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 7479	Frame, M.D.	3 ft. 9 in. x 1 ft. 3 in.; M.S. cable rack fabricated from 1.1/2 in. x 1/4 in. M.S. and 1 in. x 3/8 in. M.S.; used on frame, M.D., swbd., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 6861	RUNWAY, Cable, C.B. exch., No. 1 (W.D.)	6 ft. x 1 ft. 3 in.; M.S. cable runway fabricated from 1.1/2 in. x 1/4 in. M.S. and 1 in. x 3/8 in. M.S.; used on swbd., position, C.B., W.D. $\frac{10+50}{60}$	single	C 4270
*Y1/YA 12207	SATCHEL, No. 2	Canvas for containing power unit, SA. 6028 and Oscillator, No. 23A	single	

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7894	SECTION Cable,terminating,C.B. exchange, (W.D.),Mk.2	6 ft.x 3 ft.6 in.x 2 ft.6 in.; M.S. framework with hardwood keyboard end-piece and removable panels, for closing ends of sections; used on sections,swbd.,C.B.,W.D., <u>10+50</u> , Mk.2 60	single	C 4270
Y1/YA 7730	I.D.F.and C.T.combined C.B.exchange	4 ft.6 in.x 4 ft.3 in.x 3 ft.6 in.; M.S.framework with teak keyboard end-piece,keyboard end-piece substitute,sheet-iron roof and removable panels; used on exch.,C.B.,multiple,W.D.,unit type	single	C 4270
Y1/YA 9226	Switch,P.B.X.SA 7560	G.P.O.patt.; floor type; lamp signalling; for P.M.B.X. and P.A.B.X. manual boards	single	C 5687
Y1/YA 7895	Switchboard,C.B.(W.D.), <u>10+50</u> , Mk.2 60	3 ft.9 in.x 3 ft.6 in.x 2 ft.; M.S.framework with sheet-steel roof; fitted with keyboard assy., answering equipt. for 60 lines on 2 panels, 16 cord ccts.,rotary type ringing machine,alarm and test ccts.,traffic meters,visible index panel and auto. dial; used on exch., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 8237	SOCKET ASSEMBLY,No.1, link, U, 15/32 in.	Br., nickel plated, drilled 1/8 in.x 7/16 in. deep, outside thread No.2 B.A. with nut,spring, washer,spacer and soldering tag; used on drive and monitor unit,S.S.B.,No.1	single	C 4270

Y1/YA 2740	SOCKET Auto-dial, No.1	Consists of M.S. case 2.3/16 in. dia. x 2 1/64 in. x .078 in. with ebonite mtg. plate and 5 br. inserts; used on swbds., F. and F., units C	single	B 4874, C 4270
Y1/YA 7443	Moulded, switchboard, magneto, 10 line (W.D.)	2 in. x 1.5/16 in. x 13/16 in.; bakelite moulding with 2 Br. inserts tapped No. 0 B.A. on 1 in. centres; used on swbd., mag., 10 line, W.D.	single	C 4270
Y1/YA 3582	Mouthpiece	1 1/16 in. dia. x 1.13/32 in.; Br. ball swivel with switch cam, for mouthpieces, No. 6A	single	C 4270
Y1/YA 8368	No.3	1.437 in. long x .410 in. dia.; used with rubber mouthpieces	single	C 4270
SPRING				
Y1/YA 6227	Battery box Inner No.1	3.3/4 in. x 1/2 in. x 9/32 in. x .022 in. thick; Ni. Sil., spring hard; part of brackets bty., No. 1; used on swbd., F. and F., units C	single	C 4270
Y1/YA 6036	Outer No.1	2.5/8 in. x 1/2 in. x 5/8 in. x No. 20 S.W.G.; hard Ni. Sil. sheet; used on swbd., F. and F., units C	single	C 4270
Y1/YA 1886	Bottom	3.13/32 in. x 3/4 in. x 3/16 in.; spring steel strip with Br. plates riveted at each end; used on tel. set, F., box; for retaining tel. in case	single	C 4270
Y1/YA 3256	Buffer, capsule case	1.1/4 in. x 37/64 in. x .02 in.; Br.; horseshoe-shaped flat spring; used with contact spring on tel. hand, No. 2 and 6 and tel. 1 and 4	single	C 4270
Y1/YA 2196/4	Capsule, centre contact	2.9/32 in. x 5/16 in. x .022 in.; Ni. Sil. with Br. insert 2 1/64 in. x 9/32 in. x 9/32 in. tapped No. 6 B.A.; used on transmitter, breast, No. 1	single	C 4270
Y1/YA 3255	Contact Capsule case	1.1/2 in. x 1 in. x .012 in.; phos. Br., horseshoe-shaped flat spring with silver contacts at extremities; used on tel., hand, Nos. 3A, 4, 6 and 10	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	SPRING			
Y1/YA 6153	Contact - continued Fixed, No. 2, switch, pressel	2.1/4 in. x 1/4 in. x .036 in.; Ni.Sil., with gold-silver contact riveted in position; part of switches, pressel, No. 10; used on tel., hand	single	C 4270
Y1/YA 6154	Moving, No. 2, switch, pressel	2.1/4 in. x 1/4 in. x .036 in.; Ni.Sil., with gold-silver contacts riveted in position; part of switches, pressel, No. 10; used on tel., hand	single	C 4270
Y1/YA 2196/1	Upper	3/16 in. x .018 in.; Ni.Sil., with gold-silver contact and ebonite stud fabricated to form clip for capsule and moving contact spring; used on transmitter, breast, No. 1	single	C 4270
Y1/ZA 5406/4	Fixed Pressel, No. 3A	1.3/4 in. x 5/8 in. x 15/64 in.; Phos.Br.; pressel switch operated	single	C 4270
Y1/YA 7961	Tel., hand, No. 10	3/4 in. x 5/16 in. x 1/8 in. x .028 in. thick; phos.Br. with gold-silver contact riveted in position; part of tel., hand, No. 10; used on tel. set, J	single	C 4270



Y1/YA 6867	Flap,unit C	1.15/16 in.x 5/8 in.x 1/2 in.x .036 in.thick; Ni.Sil.,with 2 fix.holes 1/8 in.dia.for holding cord apron on swbd.,F and F.,unit C.	single	C 4270
Y1/YA 2271	For socket,mouthpiece	1.3/32 in.x 5/8 in.x 5/16 in.x .022 in.thick; phos.Br.; mount socket,mouthpiece on transmitter, breast, No.1	single	C 4270
Y1/YA 3372	Leaf,radial,3/8 in.x 1/4 in.x 26 S.W.G.	Phos.Br.,hole .116 in.dia.;end bent to form a buffer; used on transmitter,breast,No.1 and tel.attachment,hdgr.,double, Mk.3	single	C 4270
Y1/YA 7962	Moving,tele.,hand, No. 10	1.9/16 in.x 19/64 in.x .028 in.;phos.Br.; with hole .136 in.dia.and a gold-silver contact riveted in position; used on tel. set, J	single	C 4270
Y1/YA 6228	Restoring,rod,No.1	Piano wire,No.20 S.W.G.;3.1/2 turns;15/16 in.I.D.; ends bent to form eyes 1/8 in.dia.,11/32 in. between eye centres; used on clearing indicator assy. of swbd.,F. and F.,units C	single	C 4270
Y1/YA 1887	Top	1.1/2 in.x 2.1/2 in.x 1/4 in.x No.22 S.W.G.; phos.Br.; 2 fixing holes 1/8 in.dia.; used on box, Mk.1/1, tel. F.	single	C 4270
Y1/YA 5351	STILE CASING,No.4	9.3/4 in.x 1.7/32 in.x 1/8 in.; Br.; edges bevelled at 45°, 3 fixing holes .257 in.dia.; includes 3 fixing screws; 3 ebonite washers and 3 ebonite bushes; used on swbd.,command,200 line, A unit	single	C 4270
Y1/YA 7270	STILE COVFR ASSEMBLY	6.1/2 in.x 1.3/8 in.x .132 in.; sheet steel case; with paper label and celestoid strip; used on swbd.,C.B.,multiple,W.D.,unit type(section swbd., C.B., W.D., <u>10+50</u> )	single	C 4270

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6680	STRAP Connection, No.9	2.1/8 in. x 5/16 in. x No.27 S.W.G. ;Ni.Sil. ; 2 fixing holes on 1.3/4 in.centres; used on test frames,20 pr.,Mk.3 and 40 pr.,Mk.2	single	C 4270
Y1/YA 7575	Metal, No.1	13 in. x 5/8 in. ; steel; hinged strap for supporting front panel of case,line test,C.B. exch. W.D.	single	C 4270
Y1/YA 5413	STRIP Bottom,A,front,No.1	9 ft.3.3/16 in. x 2 in. x 1 in. x 3/16 in. ; M.S.angle; with drilled and tapped holes; used on swbd.,command 200 line,units A	single	C 4270
Y1/YA 2958	Connection 5 pair,No.1	6.5/16 in. x 1.1/2 in. x 1/4 in. ; moulded strip; with 10 terminal plates on 1/2 in.centres, for terminating and lacing cables; used with con., 5 pr., No.2	single	B 4959
Y1/YA 8238	6 way, No.1	2.3/32 in. x 5/8 in. x 3/8 in. ; plastic; with 6 soldering tags; mounted on M.S. plate; used on training set, No. 4A	single	C 4270
Y1/YA 8094	40 way, No.2	6.1/2 in. x 2.1/2 in. x 2.3/4 in. ; plastic; with 40 soldering tags; used on rack.tel.terminal,No.1	single	C 4270

Y1/YA 8153	40 way, No. 3	Similar to strip, connection, 40 way, No. 2, but the base is replaced by 3 moulded washers and M.S. clamping plate; used on rack, tel. terminal, No. 1 (Mobile command post)	single	C 4270
Y1/YA 7185	60 way, No. 1	Teak or maple strip; with 60 (3 x 20) soldering tags; similar to strip, connection, No. 24A but tpl. finish; size of base 6.1/2 in. x 2.1/2 in.; used on frame, I.D., 400 line	single	C 4270
Y1/YA 7186	80 way, No. 1	Teak or maple strip; with 80 (4 x 20) soldering tags; similar to G.P.O. strip, connection No. 23A but tpl. finish; size of base 8 in. x 2.1/2 in.; used on frame, I.D., 400 line	single	C 4270
Y1/YA 7187	80 way, No. 2	Teak or maple strip; with 80 (4x20) soldering tags; similar to strip; connection No. 22A but tpl. finish; size of base 6.1/2 in. x 2.1/4 in.; used on frame, I.D., 400 line	single	C 4270
Y1/YA 8095	100 way, No. 1	6.1/2 in. x 2.1/2 in. x 3.1/8 in.; plastic base; securing a moulded insulation strip with 100 (5 x 20) soldering tags; used on rack, tel. terminal, No. 1	single	C 4270
Y1/YA 7188	120 way, No. 1	Teak or maple strip; with 120 (6x20) soldering tags; similar to G.P.O. strip, connection, No. 77 but tpl. finish; size of base 8 in. x 2.1/2 in.; used on frames, I.D., 400 line	single	C 4270
Y1/YA 8264	120 way, No. 2	Teak or maple strip; with 120 (6 x 20) soldering tags; similar to G.P.O. strip, connection, No. 41A but tpl. finish; size of base 6.1/2 in. x 2.1/2 in.; used on exch., C.B., multiple, W.D.	single	C 4270
Y1/YA 3045	No. 2	G.P.O. patt.; 20 screw tags; strip base; 7.3/8 in. x 1.1/8 in.	single	C 4270
Y1/YA 3046	No. 3	G.P.O. patt.; 40 screw tags; strip base; 24.3/4 in. x 1.1/8 in.	single	C 4270

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	STRIP			
	Connection - continued			
Y1/YA 3022	No. 13	G.P.O. patt.; 40 (2 x 20) soldering tags; strip base 7.1/4 in. x 1/2 in.	single	C 4270
Y1/YA 6345	No. 22A	G.P.O. patt.; 80 (4 x 20) soldering tags; strip base 6.1/2 in. x 2.1/2 in.	single	C 4270
Y1/YA 7544	No. 24A	G.P.O. patt.; 60 (3 x 20) soldering tags; strip base 6.1/2 in. x 2.1/2 in.; used on swbd., C.B., multiple, W.D.	single	C 4270
Y1/YA 4083	No. 25A	G.P.O. patt.; 60 (3 x 20) soldering tags; strip base 8 in. x 2.1/2 in.	single	C 4270
Y1/YA 7495	No. 37	G.P.O. patt.; 100 (4 x 25) soldering tags; strip base 6.1/2 in. x 2.1/2 in.; used on terminal equipt. vehicle, type A	single	C 4270
Y1/YA 1534	No. 50	Terminal and lacing strip for terminating 10 pr. cable; used with test frame	single	24851, B 5882
*Y1/YA 12133	No. 62	G.P.O. patt.	single	
Y1/YA 11434	No. 73 (W.D.)	G.P.O. patt. soldering 160 terminals (8 x 20) 8 in. x 2.1/2 in.; end and central fixing	single	C 9519
Y1/YA 11433	No. 78	G.P.O. patt. soldering 125 terminals (5 x 25) 6.1/2 in. x 2.1/2 in.; end and central fixing	single	C 9519

Y1/YA 7232	No. 79	G.P.O. patt.; 150 (6 x 25) soldering tags; strip base 6.1/2 in. x 2.1/2 in.; used on swbd., C.B., multiple, W.D.	single	C 4270
Y1/YA 7319	No. 121A, Mk. 1	G.P.O. patt.; 50 (5 x 10) soldering tags; strip base 2.17/32 in. x 2 in. x 1/4 in.; with mtg. plate and bracket; used on swbd., C.B., multiple, W.D.	single	C 4270
Y1/YA 12134	No. 126	G.P.O. patt.	single	
Y1/YA 11369	No. 135A	G.P.O. patt. soldering 12 terminals 2.7/8 in. x 15/16 in. x 3/32 in.; includes 2 brackets	single	C 9519
Y1/YA 1872	Contact, buzzer No. 1	2.3/8 in. x 3/4 in. x 1/16 in.; plastic; with 6 contact springs	single	B 1782, B 5255
Y1/YA 4126	No. 2	2.7/16 in. x 1.5/16 in. x 3/32 in.; plastic; with 6 contact springs; used on tel. set, F.S., Mk.1	single	C 4270
Y1/YA 7558	Designation "Hold-miscellaneous"	9.9/16 in. x 9/16 in. x No. 22 S.W.G.; M.S.; used on case, line test; swbd., C.B., multiple, W.D.	single	C 4270
Y1/YA 3306	No. 8, 9.3/4 in.	G.P.O. patt.; with transparent strip; used on swbd., teleprinter, 15 and 40 line	single	C 4270
Y1/YA 6681	No. 49	11.15/16 in. x 3/8 in. x 1/16 in.; white celastoid; engraved with 11 lines; used on test frames, 20 pr. and 40 pr.	single	C 4270
Y1/YA 7559	"Speak-Voltmeter shunt"	9.9/16 in. x 5/16 in. x No. 22 S.W.G. (.028 in.); M.S.; used on case, line test	single	C 4270
Y1/YA 7554	"Subs, Batt, and Hold C.O. - ring"	9.9/16 in. x 5/16 in. x No. 22 S.W.G.; M.S.; used on case, line test	single	C 4270
Y1/YA 7560	"Test-Jack circuit"	9.9/16 in. x 9/16 in. x No. 22 S.W.G.; M.S.; used on case, line test	single	C 4270

106  
SECTION Y1

CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 2875	STRIP - continued Fanning, No. 2	10.15/16 in. x 3.1/4 in.; end slots 7/16 in. x 15/32 in. deep; G.P.O. patt.; numbered 0-9, 0-9; 20 prs. each side	single	C 4270
Y1/YA 7201	Jack, 70A	Plastic strip mounting 20 jacks; similar to jack, No. 320 BN but tropicalised; used on frame, M.D. 400 line	single	C 4270
Y1/YA 6229	Terminal Bell, No. 1	1.3/8 in. x 3/4 in. x 5/16 in.; plastic; with 2 terminals, inst., slotted, single, No. 4, large (Sec. Y3); used on swbd., F. and F., units C	single	C 4270
Y1/YA 6230	N.A., No.1	1.7/8 in. x 3/4 in. x 5/16 in.; plastic; engraved N.A. and E.; with 2 terminals, inst., slotted, single, No. 4, large (Sec. Y3); used on swbd., F. and F., units C	single	C 4270

Y1/YA 6127	10 pair, No. 1	15 in. x 2.7/16 in. x 5/8 in.; plastic; with 20 terminals, inst., slotted, single, No. 4, large (Sec. Y3); 2 cable brackets captive fixing screw; part of boxes, terminal, signal offices, Mk. 2 and Mk. 3	single	C 4270
Y1/YA 7436	22 way, No. 1	12.3/16 in. x 5/8 in. x 1/4 in.; plastic; 22 holes .149 in. dia.; 2 holes 5/32 in. dia.; used on swbd., mag., 10 line, W.D.	single	C 4270
Y1/YA 2230	SUPERPOSING UNIT 1 transformer	5.9/32 in. x 4.3/16 in. x 4 in.; M.S. case; slide-on cover with 2 hooks, safety, No. 3 (Sec. V6); with 1 transformer, superposing, No. 1; 3 terminals, inst., slotted, single, No. 4, large (Sec. Y3); 8 terminals, inst., slotted, single, No. 4, small (Sec. Y3); two 24 in. lengths of twin cord each connected to a plug, jumper, twin, No. 1 (one black, other red); used for superposing on tel. ccts.; cover used as a supporting bracket when used with frame, D. and P., 10 wire, Mk. 1/1	single	B 2912
Y1/YA 4652	3 transformer, No.1A	16.5/16 in. x 5.3/4 in. x 4.1/2 in.; M.S. case hinged cover with 2 safety hooks; with 3 transformers, superposing, No. 1; 15 terminals, inst., slotted, single, No. 4, large (Sec. Y3); 25 links, wire (2 spares); 2 socket-contacts, 5 pr., No. 1; 1 con.; used for superposing on tel. ccts. with swbd., U.C., 10 line	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELIGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7370	SUPPORT, Rail guard Frame, I.D.	M.S. 1.1/2 in. x 1/4 in.; ends bent at right-angles 3 ft. 1 in. x 1.1/8 in.; used on exch., C.B., multiple, W.D.	single	C 4270
Y1/YA 7398	Frame, M.D.	1 ft. 8.3/16 in. x 1.1/2 in. x 1/4 in. M.S.; used on exch., C.B., multiple, W.D.	single	C 4270
Y1/YA 10969	SWITCHBOARD CB 873 5 + 20 Mk.8 25 F. and F.	G.P.O. patt.; 51 in. high x 19.3/4 in. wide x 20.3/4 in. deep; weight 164 lb. Field and fortress; port.; mag.; cord type; with drop shutter line and clearing indicators, mechanically restored on line ccts., manually restored on clearing ccts.; consists of an assy. of units; providing the following facilities (a) Connection and operation between mag., auto., C.B., C.B.S.1, C.B.S.2, C.B.S. 3 tel. exch. and coupling to G.P.O. voice-operated relay (unit, signalling, No. 5) (b) Coupling swbds. together (max. capacity 180 lines)	single	C 8423 B 4804, B 8029



		(c) Line bunching for conference purposes For working into auto. exchs., 1 mtg., dial auto., No. 9, incomplete; 1 clip, No. 27; 1 cord, inst., No. 5/06E, 2.1/2 in. are needed (I.L. 11744)		
Y1/YA 4773	20 line, Mk. 2	42.1/2 in. x 21.1/2 in. x 20 in.; approx. weight 164 lb.; comprises 1 unit B/J, Mk. 2; 1 unit, C; 1 unit, D	single	B 8029
Y1/YA 4774	40 line, Mk. 2	48.1/2 in. x 21.1/2 in. x 20 in.; approx. weight 193 lb.; comprises 1 unit B. Mk. 1/1; 1 unit B/J, Mk. 2; 1 unit C; 1 unit, D	single	B 8029
	Unit			
Y1/YA 1597	A	9 in. x 2.3/8 in. x 8 in.	single	B 8029
Y1/YA 1598	A/J, Mk. 1	9 in. x 2.3/8 in. x 8 in.; used when working with auto. C.B., C.B.S.1 and C.B.S.2 tel. exch.	single	B 4804, B 8029
Y1/YA 2732	B. Mk. 1/1	19 in. x 9.3/4 in. x 5.3/4 in.; approx. weight 29 lb.; comprises 1 unit, B. case; 4 units, A; 1 plate, connection, No. 11; used with sbwd., F. and F., 40 line, Mk. 1/1 only	single	B 4804
Y1/YA 4777	B/J, Mk. 2	19 in. x 9.3/4 in. x 5.3/4 in.; approx. weight 31 lb.; comprises 1 unit, B. case; 3 units, A; 1 unit, A/J, Mk. 2; 1 plate, connection, No. 11	single	B 8029
Y1/YA 1600	C	20 in. x 18 in. x 16 in.; teak desk forming operator's keyboard and cord table; 2 flush-type metal carrying handles	single	B 4804
Y1/YA 1601	D	28 in. x 21 in. x 18 in.; teak case; with 4 flush- type metal carrying handles; provides combined stand and transport case for unit, C; has detachable panel with web satchel attached for holding recvrs., hdgr., and transmitters, breast	single	B 4804

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6733	SWITCHBOARD - continued Magneto, 10 line (W.D.)	14.3/4 in. x 9. 7/16 in. x 5.5/8 in.; max. weight 25 lb.; M.S. case; front and back hinged lid; drop indicator; single plug ended cords; lightning arrester; 5 ft. earthing braid permanently connected to case. For components, see E.M.E.R. T306/3	single	C 4270
Y1/YA 6007	Position, magneto ( $\frac{10+50}{60}$ ), No. 1	4 ft. x 2 ft. 3 in. x 2 ft. 7 in.; floor pattern; cord type; mechanically restored drop indicator; with auto. dial for working into auto. exchs; 15 cord cts. (P.L.2777)	single	C 4270
Y1/YA 9285	Telephone $\frac{10+50}{60}$ (H), No.1, Mk.1	4 ft. 7.1/4 in. high x 2 ft. 5.1/2 in. deep x 2 ft. 3 in. wide; weight 320 lb. approx. Capacity for 10 exch. and 50 extension lines. Exch. line ccts. can work into C.B.S., C.D. and auto. exch. Night alarm facility with night service on a maximum of 10 extensions; 15 cord cts. per position, extension lines work to C.B. instrument; cord cct. keys give "ring call	single	C 5687

		and speak" and "ring answer and dial". Through clearing on exch. extension calls. Each fully equipped position takes an average load of 0.5 amp. at between 16 and 24V.; ringing current can be supplied from the parent exch, a 20 V. vibrator or hand gen.		
Y1/YA 1686	TABLE, Telegraph, Mk. 1	3 ft. 5.1/2 in. x 2 ft. 1/2 in. x 2.5/8 in. (folded); wood; height when open 2 ft. 6 in.; used with field teleg. equip.	single	12263, A 2052
	TAIL, Insulated	G.P.O. patt.; includes steel scissors-hook, M.S. shackle straps, globe strain insulator, tinned Br. binder and steel wire tail		
Y1/YA 6437	Large	Used with vice, draw, No. 2 and ratchet and tongs, No. 1	single	C 4270
Y1/YA 1697	Small	Used with ratchet and tongs, Nos. 2, 3, 4 and 5	single	25465, 25965
	TAPE, Telegraph			
Y1/YA 1699	Bronze, No. 1	6.1/2 in. x 3/32 in. x .02 in.; for wire, electric, bronze, 40 lb. (Sec. Y3)	100	A9252, B 597
Y1/YA 1701	Cadmium copper, No. 1	6.1/2 in. x 3/32 in. x .02 in.; for wire, electric, bronze, 40 lb. (Sec. Y3) or cadmium copper wire	100	B 597
	Copper			
Y1/YA 1700	No. 1	8.1/2 in. x 5/32 in. x .014 in.; for wire, electric, copper, H.D., 100 lb. (Sec. Y3)	100	24698, A 9252
Y1/YA 5866	No. 2	G.P.O. patt.; for 300 lb. and 400 lb. wire	100	C 4270
	TELEPHONE	G.P.O. patt.		
Y1/YA 7408	No. 1/162, C.B., black	Handset tel. requiring separate bell-set; fitted with dummy dial; for use on C.B. manual systems	single	C 4270
Y1/YA 9389	No. 1/196, L.B., black	Handset tel. requiring separate bell-set; with tray for subscriber's personal directory, etc.	single	C 8181

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	TELEPHONE - continued			
Y1/YA 7407	No. 1/232, C.B., black	Handset tel. with tray for subscriber's personal directory; requires separate bell-set	single	C 5689
Y1/YA 9494	No. 11	Wall inst. with writing slope; for magneto or C.B.S.	single	C 8181
Y1/YA 9229	No. 121, C.B.	Wall inst.	single	C 8181
Y1/YA 10002	No. 145	For outdoor use, C.B. manual or auto. areas	single	C 8181
Y1/YA 9230	No. 153	Wall inst., weatherproof and flameproof; for use on mag. ccts.	single	C 5687
*Y1/YA 12262	No. 164, Ivory	Handset, without press switch, for tel.No. 1/162 etc.	single	C 8181
Y1/YA 9361	No. 164, red	Handset, without press switch; for tel. No. 1/162	single	C 8181
Y1/YA 10692	No. 184, black		single	C 8423
	No. 184B			
Y1/YA 5070	Black, with cord 4/54A, brown, 48 in.	Handset, with non-locking press switch which makes transmitter cct.; for use on L.B. ccts.	single	C 4270
Y1/YA 6738	Black, with cord inst. No.6/21B, brown,54 in.	Used on tel. set, F, high powered, No.1, Mk.2	single	C 4270
Y1/YA 4252	No. 184C, black, with plug No. 404	Handset, with 2 position locking press switch	single	C 4270
Y1/YA 9231	No. 221, C.B., black	Wall inst. (handset tel)	single	C 5687, C 8635

Y1/YA 9325	No. 246, black	Pendant inst. requiring separate bell-set and mtg. for dial	single	C 8181
Y1/YA 8588	No. 248, C.B.	Handset tel., for use with bell-set 39 or 39A, black	single	C 5687
Y1/YA 8847	No. 250	Lineman's portable test inst., for all systems; moulded case with carrying strap	single	C 5687
Y1/YA 9059	No. 330, C.B., black	Combined set with tray for subscriber's personal directory	single	C 5687, C 8635
	No. 332, C.B.	Combined set, with tray for subscriber's personal directory; for auto. or C.B. direct exch. line		C 8181
Y1/YA 9278	Green		single	
Y1/YA 9279	Ivory		single	
Y1/YA 9280	Red		single	
Y1/YA 11280	No. 332 (Mk.2A) F, black	Combined set, with tray for subscriber's personal directory; for auto, or direct exch. lines	single	C 8635
Y1/YA 11352	No. 333, C.B., black	Handset wall tel. for D.E.L. working	single	C 8635
Y1/YA 9232	No. 396, L.B., black	Combined set. For use on C.B.S. or mag. direct exch. lines, also for long direct exch. lines on auto. or C.B. manual systems	single	C 5687
	<b>TELEPHONE, Hand</b>			
	<b>Moving coil</b>			
Y1/ZA 29026	No. 3	Rubber moulded handle; 2 insets, mic., M.C., No. 2; moulded lead and plug, 5 point, No. 5 (Sec. Z1)	single	C 4270
Y1/YA 1898	No. 2	Moulded body; pressel switch; 1 cord, tel., hand, No. 1; 1 mic., capsule, Mk. 4; 1 plug, No. 406; 1 mouthpiece; 1 recvr., inset, No. 1L, W.D. (I.L. 2319)	single	B 3410

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	TELEPHONE, Hand - continued			
Y1/YA 1899	No. 3	Same as No. 2 but with special pressel bar which maintains permanent contact (I.L. 2319)	single	B 3410
Y1/YA 4927	No. 4	Moulded body; pressel switch; 1 cord, tel., hand, No. 3; 1 inset, carbon, differential, No. 1; 1 recur., inset, No. 1L, W.D.; 1 plug, No. 406; used with tel., L.S., No. 4, set	single	C 4270
Y1/YA 6450	No. 5, Mk. 1	Plastic body; w/o pressel switch; with 1 cord, tel., hand, No. 1; 1 mic., capsule, No. 6; 1 plug, No. 406; 1 recur., I.T.B.A., No. 5; for general use (I.L. 2646)	single	B 9551
*Y1/YA 11669	No. 5 Mk. 2	Similar to Y1/YA 6450 except that it is fitted with earphone magnetic, internal terminal, handset type, Y1/YA 11440	single	
Y1/YA 6451	No. 6	Plastic body; pressel switch; 1 cord, tel., hand, No. 1; 1 mic., capsule, No. 6; 1 plug, No. 406; 1 recur., I.T.B.A., No. 5; for general use (I.L. 2647)	single	B 9551
Y1/YA 7928	No. 10. Mk. 1	Plastic body; moisture-proof pressel switch; 1 cord, tel., hand, No. 10; 1 mic., capsule, No. 9 or 10; 1 recur., I.T.B.A., No. 5; used on tel. sets, J	single	C 4270

*Y1/YA 11672	No. 10 Mk. 2	Similar to Y1/YA 7928 except that it is fitted with earphone, magnetic internal terminal, handset type; Y1/YA 11440	single	
Y1/YA 8079	No. 11	Moulded rubber; lightweight; consists of frame assy., No. 1; case and con. assy., No. 1; cover, No. 1, recvr., watch, I.T.E.; recvr., watch, I.T.E., No. 1; mic., capsule, miniature, No. 1; used with wireless sets, No. 88, types A and B (Sec. Z1) (I.L. 5468)	single	C 4270
Y1/YA 8149	No. 12	Similar to tel., hand, No. 10 but with cord, tel., hand, No. 5; used with rack, tel. terminal, No. 1	single	C 4270
Y1/YA 8232	No. 13A. Mk. 1	<i>Similar to tel., hand, No. 11; with pressel switch in rubber moulding secured to the frame; used with wireless sets, No. 31 (Sec. Z1) (I.L. 5761)</i>	single	C 4270
*Y1/YA 11472	No. 13A Mk. 2	Differs from the Mk. 1 version in the make up of the con.	single	
Y1/ZA 28968	Power microphone No. 1A	Comprises 1 mic., hand, power, No. 1A w/o cord; 1 recvr., watch, F; 1 cord, mic. and recvr., No. 2; 1 plug, 5 point, No. 5 (Sec. Z1); 1 cord, tel., hand, No. 7 and 1 spring cord, restoring	single	C 4270
Y1/YA 9558	S.I. No. 1	Moulded handset, without pressel switch; fitted with 1 inset, standard mic., electromagnetic; 1 inset, standard receiver, electromagnetic, No.2	single	C 8181
Y1/YA 9305	No. 1A	Similar to No. 1 but fitted with 4 ft. 6 in. of 4 way cord terminating in a Mk. 4 plug	single	C 8181
Y1/YA 9559	No. 2	Moulded handset, without pressel switch; fitted with 1 inset, standard mic., carbon, No. 1; 1 inset, standard receiver, electromagnetic, No. 2	single	C 8181

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	TELEPHONE, Hand S.I. - continued			
Y1/YA 9306	No. 2A	Similar to No. 2 but fitted with 4 ft. 6 in. of 4 way cord terminating in plug, No. 404	single	C 8181
Y1/YA 9560	No. 3	Moulded handset, with pressel switch; fitted with 1 inset, standard mic., electromagnetic, No. 1; 1 inset, standard receiver, electromagnetic, No. 2	single	C 8181
Y1/YA 9561	No. 4	Moulded handset, with pressel switch; fitted with 1 inset, standard mic., carbon, No. 1; 1 inset, standard receiver, electromagnetic, No. 2	single	C 8181
Y1/YA 9309	No. 4A	Similar to No. 4 but fitted with 4 ft. 6 in. of 5 way cord terminating in a 5 pin plug	single	C 8181
Y1/YA 9310	No. 4B	Similar to No. 4 but fitted with 10 ft. of 5 way cord terminating in a 5 pin plug	single	C 8181
Y1/YA 9562	No. 4C	Similar to No. 4 but fitted with 4 ft. 6 in. of 4 way cord terminating in a Mk. 4 plug	single	C 8181
Y1/YA 10413	No. 4F	Similar to No. 4 but fitted with 4 ft. 6 in. of 4 way cord terminating in plug No. 404	single	C 8181
Y1/YA 9311	Remote control, No. 1	Moulded handset, with pressel switch and press button; fitted with 1 inset, standard mic., carbon, No. 1; 1 inset, standard receiver, electromagnetic, No. 2	single	C 8181



Y1/YA 9430	Tank mounting self-winding drum and switch assembly	Tel., hand, S.I., No. 3B mounted on a spring loaded drum; this assy. is secured into an armoured box which is in turn secured to a tank; used for communication between the infantry and the supporting tank	single	C 8181
	(Sound powered)			
Y1/YA 4682	No. 1	Similar to tel., hand, H. but fitted with 3 ft. cordage, inst., No. 2/AP; 1 plug, coupling, No. 4 and 1 socket, coupling, No. 4	single	C 4270
Y1/YA 4849	No. 2	Siemens type micro-tel., hand 46A/A; with 1 cord, tel., hand, No. 2; 1 plug, No. 406; 2 I.T.B.A., No. 5; used on tel. sets, H. Mk. 3	single	C 4270
	TELEPHONE, Head and breast			
	(Sound powered)			
Y1/YA 3920	No. 1	Consists of 2 moving-iron recvrs, on a web headband; 1 moving-iron mic. held in position by a Br. fork which in turn is clamped to a breast plate. Includes 1 cover for switch and terminal, 1 neck band and cordage, inst. 2AP	single	C 4270
Y1/YA 4417	No. 1A	Similar to No. 1, but fitted with 1 plug, coupling, No. 4 and 1 socket, coupling, No. 4	single	C 4270
Y1/YA 4090	No. 2	Batteryless tel. attachment comprising 1 recvr. hdgr. (Sound P.), No. 2 and 1 transmitter, breast (Sound P.), No. 2, Mk. 1 (I.L. 2411)	single	C 4270
Y1/YA 4418	No. 2A	Batteryless tel. attachment comprising 1 recvr., hdgr. (Sound P.), No. 2A and 1 transmitter, breast (Sound P.), No. 2, Mk. 2 (I.L. 2411)	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 8846	TELEPHONE, Intercom No. 1/1, black	G.P.O. patt Table inst. with microtel; 7 plunger keys; 1 exch. line and 5 extension lines	single	C 5687
Y1/YA 10886	No. 1/2A, black		single	C 8423
Y1/YA 8346	TELEPHONE, Tracker, No.2	13.1/4 in. x 6.1/4 in. x 3.5/8 in.; M.S. case; fitted with gen., C, tpl.; socket, 4 pt., No. 30 (Sec. Z1); bell, mag., No. 3 W.D., w/o gong; handles, gen., No. 5 and other components; for use with tracker unit on control units, mobile, A.A., No. 1 (N.I.V.) (I.L. 5664)	single	C 4270
*Y1/5805-99-949-2570	TELEPHONE SET Bridging	Comprising 4 headsets, 1 connecting box, 1 handset and connecting cables	set	
Y1/YA 1853	D Mk. 5	Wt. 10.1/2 lb. For components, see C.I.E.M.E. List E.S.200	single	B 3410, B 5882
Y1/YA 6371	Mk. 5/1	Wt. 10.1/2 lb.; as Mk. 5 but does not include recvr., hdgr., C, L.R., single, Mk. 4	single	C 4270

	F	11.3/4 in. x 7.3/4 in. x 6.3/4 in.; port.tel set; with facilities for mag. or buzzer calling; in a metal or moulded case; carried in a wood box; used on mag., C.B. or C.B.S. ccts.		
Y1/YA 2886	Mk. 2	Moulded case (I.L. 2371)	single	B 5255,B 8029
Y1/YA 6244	High power, No.1, Mk.2	12.1/2 in. x 11 in. x 6.1/2 in.; wood box; consists of a modified tel. set F. and a single stage A.F. ampfr.; used on long field tel. line (P.L. 2553)	single	C 4-70
Y1/YA 4841	H, Mk. 3	10.5/8 in. x 4.7/8 in. x 5 in.; met. C.; w/o batteries; mag. or C.B. (I.L. 11815)	single	B 5063,B 9655
Y1/YA 8032	Hand, S.P.,No.2	10 in. x 3.1/2 in. x 4.1/2 in.; wt. 2 lb.; lightweight, w/o batteries; 2 I.T.B.A., No. 5; small A.F. gen. built into the handset	single	C 4270
Y1/YA 3717	L	11.1/2 in. x 6 in. x 5.1/4 in.; wt. 11 lb.; met. C.; mag.; C.B.S.; C.B.; port; general purpose; lineman's tel. (I.L. 2322)	single	B 4476
Y1/YA 6989	Mk. 1/1	Modified version of tel. set, L.; includes two 0.5 µF. condensers mounted on bracket in lieu of 0.1 and 0.5 µF. block condenser; handles, gen., No. 3A in lieu of handles, gen., No. 3	single	C 4270
Y1/5805-99-901-3003	Metal case,w/ringer	W/hand generator 10.1/4 in. x 4.3/4 in. x 5.3/4 in. O/A. dim.; type J.; used on switch/B. mag. 10 line (W.D.) (Old Cat. No. Y1/YA 7815)	single	C 4270
*Y1/5805-99-901-2497	Plastic case, T.M.C.type T 610F	Local battery working, w/ringer, w/ hand gen. w/o dial, 9.3/4 in. lg. 9.1/4 in.w. 5.3/4 in.h. (Old cat. No. Y1/YA 12926)	single	
Y1/YA 4865	THIMBLE, No. 1	2 in. x 1.1/4 in. x 1/2 in.; G.P.O. patt.; used with ratchet and tongs, No. 1; rods, stay, No. 1 and No. 5	single	C 4270

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7487	TIE-BAR, Mounting, runway, frame, I.D.	2 ft. 9 in. long x 1 in. x 3/8 in.; M.S.; part of frame, I.D., swbds., C.B., multiple W.D., unit type	single	C 4270
Y1/YA 3806	TIGHTENER, 5/8 in.	G.P.O. patt.; fitted with bow and ratchet nut; thimble at each end; for ground stay	single	C 4270
Y1/YA 2173	TONGS Draw, light	For straining light teleg. wires by means of ratchet, teleg spring; no keys are required for the tongs but only for the ratchet; for wires up to 150 lb. per mile	pair	9014, 11259
Y1/YA 2174	Heat coil	For removing coil, heat, A	pair	16818, 26217
Y1/YA 2196	TRANSMITTER Breast No. 1	B.P. transmitter with 2 spring-contact plugs to accept sockets, coupling, No. 3 For components, see C.I.E.M.E. List E.S. 109	single	B 3410, B 5585

Y1/YA 8282	Mk. 1/1	Fully tropicalised version of transmitter, breast, No. 1	single	C 4270
Y1/YA 5877	(Sound powered) No. 2, Mk. 3	B.P. transmitter similar to transmitter, breast, No. 1 but fitted with I.T.B.A., No. 5 in place of mic., capsule, No. 8 and includes 1 switch, on-off, S.P., No. 2 (Sec. Z1)	single	C 4270
Y1/YA 1558	Inset, No. 13A	G.P.O. patt.; transmitter, inset, No. 13 (minus guard), modified to provide switch facility for transmitter, No. 23	single	C 4270
Y1/YA 7428	No. 22	G.P.O. patt.; C.B. or L.B. type for tel.; includes 1 mouthpiece, No. 16 and 1 transmitter, inset, No. 13	single	C 4270
Y1/YA 8195	Mounted	G.P.O. transmitter, No. 22 mounted on Admiralty type lampholder, fitted with twin P.V.C. cord 14/.0076; used on reception sets, Marconi, D.F.G.26 (Sec. Z1)	single	C 4270
Y1/YA 2194	No. 23	G.P.O. patt.; C.B. or L.B. moulded B.P. type with switch facility	single	C 4270
Y1/YA 3068	Fitted with plug, No. 404	G.P.O. patt.; includes 1 cord, inst., No. 4/12A, brown, 48 in. and 1 sleeve, leather, No. 1 (N.I.V.)	single	C 4270
Y1/YA 4006	With plug, No. 406	G.P.O. patt.; includes 1 cord, inst., No. 4/12A, brown, 48 in. and 1 sleeve, leather, No. 2 (N.I.V.)	single	C 4270
Y1/YA 3149	No. 23A	G.P.O. patt.; C.B. or L.B. moulded B.P. type without switching facility; includes transmitter, inset, No. 13A (N.I.V.)	single	C 4270
Y1/YA 7665	With plug, No. 404	G.P.O. patt.; includes 1 cord, inst., No. 4/12A, brown, 48 in. and 1 sleeve, leather, No. 1 (N.I.V.)	single	C 4270

## SECTION Y1

## CLASS 5805-TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6686	TUBE Insulating, fanning strip, spacing rod	1/4 in. I.D. x 11/32 in. O.D. x 2.13/16 in. long; ebonite tube; used on test frames, 20 pr., Mk. 3 and 40 pr., Mk. 2	single	C 4270
Y1/YA 8350	Packing, No. 4	G.P.O. patt.; copper; 1.3/4 in. long; to increase the dia. of 40 lb. wire to 100 lb. size	single	C 4270
Y1/YA 7911	UNISELECTOR, No. 33C	G.P.O. patt.; coil resis. 12 + 12 ohms; wiper assy., No. 321A; number wheel engraved 0-24; used with banks, contact, No. 33 (N.I.V.) on rocket projectors	single	C 4270
Y1/YA 8150	UNIT Access jack 10 cct.	14.1/4 in. x 7.3/4 in. x 7 in.; M.S. panel; fitted with M.S. framework; cover; 2 fixing brackets; 4 cableforms; 3 jacks, No. 510; 4 plugs, fixed 12 way, miniature; used on rack, tel., terminal, No. 1	single	C 4270

Y1/YA 7207	40 cct.	19 in. x 6.3/4 in. x 6.3/4 in.; M.S. framework; fitted with front and back cover; cableform; 6 jacks, No. 520BP; 2 strips, connection, No. 22A; 6 strips, wood, No. 2 (Sec. Y2); 10 fasteners, jack, No. 17; 4 labelholder assy; 30 pegs, designation; used on swbds., C.B., multiple W.D., unit type	single	C 4270
Y1/YA 8090	Alarm, No. 1	5.1/8 in. x 5.1/8 in. x 3.7/8 in.; met. C.; fitted with 1 relay; 1 key; 1 desiccator; 2 sealed miniature lampholders; two 180 ohms resistors; 1 bell, battery, No. 13A; 1 plug, fixed, 12 way, miniature, Mk. 4 (Sec.Z1); 1 plug, fixed, 6 way, S.P., miniature, Mk. 4 (Sec.Z1); used on racks, tel, terminal, No. 1	single	C 4270
Y1/YA 6460	Amplifying, No. 23D	G.P.O. patt.; for use on multiphone, ccts., amprs., up to a max. of 80 ccts.; operates from A.C. only	single	C 4270
Y1/YA 7206	Generator, answering, 20 circuit	19 in. x 6.3/4 in. x 6.3/4 in.; M.S. framework, with front and back cover, fitted with 20 indicators, M.R., No. 3; 20 jacks, M.R., No. 1, modified; 10 keys, No. 228; 20 condensers, No. 1C; 1 strip, connection, No. 24A; 2 terminals, inst., slotted, single, No. 4, small (Sec. Y3); 1 cable form; used on swbds., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 8093	Line Fuze and protector, No. 1	19.1/4 in. x 5.1/8 in. x 1 in.; M.S. framework, fitted with 10 protectors and fuzes, No. 1; used on rack, tel., terminal, No. 1	single	C 4270

## SECTION Y1

## CLASS 5805--TELEPHONE AND TELEGRAPH EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 8092	UNIT Line - continued Relay, No. 1	Met. C.; fitted with 5 relays; 5 condensers, 2 P (Sec. Z1); 5 rectifiers; 1 desiccator, 1 in.; 1 plug, fixed, 25 way, miniature, Mk. 4 (Sec. Z1); 1 plug, fixed, 4 way, miniature, Mk. 4 (Sec. Z1) and gasket; used on rack, tel., terminal, No. 1	single	C 4270
Y1/YA 7885	Multiple, 400 line, C.B. (W.D.) Mk. 2	3 ft. 10.1/2 in. x 9 in. x 2 ft. 1.1/4 in.; M.S. framework, with wood facings and 2 bulletin panels; fitted with 20 cable forms, each wired to 1 jack, No. 320BN and 2 terminal strips 60 point; spacing blocks; stile covers and designation pegs; used on exch., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 6006	Switchboard, magneto, multiple, 360 line, No.1	4 ft. 5.1/4 in. x 1 ft. 6 in. x 1 ft. 5 in.; wooden case fitted with 15 jacks, No. 520BP; 6 jacks, No. 810BN; jack spaces; terminal strips; jack fasteners; cable forms	single	C 4270



Y1/YA 8083	Telephone, 1 + 3, No. 1	14.5/8 in. x 6.1/2 in. x 3.1/4 in.; metal framework, fitted with 1 unit, common app.; 1 unit, line, 3 cct., No. 1; 1 con., miniature, 12 pt., No. 1, 1 ft.; (Sec. Z1) used on equipt., tel., terminal, No. 1	single	C 4270
	VIBRATOR, Ringing	8.5/8 in. x 5.5/8 in. x 3 7/32 in.; met. C.; converts D.C. supply to A.C. at approx. 20 c/s.; for mag. bell ringing (I.L. 2407)		
Y1/YA 2563	12 V. Mk. 1		single	B 6340
Y1/YA 10516	Mk. 2	Similar to Mk. 1 but with component changes	single	C 8181
Y1/YA 2562	24 V. Mk. 1		single	B 6340
Y1/YA 10515	Mk. 2	Similar to Mk. 1 but with component changes	single	C 8181
Y1/YA 2209	VICE, Draw, No. 2	G.P.O. patt.; for iron wire; steel, with drum ratchet; for permanent line construction; without key, draw, vice, No. 2	single	8666,26567
	WIPER			
Y1/YA 11338	No. 23	G.P.O. patt.; pre-2000 vertical marking bank	single	C 8635
Y1/YA 7932	No. 321A	G.P.O. patt.; 3 arms, double-ended; for use on uniselector, No. 33C	single	C 4270
CLASS 5820-RADIO AND TELEVISION COMMUNICATION EQUIPMENT, EXCEPT AIRBORNE				
Y1/YA 8310	BELL, 3.5 ohms, No.1	Bell, bty., C modified for A.C. working; used on reception set, S.S.B., triple diversity, No. 2 (Sec. Z1)	single	C 4270

## SECTION Y1

## CLASS 5820- RADIO AND TELEVISION COMMUNICATION EQUIPMENT, EXCEPT AIRBORNE - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 2778	CASE, Carrying, No. 4	M.S.; I.D. 8.1/4 in. x 7.9/16 in. x 6.1/4 in.; 1 key, W.T., 8A., No. 2 (Sec.Z1) mounted on underside of lid; with web cover and sling	single	B 4110,C 4270
*Y1/5820-99-943-6987	INSTALLATION KIT,Electronic	Used on recorder R.E.H. (1) and R.E.H. (3)	single	
Y1/YA 5188	LINK, Sling, Carrying	1.7/16 in. x 17/32 in.; brass, No. 10 S.W.G. dia.; rectangular link; used on case, carrying, No. 4	single	C 4270
CLASS 5830-INTERCOMMUNICATION AND PUBLIC ADDRESS SYSTEMS, EXCEPT AIRBORNE				
Y1/ZB 12914	AMPLIFIER Apparatus, E.S. No.9	For mounting in the interior of tanks, used in conjunction with W.S. Nos. 19 and 29 (Sec.Z1)	single	C 5687
Y1/ZB M94 0005	Ardente type, 615 No. 1	Met. C.; 4 valve; operated from 12 V., D.C.; for use with app., L.S., No. 3, kit No. 1	single	C 4270
Y1/YA 8791	W., Mk. 3	Battery operated general purpose ampfr.; uses 12V. sec. battery, output 615 watts	single	C 5687

Y1/ZB 11566	Complete, apparatus, L.S. No. 6	In wooden case; includes spare valves and mic. inset; 1 pin, earth, small; 20 yd. of cord, elec., U.N., twin, low, 0.001 (Sec. Y3); operated from 200/250 V., A.C.; for components, see E.M.E.R. telecom. C156/2	single	C 4270
Y1/YA 11303 *Y1/YA 12375	No. 100A No. 109A Portable, public address, No. 1	G.P.O. patt	single	
Y1/ZB 11017	Mk. 2	Met. C. W/handle; 5 valve; 15W. output; mains or bty operated; W/O valves or vibrator	single	C 4270
Y1/ZB 11681	Mk. 3	Similar to Mk. 2 but has radio interference suppression and modified second stage. For components, see E.M.E.R. telecom. 156/3	single	C 4270
Y1/YA 9333	AMPLIFIER AND LOUDSPEAKER, No. 2	G.P.O. patt.; single stage L.F. ampfr. with L.S.; working voltage 100-250 V., 50 c/s.	single	C 8181
Y1/ZB 0109	APPARATUS L.S. No. 2 Switch unit	6.1/2 in. x 2.1/4 in. x 1.5/8 in.; met. C. fitted with 4 switches, on-off, S.P., No. 8 (Sec.Z1); 10 terminals, inst., insul. wire grip, No. 4 (Sec. Y3); and lugs, connection	single	C 4270
*Y1/YA 12429	No. 21	A two-way audio communication system for use between a control station and four gun sites. Comprises -: 1 - Ampfr control group Y1/YA 12421 4 - L.S. Units Y1/YA 12422 5 - handsets, tele Y1/YA 12423 1 - Distribution Box Y1/YA 12424	single	

## SECTION Y1

## CLASS 5830-INTERCOMMUNICATION AND PUBLIC ADDRESS SYSTEMS, EXCEPT AIRBORNE - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	APPARATUS L.S. No. 21 - continued			
		1 - Case, storage Y1/YA 12425		
		1 - Con. (10 way) Y1/YA 12426		
		1 - Con. (3 way) Y1/YA 12427		
		1 - Con. (2 way) Y1/YA 12428		
*Y1/YA 12430	Kit, No.1	As for Y1/YA 12429 but without L.S. unit (Y1/YA 12422) (1 of each)	single	
*Y1/YA 12431	Kit, No.2	Comprises -: 4 - L.S. units Y1/YA 12422 4 - Hand sets, tele Y1/YA 12423	single	
	CASE, Amplifier, complete Apparatus, L.S.			
Y1/ZA 26700	No. 6	21 in. x 17.1/2 in. x 15.3/4 in.; soft wood	single	C 4270
Y1/ZA 29643	No. 6T	Impl. version of No. 6	single	C 4270
*Y1/YA 11186	CONSOLE, Control	Marconi type B.D. 595	single	

Y1/YA 2799	CONTROL UNIT, No. 1	8.1/4 in. x 7.3/4 in. x 5.1/4 in.; C.I. with 2 cable glands and detachable cover; fitted with 1 bulb, 12 V., Q (Sec.Y3); 10 ft. of cord, elec. U.N., twin, 0.0017 (Sec. Y3); 1 coupling socket, 3 point, No. 2, Mk. 1; 1 lampholder; 1 lens; 1 xform; used on tel., L.S., No. 1 set	single	B 4106,C 4270
	COVER			
Y1/YA 6408	Front telephone unit, L.S., No. 1	8.7/8 in. x 3.1/2 in. x 3/16 in. mill board; front cover of battery compartment on tel. unit, L.S., No. 1	single	C 4270
Y1/YA 5777	Inner, No. 2	Cpr. 4.1/2 in. dia. drilled with 3 fixing holes; used on tel., L.S., No. 5	single	C 4270
Y1/YA 3221	DEFLECTOR, Sound, L.S. telephone	5.5/8 in. dia. x 1.1/2 in.; metal; used on tel., L.S., No. 2 and L.S., app., L.S., No. 6	single	C 4270
	LID			
Y1/YA 6419	Case, unit, L.S., No.2	5.25/32 in. x 3.5/8 in. x 3/16 in.; hardboard; part of case, unit, L.S., No. 2	single	C 4270
	Case			
Y1/ZA 26642	Ampfr., App., L.S.,No.6	19.1/2 in. x 14 in. x 7/8 in.; softwood, complete with 2 metal straps 5 in. x 1.1/2 in. 2 fixing screws, and diagram plate screwed to the underneath side; used on ampfr., complete, app., L.S., No. 6	single	C 4270
Y1/ZA 30758	Ampfr., App., L.S.,No.6T	19.1/2 in. x 14 in. x 7/8 in.; tpl; version; for use on app., L.S., No. 6T	single	C 4270
Y1/YA 6410	Telephone unit, L.S.,No.1	9.1/4 in. x 4.3/4 in. x 3/16 in.; hardboard, edged with M.S. angle, No. 16 S.W.G., 5/8 in. x 5/8 in.; includes 1 hinge, piano, 8 in. x 3/4 in. and 1 plate, diagram, part of case, tel. unit, L.S., No. 1	single	C 4270

## SECTION Y1

## CLASS 5830-INTERCOMMUNICATION AND PUBLIC ADDRESS SYSTEMS, EXCEPT AIRBORNE - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 9792	MEGAPHONE, Power, 11.1/2 in. dia. horn	Power megaphone complete with valve, less ampfr., to operate from a 4-4.1/2 V. battery; amplifies the voice so that it can be heard up to a distance of 500 yds.	single	C 8181
Y1/YA 4705	PANEL Component, No. 1	8 in. x 2.1/4 in. x .064 in.; M.S. plate for components; used on tel., L.S., No. 2, L.S.	single	C 4270
Y1/ZA 22963	Front, P.A., No. 1, Mk.2	Plastic panel; engraved; used on ampfr., port., P.A., No. 1, Mk. 2	single	C 4270
Y1/ZA 26270	Mains, tapping 205 V./225 V./245 V., No. 1	Voltage selector strip; used on ampfr., port., P.A., No. 1, Mk.2	single	C 4270
Y1/YA 6445	Relay mounting, control unit, No. 2	2.1/4 in. x 1.1/2 in. x 1/8 in.; plastic laminated board; used on control units, No. 2, Mk. 1/1 and Mk. 2; tel., L.S., No. 2	single	C 4270
Y1/YA 4710	Switch and lamp control unit, No. 2 Mk. 1	5.5/16 in. x 2.3/4 in. x 3/16 in.; plastic board, drilled for components; used on tel., L.S., No. 2 control units	single	C 4270

Y1/YA 5592	Mk. 1/1	5.5/16 in. x 2.3/4 in. x 3/16 in.; plastic board, drilled and engraved for components; used on tel., L.S., No. 2, control units, Mk. 1/1	single	C 4270
Y1/ZA 26643	Tag, 5 way, 3.3/4 in. x 2.1/4 in., No. 1 Terminal	1/16 in. thick; used on ampfr., complete, app., L.S., No. 6	single	C 4270
Y1/YA 4709	Control Unit, No. 2, Mk. 1	5 in. x 2.3/4 in. x 1/8 in.; plastic, engraved and drilled; used on tel., L.S., No.2	single	C 4270
Y1/YA 4706	No. 1	2.11/16 in. x 2.11/16 in. x 1/8 in.; plastic board, right angled triangle; used on tel., L.S., No. 2, L.S., cases	single	C 4270
	PLATE Engraved 3/8 in. x 1.1/4 in.	Ebonite; engraved as indicated; used on ampfr., complete, app., L.S., No. 6		C 4270
Y1/ZA 26639	Earth		single	
Y1/ZA 26635	Mains fuzes		single	
Y1/ZA 26637	Mains switch		single	
Y1/ZA 26636	Microphone		single	
Y1/ZA 26638	Output indicator		single	
Y1/YA 11448	PUBLIC ADDRESS SET, 60 W. output, 24 V. battery power supplies, M.I.M.C.O. type 2258B, edition A	Comprises ampfrs, audio-frequency, M.I.M.C.O. type 1165C/ 1172C, modified (Y1/YA 11465); L.S. assys., 60 W., M.I.M.C.O. type 2293A (Y1/YA 11449); mic., hand, moving coil, noise cancelling type VC/52/MTH/S (Y1/YA 11450); mic., hand, moving coil, type B50 (Y1/YA 11451)	single	C 9519

## SECTION Y1

## CLASS 5830-INTERCOMMUNICATION AND PUBLIC ADDRESS SYSTEMS, EXCEPT AIRBORNE - continued

Cdt. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZB 12982	RACK, Mounting Amplifier, P.A., No. 1	18.1/2 in. x 10.1/2 in. x 6.1/2 in.; mounts ampfr., port., No. 1	single	C 4270
Y1/ZA 23878	RING, Inner, microphone, M.C., No. 1	Used on ampfr., P.A., port., No. 1	single	C 4270
*Y1/YA 12208	SATCHEL, No. 4	For containing ampfr., No. 109A	single	
Y1/ZA 26582	SHOCK ABSORBER Bridge, No. 9	Used on ampfr., complete, app., L.S. No. 6	single	C 4270
Y1/ZA 23540	Metalastic, No. 1	Used on app., L.S., No. 3, C.S., No. 2	single	C 4270
*Y1/YA 12122	Minifon recorder, 12 m.m.	Used on Minifon model 54	single	
*Y1/YA 12123	Minifon recorder, 14 m.m.	Used on Minifon model 54	single	
Y1/YA 6448	STRAP, Headgear, retaining, control unit, No. 2	Web, drab, 9.1/2 in. x 2 in.; with tip, br., 2 in. at one end; fitted with eyelet; used on L.S. No. 2, control units, No. 2, Mk. 2	single	C 4270
Y1/YA 2796	TELEPHONE, Loudspeaking No. 1	Speech amplifying app; valveless For C.A. For components, see C.I.E.M.E. list E.S. 2	single	B 4106, B 5584



	No. 2			
Y1/YA 7350	Control unit Mk. 1/2	Modified version of the Mk. 1/1 to permit single wire earth return working to the L.S.	single	C 4270
Y1/YA 4848	Mk. 2	Similar to Mk. 1/1 but with slight structural alterations	single	C 4270
Y1/YA 7351	Mk. 2/1	Modified version of the Mk. 2 to permit single wire earth return working to the L.S.	single	C 4270
Y1/YA 4158	Coupling unit	5.1/2 in. x 2.1/2 in. x 3 in.; met. C.; fitted with 1 jack, mic., No. 2; 1 socket, coupling, No. 2; 1 plug, coupling, No. 2, with cord, elec., U.N., 3 core, low, 0.001 (Sec. Y3); 1 plug, single, No. 9 (Sec. Z1); with cord, elec., U.N., twin, low (Sec. Y3); for connecting 2 sets of 4 L.S.; used on tel., L.S., No. 2, (8 gun, static)	single	C 4270
Y1/YA 2803	Set	Comprises tel., L.S., No. 2, control units, Mk. 1 or Mk. 1/1 or Mk. 2 with mic., hand, power, No. 1B; recvrs., hdr., C,L.R., double, Mk. 3 or No. 3; 4 L.S., tel., No. 2, mounted	single	C 4270
Y1/YA 4930	No. 4, set	Set comprises 2 tel., units, L.S., No. 1; 1 tel., unit, L.S., No. 2; 1 L.S. tel., No. 4; 1 mic. and recvrs., hdgr., assy., No. 6; 1 transmitter, breast, No. 1; 1 tel., hand, No. 4; 1 con., twin, No. 76; 150 yd. of cable, elec., DB, twisted, Mk. 3 (Sec. Y3) (I.L.2462)	single	C 4270

## SECTION Y1

## CLASS 5830-INTERCOMMUNICATION AND PUBLIC ADDRESS SYSTEMS, EXCEPT AIRBORNE - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 4928	TELEPHONE UNIT, L.S., No.2	6 in. x 3.1/2 in. x 5 in.; hardboard case; part of tel., L.S., No. 4, sets (I.L.2462)	single	C 4270
Y1/YA 8256	UNIT Amplifier and loudspeaker, No. 1	20.3/4 in. x 15.1/2 in. x 9 in.; consists of 2 stage ampfr. and L.S., P.M., 10 in., 2.5 ohms, No. 1, fitted in wooden case; used with ampfr., and playback unit, No. 1	single	C 4270
Y1/YA 6449	Energizing, loudspeaker telephone No. 2	Consists of magnet, diaphragm, back plate assy. and front plate assy.	single	C 4270
Y1/ZB 12916	Loudspeaker, No. 3	Used on L.S., P.M., projection type, 2,000 ohms, No. 1	single	C 4270
Y1/YA 9237	Transfer, intercom No. 1	G.P.O. patt.; for use on subscribers installations 1 exch line, up to 5 extensions	single	C 5687
Y1/YA 9238	No. 2	2 exch lines, up to 10 extensions	single	

CLASS 5835-SOUND RECORDING AND REPRODUCING EQUIPMENT

	ARM			
*Y1/YA 11998	Pick up	Type super 90	single	
*Y1/YA 11191	Sound reproducer	Tangential, type super 90, Mk. 2	single	
*Y1/YA 12067	Swinging	Supporting erase magnet, minifon recorder	single	
*Y1/YA 12068	Switch	Start/stop minifon recorder, model 54	single	
Y1/ZA 30023	ARMATURE, Pick-up, No. 5	1 in. x 1/2 in. x 1/4 in.; armature and reed, fitted with rubber ring, for pick-ups, E.M.I., type 12	single	C 4270
Y1/YA 12069	BELT, Driving, Minifon recorder	Model 54	single	
Y1/ZA 31663	BELT, Endless Cotton, 14 7/16 in.	14.7/16 in. inside circumference x 3/32 in. dia; for use on recorder, with playback wire No. 1	single	C 4270
Y1/ZA 32832	Rubber, 26 in. No. 1	26 in. inside circumference x 3/16 in. dia.; for use on recorders, disc, broadcast type, No. 1, Mks. 2 and 3	single	C 8635
	BLOCK			
	Connection			
	5 way			
Y1/YA 8268	No. 1	Used on units, playback and pre-ampfr., No. 1	single	C 4270
Y1/YA 8274	No. 5	2.3/8 in. x 13/16 in. x 5/8 in.	single	C 4270
Y1/YA 8284	6 way, No. 6	2.3/4 in. x 13/16 in. x 5/8 in.	single	C 4270
*Y1/YA 11331	BRAKE, Complete	Rewind; minifon recorder, model 54	single	
*Y1/YA 11329	BRAKE ACTION, complete	Forward/Reverse; minifon recorder, model 54	single	

## SECTION Y1

## CLASS 5835-SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
*Y1/YA 11330	BRAKE ASSEMBLY	Stop/start; minifon recorder, model 54	single	
Y1/ZA 31676	BRAKE RELAY ASSEMBLY, No.1	2.1/4 in. x 2 in. x 1.1/8 in.; coil resis. 500 ohms; single make; operates on 115 V., A.C.; for use on recorder, with playback, wire, No.1	single	C 4270
Y1/ZA 31794	BUSH, Oilite, special, .5 in. long, No. 1	.5 in. long x .2502 in. I.D. x .4074 in. O.D.; used on recorder, with playback, wire, No. 1	single	C 4270
*Y1/YA 11305	CABLE, Bowden type	Minifon recorder; transformer/rectifier unit	single	
*Y1/5835-99-943-9128	CAN, Storage Sound recording tape Metal 3.3/4 in. can dia.	Cad. plated; 1/4 in. tape accomodated 200 ft. reel capacity, for recorder/reproducer, sound, REH 3	single	
*Y1/5835-99-943-9129	7.5/32 in. can dia.	1500 ft. reel capacity; for recorder/reproducer, sound, REH 3	single	
*Y1/5835-99-901-2137	Steel 7.11/32 in. dia. x 15/16 in. deep	For 1200 ft. of tape, magnetic recording; used on recorders, magnetic tape w/playback wire, No. 3, kit, No. 1	single	

*Y1/YA 11195	CARTRIDGE, sound reproducer	78/LP. with sapphire styl. includes turnover mechanism enabling the correct stylus for either L.P. or 78 R.P.M. records to be selected	single	
Y1/ZA 31744	CASE, Spare parts, No. 32 filled	14 in. x 12.1/2 in. x 6.1/2 in.; weight 27 lb.; hardwood, hinged carrying case filled with spares; for use with recorder, with playback, wire, No. 1	single	C 4270
*Y1/YA 12078	CHOKE	Minifon recorder, model 54	single	
*Y1/YA 12079	CIRCLIP, DIN 799	Minifon recorder, model 54	single	
Y1/YA 8248	CLIP Disc, retaining, No. 1	Metal clips, for securing record when recording	single	C 4270
*Y1/YA 11307	Wire leader	Minifon recorder, model 54	single	
*Y1/YA 11308	CLUTCH	Minifon recorder, model 54	single	
Y1/ZA 31652	COIL, Hum, recording unit	5/8 in. dia. x 9/16 in. long; ebonite bobbin wound with 3,500 turns of No. 44 S.W.G. enam. cpr. wire; used on recorders, with playback, wire, No. 1	single	C 4270
Y1/ZA 31645	COLLAR, Steel, 3/16 in. I.D. x 7/16 in. O.D. x 1/4 in.	M.S.; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31913	CONTAINER, Empty, No. 1, wire recording	3.7/8 in. dia. x 1.3/8 in. deep; tinned plate; used on recorder, with playback, wire, No. 1	single	C 4270
*Y1/5835-99-943-8232	CONTROL, Sound recorder, reproducer	Voice operation or remote control; Wright and Weaire type	single	
*Y1/YA 12083	COVER, Erase head	Minifon recorder, model 54	single	

## SECTION Y1

## CLASS 5835-SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
*Y1/YA 12084	COVER, Housing	Minifor recorder, model 54	single	
Y1/ZA 31651	COVER, Recording head, mu-metal, 1.1/8 in. x 1.1/8 in. x 13/16 in.	Used on recorder, with play-back, wire, No. 1	single	C 4270
Y1/ZA 29857	DISC, Recording 13 in., single side, No. 1	G.P.O. patt.; cellulose-actate-coated zinc; for 1 for 1 or 4 hole fixing	single	C 4270
Y1/ZA 29858	17.1/4 in., single side, No. 1		single	C 4270
Y1/ZA 31677	DRIVE ASSEMBLY, Timing unit No. 1	Cast al. frame, includes stainless steel spindle 4.5/16 in. long, worm wheel, spiral gear wheel and oilite bushes; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31670	ERASE HEAD ASSEMBLY, No. 1	Includes coil assembly, laminations, fixing strip and erase head body; used on recorder, with playback, wire, No. 1	single	C 4270
*Y1/YA 12086	ERASE HEAD ASSEMBLY, Minifon Recorder	Without cover, model 54	single	

*Y1/5835-99-901-0051	ERASER, Magnetic, Recording Tape		single	
Y1/ZA 31644	FOLLOWER, Wire guide, steel, 1/4 in. dia. x 15/32 in.	Stainless steel; used on recorder, with playback, wire, No. 1	single	C 4270
*Y1/YA 11311	FUSE	1A; glass tubular; Minifon recorder: transformer/ rectifier unit, model 54	single	
*Y1/YA 11312	FUSE-UNIT ASSEMBLY	Minifon recorder; transformer/rectifier unit	single	
*Y1/YA 12087	GOVERNOR BRUSH ASSEMBLY	Minifon recorder, model 54	single	
*Y1/YA 12088	GUIDE, Wire	Minifon recorder, model 54	single	
Y1/ZA 22966	HANDLE, Carrying, No. 15	With brackets and clips; used on ampfr., port., P.A., No. 1, Mk. 2	single	C 4270
Y1/ZA 30585	HEAD, Cutter, B.B.C., type A	Used with disc recorders	single	C 4270
	INSERT, Microphone			
*Y1/YA 12089	Lepal type	Minifon recorder, Model 54	single	
*Y1/YA 12090	Wrist type	Minifon recorder, model 54	single	
*Y1/YA 12063	JACK PLUG, (Long)	Minifon recorder, model 54	single	
*Y1/YA 12091	JACK SOCKET ASSEMBLY	Minifon recorder, model 54	single	
Y1/ZA 31657	LATCH, Retaining, spool assembly 21/32 in. x 9/32 in. x 1/16 in.	M.S.; used on recorder, with playback, wire, No. 1	single	C 4270

## SECTION Y1

## CLASS 5835-SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
*Y1/YA 12064	LEAD AND PLUG Connecting Reproducer	Minifon recorder, model 54	single	
*Y1/YA 12092	Microphone	Wrist type; Minifon recorder, model 54	single	
*Y1/YA 12093	LEAD, Microphone	Minifon recorder, model 54	single	
*Y1/YA 11328	LEAD, Secondary	Minifon recorder; transformer/rectifier unit, model 54	single	
*Y1/YA 12094	LEVER, Brake	Stop/Start; Minifon recorder, model 54	single	
Y1/ZA 31678	MAINDRIVE ASSEMBLY, recording unit, No. 1	8.1/2 in. x 4 in. x 1 in.; consists of cast al. frame fitted with stainless steel spindle, worn wheel, pinion and bevel gears; used on recorder, with playback, wire No. 1	single	C 4270
*Y1/YA 12065	MINIATURE REPRODUCER	Minifon recorder, model 54	single	
*Y1/YA 12098	MOTOR	Minifon recorder, model 54	single	
Y1/ZA 19693	NEEDLE, Playback, packet of ten	Silent stylus type for pick up, hypersensitive, H.M.V. type; 1 needle plays 50 discs	pkt.	C 4270



	NUT			
*Y1/YA 12099	Knurled	Minifon recorder	single	
*Y1/YA 12101	Lock, hex. E.M.I. No.M; 53. 51.02.05	Used on Minifon recorder, model 54	single	
*Y1/YA 12100	Lock, hex. E.M.I. No.M; 53.61.02.05	Used on Minifon recorder, model 54	single	
	PICK-UP			
	E.M.I. type 12			
	Long arm			
Y1/ZA 30507	No. 1	Used with disc, recording, 17.1/4 in., No. 1 by Army Broadcasting Services	single	C 4270
Y1/ZA 30506	Short arm, No. 1	Used with disc, recording, 13 in., No. 1 by Army Broadcasting Services	single	C 4270
	Gramophone			
Y1/ZA/BF 28831	No. 2	"Head" only, tone arm removed; used on recorders, disc, broadcast type, No. 1, Mks. 2 and 3	single	C 4270
	POINTER AND BUSH ASSEMBLY			
Y1/ZA 31671	Seconds hand, No. 1	5/8 in. dia. x 1/4 in.; 3/16 in. spindle hole; Br.; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31674	Timing unit, No. 1	5/8 in. dia. x 1/4 in.; 5/16 in. spindle hole; Br.; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31673	POINTER AND KNOB ASSEMBLY			
	Timing unit, No. 1	5/8 in. dia. x 7/16 in.; 3/16 in. spindle hole; 3/8 in. deep; br.; used on recorder, with playback, wire, No. 1	single	C 4270

## SECTION Y1

## CLASS 5835--SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZA 31662	PULLEY Double-V., 3.7/16 in. dia. x 1.3/8 in. thick x 1/4 in. bore, No. 1	Double pulley for fast and slow speeds; used on recorder, with playback, wire, No. 1 (IL.5573)	single	C 4270,C 5687
Y1/ZA 32835	Rubber, 1/4 in. I.D. x 1.3/4 in. O.D. x 5/8 in., No. 1	<i>Rubber wheel forced on brass bush; used on recorders, disc, broadcast type, No. 1, Mks. 2 and 3</i>	single	C 4270,C 8635
Y1/ZA 31658	Single-V., 2.31/32 in. dia. x 1.3/8 in. thick x 1/4 in. bore, No. 1	Single pulley; used on recorder, with playback, wire, No. 1	single	C 4270,C 5687
Y1/ZA 31796	PULLEY AND BUSH ASSEMBLY Rewind, No. 1	1.3/8 in. dia. x 1/2 in.; duralumin; with oilite bush; single speed; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31795	Wind, No. 1	1.3/8 in. dia. x 3/4 in.; duralumin; with oilite bush; 2 speed; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31650	Wire, guide, No. 1	1.15/16 in. dia. x 7/16 in.; duralumin; with oilite bush; used on recorder, with playback, wire, No. 1	single	C 4270

	PUSH ROD			
*Y1/YA 12103	Long	Minifon recorder, model 54	single	
*Y1/YA 12104	Short	Minifon recorder, model 54	single	
Y1/ZA 31661	RATCHET, Stainless steel, 32 teeth, 15/16 in. x 1.9/16 in. O.D. x 1/8 in.	Stainless steel; used on recorder, with playback, wire, No. 1	single	C 4270
	RECORDER			
	Disc			
*Y1/YA 12137	M.S.S.type CLED/3/3	Comprises: disc recorder; 50 watt ampfr., R.A.51; control/equaliser unit CA/8; metal cases for items 2 and 3	single	
Y1/YA 8179	No. 1	16.3/8 in. x 12 in. x 9.3/8 in.; edge drive recorder; fitted with cutter head and traverse gear; mounted on metal plate; used on training set, No. 5A	single	C 4270
	Magnetic tape with playback			
Y1/YA 9500	No. 4	Lightweight battery operated magnetic tape recorder with canvas carrying case. Includes microphone, headphones, and 6 reels of tape contained in lightweight carrying case. Does not include batteries. Recorder weight 14.1/2 lb., size 14 in. x 7 in. x 8 in.	single	C 6601
*Y1/YA 12019	No. 4B	E.M.I type L2/A battery operated recorder tape speed 3.3/4 in./SPC playing time 30 min. with carrying case. 14 in. x 7 in. x 8 in. weight 14.1/2 lbs.	single	
Y1/YA 8667	R.E.H.I.	Admiralty patt. portable type recorder and playback, with microphone, hand. M.C., 100,000- ohms, No. 7 and mains lead; includes a box of working spares	single	C 5687

## SECTION Y1

## CLASS 5835-SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZA 31075	RECORDER - continued With playback, wire, No.1	15.1/2 in. x 13 in. x 10.3/4 in.; magnetic wire recorder and reproducer (IL.5573)	single	C 4270
*Y1/YA 11368	Wire with playback Minifon, kit No. 1	Used on Minifon model 54	single	
*Y1/YA 11314	Wire, with playback Minifon model 54	Includes green leather carrying case	single	
*Y1/5835-99-901-2114	RECORDER-REPRODUCER SET Sound Admiralty outfit R E H (3)	Comprises; Recorder-Reproducer, sound Microphone, dynamic Inter connecting box Control, sound, recorder-reproducer Tape, sound recording (1200 ft) Tape, sound recording (200 ft) Maintenance kit, elec. equipt.	single	
		943-8235 972-6181 943-7003 943-8232 943-6981 943-8239 943-8229		

*Y1/5835-99-901-2115	R E H (4)	Comprises; Recorder-Reproducer Sub-assy. sound Ampfr. power supply Microphone, dynamic Inter connecting box Installation kit Rack, 19 in. design 1 Control, sound recorder-reproducer Tape, sound recording (1200 ft) Tape, sound recording (200 ft) Maintenance kit, elec. equipt	943-8238 943-8230 972-6181 943-7003 943-6987 AP 54819 943-8232 943-6981 943-8239 943-8229	single
*Y1/YA 12056	Sound E.M.I. type TR 52/2C	Port. tape recorder; 7.1/2 to 3.3/4 i.p.s. tape speed; 20 in. x 17.1/2 in. x 13.1/2 in.; weight 80 lb. for Forces Broadcast System		single
*Y1/YA 11545	TR.90/C/15/F/C/A	Full track, tape; 10 watt monitor amp.;		single
*Y1/YA 12618	Sound, magnetic tape type Ficord 1A 1/4 in.W. 50 to 12,000 cycles	7.1/2 in. and 1.1/8 in. per sec; 4.2 V. batteries 9.5/8 in. x 5 in. x 2.5/8 in. o/a dim. Transistorised port. tape recorder; 7.1/2 in. and 1.7/8 in. per sec. tape speed; battery operated		single
*Y1/5835-99-943-8235	1/4 in. W.60 to 10,000 cycles	1.7/8 in. 3.3/4 in. 7.1/2 in. per sec. Comprises; Recorder-reproducer sub-assy. sound ampfr-power supply	943-8238 943-8230	single
*Y1/YA 11784	Sound, Wright and Weaire type YD/B	Port, type recorder c/w Reslo ribbon microphone and mic. disc stand		single

## SECTION Y1

## CLASS 5835--SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
*Y1/YA 12105 Y1/ZA 31653	RECORDING HEAD ASSEMBLY Minifon recorder No. 1	Minifon model 54 Comprises coil, pole piece, laminations, cover; used on recorder with playback, wire, No. 1	single single	C 4270
*Y1/5835-99-942-1756	REEL, Sound recording tape Metal	7 in. dia; 1/2 in. wide, 1/4 in. max. width of tape, with locking devices, W and W DNA 1308	single	
Y1/5835-99-901-2090	Plastic	7 in. disc 1/2 in. wide, 1/4 in. max. width of tape	single	
*Y1/YA 12124	SPACER, brass	Minifon recorder, model 54	single	
Y1/ZA 31680	SPINDLE ASSEMBLY Recording unit, No. 1	31/64 in. dia. x 7.5/8 in.; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31672	Wire feed, No. 1	3/16 in. dia. x 5.3/4 in.; stainless steel, fitted with wire feed finger and clip; used on recorder, with playback, wire No. 1	single	C 4270

Y1/ZA 32833	SPINDLE AND IDLER ASSEMBLY; No. 1	1.13/16 in. x 1,3/4 in. x 2.1/4 in.; idler assy. mounted on M.S. spindle 2.3/16 in. long; flange at bottom of assy.; used on recorders, disc, broadcast type, No. 1, Mks. 2 and 3.	single	C 4270, C 8635
*Y1/YA 12009	SPLICER, tape, sound, recording	Bib type	single	
Y1/ZA 31745	SPOOL Empty, wire recording, No. 1	Plastic spool for 1/2 lb. of recording wire; used on recorder, with playback, wire, No. 1	single	C 4270
*Y1/YA 12106	Take up	Minifon recorder, model 54	single	
*Y1/YA 11324	Wire, empty	Minifon recorder, model 54	single	
*Y1/YA 12061	Wire, filled, 1/2 hour	Minifon recorder, model 54	single	
*Y1/YA 12060	Wire, filled, 1 hour	Minifon recorder, model 54	single	
*Y1/YA 12361	SPRING Clamping Contact	G.P.O. patt. 1/SSP/481	single	
Y1/ZA 31788	Nickel silver, leaf, bent, 2.1/8 in. x 11/16 in. x 9/16 in., 28 S.W.G.	Ni. sil.; 15° set; c/w gold-silver contact; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31789	Nickel silver, leaf, 2 in. x 5/8 in. x 9/16 in., 28 S.W.G.	Ni. sil.; c/w gold-silver contact; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31667	Phos. B., helical, torsion, L.H., 9 turns, 11/32 in. I.D. x 15/16 in., 24 S.W.G. axial end	9 turns of close wound phos. Br. wire, No. 24 S.W.G.; used on recorder, with playback, wire, No. 1	single	C 4270

## SECTION Y1

## CLASS 5835-SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZA 31654	SPRING - continued Phos. Br., leaf, bent, 1.1/2 in. x 1/4 in. x 11/32 in., 28 S.W.G.	Used on recorder, with playback, wire, No. 1	single	C 4270
Y1/YA 11336	Recording head guide Steel	Minifon recorder, model 54	single	
Y1/ZA 31660	Helical, compression 1.1/2 turns, 1.1/4 in. O.D. x 15/16 in., 13 S.W.G.	Used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31655	3 turns, 2 in. I.D. x 3/8 in., 11 E.M.W. gauge		single	
Y1/ZA 31656	8 turns, 5/32 in. O.D. x 13/16 in., 10 E.M.W. gauge		single	
Y1/ZA 31643	12 turns, 1/8 in. dia x 7/16 in., 4 E.M.W. gauge		single	



Y1/ZA 31666	Helical, tension 18 turns, 3/16 in. I.D. x 1.5/16 in. hook end, 24 S.W.G.	Used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31668	Helical, torsion L.H., 3 turns, 17/32 in. I.D. x 3/4 in., 29 E.M.W. gauge	Used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31669	R.H., 3 turns, 17/32 in. I.D. x 3/4 in., 29 E.M.W. gauge	Used on recorder, with playback, wire, No. 1	single	C 4270
*Y1/YA 12527	SPRING ASSEMBLY, 1/DSP/1053	G.P.O. patt	single	
*Y1/YA 11323	STETHOPHONE	Minifon recorder, model 54 fitted with long jack plug	single	
*Y1/YA 12260	STOP, Finger, SS	Parts No. 2/SST/46 G.P.O. patt.	single	
	STYLUS			
Y1/ZA 24594	Cutting K.S.5	Supplied in packets of 12; used on training set, No. 5A	single	C 4270
Y1/ZA 30398	Type S.C. 2	9/16 in. long; sapphire-tipped cutting stylus; short shank	single	C 4270
Y1/ZA 30399	Type S.C. 3	3/4 in. long; sapphire-tipped cutting stylus; long shank	single	C 4270
Y1/ZA 30400	Reproducing type, S.P.2	7/16 in. long; sapphire-tipped reproducing stylus	single	C 4270
*Y1/YA 11997	Sound reproducing	Diamond, L.P.	single	

## SECTION Y1

## CLASS 5835-SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZA 32829	TAPE	<i>Driving, spring steel, 48.1/8 in. x 1 in. x .0045 in., No. 1</i>	<i>single</i>	<i>C 4270, C 8635</i>
		<i>For driving cutter head across disc; used on recorders, disc, broadcast, No. 1, Mks. 2 and 3</i>		
	Magnetic recording Plastic, 1/4 in. wide 1,200 ft. long, 7 in. dia.			
*Y1/5835-99-942-1757	Metal reel Packed in metal container		<i>single</i>	
*Y1/5835-99-901-2138	Plastic reel Packed in plastic bag and metal container		<i>single</i>	
*Y1/5835-99-901-2139	Packed in metal container		<i>single</i>	
	Sound recording Plastic, 1/4 in. wide, 1,200 ft. long, 7 in. dia.			
	Metal reel			

Y1/5835-99-943-6981	Packed in plastic bag and cardboard container		single	
Y1/ZA 31679	TIMING ASSEMBLY, Recording unit, No. 1	3.1/2 in. x 3 in. x 1.7/8 in.; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/YA 12066	VOLUME CONTROL	3 megohms, minifon recording, model 54	single	
	WHEEL			
	Gear	Used on recorder, with playback, wire No. 1		
Y1/ZA 31648	Bevel, phos, Br., 20 teeth, 3/16 in. I.D. x 7/16 in. O.D. x 7/16 in.		single	C 4270
Y1/ZA 31647	Spiral, L.H., stainless steel, 10 teeth, 3/16 in. I.D. x 1/2 in. O.D. x 1 in.		single	
Y1/ZA 31641	Spiral, L.H., stainless steel, 20 teeth, 3/16 in. I.D. x 15/16 in. O.D. x 1/2 in.		single	
Y1/ZA 31664	Phos. Br., rubber tyred, 1.1/32 in. O.D. x 1/2 in. thick, x 1/4 in.	Used on recorder, with playback, wire, No.1	single	C 4270
	Worm			
Y1/ZA 31646	Phos. Br., 20 teeth, 3/16 in. bore x 23/32 in. O.D. x 1/2 in.	Used on recorder, with playback, wire	single	C 4270
Y1/ZA 31960	WIRE, Recording, 1/2 lb. spool, No. 2	Carbon steel; wound on spool, empty, wire, recording, No. 1; used on wire recorder, models 50 and 50A (N.I.V.)	single	C 4270

## SECTION Y1

## CLASS 5835-SOUND RECORDING AND REPRODUCING EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZA 31640	WORM, Stainless steel 1 start, R.H., 3/16 in. bore x 1/2 in. O.D. x 1 in.	Used on recorder, with playback, wire, No. 1	single	C 4270
Y1/ZA 31665	4 start, R.H., 3/16 in. bore x 17/32 in. O.D. x 1.1/16 in.		single	
CLASS 5850-VISIBLE AND INVISIBLE LIGHT COMMUNICATION EQUIPMENT				
Y1/YA 8159	ADAPTOR ASSEMBLY, Ball- socket, L.S.D.S.R., lightweight	2.3/4 in. x 2 in. dia.; duralumin; for fixing L.S.D.S.R., lightweight to stands, lamp or helio.	single	C 4270
Y1/YA 0966	ADAPTOR, 2 point	1.1/4 in. x 1 in. x 13/32 in.; plastic; with 2 brass socket inserts and 2 threaded bushes. Used on L.S.D.S.R., lightweight	single	C 4270

Y1/YA 0942	BOX Spare parts, Mk. 2	4.1/8 in. x 2 in. x 1.3/4 in. tin, empty; for carrying 3 spare bulbs and set of spare parts; for use with L.S.D.S.R.	single	B 1276
Y1/ZB.M94.0006	Spare parts, filled, No. 1	Metal box filled with spare parts for use on app., L.S., No. 3, kits, No. 1. For contents, see C.I.E.M.E. list E.S. 305	single	C 4270
Y1/YA 7695	CONTACT, Plunger switch No. 1	5/32 in. x 1/8 in. dia.; brass; threaded No. 10 B.A.; used on plunger switch on L.S.D.S.R., lightweight	single	C 4270
Y1/YA 1000	DISC Amber	Celluloid, 3.3/4 in. dia.; used on L.S.D.S.R.	single	A 6420,C 4270
Y1/YA 1001	Green		single	
Y1/YA 1002	Ruby		single	
Y1/YA 7700	EYE-PIECE,Rubber, Mk. 2	1.7/8 in. dia. x 1.3/4 in. long; rubber mouldings; used on L.S.D.S.R., lightweight	single	C 4270
	FILTER	7.3/8 in. dia. x .040 in. thick cellulose-acetate disc, fitted with 3 spring clips; used on lamps, beacon, sig., Mk. 1		C 4270
Y1/YA 7631	Green, detachable, 7.3/8 in. dia.		single	
Y1/YA 7630	Red, detachable, 7.3/8 in. dia		single	
Y1/YA 1009	FRONT, Projector	4.1/8 in. dia. x 1 in.; front frame assy., complete with glass, rubber packing ring and retaining rings; used on L.S.D.S.R., projectors, Mk. 2	single	A 6420,C 4270

## SECTION Y1

## CLASS 5850-VISIBLE AND INVISIBLE LIGHT COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 1011	GLASS, Front	3.562 in. dia. x .160 in. thick; clear glass; used on L.S.D.S.R.	single	C 4270
Y1/YA 7633	HANDLE, Lamp, with S.P. switch	Trigger handle assy.; used on lamps, beacon, sig., Mk. 1	single	C 4270
Y1/YA 1489	HEAD, Tripod, threaded	2.1/4 in. dia. x 1.3/8 in. brass; or Gm. threaded 14 t.p.i. Whitworth form; used on stand, lamp or helio. A, Mk. 3	single	C 4270
Y1/YA 0712	HELIOGRAPH, 5 in., Mk.5	In leather case; consisting of double-jointed sighting rod with vane; duplex mirror mounted in "U" frame; signalling mirror mounted in "U" arm, complete with threaded socket, signalling key and tangent screw; sighting arm; adjusting tool; spare mirror box containing 1 duplex mirror, 1 signalling mirror and paper discs; filled spare parts pocket; without 1 stand, lamp or helio., A, Mk. 3 (IL.2325)	single	13195,B 7101

Y1/YA 5232	HOLDER, Bulb, lamp, signalling daylight	Includes lead and plug	single	C 4270
Y1/YA 7844	HOOD, Canvas, battery clip	Cover for battery clip; used on lamp, beacon, sig., Mk. 1	single	C 4270
Y1/YA 1495	HOOK, Anchoring	4.1/2 in. x 3/16 in. dia.; brass; threaded No. 2 B.A.; includes nut; used on stand, lamp or helio., A, Mk. 3	single	C 4270
	INDICATOR			
	Signal, red and green, C.D.	Sig. app. for visual acknowledgement of orders given by Gun Position Officers or Battery Commanders; comprises a 2 light at each gun position and a 6 light at the command post or battery observation post; without 2 batteries, secy., port., 6 V., 85 Ah., Mk. 3 (Sec.Z2)		
Y1/YA 2767	2 light	6.7/8 in. x 2.7/8 in. x 4.1/4 in.; metal case with hinged cover and removable metal panel; fitted with 2 bulbs, 3.5 V., P (Sec.Y3); 1 hook, safety, No. 3, Mk. 1 (Sec. V6); 2 lampholders; 1 lens, green; 1 lens, red; 1 push button; 1 switch, on-off, S.P.; includes 2 spare bulbs	single	B 4108
Y1/YA 3234	Push button	Spring loaded plunger type with green plastic knob, 1.1/2 in. dia.	single	C 4270
Y1/YA 2790	Switch, on-off, S.P.	Panel mounting, spring snap action type; with moulded screw cover, coloured red	single	B 4108
Y1/YA 2768	6 Light	Met. C.; with wall fixing plates; fitted with 6 bulbs, 3.5 V., P (Sec. Y3); 6 lampholders; 3 lenses, green; 3 lenses, red; one 6 light resis., 40 ohms, 10 terminals, insulated; all mounted on removable metal panel; includes 4 spare bulbs	single	B 4108

## SECTION Y1

## CLASS 5850-VISIBLE AND INVISIBLE LIGHT COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 2792	INDICATOR Signal, red and green, C.D. - continued Lampholder	M.E.S., with semi-circular securing plate; includes 2 No. 6 B.A. x 1/2 in. rd. hd. screws and locknuts	single	B 4108
Y1/YA 2793	Lens	Coloured cut-glass, 1.1/8 in. dia. with metal securing plate	single	B 4108
Y1/YA 2794	Green Red		single	
Y1/YA 2776	LAMP, Signalling Daylight, short range	In 2 metal cases (1 for spare battery). Suitable for mounted or dismounted services. For components, see C.I.E.M.E. list E.S.342	single	B 4110
Y1/YA 7454	Daylight, short range, lightweight	A lightweight battery-operated signalling lamp; the complete equipment fits into a tropic- proof canvas carrying case (IL.2902)	single	C 4270



Y1/YA 1497	LEG	3 ft. 2 in. x 1.7/64 in.; hardwood; includes M.S. shoe; used on stand; lamp or helio., A, Mk. 3	single	C 4270
Y1/YA 5186	LID, Projector compartment	6.1/2 in. x 5 in. x 1/4 in.; M.S., No.22 S.W.G.; used on L.S.D.S.R., case, carrying	single	C 4270
Y1/YA 0953	LIGHTING ATTACHMENT No. 1	Used with L.S.D.S.R. 1.1/2 in. dia. x 2.1/4 in. long; metal body; torch, with button strap, switch and flexible lead with 2 point plug	single	A 7174,C 4270
Y1/YA 5218	No. 2	Similar to lighting attachment, No. 1 but with plastic body	single	C 4270
Y1/YA 5189	LINK, Waistbelt	2 in. x 1.5/16 in.; hard brass; No. 10 S.W.G. dia. rectangular link; used on L.S.D.S.R., case, carrying	single	C 4270
Y1/YA 1496	NUT Anchoring, hook	Br., B.S.W. 1/4 in. hex. nut tapped No. 2 B.A.; used on stand, lamp or helio., A, Mk. 3	single	C 4270
Y1/YA 6306	Brass, special, B.S.W.,	Used with eyebolts on lamp, signalling, yard-arm, Mk. 2	single	C 4270
Y1/YA 7710	Captive, 4 B.A., No. 1	3/4 in. dia. x 5/8 in.; brass; used on L.S.D.S.R., lightweight	single	C 4270
Y1/YA 5193	Special No. 2 B.A., No. 1	11/32 in. dia. x 1/8 in. thick; used on L.S.D.S.R.	single	C 4270
Y1/YA 5194	No. 4 B.A., No. 1	1/4 in. dia. x 3/32 in. thick; used on L.S.D.S.R.	single	C 4270
Y1/YA 4146	Wing, special, tapped, No. O.B.A., No.1	Brass, No. 12 S.W.G.; used on L.S.D.S.R., projectors	single	C 4270

## SECTION Y1

## CLASS 5850-VISIBLE AND INVISIBLE LIGHT COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5231	PACKER Frame, front	3.687 in. O.D. x 3.437 in. I.D. x .046 in. thick; rubber ring; for glass of L.S.D.S.R., projector	single	C 4270
Y1/YA 5239	Metal, .760 in. x .250 in.	.062 in. thick; brass; used on L.S.D.S.R., projector	single	C 4270
Y1/YA 5176	Wood, spare battery box	6.11/16 in. x 4.9/16 in. x 4 mm.; used on L.S.D.S.R., spare battery box	single	C 4270
Y1/YA 5191	PANEL, Connection	3.1/2 in. x 1/8 in. x 1/4 in.; ebonite; includes strips and socket connections; used on L.S.D.S.R.	single	C 4270
Y1/YA 4147	PIN Collar	1/ in. I.D. x 3/8 in. O.D. x 3/4 in.; Br; used on L.S.D.S.R., projector	single	C 4270
Y1/YA 5203	Hinge, 1/8 in. x 6.1/2 in.	1/8 in. dia. x 6.1/2 in.; H.D. Br; used on L.S.D.S.R., case, carrying, No. 4	single	C 4270
Y1/YA 0948	PLATE, Instruction Keys, signalling	2.1/4 in. x 1.1/4 in. x .03 in.; plastic, white, engraved; used on L.S.D.S.R.	single	B 1276,C 4270

Y1/YA 7704	L.S.D.S.R., lightweight	3.5 in. x 2.3/8 in. x .022 in.; Al. with instructions engraved	single	C 4270
Y1/YA 5241	PROTECTOR, Reflector	3.5 in. dia. x .062 in. thick; asbestos millboard; mirror protector on L.S.D.S.R., projector	single	C 4270
Y1/YA 2954	REFLECTOR, Projector	3.3/4 in. dia. x 3/4 in. glass reflecting mirror with brass rim spun on; used on L.S.D.S.R.	single	C 4270
	ROD			
Y1/YA 7713	Handle, projector, No. 1	4.1/8 in. x 3/16 in. dia.; Br., threaded No. 2 B.A. at each end; used on L.S.D.S.R., lightweight	single	C 4270
Y1/YA 7712	Retaining, 4 B.A. x 4.7/8 in.	M.S. rod, 4.7/8 in. long, screwed No. 4 B.A. at both ends (1/4 in. - 1/2 in.) used on L.S.D.S.R.	single	C 4270
Y1/YA 1014	SCREEN, Night	3.3/4 in. dia. x 7/8 in.; M.S.; fitted to front to front of lamp, adjustable for the amount of light shown; used on L.S.D.S.R.	single	B 9974, C 4270
	SLING			
Y1/YA 2777	Box, spare battery	24 in. x 1 in.; web, drab, thick, with brass tips; used on L.S.D.S.R., spare battery box	single	B 4110, C 4270
Y1/YA 2779	Case, carrying	4 ft. 2 in. x 1 in.; web, drab, thick, with 2 in. wide shoulderpiece, brass tips and 2 buckles, brass, 1 in.; used on L.S.D.S.R., case carrying, No. 4	single	B 4110, C 4270
Y1/YA 4907	SOCKET, Key, signalling	.125 in. I.D. x .31 in. O.D. x 13/16 in.; Br., one end threaded No. 2 B.A. for 1/4 in.; used on L.S.D.S.R.	single	V 4270

## SECTION Y1

## CLASS 5850- VISIBLE AND INVISIBLE LIGHT COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0961	SPIKE	1/2 in. dia. x 7.1/2 in.; M.S., one end threaded 1/2 in. B.S.W., the other end flattened and pointed; used with L.S.D.S.R.	single	A 7174,C 4270
Y1/YA 0962	Extension	1/2 in. dia. x 7 in.; M.S., one end threaded 1/2 in. B.S.W. with 1/2 in. B.S.W. socket at the other end; used in conjunction with spike on L.S.D.S.R.	single	
Y1/YA 5240	SPRING Contact Bulb-holder	1.3/4 in. x 1 in. x .016 in.; phos. Br., spring tempered; used on L.S.D.S.R., projector	single	C 4270
Y1/YA 1015	Reflector	1.3/8 in. free length x .34 in. I.D. x 1.1/2 in. max. O.D. Ni. Sil. wire No. 14 S.W.G.; volute spring of 6 turns; used on L.S.D.S.R., projector	single	C 4270
Y1/YA 1012	Retaining, front	Ni. Sil. wire No. 16 S.W.G.; single coil; retains front glass in L.S.D.S.R., projector	single	B 9974,C 4270

Y1/YA 1487	STAND, Lamp or heliograph, A, Mk. 3	Consists of 3 legs made of hardwood, tubular metal or rolled metal, fixed at one end to a brass or gunmetal head to which can be fitted the helio. or lamp; fitted with webbing carrying strap, 3 ft. 6 in. long; used for helio., 5 in. and L.S.D.S.R. For components, see C.I.E.M.E. list E.S. 342	single	B 3075, B 7101
Y1/YA 1505	STRAP, Shoulder, type A	Webbing; 2 in. wide x 36 in.; adjustable length; with webbing 1 in. wide x 20 in. long, terminating in a web collar 3.1/4 in. long x 1.15/16 in. I.D.; used with stand, lamp or helio., A, Mk.3, with wood or tubular metal legs	single	C 4270
CLASS 5895-MISCELLANEOUS COMMUNICATION EQUIPMENT				
Y1/YA 1084	PANNIER, Signalling	Wicker, without padlock and key; for pack, transport sig. app.	single	11760, A 7725
GROUP 59-ELECTRICAL AND ELECTRONIC EQUIPMENT COMPONENTS				
CLASS 5905-RESISTORS				
Y1/YA 10612	ATTENUATOR, P.O. type No. 3/20	G.P.O. patt. No. 3. The value in dbs. is as shown after the oblique stroke in the designation No.	single	C 8423

## SECTION Y1

## CLASS 5905-RESISTORS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZA 31702	COVER, Potentiometer, No.2	9/16 in. dia. x 9/16 in. long; Br., knurled, tapped 3/8 in. 26 t.p.i.; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/YA 0629	POTENTIOMETER, No. 1	1.1/2 in. dia. x 1.7/16 in.; 500 ohms + 20 per cent., carbon type in metal cover with 3 soldering tags for use on various sig. apps.	single	B 6339
Y1/YA 7703	RESISTANCE ASSEMBLY, 4 ohms, No. 1	5 in. x .64 in. long; 4 ohms wire wound resis. with brass outer cover; used on L.S.D.S.R.	single	C 4270.
*Y1/YA 12107	RESISTOR 200 ohms 1/2 W.	Minifon recorder, model 54	single	
*Y1/YA 12108	2,500 ohms	Minifon recorder, model 54	single	
*Y1/YA 12126	5,000 ohms	Minifon recorder, model 54	single	
*Y1/YA 12109	.35 megohms	Minifon recorder, model 54	single	
*Y1/YA 12111	2 megohms	Minifon recorder, model 54	single	
*Y1/YA 12112	3 megohms	Minifon recorder, model 54	single	
*Y1/YA 12113	5 megohms	Minifon recorder, model 54	single	
*Y1/YA 12062	10 megohms	Minifon recorder, model 54	single	
*Y1/YA 12110	17 megohms	Minifon recorder, model 54	single	

Y1/YA 1596	Spool, No. 1, 100 ohms	4.11/32 in. x 1.15/32 in. x 3/16 in.; G.P.O. patt. 45 W., 2 soldering tags at one end; used on swbd., F. and F., unit C	single	B 4804
Y1/YA 8129	RHEOSTAT, T	G.P.O. patt.; 0-12,000 ohms adjustable by 400 ohms graduations	single	C 4270
CLASS 5910-CAPACITORS				
CAPACITOR				
*Y1/YA 12071	.0025 $\mu$ F, M1 53.24-01	Minifon recorder, model 54	single	
*Y1/YA 12072	.0025 $\mu$ F, M1 53.41-10-02	Minifon recorder, model 54	single	
*Y1/YA 12073	.01 $\mu$ F	Minifon recorder, model 54	single	
*Y1/YA 12074	.1 $\mu$ F	Minifon recorder, model 54	single	
*Y1/YA 12075	3.5 $\mu$ F	Minifon recorder, model 54	single	
*Y1/YA 12076	10 $\mu$ F, 2 V.	Electrolytic Minifon recorder, model 54	single	
*Y1/YA 12077	50 $\mu$ F	Minifon recorder, model 54	single	
*Y1/YA 11306	50 $\mu$ F elect.	Minifon recorder, transformer/rectifier unit, model 54	single	
CONDENSER				
Y1/YA 2373	1. C	200 V., D.C. working, paper dielectric, tinned plate case, fixing centres 1.9/16 in.	single	B 1434
Y1/YA 0477	2, D	1.3/16 in. x 9/16 in. x 2.5/8 in.; 1 $\mu$ F	single	B 1434
Y1/YA 2374	P.5, C	1.3/4 in. x 9/16 in. x 2.5/8 in.; 2 $\mu$ F	single	B 3410
		1.3/4 in. x 9/16 in. x 2.5/8 in.; .5 $\mu$ F		

## SECTION Y1

## CLASS 5920-FUSES AND LIGHTNING ARRESTERS

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/5920-99-901-2535	BLOCK, Telephone protector	Plastic; 1.1/4 in. lg., 0.469 in. W., 0.395 in.thk. used with kit, extension tel. C B. exchange (Old Cat. No. Y1/YA 7683)	single	
Y1/YA 8290	CASE, Metal, spare fuse, No. 1	7.13/16 in. x 6.1/8 in. x 1.9/16 in.; for holding fuses, No. 31/2 and No. 37/3	single	C 4270
Y1/YA 8356	COVER, Fuse-mounting, No. 4028	6.15/16 in. x 9 5/16 in. x 3.7/8 in.; G.P.O. patt.	single	C 4270
Y1/YA 4952	FUSE No. 1/0.25	G.P.O. patt. First number denotes type, second number denotes safe current in amps. which is half the fusing current Glass tube 0.25A rating, 2.1/8 in. long with 1/4 in. brown band round tube; resis, cold 3 ohms.	single	C 4270
Y1/YA 2597	No. 1/1.5	1/4 in. dia. porcelain tube with nickelled brass caps for ciip fitting; overall length 2.1/8 in.	single	25466,B 8027
Y1/YA 3506	No. 1/3	Glass tube, length 2.1/8 in. approx.; fusing current 3 amp.; used on rectifier, type 66B (Y2/YB 08222)	single	C 4270
Y1/YA 2598	No. 2/1.5	1/8 in. dia. glass tube with slotted lugs for screw fixing; length between centres 2.3/16 in.	single	25466,B 8027



Y1/YA 5055	No. 5/2	Alarm with indicator type 1.5A rating; fixing centre 1.1/4 in.; 5/32 in. slots; red bead	single	C 4270
Y1/YA 9283	No. 15/15		single	C 8181
Y1/YA 7403	No. 20/5	Cartridge type, fixing centre 3.1/8 in.; for ccts. not above 250 V.; used on exchange, magneto, W.D., unit type	single	C 4270
Y1/YA 9192	No. 20/10		single	C 8181
Y1/YA 9281	No. 23/60		single	C 8181
Y1/YA 9282	No. 23/100		single	C 8181
Y1/YA 2599	No. 28/1.5		single	B 2172
Y1/YA 9639	No. 35/0.25		single	C 8181
Y1/YA 6879	No. 35/1		single	C 4270
Y1/YA 7684	No. 37/2.5	Flat type, fixing centre 3.1/4 in. Flat strip with slotted ends, fixing centre 1.9/16 in.; yellow; for fuse mounting No. 2435A	single	C 4270
*Y1/5920-99-901-2113	Open link	Hex. porcelain tube, with knife edge contacts, 2.5A rating; length overall 1.13/16 in.; for protectors and fuse, No. 1.2/2; used on kit, extension tel., C.B. exchange G.P.O. patt.; 57/10, 10 amp., 5.3/16 in. lg. 1.1/4 in. dia.	single	
	FUSE MOUNTING			
Y1/YA 6375	No. 101	G.P.O. patt.; ebonite base with side clips for 1 fuse, No. 1/1 C	single	C 4270
Y1/YA 9163	No. 101A	G.P.O. patt.; 3 in. x 3/4 in. x 1.3/16 in.; for fuses 1/.... end or rear connections	single	C 5687
Y1/YA 7571	No. 102	G.P.O. patt.; ebonite base with side clips; for 1 fuse, No. 1/1C	single	C 4270
Y1/YA 7268	No. 131B	G.P.O. patt.; 3.1/4 in. x 1 in.; with fixing brackets for 1 fuse, No. 31/.... (Sec. Y2)	single	C 4270
Y1/YA 7311	No. 631B	G.P.O. patt.; for 6 fuses, No. 31/.... (Sec. Y2); used on swbd., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 6499	No. 731A	G.P.O. patt.; 5.3/8 in. x 3.7/16 in.; for 7 fuses No. 31/...., (Sec. Y2)	single	C 4270

## SECTION Y1

## CLASS 5920-FUSES AND LIGHTNING ARRESTERS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7312	FUSE MOUNTING - continued No. 1031C	G.P.O. patt.; for 10 fuses No. 31/.... (Sec. Y2); used on swbd., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 10249	No. 2435A	G.P.O. patt.; for 24 fuses No. 35/....	single	C 8181
Y1/YA 2876	No. 4002	G.P.O. patt.; 10.31/32 in. x 4.3/8 in.; sheet iron base with ebonite insulation	single	C 4270
Y1/YA 7674	No. 4028	G.P.O. patt.; 10 in. x 3.1/2 in. x 9.1/2 in.; sheet iron framework with 2 hinged sides; for 40 fuses No. 28/2; does not include cover	single	C 4270
Y1/YA 6875	No. 4028 complete	G.P.O. patt.; includes cover, fuse mounting, No. 4028	single	C 4270
CLASS 5930-SWITCHES				
Y1/YA 1881/1	BUTTON Buzzer, switch, telephone sets F	Approved black bakelite push button	single	C 4270

*Y1/YA 11332	Rewind lever	Minifon recorder, model 54	single	
*Y1/YA 12070	Start/stop	Minifon recorder, model 54	single	
COVER				
Y1/YA 3369	Switch, loudspeaker, telephone, No. 2	2 in. dia. x 1/16 in. thick; insertion sheet rubber with 3 holes 5/32 in. dia.; used on L.S. tel. No. 2, mounted	single	C 4270
Y1/YA 5585	Switch, S.P., No. 2	1.5/8 in. x 1.7/16 in. x 1.1/4 in. x 3/32 in. thick; plastic moulding; used on transmitter, breast (sound P) No. 2 Mk., 2	single	
DISC, Indication, telephone key switch				
Y1/5930-99-901-2488	Black	Plastic, 0.093 in. thk. x 0.357 in. dia.; P.O. label, No. 84	single	
*Y1/5930-99-901-3171	Red	Old Cat. No. Y1/YA 6883	single	
Y1/5930-99-901-3172	White	Old Cat. No. Y1/YA 10475	single	
		Old Cat. No. Y1/YA 3881		
HANDLE				
Key				
Brass, tapped 1/4 in. B.S.W.				
Y1/YA 8279	No. 1	5/16 in. dia. x 5/8 in.; used on key, No. 12, W.D.	single	
	No. 1 (W.D.)	3/8 in. dia. x 7/8 in. long; plastic; knurled, tapped No. 2 B.A.; colour as stated; for use with vertical lever type keys		
Y1/YA 7164	Blue		single	
Y1/YA 7161	Green		single	
Y1/YA 7159	White		single	
Y1/YA 7163	Yellow		single	
Y1/YA 4820	No. 2, black	3/16 in. dia. x 1.5/32 in. long; plastic; tapped No. 4 B.A.	single	

## SECTION: Y1

## CLASS 5930-SWITCHES- continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	HANDLE			
Y1/YA 5311	Key - continued No. 5 (W.D.)	3/8 in. dia. x 9/16 in. long; M.S.; N.P.D.; tapped No. 2 B.A.	single	
Y1/YA 7323	No. 6, black	7/16 in. dia. x 7/16 in. long; plastic; tapped No. 4 B.A.; used on G.P.O. plunger type keys, No. 279		
Y1/YA 7332	No. 7, black	G. <sup>o</sup> .O. patt.; plastic with metal fittings; for linking 2 std. lever keys at 3/4 in. centre for simultaneous operation	single	
Y1/5930-99-940-1887 Y1/5930-99-940-1892 Y1/5930-99-940-1888 *Y1/5930-99-940-1921	KNOB, Telephone key switch Black Grey Red White	Plastic; 7/8 in. long x 3/8 in. dia.  Old Cat. No. Y1/YA 7162 Old Cat. No. Y1/YA 7165 Old Cat. No. Y1/YA 7160 Used on repeater, synchronous regenerative (Y2/YB 0886)	single single single single	C 4270

		SWITCH		
Y1/YA 3777	3 way, R.A.	8 in. x 5.3/8 in. x 4.3/4 in.; painted hardwood case; hinged front; web carrying strap; with 3 keys, No. 68, white; 6 terminals, inst., slotted, single, No. 4, small (Sec. Y3); used for controlling communication between battery, command posts and observation posts	single	B 5750
Y1/YA 1881	Buzzer, telephone, F	Spring set mounted on alloy cast plate, with press button	single	B 1782, C 4270
*Y1/YA 12125	Contract assembly	Start/stop; Minifon recorder, model 54	single	
Y1/YA 1882	Cradle, telephone set, F	Complete with tension spring and lever	single	B 1782, C 4270
Y1/ZA 26438	Key, normal 2 pole, 2 position, No. 1	4.9/16 in. x 1.3/4 in. x 7/8 in.; 6 point, 2 position, lever key; used on wireless set, No. 26, Mk. 2 (Sec. Z1)	single	C 4270
Y1/ZA 26439	2 + 2 pole, 3 position, No. 1	4.9/16 in. x 1.3/4 in. x 7/8 in.; 12 point, 3 position, lever key; used on wireless set, No. 26, Mk. 2 (Sec. Z1)	single	C 4270
Y1/YA 4358	Loudspeaker, No. 1	Switch, push button, S.P., No. 1 (Sec. Z1), with special button, 1 in. dia.; used on tel., L.S., No. 2, L.S.	single	C 4270
Y1/YA 7693	Plunger, No. 1	3/4 in. dia. x 1.1/2 in.; tubular, plunger; used on L.S.D.S.R., lightweight	single	C 4270
*Y1/YA 12055	Press button S.P., Bulgin type S.366	Biased 'on' 7/8 in. dia. x 1.1/8 in.; plunger type; used on mic., hand, power, No. 1, 1A, 1B	single	C 4270
Y1/YA 3204	S.P., No. 1		single	C 4270
Y1/YA 4843	Cable mounting	2.1/4 in. x 2 in. x 1 in.; plunger type; housed in aluminium casting; 2 plastic gland nuts for side entry of cables; used on mic., respirator, power, No. 1 and con., plug, No. 16 (Sec. Z1)	single	C 4270

## SECTION Y1

## CLASS 5930-SWITCHES - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	I. of C. ref.
1	2	3	4	5
Y1/YA 6152	SWITCH - continued Pressel, No. 10	3.7/16 in. x 5/16 in. x 3/8 in.; single make spring set; secured to mounting plate; complete with soldered connections; used on tel., hand	single	C 4270
Y1/YA 5095	Telephone No. 1	G.P.O. key, No. 279, modified; fitted with a knob engraved C.B.; used on tel. set, L.	single	C 4270
Y1/YA 6951	No. 2	Similar to switch, tel., No. 1, but with different fixing centres; used on tel. set, H. Mk. 3	single	C 4270
Y1/YA 7954	No. 3	Plunger type; 2 change over and 1 break spring sets; knob engraved "KEY" used on tel. set, J.	single	C 4270
	Telephone key	In the detail for telephone key switches B. signifies Break C. signifies Change-over (B before M) K. signifies Change-over (M before B) L. signifies Locking M. signifies Make N. signifies Non-locking S. signifies Stop The first side is that with the springs nearest to the frame		

Y1/5930-99-940-1864	G.P.O. type No. 68	Lever type; 1st position S, 2nd position 2C, S/L; used on switchboard A.A., 5 line (Old Cat. No. Y1/YA 3118)	single	A 567,C 4270
*Y1/5930-99-932-5791	Tpl.	With a tropical finish; used on repeater, synchronous, regenerative (Y2/YB 08866)	single	
Y1/5930-99-940-1855	G.P.O. type No. 172	2 lever, normal; 2C, NL/4C, L; used on BID 560/1 (Old Cat. No. Y1/YA 3120)	single	C 4270
Y1/5930-99-012-0146	G.P.O. type No. 174	3 lever type; 1st position 2C, centre position neutral, 2nd position 2C, N/L; used on signalling equipment, No. 10 (Old Cat. No. Y1/YA 6454)	single	B 5252,C 4270
Y1/5930-99-940-1848	G.P.O. type No. 212	3 lever type; 1st position 2C, centre position neutral, 2nd position 2C, L/L	single	C 4270
*Y1/5930-99-932-5790	Tpl.	With a tropical finish	single	
Y1/5930-99-012-0180	G.P.O. type No. 216	3 lever, normal; 2C, NL/2C, NL; used on BID 560/1 (Old Cat. No. Y1/YA 2761)	single	B 5064,C 4270
Y1/5930-99-901-0650	G.P.O. type No. 228	Plunger type, 2 position, 1st S, 2nd 2C, N; 300 mA. 1 amp. DC. (Old Cat. No. Y1/YA 7179)	single	C 4270
*Y1/5930-99-911-4130	G.P.O. type No. 229	Plunger type; 3M, N; used on test set, radar, 4339	single	
Y1/5930-99-940-1870	G.P.O. type No. 236	3 lever type; 3 positions, 1st 3C, centre neutral, 2nd 3C, L/L (Old Cat. No. Y1/YA 3122)	single	B 5064,C 4270
*Y1/5930-99-943-3564	G.P.O. type No. 244	2 lever, normal; 2K/2K, NL/NL (Old Cat. No. Y1/YA 8527 NIV)	single	
Y1/5930-99-940-1861	G.P.O. type No. 287	Lever, normal; 2C/4C, NL/NL (Old Cat. No. Y1/YA 3183)	single	C 4270
Y1/5930-99-940-1867	G.P.O. type No. 289	Lever normal; S/6C, S/L; used on BID 560/1 (Old Cat. No. Y1/YA 6341)	single	C 4270
Y1/5930-99-940-1879	G.P.O. type No. 291	Lever, normal; 4C/N11, NL/S (Old Cat. No. Y1/YA 7218)	single	C 4270
Y1/5930-99-940-1872	G.P.O. type No. 300	Lever normal; 2K, 2C/2K, 2C, L/L (Old Cat. No. Y1/YA 7221)	single	C 4270
*Y1/5930-99-943-9357	Muirhead type C-401-A	Lever, normal, low capacity; 3C, N; used on flight safety transmitter	single	

## SECTION Y1

## CLASS 5930-SWITCHES - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L of C. ref.
1	2	3	4	5
	SWITCH - continued			
Y1/YA 3062	Tumbler No. 1M	G.P.O. patt.; 5A., S.P.; quick make and break; semi-recessed type, circular porcelain base and moulded cover; base 1.13/16 in. dia.; used on A.A. Command mobile station and keyboard, multiple, A.D1316	single	C 4270
Y1/YA 7500	No. 8	G.P.O. patt.; 4A.; porcelain base; plastic cover and dolly, used on terminal equipt. vehicle, type A and B	single	C 4270
Y1/YA 3662	No. 9	G.P.O. patt.; 5A., double pole; 1 way, 2M action; earthed frame; white porcelain base; polished Br. cover and knob; used on A.A. Command static station keyboard, multiple, A.D. 1316; tester, TG, 956 and 958 (Sec. Z4)	single	C 4270
Y1/YA 4672	No. 28	G.P.O. patt.; 5A; 2 way with OFF position; circular porcelain base with moulded cover; base 2.1/4 in. dia. with 1.5/8 in. fixing centres; used on swbds.	single	C 4270



CLASS 5935--CONNECTORS, ELECTRICAL

Y1/5935-99-901-2534	ADAPTOR Electrical, plug to plug	With shell, co-axial; P.O. link, U, used on analyser, spectrum H.F. (Old Cat. No. Y1/YA 12611)	single	
Y1/ZA 12651	Valve, No. 2	For adapting 4 pin American type holders to take international octal valves	single	C 4270
Y1/YA 7587	BAG, Waterproof, connectors, No. 16	9.7/8 in. x 2.1/2 in.; plastic; for carrying connectors, double, No. 16	single	C 4270
Y1/ZA 13343	BUSH, Screwed, No.1	5/8 in. long x 5/8 in. O.D. x 1/4 in.I.D.; plastic moulding with brass insert, threaded 11/32 in. dia. 32 t.p.i. Whitworth form; part of jack, mic., No. 4A	single	C 4270
Y1/YA 3788	CONNECTOR, Superposing unit	13.1/4 in. of twin flex cord or of wire, electric, slip back, .0006 twin (Sec.Y3); green/yellow; fitted with 2 plugs, jumper, twin, No.1 (1 black, 1 red)	single	B 2912
Y1/ZA 31873	CONNECTOR ASSEMBLY, 22 in. long, with bayonet type plug and socket	22 in. long; 12 in. and 8 in. of P.V.C., S.S.C., screened 7/36 wire connected by bayonet type plug and socket; for connecting recorder to ampfr. on recorder, with playback, wire, No. 1	single	C 4270
	COVER			
	Plug No. 1	1.94 in. long x .485 in. O.D. x .344 in. I.D. Fibre tube; for plug, No. 201		C 4270
Y1/YA 4792	Red No. 2	Similar to G.P.O. patt., cover, plug, No. 10 1.468 in. long x .434 in. O.D. x .336 in. I.D. Fibre tube, for plug, No. 310B; similar to G.P.O. part No. 2/SCO/38	single	C 4270

## SECTION Y1

## CLASS 5935-CONNECTORS, ELECTRICAL - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	COVER			
	Plug			
	No. 2 - continued			
Y1/YA 6206	Black		single	
Y1/YA 6207	Red		single	
Y1/YA 8840	1/SCO/40, Black	G.P.O. patt.; cover for plug, No. 316, black	single	C 5687
Y1/YA 8841	1/SCO/40, Red	G.P.O. patt.; cover for plug, No. 316, red	single	C 5687
Y1/YA 8839	1/SCO/42	G.P.O. patt.; cover for plug, No. 404	single	C 5687
*Y1/YA 12261	2/SCO/45	G.P.O. patt.; cover for plug, No. 2404A	single	
Y1/YA 8315	Rubber, 1 in. O.D. x 1.3/32 in. No. 1	Used on jack, tel, No. 12	single	C 4270
	FASTENER			
Y1/YA 5309	Jack, No. 14	G.P.O. patt. Length 1.1/16 in.; dia. of head 63/64 in.; screwed 1 B.A.; used on various swbds.	single	C 4270
Y1/YA 6335	Jack, No. 17	Length 1.1/16 in.; dia. of head 47/64 in.; screwed 1 B.A.; used on various swbds.	single	
Y1/YA 1182/1	GRIP, Cord, for plug, No. 406	1 in. x 3/8 in. x 13/32 in.; plastic moulding; part of plug, No. 406, secures cord to plug	single	C 4270

Y1/YA 7383	JACK-BOX ASSEMBLY, Frame, M.D.	13 in. x 9.1/2 in. x 6.1/2 in.; box-like assy. for mtg. on angle uprights of I.D.F.; for housing 2 jack strips; used on exch, C.B., multiple, W.D., unit type, "N" positions, complete station	single	C 4270
Y1/YA 7344	JACK-FASTENER DRIVER, No.3	G.P.O. patt.; used with screwdriver, inst., No. 7	single	C 4270
Y1/ZA 25382	JACK 5 point, No. 1	3 in. x 1.1/8 in. x 1/2 in.; panel mtg.; used on wireless set, No. 68T, receiver broadcast, P.C.R., No. 2 (Sec. Z1)	single	C 4270
Y1/YA 7202	H59C	Similar to G.P.O. jack 200 B6/N but fitted with bush; tropically finished	single	C 4270
Y1/YA 4757	Lamp No. 16	G.P.O. patt. For 1 lamp, No. 2	single	C 4270
Y1/YA 3052	No. 19A	For 10 lamps, No. 2; used on swbd., teleprinter 15 line and 40 line (Sec. Y2)	single	
Y1/ZA 4393	Microphone No. 1	1.3/8 in. x 15/16 in. x 5/8 in.; ebonite block fitted with contact springs for use with plug, single, No. 10 (Sec.Z1)	single	B 3254,C 4270
Y1/ZA 4394	No. 2	1.1/2 in. x 15/16 in. x 1/2 in.; plastic moulding, fitted with 2 contact springs; for use with plug, single, No. 10 (Sec.Z1)	single	B 4117,C 4270
Y1/ZA 13587	No. 2D	1.1/2 in. x 15/16 in. x 1/2 in.; similar to jack, mic., No. 2 but fitted with shorting spring	single	C 4270
Y1/ZA 4353	No. 4	1.1/2 in. x 5/8 in. x 5/8 in.; plastic moulding fitted with 2 contact springs; panel mtg.	single	B 5586,C 4270
Y1/ZA 4355	No. 4A	1.1/2 in. x 5/8 in. x 5/8 in.; similar to jack, mic., No. 4 but with additional side contacts	single	C 4270

## SECTION Y1

## CLASS 5935--CONNECTORS, ELECTRICAL - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 1876	JACK - continued Moulded, 4 way	2.5/16 in. x 1.9/16 in. x 15/32 in.; 4 way jack to take plug, No. 406; used on tel. set, F., Mk. 1 and 2	single	B 5255,C 4270
Y1/YA 2282	M.R., No. 1	5 point; with spring lever for restoring indicator shutter; accepts plugs, No. 310B	single	B 4804
Y1/YA 2739	M.R., No. 1A	Similar to jack, M.R., No. 1 but without spring lever; used on swbd., F. and F.	single	B 4804,C 4270
Y1/YA 6213	M.R., No. 1A, mounted, 12	Consists of 12 jacks, M.R., No. 1A; 12 indicators, M.R., No. 1A and 1 plate, mtg, jack, M.R., No. 1A, 12 way; used on swbd., F. and F.	single	C 4270
Y1/YA 7136	M.R., No. 2	6 point; with spring lever for restoring indicator shutter; used on swbd., magneto, $\frac{10 + 50}{60}$	single	C 4270
Y1/YA 7434	M.R., No. 3	Tropical finished 2 point jack, with spring lever for restoring indicator shutter; used on swbd., mag. 10 line, W.D.	single	C 4270
Y1/YA 0814	No. 8A	Similar to jack, No. 8, except that centre springs are short-circuited when plug, No. 406 is out; used on fullerphone, Mk. 3/1	single	25325

Y1/YA 3977	No. 19	G.P.O. patt.; 4 way; accepts plug, No. 404	single	C 4270
Y1/YA 3054	No. 20	G.P.O. patt.; 2 socket, 4 way; accepts plug, No. 404	single	C 4270
Y1/YA 11390	No. 20A	G.P.O. store; for general use; surface fixing, comprises 1 jack, No. 20 mounted in case	single	C 9519
Y1/YA 8499	No. 26	G.P.O. patt.; 12, 2 way, for selector racks, etc.	single	C 5687
Y1/YA 2051	No. 52	G.P.O. patt.; 9 socket, 1 way; for use with plug, No. 903	single	B 4105
Y1/YA 8851	No. 53	G.P.O. patt.; 12, 2 way	single	C 5687
Y1/YA 8125	No. 56	G.P.O. patt.; 13 socket, 1 way; accepts plug, No. 1301	single	C 4270
Y1/YA 7578	No. 62	G.P.O. patt.; 8 socket, 2 way; accepts plug, No. 1605; springs 9 and 11 make when plug removed	single	C 4270
Y1/YA 7320	No. 62B	G.P.O. patt.; similar to No. 62 except springs 9, 11, 14 and 16 make when plug removed	single	C 4270
Y1/YA 7365	No. 200B6/N, assembly, frame, I.D.	Consists of jack No. 200 B6/N secured to right angle bracket for securing to upright of I.D.F.; used on exch., C.B., multiple, W.D., unit type, "N" position, complete station	single	C 4270
Y1/YA 7375	No. 200B6/N, assembly, No. 1 frame, M.D.	Consists of 1 jack, No. 200B6/N; secured to 2.1/2 in. long bracket; for securing to upright of M.D.F.; used on exch., C.B., multiple, W.D., unit, type "N" position, complete station	single	C 4270
Y1/YA 7376	No. 200B6/N, assembly, No. 2, frame, M.D.	Consists of 1 jack, No. 200B6/N; secured to bracket and plate for securing to upright of M.D.F.; used on exch., C.B., multiple, W.D., unit type, "N" position	single	C 4270
Y1/YA 8586	No. 301 BN	G.P.O. patt	single	C 5687
Y1/YA 3289	No. 310BN	G.P.O. patt.; 10 jacks, No. 300B1, mounted	single	C 4270
Y1/YA 3526	No. 320BN	Similar to G.P.O. patt.; 20 jacks, No. 300B1, but engraved 1-5, 1-5, A, B, C, D, E	single	C 4270
Y1/YA 3981	No. 500B3	G.P.O. patt.; 5 point	single	
Y1/YA 3233	No. 500B6/G	G.P.O. patt.; 5 point; fixed by 6 B.A. screw	single	C 4270

## SECTION Y1

## CLASS 5935-CONNECTORS, ELECTRICAL - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	<b>JACK - continued</b>			
Y1/YA 3285	No. 500B6/N	G.P.O. patt.; 5 point; fixed by nut	single	C 4270
Y1/YA 3731	No. 501B0	G.P.O. patt.; 1 jack, No. 500B6 and 1 mtg., jack	single	C 4270
Y1/YA 9205	No. 505BR	G.P.O. patt	single	C 5687
Y1/YA 3529	No. 510B0	G.P.O. patt.; 10 jacks, No. 500B1, mounted	single	C 4270
Y1/YA 8850	No. 510BS	G.P.O. patt.; 10 jacks, 500B6	single	C 5687
Y1/YA 5817	No. 700B6	G.P.O. patt.; 7 point switch spring; fixed through frame by wood screw	single	C 4270
Y1/YA 6877	No. 710B0	G.P.O. patt.; 10 jacks, No. 700B6, mounted	single	C 4270
Y1/YA 7130	No. 800B6/N	G.P.O. patt.; 8 point; secured by nut	single	C 4270
Y1/YA 9206	No. 801BN	G.P.O. patt.; 1 jack 800B6	single	C 5687
Y1/YA 9207	No. 805BN	G.P.O. patt.; 5 jacks 800B6	single	C 5687
	Telephone			
Y1/5935-99-940-1780	G.P.O. type 8	Mates with Y1/5935-99-940-1766 (Old Cat. No. Y1/YA 0180)	single	
Y1/5935-99-940-1779	G.P.O. type 20	Mates with Y1/5935-99-940-1765 (Old Cat. No. Y1/YA 10077)	single	
Y1/5935-99-940-1785	G.P.O. type 61C	16 way, 2 contacts (Old Cat. No. Y1/YA 10401)	single	
Y1/5935-99-940-1777	G.P.O. type 65	Mates with Y1/5935-99-940-1765 (Old Cat. No. Y1/YA 9534)	single	

Y1/5935-99-940-1771	G.P.O. type 500 B6	Mates with Y1/5935-99-940-1764 (Old Cat. No. Y1/YA 5318)	single	
Y1/5935-99-940-1781	G.P.O. type 510	Mates with Y1/5935-99-940-1760 (Old Cat. No. Y1/YA 8283)	single	
Y1/5935-99-940-1783	G.P.O. type 520	Mates with Y1/5935-99-940-1764 (Old Cat. No. Y1/YA 4001)	single	
Y1/5935-99-940-1772	G.P.O. type 800	Mates with Y1/5935-99-940-1758 (Old Cat. No. Y1/YA 4687)	single	
Y1/5935-99-940-1782	G.P.O. type 810	Mates with Y1/5935-99-940-1756 (Old Cat. No. Y1/YA 3290)	single	
Y1/ZA 4389	No. 1	1.7/8 in. x 15/16 in. x 5/8 in.; plastic body, fitted with 2 springs, each with 2 contacts; to accept 2 plugs, single, No. 9 or No. 10 (Sec. Z1)	single	B 6341,C 4270
Y1/ZA 4390	No. 2	1.13/16 in. x 7/8 in. x 1/2 in.; plastic body, fitted with 2 springs, each with 2 contacts; to accept 2 plugs, single, No. 9 or No. 10 (Sec. Z1)	single	B 4117,C 4270
Y1/ZA 11411	No. 4	3.7/16 in. x 1.1/8 in. x 1/2 in.; 8 point jack	single	C 4270
Y1/ZA 16938	No. 7	1.1/2 in. x 7/8 in. x 5/8 in. plastic moulding, 2 way, with closed cct. contacts	single	C 4270
Y1/ZA 31872	No. 9	2.1/2 in. x 3/4 in. x 9/16 in.; 3 point jack; used on recorder, with playback, wire, No. 1	single	C 4270
Y1/YA 8277	No. 12	7/8 in. x 1.3/8 in.; panel fixing, 2 point jack; used on wireless set, No. 31 (Sec. Z1)	single	C 4270
	Single			
Y1/5935-99-943-6969	1 break	Old Cat. No. Y1/ZA 4369	single	C 4270
Y1/5935-99-972-8553	1 break, A.P.103560	Igranic type P72 (Old Cat. No. Y1/YA 9018)	single	
Y1/5935-99-972-9652	2 break	ADM 23359 (Old Cat. No. Y1/ZA 11682)	single	C 4270
*Y1/5935-99-932-6349	2 making contacts	Mates with Y1/5935-99-100-0343	single	
Y1/5935-99-100-1955	3 point; No. 300 B6/N	Old Cat. No. Y1/YA 5254	single	C 4270

## SECTION Y1

## CLASS 5935-CONNECTORS, ELECTRICAL - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5952	NUT, Special No. 2 B.A., No. 2	9/32 in. dia. x 3/32 in.; Br., round, knurled, for plug, jumper, single, No. 2	single	C 4270
Y1/YA 2196/7	PIN, Plug	Consists of Br. spindle 1/4 in. sq. section x 1.9/64 in. long turned down to 1/8 in. dia. for 5/8 in. of its length, with 2 contact springs, used on transmitter breast (Sound P.) No. 2, Mks. 1 and 2, tel. attachment, hdgr., double, Mk. 3 and transmitter, breast, No. 1	single	C 4270
Y1/YA 7692	PLUG 3 point, No. 22  5 pair, No. 1	1.3/4 in. x 1/2 in. x 3/8 in.; plastic; fitted with 3 slotted plugs; used on L.S.D.S.R., lightweight  2.11/16 in. x 1.5/16 in. x 3 in.; met. C. with 10 Br. contacts in pairs; fits socket contacts, 5 pr., No. 1	single	C 4270  B 2912
Y1/YA 2541 Y1/YA 2540	Black Red		single single	



Y1/YA 8135	6 way, No. 1	2.875 in. x 1.5 in. x .5 in.; S.R.B.P. fitted with 3 long and 3 short contact strips; used on tester, continuity, C.B. exchange	single	C 4270
Y1/YA 6150	10 point, No. 6	3.3/8 in. x 2.1/8 in. x 1.3/4 in.; plastic; fitted with 10 plugs, banana, No. 3 small (Sec. Z1); used on con, 5 pair, No. 4B	single	C 4270
Y1/YA 6739	12 point, No. 5	1.7/8 in. x 1.5/8 in. 1 in.; 12 way plug with metal cover and cable clamp with side entry; used on tel. set, F. high powered, No. 1, Mk.2	single	C 4270
Y1/YA 3212	Coupling No. 2	2.1/8 in. dia. x 1.7/8 in.; 3 pin type; 2 plugs O.Z., 4 mm., tapered (Sec. Z1); and 1 plug O.Z., 5 mm. tapered (Sec. Z1), fitted in copper case; used on tel., L.S., No. 2, set	single	C 4270
<b>Electrical</b>				
Y1/5935-99-901-0198	Single pole, fixed	Old Cat. Nos. Y1/YA 3944 and Y1/YA 6429	single	
Y1/5935-99-901-6741	20 pole, free	2 amp., 250 V., D.C., 180 V., A.C., Plessey type 2 CZ 108603 (Old Cat. No. Y1/YA 11026)	single	
Y1/5935-99-940-1756	G.P.O. type No. 201, red	Mates with Y1/5935-99-940-1770 or 1771 or 1772 (Old Cat. No. Y1/YA 1169)	single	
Y1/5935-99-940-1832	G.P.O. type No. 316, cerise	Mates with Y1/5935-99-940-1772 (Old Cat. No. Y1/YA 10709)	single	
Y1/5935-99-940-1764	G.P.O. type No. 316, black	Mates with Y1/5935-99-940-1772 (Old Cat. No. Y1/YA 5294)	single	
Y1/5935-99-940-1769	G.P.O. type No. 3201	Mates with Y1/5935-99-940-1785 (Old Cat. No. Y1/YA 10405)	single	
Y1/5935-99-940-1766	Type No. 406	Mates with Y1/5935-99-940-1780 (Old Cat. No. Y1/YA 1182)	single	
<b>Jumper</b>				
	Single, No. 1	Plastic body, with side entry for wire; phos. B. pin, split; for use on test frames		B 2912
Y1/YA 2724	Black		single	
Y1/YA 2725	Red		single	B 4806

## SECTION Y1

## CLASS 5935-CONNECTORS, ELECTRICAL - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	PLUG			
Y1/YA 4778	Jumper - continued Single, No. 2	.115 in. dia. x 11/16 in.; Br.; fitted with special No. 2 B.A. nut; for used with panel, socket, No. 1	single	B 8029
	Twin, No. 1	Plastic body, with side entry for wire; phos. B pins, split; same gauge and spacing as links, wire; for use on test frame, and superposing units		B 2912
Y1/YA 2717	Black		single	
Y1/YA 2718	Red Twin, No. 2	Plastic body with 2 phos. B. pins; same gauge and spacing as links, wire; for use with con., jumper, twin, No. 2	single	B 5064
Y1/YA 2922	Black		single	
Y1/YA 2923	Red		single	
*Y1/YA 11334	Microphone, tpl. No. 201	Minifon recorder model 54 G.P.O. patt.; swbd., type "A" gauge; for use with various sig. apps.	single	B 3011, B 5882
Y1/YA 2754	Black		single	

Y1/YA 3650	With cords, swbd., No. 230 Black	2 plugs, No. 201, black, fitted to cord, swbd., No. 230, black; used on swbd., U.C., 10 line, Mk. 2	single	C 4270
Y1/YA 3649	Red	2 plugs, No. 201, red, fitted to cord, swbd., No. 230, red; used on swbd., U.C., 10 line, Mk. 2	single	C 4270
Y1/5935-99-940-1759	No. 301 Black	Old Cat. No. Y1/YA 3947	single	
Y1/5935-99-940-1758	Red No. 316	Old Cat. No. Y1/YA 1179 G.P.O. patt.; triple contact with insulated body; swbd., type "B" gauge for use on various swbds.	single	
Y1/YA 3293	<i>Red</i>		<i>single</i>	<i>C 4270</i>
Y1/YA 3502	With cords, swbd., No.349(W.D.), green	Used on swbd., command, 200 line	single	C 4270
Y1/YA 8121	No. 406, Mk. 2	Plastic; fitted with 4 split pins; used on recvrs., hdgr., D, L.R., double, No. 5N and No. 5P	single	C 4270
Y1/YA 8130	No. 1301	G.P.O. patt.; 13, 1 way pins; used on tester, T.G. 958 (Sec.24)	single	C 4270
Y1/YA 7318	No. 1603	G.P.O. patt.; 8, 2 way flat pins; used on swbd., C.B., multiple, W.D., unit type	single	C 4270
	Telephone G.P.O. type No. 316	3 conductors, single shank, 0.25 in. dia., 3.213 in. lg. O/A.		C 4270
Y1/5935-99-940-1761	Black	Old Cat. No. Y1/YA 3500	single	
*Y1/5935-99-901-0161	Green		single	
*Y1/5935-99-940-1760	Red	Old Cat. No. Y1/YA 9730	single	
Y1/5935-99-940-1765	4 conductors per shank	Shell 1.125 in. dia.; 3.3/4 in. lg. O/A. (Old Cat. No. Y1/YA 3179)	single	C 4270

## SECTION Y1

## CLASS 5935-CONNECTORS, ELECTRICAL - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 8267 Y1/YA 8148	SOCKET 1/SSO/14 4 point, No. 30	G.P.O. patt.; used for 1/8 in. to 5/16 in. panels 1.29/32 in. x 1.9/16 in. x 15/32 in.; moulded body with 4 sockets .22 in. I.D. on 7/16 in. centres; used with plug, No. 406, Mk. 2 on rack, tel. terminal, No. 1	single single	C 4270 C 4270
Y1/YA 6149	10 point, No. 5	3.7/8 in. x 2.1/8 in. x 1.3/4 in.; moulded body with 10 sockets 5/32 in. I.D.; used on con., 5 pr., No. 4A and 4B, fits plug, 10 pt., No. 6	single	C 4270
Y1/YA 6763	12 point, No. 5	1.5/8 in. x 1.1/4 in. x 3/4 in.; moulded body with 12 sockets; used with plugs, 12 pt., No. 5 on tel. set, F., H.P., No. 1, Mk. 2	single	C 4270
*Y1/5935-99-901-3057 *Y1/5935-99-901-3061 *Y1/5935-99-901-2960	Electrical 1 pole, 2 amp., 2 KV., D.C. Black Blue Brown	Fixed; used on transponder set, M 347	single single single	

*Y1/5935-99-901-3060	Green		single	
*Y1/5935-99-901-3058	Orange		single	
*Y1/5935-99-914-7189	Red		single	
*Y1/5935-99-901-3062	Violet		single	
*Y1/5935-99-914-5028	White		single	
*Y1/5935-99-901-3059	Yellow		single	
*Y1/5935-99-100-3995	4 pole, free, male shell	Non-sealed, straight entry, F and E. type EP-CG-4-11; used on port. supply unit BD 594 (Old Cat. No. Y1/YA 12176)	single	
*Y1/5935-99-901-3122	7 pole, 1000 V., D.C.	Fixed; used on radio station D 11/R230	single	
*Y1/5935-99-911-4121	8 pole, relay type S.M. 5A	Used on data analysis programming group	single	
*Y1/5935-99-972-9795	12 pole, relay type, S 42271	Fixed straight entry (Old Cat. No. Y1/YA 8423)	single	
Y1/5935-99-901-2491	32 pole, 0.5 amp., 50 V., D.C.	Fixed; P.O. jack, No. 40; used on BID 08 (Old Cat. No. Y2/YB 00581)	single	
Y1/ZC 15668	SPRING, Flat No. 5	Used on jack, mic., No. 2D	single	C 4270
Y1/ZC 15669	No. 6	1.062 in. x .25 in.; Ni. Sil.; w/indent and hole 1 in. x .25 in.; spring steel w/hole	single	

CLASS 5940-LUGS, TERMINALS, AND TERMINAL STRIPS

Y1/YA 2354	BLOCK Terminal No. 6	G.P.O. patt.; 6.3/4 in. x 5.1/4 in. x 1.1/4 in. with metal cover for connecting 10 pair P.C. cable to indoor wiring	single	C 5687
------------	----------------------	---	--------	--------

## SECTION Y1

## CLASS 5940-LUGS, TERMINALS, AND TERMINAL STRIPS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	BLOCK			
	Terminal - continued			
Y1/YA 3553	No. 13	G.P.O. patt.; 4 pair, for terminating paper core cable	single	C 4270
Y1/YA 8488	No. 17, G.P.O.	G.P.O. patt.	single	C 5687
Y1/YA 2351	No. 20/2, black	G.P.O. patt.; 2.1/4 in. x 1.3/4 in. x 15/16 in.; with 2 connecting plates	single	C 4270
Y1/YA 2352	No. 20/4, black	G.P.O. patt.; 3.1/2 in. x 1.3/4 in. x 15/16 in.; with 4 connecting plates	single	C 4270
Y1/YA 2353	No. 20/8	G.P.O. patt.	single	C 5687
Y1/YA 6115	No. 20/12, black	G.P.O. patt.; 5.1/2 in. x 3.1/2 in. x 15/16 in.; with 12 connecting plates	single	C 4270
	BOARD			
	Terminal screwed head			
*Y1/5940-99-943-8587	2 terminal	1.1/2 in. lg, 7/8 in. wide, 13/32 in.; MIKACIN moulding	single	
*Y1/5940-99-943-8586	12 terminal	5.3/8 in. lg. 7/8 in. wide, 7/8 in. high; phenolic moulding (black)	single	

	<b>BOX</b>			
Y1/YA 2347	Terminal, signal office Mk. 2	Case, terminal fitted with 2 connector cables, 30 yd. terminating in plugs, 5 pr., No. 1	single	B 4959
Y1/YA 2773	Cases, terminal	17 in. x 4.3/4 in. x 3.3/8 in.; moulded case, with cable grip and removable batten on which are mounted 20 terminals	single	B 4959
Y1/YA 2774	Connector-cable, 30 yd.	30 yd. of cable, elec., D.3, 5 pr.(Sec.Y3) with ends prepared, one to suit plug, 5 pr., No. 1 and the other to suit the terminal batten of case, terminal	single	
Y1/YA 2723	Mk. 3	Similar to Mk. 2 but connector-cable terminating in strip, connection, 5 pr., No. 1	single	B 5748
Y1/YA 2957	Connector-cable, 30 yd.	30 yd. of cable, elec., D.3, 5 pr. (Sec. Y3) with ends prepared, one to suit strips, connection, 5 pr., No. 1 and the other to suit the terminal batten of case, terminal	single	
Y1/YA 9764	Mk. 4	Plastic box fitted with 20 terminals, inst., non-insulated, universal, slotted sealed 2 B.A. stem (Sec. Y3) and 30 yds. of cable, switch- board, 21 wire, 9.1/4 P.V.C. (Sec. Y3) terminated in a 20 way plug	single	C 8181
	<b>COVER</b>			
Y1/YC 00758	For block, terminal No. 6	G.P.O. patt.	single	C 5687
Y1/YA 9144	No. 8		single	
Y1/YA 9146	No. 13		single	
Y1/YA 9147	No. 14		single	

## SECTION Y1

## CLASS 5940-LUGS, TERMINALS, AND TERMINAL STRIPS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6122	COVER - continued Terminal, box, No. 1	17.3/8 in. x 4.7/16 in. x 17/32 in.; plastic moulding; includes engraved plate and 2 screws, special, B.S.W., 1/4 in. x 1.7/8 in. made captive in cover by split pin; used on box, terminal, signal office	single	C 4270
Y1/YA 5153	LUG, Special, vibrator, No. 1	1.1/4 in. long x 3/32 in. wide x No. 21 S.W.G., br. 2 way tag, centre-hole fixing; used on vibrators, ringing, 12 and 24 V.	single	C 4270
Y1/YA 6124	PLATE, Engraved, No. 11	13.3/4 in. x 2.5/8 in. x 1/16 in.; plastic, white; engraved with 9 lines 1.3/8 in. apart; used on boxes, terminal, signal office, Mks. 2 and 3	single	C 4270
Y1/YA 5361	TERMINAL Assembly, No. 1	No. 3 B.A. screw terminal with hexagonal fixing cap; used on swbds., command, 200 line	single	C 4270



Y1/YA 6685	Earth, No. 5	Br. hex. stud, 2.1/8 in. long, both ends threaded No. 2 B.A.; fitted with round knurled nut 1/2 in. dia. engraved "E"; used on test frames, 20 pr., Mk. 3 and 40 pr., Mk. 2	single	C 4270
*Y1/5940-99-901-3144	Lead through	0.5 in. lg. x .125 in. dia. O/A. dims, press fit fit mtg. PTFE; insulation; used on trans/rec.A43	single	
	Lug			
*Y1/5940-99-901-3147	2 BA. mtg. hole 53/64 in. x 5/16 in. x .031 in.	Copper, electro tinned, solderless, flat type .050 in. max. dia. cable accommodated; for Corporal	doz.	
*Y1/5940-99-901-3148	27/32 in. x 11/32 in. x .031 in.	.064 in. max. dia. cable accommodated; for Corporal	doz.	
*Y1/5940-99-900-3936	4 BA. mtg. hole 5/8 in. x 3/8 in.	Br. tinned; 1/6 in. dia. cable hole; solder; used on radar, A.A. No. 4, Mk. 7/3	doz.	
*Y1/5940-99-901-3145	Post	0.295 in. lg. x .125 in. dia. O/A. dims.; push fit mtg. CLIX polytag PT 21; used on trans/rec., A43	single	
*Y1/5940-99-901-2014	Spine	24 terminals; 5.7/8 in. lg., 1 in. max., 7/8 in. min. W., 7/32 in. max. 3/16 in. min. deep; nylon filled bakelite; self supporting; Cossor drg. DC 10140/14; used on radar, A.A., No. 4, Mk. 7/3	single	
Y1/YA 2101	Spring, No. 1	1.1/2 in. lg.; to take conductors up to .120 in. dia.; for use with links, wire, on test frames	single	B 2172
	TERMINAL BOARD			
*Y1/5940-99-901-2959	1.13/16 in. x 7/8 in. x 3/4 in.	Mikacing; 3 terminals; used on transponder set, M347	single	
*Y1/5940-99-901-2983	6.15/16 in. x 1.1/8 in. x 27/32 in.	Phenolic moulding; 12 screw type terminals; 12 amp. working; used on transponder set, M347	single	

## SECTION Y1

## CLASS 5940-LUGS, TERMINALS, AND TERMINAL STRIPS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
*Y1/5940-99-901-3149	TERMINAL BOX 3.865 in. dia. x 2.5 in. high	Phenolic; w/cover	single	
*Y1/5940-99-943-3565	TERMINAL STRIP, Grounding	8 wire accommodation; 4 in. lg. x 1/2 in. w. x 18 SWG thk.; br.; 2 fixing holes	single	
CLASS 5945-RELAYS, CONTACTS, AND SOLENOIDS				
Y1/YA 7723	ARMATURE, Relay, No.A12/3	Plain armature fitted with .012 in. residual stud; used on 3000 type relays	single	C 4270
Y1/YA 5784	COVER Dustproof, relay, No. 1	Nitro-cellulose-proofed cotton cambric bag. 2.3/4 in. x 2.1/2 in. x 1.1/16 in. with draw cord; for relay, line, No. 1	single	C 4270

Y1/5945-99-901-3720	Electrical relay	Steel; 2.3/8 in. lg. x 1.1/4 in. w. x 4.11/16 in. h.; P.O. relay cover, AN; used on swbd., A.A., 5 line, Mk. 1 (Old Cat. No. Y1/YA 2235)	single	C 4270
Y1/YA 7131	Relay A.P.	3.27/32 in. x 2.21/64 in. x 2.21/64 in.; G.P.O. patt. metal; for 2 relays, 3,000 type	single	C 4270
Y1/YA 5436	A.T.	3.1/16 in. x 1.521 in. x .73 in.; metal; for relay, No. 600, W.D., A	single	C 4270
Y1/YA 7256	A.Y., 9.11/64 in.	9.11/64 in. x 3.25/64 in. x 3.19/32 in.; metal; used with mtg. No. F157/10, AV	single	C 4270
*Y1/5945-99-901-2005	PLATE, Mounting relay, 151/2B	G.P.O. patt.; used on recorder, reproducer, dual channel	single	
	RELAY	Detail for relays; A or M. signifies Make B. signifies break C. signifies Change-over (B before M) K. signifies Change-over (M before B)		
Y1/YA 4977	1/0, No. 1	1.15/16 in. x 1.1/4 in. x 1.9/16 in.; single coil 1/4 ohm; contacts 1B; used on tel., L.S., No. 2 set	single	C 4270
Y1/YA 8337	24 V. multi-spring set No. 1	Coil 24 V.; contacts 3M, 3C; heavy duty	single	C 4270
Y1/YA 8338	No. 2	Coil 24 V.; contacts 1M, 4B. 1C; heavy duty	single	C 4270
*Y1/YA 12907	Armature 10V., 1 amp., 200 V., 50 mA., D.C.	Contact arrangement at 3 position; 4 in A., 95 ohms, 95 ohms D.C. coils, TMC type 5 HH3; used on Radio Stn. D11/R230	single	
*Y1/5945-99-999-4741	28 V., 30 amp, D.C.	1 M contact; 16 to 29 V.; 250 ohms; D.C. coil; Plessey type AD/IM/28/30; used on transponder set M 347	single	

## SECTION Y1

## CLASS 5945-RELAYS, CONTACTS, AND SOLENOIDS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	RELAY			
*Y1/5945-99-901-3357	Armature - continued 30 V., 0.5 amp., D.C.	Single changeover contact; 15 V., 425 ohms D.C. coil; Smith's type 11 PCR/3; used on trans/rec. radio A 43 R, Mk. 2	single	
*Y1/5945-99-901-3615	30V., 10 amp., D.C.	4 pole double throw contacts, 26V., 150 ohms D.C. coil; Diamond H type BR 115C1P-1C; used on camera, aircraft, F 95, Mk. 5	single	
*Y1/5945-99-901-0629	60 V., 4 amp., AC/DC, 300 V; 4 amp., D.C.	Contact arrangement 2B 2B; 24 V., 670 ohms D.C. coil type SM4. No. 2; used on wireless set C42 (Old Cat. No. Y1/YA 9977)	single	
*Y1/5945-99-901-0387	100V; 075 amp., D.C.	2A and 1C contacts; 6 V., 65 ohms D.C. coil; Ericsson type N29931 BC3; used on trans-rec, radio, A41	single	
*Y1/5945-99-901-3358	100 V., 1 amp., D.C.	Two changeover contacts; 8 V., 90 ohms D.C. coil; Varley type VP2/CAA/7; used on trans/rec. radio A43R, Mk. 2	single	
*Y1/5945-99-901-3359	100 V., 1 amp., D.C.	Four changeover contacts; 12 V., 230 ohms D.C. coil; Varley type VP4/CAA/9; used on trans/rec. radio A43R, Mk. 2	single	
*Y1/5945-99-580-0469	200 V. max., AC/DC	Contact arrangement 1C; 200 ohms, 0.94 mA. and D.C. coil; IMC type 3N1 (Z); used on equipt., Monitor, keying frequency shift	single	

*Y1/5945-99-901-3356	200 V. max., AC/DC., S.P.	Double throw contacts; two 470 ohms, 0.83 m A.D.C. coils; T.M.C. type 5P6; used on distributor-transmitter, teleprinter (5815-99-901-3295)	single
*Y1/5945-99-943-9131	200 V., 1 amp. 10 watts, D.C.	3 positions; 4mA., 14 ohms, D.C. coil T.M.C. type 5HA 18B; used on power system test set, Mk.2	single
*Y1/5945-99-901-0542	200 V. 50 mA., 10 V. 1 amp., D.C.	Contact arrangement at 3 position; 4 mA., 55 ohms, D.C. coil, T.M.C. type 5 HH7; used on electronic unit BID 60/1	single
*Y1/5945-99-901-2487	200 V. 50 mA., 525 mV.	1 changeover; 105 ohms coil; T.M.C. type 6U 38; used on trans., radio, Marconi type HS 51	single
*Y1/5945-99-933-0516	200 V. 50 mA., D.C.	Contact arrangement at 3 positions; 270 mV., 90 ohms, DC coil; used on app., carrier, tel., 12 channel	single
*Y1/5945-99-901-2322	230 V., 2.1/2 amp., A.C.	2 M contacts; 230 V., A.C. coil; B and R type T.01; for use on equipt., radar; A.A., No.3, Mk.7/4	single
*Y1/YA 12606	250 V., 2B and B	Contact arrangement; 625 ohms + 625 ohms; 23-37 V., D.C. coil; STC type 4663 MJG/TFS; used on plate, graining and paper cutting equipt.	single
*Y1/5945-99-901-3418	250 V., 5 amp., A.C., 1M1C contacts	24 V., 890 ohms, D.C. coil; Magnetic Devices 596/890/AC2/24; used on camera, still picture, Vinten, F95, Mk. 6	single
*Y1/5945-99-901-3417	250 V., 5 amp., A.C., 3M contacts	24 V., 890 ohms, D.C. coil; Magnetic Devices 596/890/AE2/24; used on camera, still picture, Vinten, F95, Mk. 6	single
*Y1/5945-99-901-3226	250 V. max., 1 amp. max., 1M1B contacts	2000 ohms D.C. coil; AEI type RDJ 4793 AA; used on trans., radio, Marconi type HS 51	single
*Y1/5945-99-901-3225	250 V. max., 1 amp. max., 3M1B contacts	200 ohms D.C. coil; AEI type RDJ 4146 AA; used on trans., radio, Marconi type HS 51	single
*Y1/5945-99-901-3224	250 V. max., 1 amp. max., 5M1B	2000 ohms D.C. coil; AEI type RDJ 6477; used on trans., radio, Marconi type HS 51	single
*Y1/5945-99-901-3288	250 V. max., 5 amp. max., 1M3B contacts	150 ohms D.C. coil; AEI type RDJ 6886; used on trans., radio, Marconi type HS 51	single

## SECTION Y1

## CLASS 5945-RELAYS, CONTACTS, AND SOLENOIDS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	RELAY			
	Armature - continued			
*Y1/5945-99-901-3289	250 V. max., 5 amp. max., 2M2B contacts	150 ohms D.C. coil; AEI type RDJ 6887; used on trans. radio, Marconi type HS 51	single	
*Y1/5945-99-901-3227	250 V. max., 5 amp. max., 3M1B contacts	200 ohms D.C. coil; AEI type Y1310/J4; used on trans. radio, Marconi type HS 51	single	
*Y1/5945-99-901-0450	300 V. max., 1 amp. D.C. max.	Contact arrangement 1 C and 1 C; anode voltage, 7600 ohms D.C. coil; type SM 4 No. 5; used on wireless set, C42	single	
*Y1/5945-99-901-0449	300 V. max., 1 amp. D.C. max.	Contact arrangement 2C and 2C; 24 V; 670 ohms D.C. coil; type SM 4 No. 1; used on wireless set, C42	single	
*Y1/5945-99-901-0264	300 V, D.C. max., 1 amp. max. AC/DC	2C and 2C contacts; 12 V., 180 ohms D.C. coil type M 1141; used on wireless set, C42	single	
*Y1/5945-99-100-7359	300 V., 2 amp., D.C., 300 V., 4 amp., A.C.	Contact arrangement 2KTM; 24V., 670 ohms D.C. coil G.E.C. drg. M 1625	single	
*Y1/5945-99-901-0388	300 V. max., 4 amp. max. AC/DC	2A and 2A contacts; 24 V., 670 ohms D.C. coil, G.E.C. type M 1133; used on wireless set, C12 (PSU)	single	

*Y1/5945-99-901-0889	300 V. 100 mA., D.C.	Contact arrangement 4C, 5000 ohms coil; G.E.C. drg. M 1102; used on MALKARA	single	
*Y1/5945-99-901-0628	300 V. 100 mA., AC/DC, 60 V., 1 amp D.C.	Contact arrangement 1C and 1C, 24 V., 670 ohms D.C. coil, type SM 4 No. 3; used on wireless set C42	single	
*Y1/5945-99-901-0260	500 V. max. 20 amp. max. AC/DC	2 pole double throw contacts; 20-26 V. D.C. coil; B. and R. type J.04; used on equip. radar. A.A., No. 3 Mk. 8	single	
*Y1/5945-99-901-0610	550 V., 12 amp., AC/DC	Contact arrangement 2A and 2A; 230 V., A.C. 60 V., D.C. 1500 ohms., D.C. coil; Londe XLFX/65A/2M56/U; used on RED SHOES test equipment	single	
*Y1/5945-99-940-1965	Non sealed, high speed	Carpenter type 3 SE1; used on BID 560/1, BID 30	single	
*Y1/5945-99-011-9144	Sealed, normal type 105 ohms	4 change overs; type SM5D-N72; used on power supply type W100	single	
*Y1/5945-99-901-3221	500 + 500 ohms	1 change over; type 130D; used on W/set C11	single	
Y1/YA 7985	H.S. No. 6	Coils 250 ohms + 250 ohms; contacts 1C	single	C 4270
Y1/ZA 3193	No. 8	Coils 1,000 ohms + 1,000 ohms in series; contacts 1C	single	C 4270
Y1/ZA 10109	No. 9	Coils 1,000 ohms + 1,000 ohms. contacts 1C	single	C 4270
*Y1/5945-99-911-4074	Magnetic 350 V. max. 1 amp. max. D.C.	8 change over contacts; 24 V., 550 ohms D.C. coil; Ericsson type N22603 AD1; used on launcher, guided missile, K1A1	single	
*Y1/5945-99-932-1732	Non sealed High speed	1 change over; 560 + 560 + 450 ohms; type 5M8; used on Firestreak, overall test set, Mk. 2	single	
*Y1/5945-99-943-8811	Normal duty	2 M/2M; 540 ohms; type LF; used on starter, motor (100-1872)	single	

## SECTION Y1

## CLASS 5945-RELAYS, CONTACTS, AND SOLENOIDS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	RELAY			
	Magnetic - continued			
	Sealed			
*Y1/5945-99-932-0971	Heavy duty	4 change overs; 440 ohms; type N22618 ADI; used on test set group, guided missile (100-2962)	single	
*Y1/FV 234321	Normal duty	4 M, 4 B, 30 ohms, solenoid type; used on Churchill flail station keeping equip.	single	
	S.I. and C type	Used on unit, signalling, V.F., 5 channel		
*Y1/YA 12365	4632 ABT, TFS		single	
*Y1/YA 12363	4632 AEL, TFS		single	
*Y1/YA 12362	4634 AFY, TFS		single	
	No. 600 type (W.D.)	3.1/2 in. x 1.1/2 in. x 3/4 in.; similar to G.P.O. 600 type series except in value of coil and combination of springs; tropical finish		C 4270
Y1/YA 3776	A. without relay cover, A.I.	Coil 1,000 ohms; contacts 1B	single	
Y1/YA 7034	J	Coil 100 ohms; contacts 2B	single	
Y1/YA 7035	K	Coil 100 ohms; contacts 1M	single	
Y1/YA 7452	M	Coil 3,000 ohms; contacts 1C	single	
Y1/YA 7514	N	Coil 200 ohms; contacts 4C	single	
Y1/YA 7580	R	24 volt working; contacts 2C	single	
Y1/YA 7581	S	24 volt working; contacts 4C	single	



Y1/ZA 21858 -  
Y1/YA 8132

Y1/YA 7019

Y1/YA 7020

Y1/YA 7021

Y1/YA 7022

Y1/YA 7023

Y1/YA 7024

Y1/YA 7025

Y1/YA 7026

Y1/YA 7027

Y1/YA 7028

Y1/YA 7029

Y1/YA 7030

Y1/YA 7031

Y1/YA 7032

Y1/YA 7033

Y1/YA 7335

Y1/YA 7450

Y1/YA 7502

Y1/YA 7503

W  
No. 625  
No. 3,000 type (W.D.)

BN

BO

BP

BQ

BR

BS

BT

BU

BV

BW

BX

BY

BZ

CA

CB

CQ

CT

CW

CX

Coil 70 ohms; contacts 2M, 1B  
G.P.O. patt.; 100 ohms; contacts 1M  
4 in. x 1.3/4 in. x 1 in.; similar to G.P.O.  
3,000 type series except in value of coil and  
combination of springs; tropical finish  
Coil 2,000 ohms; contacts 1M, 1.1/2 in. slug,  
armature end  
Coil 100 ohms; contacts 1M  
Coil 500 ohms + 500 ohms; contacts 1M  
Coil 100 ohms; contacts 1B  
Coil 2,000 ohms + 2,000 ohms; contacts 2M  
Coil 2,000 ohms + 1,200 ohms; NT contacts 3C, 1M  
Coil 2,000 ohms; contacts 2C; 1.1/2 in. slug,  
armature end  
Coil 20 ohms; contacts 2M  
Coil 2,000 ohms; contacts 1M, 1B, 1K; 1/2 in.  
slug, armature end  
Coil 1 ohm + 2,000 ohms; contacts 1B, 1M  
Coil 200 ohms; contacts 1B, 1M  
Coil 2,000 ohms; contacts 1B, 2M, 1C  
Coil 500 ohms; contacts 1M. 1K  
Coil 100 ohms; contacts 2M, 2B, 2C  
Coil 2,000 ohms; contacts 2M. 2B. 1C; 1.1/2 in.  
slug, armature end  
Coil 200 ohms + 200 ohms; contacts 2M  
Coil 3,750 ohms; contacts 1B; slugged  
Coil 2,000 ohms; contacts 2C  
Coil 2,000 ohms; contacts 2B

single  
single C 4270  
B 6014,C 4270

single

single

single

single

single

single

single

single

single

single

single

single

single

single

single

single

single

single

single

## SECTION Y1

## CLASS 5945-RELAYS, CONTACTS, AND SOLENOIDS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	RELAY			
	No. 3,000 type (W.D.)			
	- continued			
Y1/YA 3901	D	Coil 1,000 ohms + 1,000 ohms; contacts 1M	single	
Y1/YA 7506	DA	Coil 1,000 ohms; contacts 1K	single	
Y1/YA 7507	DB	Coil 2,300 ohms; contacts 1K	single	
Y1/YA 7508	DC	Coil 2,000 ohms; contacts 2M	single	
Y1/YA 7509	DD	Coil 1,000 ohms; contacts 2M	single	
Y1/YA 7510	DE	24 V. working; contacts 2C	single	
Y1/YA 7511	DF	24 V. working; contacts 1M	single	
Y1/YA 7515	DI	Coil 2,000 ohms; contacts 1C; armature modified	single	
Y1/YA 7517	DJ	Coil 1,000 ohms; contacts 2B, 2M. 1C; (1C. low capacity)	single	
Y1/YA 8019	FG	Coil 100 ohms; contacts 2M, 2B; heavy duty type	single	
Y1/YA 8246	HH	Coil 1,000 ohms; contacts 3M, 1B	single	
Y1/YA 8300	HM	Coil 500 ohms; contact 6K	single	
Y1/YA 8307	HP	Coil 6,000 ohms; contacts 2M, 1B	single	
Y1/YA 8339	HR	Coil 6,500 ohms; contacts 1M; heavy duty	single	
Y1/YA 8341	HS	Coil 20,000 ohms; contacts 2C	single	

Y1/ZA 16209	HT	Coil 4,000 ohms; contacts 1M; heavy duty	single	
Y1/YA 2860	P	Vibrating type; coil 50 ohms + 500 ohms N.I. shunt	single	B 6340
Y1/YA 2862	Q	Vibrating type; coil 200 ohms + 1,000 ohms N.I. shunt	single	B 6340
Y1/YA 11366	No. 3525	G.P.O. patt.; No. 3,000 type relay	single	C 8635
Y1/YA 11364	No. 5282	G.P.O. patt.; No. 3,000 type relay	single	C 8635
	Solenoid			
*Y1/5945-99-901-0256	Pullin type S10, 24V.	Used on test set group, guided missile (100-2962)	single	
*Y1/5945-99-100-2793	2 pole, 230V., D.C., 25 amp.	Single throw; Arrow type 460242 U; used on power supply set (100-1501)	single	
*Y1/5945-99-901-3421	24 V., 25 amp.	Contacts 2B, 2M, 24V., 127 ohm. D.C. coil (Old Cat. No. Y1/YA 11066); used on wireless sender, C11-PSU	single	
Y1/YA 6730	RELAY SET, B/W junction, No. 1	Consists of 9 relays, 4 resistors, 5 condensers, 4 rectifiers, 1 transformer, 1 tag block; fitted to mtg. plate; includes front and rear cover, used on swbd., position, C.B., (W.D.), 10 + 50	single	C 4270

CLASS 5950-COILS AND TRANSFORMERS

	CHOKE			
	A.F.			
Y1/ZA 30662	6H, 60 mA, No. 1	3.1/2 in. x 2.5/8 in. x 2.3/8 in. D.C. resis. 175 ohms	single	C 4270
Y1/ZA 1043	No. 45	3.5 in. x 3.375 in. x 4.312 in. high, D.C. resis. 275 ohms.; winding 6,100 turns of 32 S.W.G. enam. cpr. wire; used on ampfr., port., P.A., No. 1, Mk. 2	single	C 4270
	COIL			
	Induction			
Y1/YA 3994	No. 2 (W.D.)	2.5/8 in. x 1.1/8 in. x 1 in.; 4 windings, 1 ohms., 20 ohms., 40 ohms., 500 ohms.; used on swbds., mag.	single	C 4270

## SECTION Y1

## CLASS 5950 - COILS AND TRANSFORMERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	COIL Induction - continued			
Y1/YA 5794	No. 3/16	G.P.O. patt.; P. 4 ohms., 1st. S. 20 ohms., 2nd S. 440 ohms.; has 6 tags and cover for operator's, tel. cct. on C.B. swbd.	single	C 4270
Y1/YA 7137 Y1/YA 11010	No. 3/16 (W.D.) No. 6	Similar to G.P.O. No. 3/16 but with tropical finish G.P.O. patt.; P.11 ohms, 1st S.58 ohms, 2nd S.240 ohms; base 7.1/8 in. x 2 in., 7 tags for operators cct. C.B. manual systems	single single	C 4270 C 8423
Y1/YA 7142	No. 9 (W.D.)	P.26 ohms, S.17 ohms, with metal/cover 5.5/8 in. x 1.17/32 in. x 1.21/32 in.; used on operators' ccts with tropical finish	single	C 4270
Y1/YA 0464	No. 12	G.P.O. patt.; P.1 ohm, S.25 ohms; standard coil for tel. and swbds	single	26018, A 2051
Y1/YA 10887	No. 16	G.P.O. patt.; P.4 ohms, 1st S.20 ohms, 2nd S.440 ohms; 3 separate windings 6 tags for operators cct. on C.B. swbds	single	C 8423
Y1/YA 4339	No. 18	G.P.O. patt.; P.33 ohms, S.17 ohms; for C.B. tel. and bell sets of the moulded type	single	C 4270
Y1/YA 7686	No. 18A	G.P.O. patt.; similar to No. 18 but for earlier types of C.B. tel. and bell sets (wooden type)	single	C 4270
Y1/YA 2370	No. 21 (W.D.)	3 windings; 1 ohms, 17 ohms and 32 ohms; similar to	single	B 4804

Y1/YA 3804	Mounted	G.P.O. patt. No. 21 but tropical finish; used on swbd., F. and F., unit C Coil induction, No. 21, W.D., in metal housing with contact plate; for use on tel. sets, F in lieu of buzzer, T, Mk. 1 when buzzer calling is not required	single	B 5255
Y1/YA 7688	No. 27	G.P.O. patt.; anti-side tone induction coils, for tel., No. 1/226 C.B., used in kits, extension, tel. C.B. exch.	single	C 4270
Y1/YA 4686	No. 27 (W.D.), A	Similar to G.P.O. patt. No. 27 but with different fixing centre; tropically finished	single	C 4270
Y1/YA 4674	Repeating No. 4001A	G.P.O. patt.; 2 toroidal coils each with iron shell on wooden base 10.3/4 in. x 4 in.; with 16 tags at one end; 4 windings each 18-24 ohms	single	C 4270
Y1/YA 0467	No. 4006A, minus base	Toroidal, with iron shell; 2 P windings 37 ohms, 2 S. windings 31 ohms each; incomplete; used as component of other instruments	single	24851, B 2912
Y1/5950-99-100-1810	Telephone induction	4 windings, 1.2 ohms x 52 ohms x 53 ohms x 600 ohms; 2.1/16 in. long x 13/16 in. wide x 1.1/8 in. high (Old Cat. No. Y1/YA 7322)	single	C 4270
Y1/YA 12011	DEMAGNETIZER	Wright and Weaire type; for depolarising recorder heads	single	
Y1/YA 2861	TRANSFORMER 12 V.	3.7/8 in. sq. x 2.9/16 in.; met. C.; P. resis. 110 ohms max.; S.7 ohms max.; toroidally wound; tapped windings with 7 soldering lugs; used on vibrator, ringing, 12 V.	single	B 6340

## SECTION Y1

## CLASS 5950 - COILS AND TRANSFORMERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	TRANSFORMER - continued			
Y1/YA 2863	24 V.	3.7/8 in. sq. x 2.9/16 in.; met. C.; P. resis. 110 ohms max.; S.30 ohms max.; toroidally wound; tapped windings with 7 soldering lugs; used on vibrator, ringing, 24 volt	single	B 6340
*Y1/YA 12012	Audio-frequency	Wright and Weaire type 941; used on mic-matching unit, type TU/30/GL	single	
Y1/YA 5130	Bell, No. 1	Input 200/260 V.; output 4/8/12 V.; used on wireless set, No. 16, complete station (Sec. Z1); and perforator, keyboard, No. 9W (Sec. Y2)	single	C 4270
Y1/YA 8115	Input, No. 12	P.100 turns of 43 S.W.G.; S.2,200 turns of 46 S.W.G.; windings brought out of 5 tag panel in base; totally enclosed in octagonal metal case; used on ampfr., field tel., No. 1	single	C 4270
Y1/YA 3371	Loudspeaker, telephone, No. 2	3.1/4 in. x 1.3/4 in. x 2 in.; P.66 turns; S.600 turns; brought out to 10 way tag panel on top; used on tel., L.S., No. 2, set	single	C 4270
Y1/YA 4978	Microphone A	3.1/4 in. x 1.3/4 in. x 2 in.; P.44 turns, centre tapped, No. 20 S.W.G.; S.300 turns, centre tapped, No. 24 S.W.G.; terminations brought out to 8 way tag panel mounted on top; used on tel., L.S., No. 2, control unit, Mk. 2	single	C 4270

Y1/YA 2800	E	P.206 ohms; S.60 ohms; used on tel., L.S., No. 5 and tel., L.S., No. 1	single	B 4106
Y1/YA 3366	F	3.3/16 in. x 1.3/4 in. x 2 in.; P.36 turns, centre tapped, No. 18 S.W.G.; S.4 sections each 300 turns of No. 36 S.W.G., finish of each section commoned; windings brought out to 10 way tag panel mounted on top; used on tel., L.S., No. 2, set	single	C 4270
*Y1/YA 11326 Y1/YA 7317	Minifon recorder No. 3/48A	Transformer/rectifier unit; used on Minifon Model 54 3.3/4 in. x 2.3/8 in. x 2 in. G.P.O. patt. voltage ratio 1:1; used on swbd., C.B., multiple, (W.D.), unit type	single single	C 4270
Y1/YA 7923	No. 35A	3/4 in. x 2.7/8 in. x 1.1/4 in.; G.P.O. patt.; voltage ratio 1:2; tubular, with fixing luqs; anti-side tone; for tel. No. 1/62, etc.	single	C 4270
Y1/YA 3874	No. 48B	4 in. x 2.5/8 in. x 2 in.; G.P.O. patt.; voltage ratio 1.27:1; used on unit, signalling, V.F., No. 2	single	C 4270
Y1/YA 8205	No. 49A	G.P.O. patt.; comprises balanced pair of transformers, No. 48A, (N.I.V.), mounted on a common plate	single	C 4270
Y1/YA 5735	No. 61B	4 in. x 2.5/8 in. x 2 in. G.P.O. patt.; voltage ratio 3:1; inductance 9H	single	C 4270
Y1/YA 5855	No. 67A	4 in. x 2.5/8 in. x 2 in. G.P.O. patt.; voltage ratio 9:1; inductance 28H	single	C 4270
*Y1/YA 11327 Y1/YA 8116	Output Minifon recorder No. 77	Used on Minifon model 54 P.3,290 turns of No. 46 S.W.G.; S.735 turns of No. 43 S.W.G.; windings brought out to 4 way tag panel on base; totally enclosed in octagonal met. C.; used on ampfr., field tel., No. 1	single single	C 4270
Y1/YA 2798	W	P. winding 200 ohms; S. winding 0.2 ohms; used on tel., L.S., No. 1	single	B 4106

## SECTION Y1

## CLASS 5950 - COILS AND TRANSFORMERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	TRANSFORMER - continued			
Y1/YA 2185	Superposing, No. 1	3.3/8 in. x 3.13/16 in. x 1.13/16 in.; in metal screened case; 2 pair balanced toroidal windings, 1:1 ratio; used in superposing unit, 1 transformer and 3 transformer	single	B 2912
Y1/YA 3367	Telephone, No. 29	3.3/16 in. x 1.3/4 in. x 2 in.; P.150 turns of No. 24 S.W.G.; S.4 sections, each 300 turns of No. 36 S.W.G., finish of each section commoned; windings brought out to 10 way tag panel mounted on top	single	C 4270
	UNIT			
Y1/ZA 17330	Transformer, microphone, No. 2	With 1 transformer, mic., No. 23 (Sec. Z1), used on mic., hand, power, No. 1A	single	C 4270
*Y1/YA 12128	Transformer/rectifier	Model 2556; used on Minifon model 54	single	
	CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS			
Y1/ZA 17545	ARMATURE, Microphone, throat low level, No. 2	1.9/16 in. x 9/32 in. x 1/16 in.	single	
Y1/ZA 17552	BRIDGE, Metal, No. 1, neckband	2 in. x 1/2 in. x 1/32 in.; metal bridge; for connecting the 2 units of microphones, throat low level	single	



*Y1/5965-99-901-0201	CAP, Electrical	2.525 in. dia. x 0.89 in.; phenolic; used on tel., hand	single	B 1782, C 4270
Y1/ZA 0820	CAPSULE, Microphone, R/T., No. 1	2.7/32 in. dia. x 5/8 in.; granular carbon type	single	C 4270
CASE				
Y1/ZA 25223	Microphone, hand, I.T.E., No. 18	2.1/2 in. long x 1.425 in. x 1.9/64 in. rubber moulding	single	C 4270
Y1/ZA 27795	Moulded, microphone, hand, No. 13	2.3/4 in. dia. x 1.3/4 in.; 3 piece plastic moulding	single	C 4270
Y1/5965-99-940-1178	Receiver, I.T.E., No. 1	2.187 in. dia. x .843 in.; plastic moulding; used on receiver, I.T.E., No. 1	single	C 4270, C 8181
Y1/YA 8185	Rubber, microphone No. 2	1.1/2 in. dia. x 1.11/32 in.; moulded rubber; for mic. capsule, miniature, No. 1; used on tel., hand, No. 11	single	C 4270
Y1/YA 8215	No. 3	1.1/2 in. dia. x 1.11/32 in.; moulded rubber; for mic. capsule, miniature, No. 1; used on mic. and recvr., hdgr. No. 15	single	C 4270
CLIP				
Y1/ZA 26329	Microphone, hand (I.T.E.), No. 18	3 in. long x 7/8 in. x 7/8 in.; crocodile clips with plastic jaws and wiring clip attached; for clipping microphone to clothing	single	C 4270
Y1/ZA 25314	Pad, receiver, watch, J	3.1/2 in. x 2.13/16 in. x 3/8 in.; M.S. No. 24 S.W.G. oval shaped ring 3/16 in. wide	single	C 4270
Y1/ZA 29351	Securing, cover, No. 1	2.184 in. dia. x .375 in.; metal clip for securing front and rear covers on recvr., watch, C, H.R., No. 9	single	C 4270
Y1/ZB 12918	CONE, Loudspeaker, No. 8	Fabric paper cone, includes speech coil; 1 in. dia.; used on L.S., No. 8	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
*Y1/YA 12080 *Y1/YA 12081 *Y1/YA 12082 Y1/YA 8186	CONTACT ASSEMBLY Complete, Minifon recorder H.T. battery L.T. battery Motor battery Microphone, No. 1	Used on Minifon model 54    Circular contact assembly, 1 in. dia.; for making contact with mic. capsule, miniature, No. 1; used on tel. hand, No. 11	single single single single	C 4270
Y1/ZA 24234	CONTACT, Side spring, micro., No. 7	1/2 in. x 3/16 in. x .0148 in. thick; Ni. sil., contact spring, "J" shape; used on mic., hand, No. 7	single	C 4270
Y1/ZA 29352	COVER Back, receiver, watch, No. 1 Front	For recvr., watch, C, H.R., No. 9	single	C 4270
Y1/ZA 27788	Microphone, hand, No. 13	Plastic	single	C 4270
Y1/ZA 23877	Microphone, M.C., No. 1	Metal	single	C 4270
Y1/ZA 29353	Receiver, watch, No. 1	Rubber; fits over recvr., watch C., H.R., No. 9	single	C 4270
Y1/ZA 17547	Latex, No. 1, cord end	Used on mic., throat, low level, No. 2	single	C 4270
Y1/ZA 17546	Latex, No. 1 top	Used on mic., throat, low level, No. 2	single	C 4270
Y1/ZA 15849	Microphone, hand, No. 7	2.5/16 in. x 1.1/8 in.; plastic moulding	single	C 4270

Y1/ZA 10041	Microphone, terminal, No. 1	11/16 in. dia. x 11/32 in.; 26 t.p.i.; used on mic., hand, Nos. 3, 4, 7 and 8	single	
Y1/YA 4620	Microphone, transmitter, breast, (sound P.), No. 1	Plastic moulding; 2.1/8 in. dia. x 3/4 in.; used on transmitter, breast, (Sound P.), No. 1	single	C 4270
Y1/YA 4662	Moulded case	9.7/8 in. x 6 in. x 1.7/16 in. plastic moulding; includes diagram plate, 3 fixing screws and 3 special nuts; used on tel. set, F. Mk. 1/1 and Mk. 2	single	C 4270
Y1/5965-99-940-1179	No. 1, receiver, watch, I.I.E.	Rubber moulding 1.5/8 in. dia. x 7/8 in.; single inlet; for covering rear of receiver, watch	single	C 4270
Y1/ZA 14289	No. 2, microphone, throat unit, L.L.	Used on mic. and recvr., hdgr. assy., No. 5	single	C 4270
Y1/5965-99-940-1180	No. 2, receiver, watch, I.I.E.	Rubber moulding 1.5/8 in. dia. x 7/8 in.; double inlet; for covering rear of receiver, watch	single	C 4270, C P181
Y1/YA 8280	No. 8, G.P.O.	4 in. x 1.1/2 in. x 1.3/4 in.	single	C 4270
	DIAPHRAGM			
Y1/YA 0529	C	G.P.O. patt.; No. 24; for receiver, watch C	single	B 1111, B 4806
	Loudspeaker			
Y1/YA 2857	No. 1	3 in. dia x 5/8 in. deep; Al., with moulded front cover and rubber washer; fitted with moving coil; resis. 6-7 ohms; for use in tel. L.S., No. 1, No. 2 and No. 3, L.S.	single	B 4106
	Re-entrant			
Y1/ZB 10262	500 ohms, No. 2	Paper diaphragm	single	C 4270
Y1/YA 0532	No. 12	G.P.O. patt.; stalloy, 2.1/16 in. dia. x 0.01 in.		24302, A 460
Y1/YA 3132	No. 25	G.P.O. patt.; permendur, 2.1/16 in. dia.; used on recvr., hdgr., No. 10A	single	C 4270
Y1/ZA 24509	DISC, Insulating, microphone, hand, No. 7	Used on mic., hand, No. 7	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5581	EAR-CUSHION A	3 in. O.D. x 7/8 in.; rubber; centre hole 3/4 in. dia.; used on tel., head and breast (Sound P.), No. 2 and 2A	single	C 4270
Y1/ZA 11382	F	3.1/2 in. O.D. x 2.1/4 in. I.D.; sponge rubber ring, with velvet cloth cemented on and fitted with draw cord; used on recvr., watch, F.	single	C 4270
Y1/YA 4606	G	2.3/4 in. O.D. x 1.5/8 in. I.D. x 1/8 in.; rubber, moulded ring; used on recvr., hdgr., (Sound P.), No. 1	single	C 4270
Y1/YA 11439	EARPHONE, magnetic, external terminals, headset type	Comprises: 1 inset, earphone, electromagnetic (Y1/5965-99-940-2368); 1 case, earphone, magnetic, external terminals, headset type (Y1/YA 11438); 1 gasket, rubber, 1.27/32 in. O.D. x 1.9/16 in. I.D. x .06 in. (Y1/YA 9548); 1 earpiece, earphone, magnetic (Y1/YA 11431); 1 ring, externally threaded, plastic, 2.1/8 in. O.D. x 7/32 in., earphone, headset type (Y1/ZA 19009)	set	C 9519
Y1/5965-99-901-2503	EARPHONE ELEMENT, G.P.O. type 2P, black	Magnetic type, 50 ohms non-impedance (Old Cat. No. Y1/YA 8595) (NIV)	single	

Y1/YA 5135	EAR-PIECE A	2.5/8 in. dia. x 1 in. wide; plastic moulding, with centre hole 1/4 in. dia., used on tel. hand (Sound P.), No. 2	single	C 4270
Y1/YA 4653	Moulded, receiver, watch, (Sound P.), No. 1	2.3/8 in. dia. x 3/4 in. wide; plastic moulding; used on recvr., watch, (Sound P.), No. 1	single	C 4270
Y1/YA 4259	No. 2	G.P.O. patt.; used in kit, extension, tel., C.B. exch.	single	C 4270
*Y1/YA 11801	Green		single	
*Y1/YA 11802	Ivory		single	
*Y1/YA 11803	Red		single	
Y1/YA 3133	No. 22	G.P.O. patt.; used on recvr., hdgr., No. 10A	single	C 4270
Y1/ZA 5807	Receiver, watch "C"	2.7/16 in. dia. x 29/64 in.; plastic	single	C 4270
Y1/ZA 29837	C, H.R., No. 9	2.1 in. dia. x 7/16 in.; plastic	single	C 4270
Y1/ZA 19011	D, L.R., No. 5	2.1/2 in. dia. x 27/32 in.; plastic; 2.085 in. I.D., threaded 24 t.p.i. Whitworth form; used on recvr., watch, D, L.R., No. 5	single	C 4270
*Y1/YA 12085	Stethophone, minifon recorder	Used on Minifon, model 54	single	
Y1/YA 3206	EXTENSION HANDLE	1.1/8 in. dia. x 3.1/4 in. long; Al. casting; grip portion of handle; used on mic., hand, hand, power, No. 1, Mk. 1 and Mk. 2, No. 1A and 1B	single	C 4270
Y1/ZA 5427	EYE-BOLT, Microphone, hand	Br., 3/4 in. long; threaded No. 6 B.A. 13/32 in.	single	C 4270
Y1/YA 8217	FRAME ASSEMBLY, Microphone and receiver	Spring steel wire, No. 13 S.W.G., frame for holding mic. support and recvr.; used on mic. and recvr., hdgr., assy., No. 15	single single	C 4270 C 4270
Y1/ZB/M94 0016	GIMBAL, Loudspeaker, re-entrant, No. 1	Comprises 1 arm, fork, supporting, L.S. Ardente No. 1; 1 base, pedestal, No. 1; 2 bolts, special locking, No. 1; 1 bracket, supporting, horizontal, No. 1	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZA 23881 Y1/ZA 23880	GUARD Gauze Copper, M.C., No. 1 Stainless, M.C., No. 1	3.1/4 in. dia.; used on mic., M.C., No. 1 100 mesh 12 mesh	single single	C 4270 C 4270
Y1/ZA 23879 Y1/ZB 12979	HANDLE Microphone M.C., No. 1 No. 1	Metal handle for holding mic., M.C., No. 1 5 in. long x 1/2 in. dia., M.S. handle fitted with 2 semi-circular M.S. clips for securing mic.; used with ampfr., port., P.A., No. 1, Mk. 3, kit, No. 2	single single	C 4270
Y1/ZA 24510	Microphone, hand, No. 7	6.1/2 in. x 2.5/8 in. x 1in.; plastic moulding fitted with pressel switch lever, and contact springs; used on mic., hand, No. 7	single	C 4270
*Y1/5965-99-901-2048	HANDSET 4 pole, No. 3C	With switch; with 6 ft. lg. cord, terminated with plug type M4, br, 1/0; used on tel. set, bridging	single	
Y1/5965-99-901-3112	6 pole	With switch; with 4 ft. 6 in. lg. cord, terminated with plug type M4, br.; used on wireless set C 41 (Old Cat. No. Y1/YA 9307)	single	

*Y1/5965-99-901-1503	Redifon	Drq.A6257/S edition A;used on transmitter-receiver, radio, A43R, Mk. 1	single	
Y1/5965-99-901-3290	W/switch,No.3B	W/12 ft. lg, cord; w/o terminations; used on tele. hand tank mtg., self winding drum and switch assy. (Old Cat. No. Y1/YA 9308)	single	
	HEAD-BAND			
Y1/YA 2280	C, Mk. 4	2 metal bands, folding from centre; has 1 adjustable pivot piece with 2 screws for securing 1 recvr., watch, C, L.R.; for use with recvr., hdgr., C, L.R., single, Mk. 4	single	B 3410
Y1/YA 7714	No. 6	G.P.O. patt; perforated steel band; for recvr., hdgr., No. 10A	single	C 4270
	Web			
Y1/YA 5000	No. 3	Web, drab, twill, 3 in. wide x 6.3/4 in. long, through which is passed a 1 in. wide web head band; adjustable for length by means of 2 M.S. slides; used on recvr., hdgr., double	single	C 4270
Y1/YA 7924	No. 4, Mk. 2	Elastic, double ply, 1 in. wide x 8 in. long to which is sewn at each end 1 in. wide khaki webbing; one end adjustable for length; used on recvr., hdgr., C, H.R., double, No. 9 and 9A	single	C 4270
Y1/5065-99-940-1181	No. 5	2 lengths of 3/4 in.web, drab,13 in.and 10.1/2 in. long stitched together to form a "D"; adjustable used on mic. and recvr., hdgr, assy., No. 11	single	C 4270,C 8181
Y1/YA 7986	No. 7	Web, drab, drill, 3/4 in. wide x 4 ft. long to which is stitched a 13.1/2 in. loop; used on recvr., hdgr., D, L.R., No. 5, single	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/5965-99-940-0046	HEADSET, Electrical I.T.E., No. 1B	Comprises 1 con. double, No. 19; 1 cord, con., No. 15; 2 recvrs., watch, I.T.E., No. 1; headband, web, No. 5; 1 neckband, metal, No. 4; 1 cover, No. 1, recvr., watch, I.T.E.; 1 cover, No. 2, recvr., watch, I.T.E. (This item was previously known as receiver, headgear, I.T.E., double, No. 1B)	single	C 8181
*Y1/5965-99-901-2007	2 magnetic earphones Terminated with Painton plug No. 500208	Comprises 2 earphones, magnetic terminals, headset type YA 11439 (BK 10559); 1 neck band, metal, No. 2 (BK 2597); 1 headband, web, No. 3 (BK 10076); 1 cord, con., double, No. 24, I.T.B. 146113, BK 9500; 1 plug, 8 pole, free, polarised, straight entry, No. 1 (Z1/5935-99-940-2281) (Painton plug No. 500208); 1 cord con., double, No. 17 (P. No. 46412, BK 9500); used on wireless set, C43, CSL/104/2	single	
*Y1/5965-99-901-2324	Terminated with P.O. plug, No. 201	Used on wireless set, B44, Mks. 1 and 2 (This item was previously known as receiver, headgear, I.T.E., double, No. 2, Y1/YA 8600)	single	



*Y1/5965-99-901-1502	HEADSET, Microphone	Two electromagnetic earphones; carbon type mic.; plug type con.; used on trans-rec. radio, A43R, Mk. 1	single	
	HOLDER			
*Y1/5965-99-943-9279	Loudspeaker, 3.1/4 in.	Moulded rubber, used on L.S., P.M., 9 ohms, 3.1/4 in. (Old Cat. No. Y1/YA 9686)	single	
Y1/ZA 5371/3	Microphone, hand No. 3	6.1/2 in. x 2.9/16 in. x 31/32 in.; plastic, part of mic., hand, No. 3	single	C 4270
Y1/ZA 5406/1	No. 3A	6.1/2 in. x 2.9/16 in. x 31/32 in.; similar to No. 3 but with hole tapped No. 6 B.A. for fixing strap hook; part of mic., hand, No. 3A	single	C 4270
Y1/ZA 5470/1	No. 3B	Similar to No. 3 but engraved Mic., hand, No. 3B	single	C 4270
Y1/ZA 5418/1	No. 3C	Similar to No. 3 but engraved Mic., hand, No. 3C	single	C 4270
Y1/ZA 17204	No. 4	Similar to No. 3 but engraved Mic., hand, No. 4	single	C 4270
Y1/ZA 17205	No. 4A	Similar to No. 3 but engraved Mic., hand, No. 4A	single	C 4270
Y1/ZA 17537	No. 8	Similar to No. 3 but engraved Mic., hand, No. 8	single	C 4270
Y1/ZA 33500	Microphone, No. 1	2.1/2 in. long x 1.1/8 in. dia. 3 way socket for securing mic. to stand; used on mic., S.T.C., type 4021C	single	C 4270
	HOOK			
Y1/YA 2810/1	No. 1	1.1/2 in. x 1/2 in. x 1/8 in. Br.; for suspending mic. on control unit. Part of mic., hand, power, No. 1, Mk. 1 and Mk. 2	single	C 4270
Y1/YA 3207	No. 1A	1.1/2 in. x 1/2 in. x 1/8 in. Br.; for suspending mic. on turret of tank. Part of mic., hand, power No. 1A	single	C 4270
Y1/ZA 5428/2	Swivel, loop, No. 2	Used on mic., hand., No. 3A, B and C	single	C 4270
	HORN			
Y1/YA 5778	Deflecting, No. 1	5 in. dia. x 5 in. deep, Cpr., with centre fixing hole; part of tel., L.S., No. 5	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS. HANDSETS. MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	HORN - continued			
	Inner, L.S.			
Y1/ZB/M94 0017	Re-entrant, No. 1	Used on L.S., re-entrant, 15 ohms, No. 1	single	C 4270
Y1/ZB 11310	Re-entrant, No. 2	Used on L.S., re-entrant, 15 ohms, No. 2A	single	C 4270
Y1/YA 2804/1	Telephone, No. 2	7.5/16 in. dia. x 2 in. deep, Cpr., with 3 fixing holes 9/32 in. dia.; part of L.S., tel., No. 2	single	C 4270
	Outer, L.S., re-entrant			
Y1/ZB/M94 0018	No. 1	Used on L.S., re-entrant, 15 ohms, No. 1	single	C 4270
Y1/ZB 11311	No. 2	Used on L.S., re-entrant, 15 ohms, No. 2A	single	C 4270
Y1/ZB 11312	Spinning, No. 1	Used on L.S., re-entrant, 15 ohms, No. 2A	single	C 4270
	INDICATOR			
	M.R., No. 3			
Y1/YA 6394	N.P. or white	Mechanically restored; shutter finished white inside and black outside with white celastoid label; resis. 1,000 ohms.	single	B 8783
Y1/YA 7467	M.R., No. 4	Mechanically restored; fitted with white celastoid label; resis. 1,000 ohms.	single	C 4270
Y1/YA 7435	M.R., No. 4A	Similar to indicator, M.R., No. 4 but inside of label holder painted with luminous paint and label made of transparent plastic; used on swbd., mag., 10 line, W.D.	single	C 4270
Y1/YA 0780	No. 2200, A	G.P.O. patt.; 500 ohms x 500 ohms.gravity armature type; used on various sig. apps.	single	A 2218,B 8030

Y1/YA 6878	No. 2210, A0	G.P.O. patt.; consists of 10 indicators, No. 2200, A fitted on mtg. No. 05/10B	single	C 4270
Y1/YA 6347	No. 2800, C, W.D.	Similar to G.P.O. patt.; 1,000 ohms + 1,000 ohms, disc sig. with local contacts; includes 1 glass, No. 21 and 1 cover; used on swbds., command	single	C 4270
Y1/YA 11397	No. 2800, dummy	G.P.O. store; for spare positions in lieu of indicator, No. 2800, C, W.D., (Y1/YA 6347) on mounting No. 130/10A (Y1/YA 6458)	single	C 9519
Y1/YA 5796	No. 4000, A	G.P.O. patt.; 500 ohms. + 500 ohms. drum armature with drop shutter for use on auto. and C.B.P.B.X. swbds. (does not respond to dialling impulses); includes 1 label No. 59, white; 1 shutter, indicator, No. 4000 A	single	C 4270
INSET				
Y1/YA 5054	Carbon, differential, No. 1	Siemens type 500 D.B. low resis.; 20 ohms. using granules, No. 4; used on mic., hand, No. 9 and No. 12	single	C 4270
Y1/YA 2815	Microphone, hand, power, No. 1	Differential multi-electrode; br. body with moulded front cover, 2.3/4 in. dia. x 1.1/8 in. deep; used on mic., hand, power, No. 1A	single	B 5584, C 4270
Y1/ZA 11383	Microphone, moving coil No. 1	1.3/4 in. x 1.1/8 in.; used on mic., hand, No. 7	single	C 4270
Y1/ZA 17602	No. 2	2 in. dia. x 1 in.; used on mic., hand, No. 13	single	C 4270
Y1/YA 5275	Telephone, balanced armature, No. 5	2 in. dia. x 1 in. deep; mazak mtg. plate; AF. diaphragm; inset for tel., hand (Sound P)	single	C 4270
Y1/YA 7588	Telephone, balanced armature, No. 5, H.R.	Similar to I.T.E.A., No. 5 but fitted with high resis. coil; used on recvr., hdgr., D, H.R. double, No. 5	single	C 4270
Y1/YA 6806	Telephone, equalized, No. 1	Differential tel. inset; for use as a recvr. or mic. 1 in. dia. with 4 terminal plates on rear; used on recvr., watch, I.T.E., No. 1; recvr., hdgr., I.T.E., double, No. 1; mics., hand (I.T.E.), No. 17 and 18	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/5965-99-940-1182	INSET Telephone, equalized, No. 1 - continued Mk. 2	Modified version of I.T.E. No. 1 with 3 terminal plates	single	C 4270, C 8181
Y1/ZA 23547	LEG, Base, stand, No. 1	Metal legs of tripod stand for mic., M.C., No. 1	single	C 4270
Y1/ZA 10042	LEVER Microphone pressel switch, No. 1	Plastic moulding, pivoted by 1 screw, br., B.A., ch. hd. No. 6 x 11/16 in.	single	
Y1/ZA 27794	Switch, pressel, mic., hand, No. 13	1 in. x 7/8 in. x 9/16 in.; plastic moulding, "T" shape with serrated edge	single	
Y1/YA 4711	LID Microphone compartment, control unit, No. 2	9.3/16 in. x 3.7/16 in.; br. with 2 hinges secured on rear edge, and diagrams reproduced on each face of the lid; used on tel., L.S., No. 2, control units, Mk. 1 and Mk. 1/1	single	C 4270
Y1/YA 6444	Mk. 2	Similar to lid, mic. compartment, control unit No. 2 but with different diagram reproduced on one face	single	C 4270

LOUDSPEAKER			
Y1/ZB 13037	E.M., 5 in., 1,200 ohms, No. 1	5 in. dia. x 2.1/2 in. wt. 1.3/4 lb.; speech coil impedance 2 ohms. at 400 c/s; field resis. 1,200 ohms.; used on reception set P.C.R. 201 (Sec. Z1)	single C 4270
Y1/ZB 10706	No. 4, Mk. 2	3.1/2 in. x 3.1/2 in. x 2.3/16 in.; speech coil impedance 15 ohms. at 400 c/s; used on recorder, with playback, wire, No. 1	single C 4270
Y1/ZB 0574	No. 8	6.1/2 in. dia. x 2.3/4 in.; speech coil, 1 in. dia., 2.4 ohms. impedance; used on reception set, R.208 (Sec. Z1)	single C 4270
Y1/ZB 0575	No. 9	8 in. dia. x 4.1/4 in. wt. 4 lb., speech coil impedance 2.6 ohms. at 400 c/s; used on recvr., broadcast, type A, No. 1, type B, No. 2	single C 4270
P.M.			
*Y1/YA 12909	2.1/2 in., 3 ohms	Voice coil impedance 15 ohms.; 2.1/2 in. dia. x 1.5/16 in. deep; Electro Acoustic Industries type 2P	single
*Y1/5965-99-972-9307 Y1/YA 8439	2.1/2 in., 2.4 watts 3 in., 3.2 ohms, No. 1	3 ohms. voice coil Speech coil impedance 4 ohms. at 1,000 c/s, size 3.1/2 in. x 3.1/2 in. x 2 in.	single single C 5687
Y1/ZB 12855	3 in., 10 ohms, No. 1	3.1/4 in. dia. used on reception set, R209 (Sec. Z1)	single C 4270
*Y1/5965-99-943-9280	3.1/4 in. 9 ohms.	Voice coil impedance 9 ohms.; 3.1/4 in. dia. x 1.3/4 in. long (Old Cat. No. Y1/YA 9684)	single
Y1/YA 8515	4 in., 3 ohms, No. 1	Speech coil impedance 3 ohms. size 4 in. x 4 in. x 2.1/8 in.	single C 5687
Y1/YA 8481	5 in., 3 ohms, No. 1	Speech coil impedance 3 ohms., size 5 in. dia. x 2.3/4 in.	single C 5687
Y1/YA 8502	5 in., 3 ohms, No. 2	Speech coil impedance 3 ohms., size 5 in. dia. x 2.3/8 in.	single C 5687
Y1/YA 8739	5 in., 3 ohms, No. 4	Speech coil impedance 3 ohms., size 5.1/16 in. dia. x 2.13/32 in. deep, fully tropical	single C 5687

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	LOUDSPEAKER P.M. - continued			
Y1/ZB 13185	46 ohms, mounted, No. 1	8.3/4 in. dia. x 4 in.; L.S. fitted into metal case, with connector terminating in 2-point plug; used on training sets, universal wireless, No. 1, Mk. 1 and Mk. 2 (Sec. Z1)	single	C 4270
Y1/ZB 12871	7,000 ohms, No. 1	Speech coil 3 ohms. impedance; fitted xform. used on recvr., broadcast, type E, No. 1 (Sec. Z1)	single	C 4270
Y1/ZB 12745	No. 1	6.5/8 in. dia. x 3 in.; wt. 2 lb.; speech coil 2.6 ohms. impedance; used on L.S., 600 ohms.	single	C 4270
Y1/ZB 12617	6.1/2 in., 5,000 ohms,	6.1/2 in. dia. x 3 in.; speech coil 2.0 ohms. impedance; output xform. ratio 50:1; used on wavemeter, standard, No. 2 (Sec. Z4)	single	C 4270
*Y1/5965-99-901-2219	8 in. 3 ohms	Voice coil impedance 3 ohms, 5 watts peak; size 8 in. dia.; Electro Acoustic Industries type 8C/155	single	
Y1/ZB 13029	5 ohms, No. 1	8 in. dia. x 3.1/2 in.; speech coil 5 ohms. impedance; used on ampfr., monitoring, broadcast, 3 watt, No. 1 (Sec. Z1)	single	C 4270
Y1/ZB 13438	10 in., 2.5 ohms, No. 1	10.1/4 in. dia. x 4.5/8 in.; resist. 2.5 ohms. no xform. fitted	single	C 4270
Y1/ZB 12834	12 in., 15 ohms, No. 1	12 in. dia.; triple cone; speech coil 15 ohms impedance; used by Army Broadcasting Services	single	C 4270

Y1/ZB 12917	Protection type, 2,000 ohms, No. 1	19.1/2 in. x 12.1/2 in. x 12.1/2 in. wt. 15 lb.; metal diaphragm, speech coil impedance 8 ohms.; includes xform.; has re-entrant horn with a square section flare; xform. ratio 17:1; used on app. L.S., No. 9 kit, No. 1	single	C 4270
	Re-entrant			
*Y1/YA 10559	15 ohms No. 1	12 in.; used on app., L.S., No. 16	single	
Y1/ZB 11178	No. 2	7 in. x 7 in. x 7.1/2 in.; wt. 12 lb.; moulded re-entrant horn; paper diaphragm; speech coil impedance 15 ohms.; fitted with carrying handle, 4 ft. cable and plug	single	C 4270
Y1/ZB 11318	500 ohms, No. 1A	14.3/4 in. dia. x 15.5/8 in.; wt. 25.1/2 lb.; speech coil impedance 15 ohms.; metal re-entrant horn; metal diaphragm; fitted with "U" shaped mtg. bracket, single-horn fixing; xform. ratio 5:8:1; used on app., L.S., No. 2, complete station, No. 1	single	C 4270
	Telephone			
Y1/YA 2797	No. 1, mounted	Co-axial patt.; consisting of L.S., tel., No. 1, suspended in M.S. gimbal mounted on tripod; height overall 12 in.; used on tel., L.S., No. 1, set	single	B 4106, C 4210
Y1/YA 2804	No. 2, mounted	Consists of L.S., tel., No. 2, unmounted; cases, L.S. tel. No. 2; switches, L.S., No. 1; panel ass. and terminal panel ass.; part of tel., L.S., No. 2, set	single	C 4270
Y1/YA 7352	No. 2, mounted, Mk. 1/1	Modified version of L.S., tel., No. 2, mounted, to incorporate facilities for jacking in recvr. hdgr.; used on tel., L.S., No. 2 (Heavy A.A.)	single	C 4270
Y1/YA 4926	No. 4	14.1/2 in. x 8 in. x 6.1/4 in.; horn type, flare opening 7.1/4 in. x 6 in.; includes I.F.B.A. No. 5; used with tel., L.S., No. 4, set	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 11449	LOUDSPEAKER ASSEMBLY, 60W, M.I.M.C.O., type 2293A	L.S., containing 6 pressure units; complete with line matching xform., cymbal bracket and spigot mtg.	single	C 9519
Y1/ZA 15843	MICROPHONE AND RECEIVER HEADGEAR ASSEMBLY No. 6	Consists of 2 recvrs., watch, D, L.R., No. 5; headband, web No. 3; neckband, metal, No. 2; mic., hand, No. 9A; cord, tel., hdgr., double, No. 3; plug No. 406	single	C 4270
Y1/ZA 17604	No. 9	Consists of 2 recvrs., watch, J; headband, web No. 3; neckband, metal, No. 3; cord, mic. and recvr., No. 9; plug, 5 point, No. 5 (Sec. Z1); mic., hand power, No. 1A w/o cord	single	C 4270
Y1/ZA 21514	No. 10	Consists of 2 recvrs., watch, J; mic., hand, No. 13; headband, web, No. 3; neckband, metal No. 3; cord, mic. and recvr., No. 10; 2 cords, con. mic. and recvrs., No. 10 (I.L. 11684)	single	C 4270
Y1/ZA 25221	No. 11	Consists of 2 recvrs., watch, I.T.E., No. 1; mic., hand, No. 18; headband, web, No. 5; neckband, metal, No. 4; moulded 3 pin plug (I.L. 2977)	single	C 4270
Y1/ZA 26519	No. 12	Consists of recvr., hdgr., D, L.R., double, No. 5E; mic., throat, low level, No. 2B; 3 pin plug	single	C 4270



Y1/ZA 27661	No. 14	Consists of recvr., hdgr., I.T.E., double, No. 1A; mic., throat low level, No. 2B; 3 pin plug moulded to recvr. lead (I.L. 2977)	single	C 4270
Y1/ZA 32998	No. 15	Consists of recvr., watch, I.T.E., No. 1; mic. capsule, miniature, No. 1; headband, web, No. 3; used on wireless set, No. 88 (Sec. Z1) (I.L. 3034)	single	C 4270
Y1/ZA 34167	No. 16A	Consists of 2 recvrs., watch, I.T.E.; headband, web, No. 5; neckband, metal, No. 4; mic., hand, with mic. capsule, miniature, No. 1; used on wireless set, No. 31 (Sec. Z1) (I.L. 5563)	single	C 4270
*Y1/YA 12145	S.I., No. 2B	Used on piers, panel HGB davit, MEXE project No. E/B18	single	
<b>MICROPHONE</b>				
Y1/YA 2308	Capsule Mk. 5	For use in tel. transmitters 2.9/32 in. dia. x 1.1/16 in. deep; immersed electrode, carbon granule type; modified internally for use with anti-gas respirators; red bands are painted on granule chamber and diaphragm guard; includes a rubber washer; used with mic., respirator, No. 1 and No. 2	single	B 2344, B 5585
Y1/YA 8123	Miniature, No. 1	1.3/32 in. x 1.5/16 in.; carbon granules; used on W.S. 88B, tel., hand, No. 11 and mic., hand, No. 20	single	C 4270
Y1/YA 7873	No. 9	Carbon granule type, immersion proof version of the Mk. 4	single	C 4270
Y1/YA 7982	No. 10	Waterproof; immersed electrode, carbon granule type; used on tel. set, J	single	C 4270
*Y1/YA 12141	Dynamic Hand type, 25 ohms, Vitavox CN 172	Push to talk type; for forces Broadcasting Services	single	

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	MICROPHONE			
	Dynamic			
	Hand type, 25 ohms, Vitavox - continued			
Y1/YA 11451	CN 174	Push to talk type; used on public address sets MIMCO type 2258 B, edition A	single	
*Y1/YA 12037	S.T.C. type 4021-J	For Forces Broadcasting Services	single	
	Hand			
Y1/ZA 5428	Loop, No. 2	38.1/2 in. x 3/4 in. wide; web; fitted with swivelled spring catch, br. buckle and 2 br. tips; used on mic., hand, Nos. 3A and 3C	single	B 3093, C 4270
Y1/ZA 5374	Mouthpiece	1.9/16 in. dia. x 2.1/4 in. x 5/64 in. thick; rubber; horn shaped; used on mic., hand, Nos. 9 and 9A	single	B 3093, C 4270
Y1/ZA 5371	No. 3	Plastic moulding; handle fitted with mic., capsule, No. 10; pressel switch; cord, mic., hand, No. 3; plug single, No. 10 (Sec. Z1) (I.L. 2316)	single	B 1330, C 4270
Y1/ZA 5406	No. 3A	Similar to No. 3 but fitted with capsule, mic., R.T., No. 1; cord, mic., hand, No. 3A; mic., hand, loop, No. 2 (I.L. 2316)	single	B 3093, C 4270
Y1/ZA 5470	No. 3B	Similar to No. 3 but fitted with capsule, mic., R.T., No. 1; cord, No. 3B; plug, No. 301, red (I.L. 2316)	single	C 4270

Y1/ZA 5418	No. 3C	Similar to No. 3 but fitted with cord, mic., hand, No. 3C (I.L. 2316)	single	B 4117, C 4270
Y1/ZA 5313	No. 4	Plastic moulding; handle fitted with pressel switch, mic., capsule, No. 10; cord, mic., hand, No. 4; socket, 4 point, No. 7 (Sec. Z1) (I.L. 2495)	single	B 5586, C 4270
Y1/ZA 12841	No. 4A	Similar to No. 4 but fitted with cord, mic., hand, No. 4A (I.L. 2495)	single	C 4270
Y1/ZA 2902	No. 7	Similar to No. 3 but fitted with inset, mic., M.C., No. 1 and pressel switch has 2 make contacts (I.L. 2623)	single	C 4270
Y1/ZA 26797	No. 7A	Similar to No. 7 but fitted with socket, single type, Air Ministry No. 520 and socket, 4 point, No. 7 (Sec. Z1)	single	C 4270
Y1/ZA 13859	No. 8	Similar to No. 4 but with different springs; with 1 socket, 4 point, No. 7 (Sec. Z1) (I.L. 2495)	single	C 4270
Y1/ZA 17208	No. 9, without inset and cord	Includes pressel handle; cover; mouthpiece; and contacts	single	C 4270
Y1/ZA 26695	No. 9A	Similar to No. 9 but fitted with 1 cord, mic., hand, No. 9A	single	C 4270
Y1/ZB/M54 0004	No. 10	Metal case with 1 switch, on-off, S.P., No. 2 (Sec. Z1); 1 inset, mic., hand, No. 10; with 33 ft. cord. electric, U.N., 3 core, low, .001 (Sec. Y3) and 1 plug, 3 point, No. 13 (Sec. Z1)	single	C 4270
Y1/ZA 21270	No. 10A	Similar to No. 10 but with lead 15 ft. long	single	C 4270
Y1/ZA 17605	No. 13	Plastic moulding hand mic. with 1 inset. mic., moving coil, No. 2	single	C 4270
Y1/YA 8599	No. 13B	Similar to No. 13 but fitted with 4 ft. 6 in. of 4 core screened cable (leads, hand, No. 13B (N.I.V.))	single	C 8181
Y1/ZA 24791	No. 16	Similar to No. 4 but with P.V.C. lead and mic., capsule, No. 7	single	C 4270
Y1/ZA 32986	No. 16A	Similar to No. 16 but with mic., capsule, No. 10	single	C 4270
Y1/ZA 31704	I.T.E., No. 19	Used on recorder, with playback wire, No. 1	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	MICROPHONE Hand - continued			
	Power			
Y1/YA 2810	No. 1, Mk. 1	Metal case with suspension hook and clip for holding down pressel switch; includes 1 con., No. 1; 1 con., No. 2; 1 inset; 1 mouthpiece; 1 plug, 3 way; 1 switch; 1 washer, packing; used on tel., L.S., No. 1, set (I.L. 2367)	single	B 5584
Y1/YA 4154	No. 1, Mk. 2	Similar to mic., hand, power, No. 1, Mk. 1, except that con., No. 1A replaces con. No. 1; used on tel., L.S., No. 1	single	B 5584
Y1/YA 2813	No. 1A	Similar to mic., hand, power, No. 1, Mk. 1 except that con. is replaced by 5 ft. of cord, elec., U.N., 3 core, low, 0.0006 (Sec. Y3) (I.L. 2367)	single	C 4270
Y1/YA 2814	No. 1B	Similar to No. 1A except that length of cord is 6.1/2 ft. (I.L. 2367)	single	C 4270
*Y1/YA 11048	S.I., No. 5 and neck band snatch harness	Commanders mic. for use with wireless control harness, type A	single	
	Hand, moving coil			
	Noise cancelling			
Y1/YA 11450	Type 52/MTH/S	Luotraphone type VC52/MTH/S; without cord and plug	single	C 9519

*Y1/YA 12590	Magnetic, hand type	300 ohms. impedance; 6 ft. cable terminating in 6 pole plug; used on system control box, No. 2 W/Set B70	single	
*Y1/YA 12444	M.C., type 4035-D		single	
*Y1/YA 11333	Minifon recorder, tpl.	Used on minifon model 54	single	
Y1/ZA 5369	Respirator No. 1	Comprises 1 cord, mic., hand, No. 3; 1 mic., capsule, Mk. 5; 1 moulded holder and cover; 1 plug, single, No. 10 (Sec. Z1)	single	C 4270
Y1/YA 2309	No. 2	Comprising moulded holder with contact springs and cover; 2 spring contact plugs to accept sockets, coupling, No. 3 (Sec. Z1); fitted with mic., capsule, Mk. 5; used with various tel. attachments and con., twin, No. 76 and No. 76A (Sec. Z1) in conjunction with respirators, anti-gas (Sec. A2)	single	B 2344, B 5585
Y1/YA 2816	Power No. 1	Power mic., for attaching to respirators, anti-gas (Sec. A2), includes mic., hand, power, inset; used with tel., L.S., No. 2	single	C 4270
*Y1/YA 12132	Ribbon Reslo type RBL/T	Used on recorder, type 3C/FN and YD/B	single	
*Y1/YA 12129	Wright and Weaire RBL/TM	Comprises Reslo type RBL/T mic. (30-50 ohms), complete with Wright and Weaire matching unit built into lead	single	
*Y1/YA 12096	Standard lapel type	Minifon recorder, model 54	single	
Y1/ZA 31287	S.T. and C., type 4021C	Used on ampfrs., port., P.A., No. 1, Mk. 3	single	C 4270
Y1/ZA 27864	Throat, low level No. 2B	Similar to No. 2, Mk. 2 but fitted with a short lead and 2 pin plug	single	C 4270
Y1/ZA 27863	No. 2C	Similar to No. 2B but without plug	single	C 4270
*Y1/YA 12097	Wrist type, Minifon recorder	Minifon model 54	single	

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
*Y1/5965-99-901-1184	MICROPHONE ELEMENT	Used in magnetic type mic.; 1.833 in. dia. .770 in. high, O/A. dim.; 300 ohms. nominal impedance. 200 to 3400 cycles frequency range - 76 db.	single	
Y1/5965-99-901-0204	Carbon type, 30 ohms.	ref IV/dane/sq. cm. (Old Cat. No. Y1/YA 8549) Used on tel., hand (Old Cat. No. Y1/YA 7226)	single	
*Y1/YA 12131 *Y1/YA 12013	MICROPHONE MATCHING UNIT Wright and Weaire Type TU/30/G Type TU/30/GL	Used on recorders type 3C/FN and YD/B	single single	
Y1/ZA 12354 Y1/ZA 12672 Y1/YA 2856	MOUTHPIECE, Microphone No. 2 No. 3 Hand power, No. 1	Moulded rubber Plastic moulding 3.17/32 in. x 1.9/16 in.; soft rubber, moulded, combined mouthpiece and gasket; used on mics., hand, power, No. 1, Mks. 1 and 2, No. 1A and No. 1B	single single single	C 4270 C 4270 B 4016, C 4270
Y1/5965-99-901-0202	Plastic	2.11/16 in. dia. x 2.7/32 in. high (Old Cat. No. Y1/YA 3134); used on tel. hand No. 184	single	C 4270

Y1/YA 5589	NECKBAND Assembly. No. 1	Consists of 24 in. web, drab, 1 in., thin; and metal clip for transmitter breast	single	C 4270
Y1/YA 5098	Metal No. 1	Consists of 13 S.W.G. steel wire stirrups and hooks; for use on recvr. hdgr.	single	C 4270
Y1/YA 5001	No. 2	Spring steel wire No. 13 S.W.G. neckband and stirrup secured by M.S. clip	single	C 4270
Y1/YA 5099	No. 3	Spring steel wire No. 13 S.W.G. neckband and stirrup secured by tin plate clip	single	C 4270
Y1/5965-99-940-1183	No. 4	Spring steel wire No. 13 S.W.G. neckband and stirrup secured by M.S. clip	single	C 4270, C 8181
Y1/ZA 17551	No. 1 L.H.		single	
Y1/ZA 17550	R.H.		single	
Y1/ZA 23546	NUT, Locking, 5/16 in. Whit., special, No. 1	For locking legs on stand, mic., M.C., No. 1	single	C 4270
Y1/ZA 25313	PAD Ear, receiver, watch, J	3.13/16 in. x 3.3/16 in. x 15/16 in. (elliptical); soft rubber	single	C 4270
Y1/YA 8220	Ear, rubber, No. 2	2.406 in. dia. x .609 in.; used on mic. and recvr. hdgr. assy., No. 15 and No. 16A	single	C 4270
Y1/YA 7715	Headgear, receiver, No. 3	1.3/4 in. dia. shallow cup with leather diaphragm, G.P.O. patt. for single hdgr. recvr.	single	C 4270
Y1/ZA 24512	PIN Buffer 11/64 in., Micro., No. 7	.089 in. dia.; br.; used on mic., hand, No. 7	doz.	C 4270
Y1/ZA 24513	3/16 in., Micro., No. 7		doz.	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/ZB/M94 0020	PLATE Back, deflector, sound, No. 1	With gasket, rubber, 6.3/4 in. x 1/16 in.; used on L.S., re-entrant, 500 ohms, No. 1A	single	C 4270
Y1/YA 2196/5	Clamp, for springs, contact	1.3/8 in. x 11/16 in. x 5/16 in.; plastic; used on transmitter, breast, No. 1 and tel. attachment, hdgr., double, Mk. 3	single	C 4270
Y1/ZB/M94 0021	Front fixing, unit, energising, No. 1 mounting	Used on L.S., re-entrant, 500 ohms, No. 1A	single	C 4270
Y1/ZB 12980	L.S., re-entrant, 500 ohms, No. 1A	Used on ampfr., port., P.A., No. 1, Mk. 3, kit, No. 2	single	C 4270
Y1/ZA 10044	PLUNGER, Microphone, pressel switch	.092 in. dia. x 1/4 in.; head dia. 5/32 in. br.; used on mic., hand, Nos. 3, 4 and 8	doz.	C 4270
Y1/ZA 14293	PROTECTOR, Rubber, No. 1	3.1/2 in. x 1.3/4 in. x 5/8 in. x .015 in.; used on mic. and recvr., hdgr. assy, No. 1	single	C 4270
Y1/ZA 18577	RECEIVER, Headgear C, H.R., double No. 2	Comprises 1 cord, tel., hdgr., double, No. 2; 2 recvrs., watch, C. H.R.; 1 head band, web, No. 3; 1 neckband, metal, No. 1	single	C 4270



Y1/ZA 18578	No. 3	Comprises 1 cord, tel., hdgr., double; No. 4; 2 recvrs., watch, C, H.R., 1 headband, web, No. 3; 1 neckband, metal, No. 1; 1 plug, No. 201, red	single	C 4270
Y1/ZA 18579	No. 4	Comprises 1 cord, tel., hdgr., double, No. 2; 2 recvrs., watch, C, H.R., 1 headband, web, No. 3; 1 neckband, metal, No. 1; 1 plug, single, No. 9 (Sec. Z1)	single	C 4270
Y1/ZA 18580	No. 5	Comprises 1 cord, tel., hdgr., double, No. 4; 2 recvrs., watch, C, H.R., 1 headband, web, No. 3; 1 neckband, metal, No. 1; 1 plug, No. 310B, red	single	C 4270
Y1/ZA 18581	No. 6	Comprises 1 cord, tel., hdgr., double, No. 3; 2 recvrs., watch, C, H.R.; 1 headband, web, No. 3; 1 neckband, metal, No. 1; 1 plug single, No. 9 (Sec. Z1)	single	C 4270
Y1/ZA 18582	No. 7	Comprises 1 cord, tel., hdgr., double, No. 2; 2 recvrs., watch, C, H.R.; 1 headband, web, No. 3; 1 neckband, metal, No. 1; 1 plug, 2 point, No. 19 (Sec. Z1)	single	C 4270
Y1/ZA 25219	No. 9	Comprises 1 cord, tel., hdgr., double, No. 11 or No. 13; 2 recvrs., watch, C, H.R., No. 9; 1 headband, web, No. 4 or No. 4, Mk. 2; 1 strap, chin, No. 1 or No. 1, Mk. 2	single	C 4270
Y1/YA 8782	No. 13	Comprises cord, inst., 4/36A, brown, 84 in.; 2 recvrs., watch, C, H.R.; 1 headband, web, No. 3; 1 neckband, metal, No. 1 and 1 plug, No. 406, Mk. 2	single	C 5687
Y1/ZA 18205	C, L.R., double. No. 5	Comprises 1 cord, tel., hdgr., double, No. 3; 2 recvrs., watch, C, L.R.; 1 headband, web, No. 3; 1 neckband, metal, No. 1; 1 plug, single, No. 9 (Sec. Z1)	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	RECEIVER, Headgear C, L.R., double - continued			
Y1/ZA 18204	No. 6	Comprises 1 cord, tel., hdgr., and breast, No. 1; 2 recvrs., watch, C, L.R., 1 headband, web, No. 3; 1 plug No. 406; 1 neckband, metal, No. 1; 1 socket, coupling, No. 3	single	C 4270
Y1/ZA 18203	No. 7	Comprises 1 cord, tel., hdgr., double, No. 4; 2 recvrs., watch, C, L.R.; 1 headband, web, No. 3; 1 neckband, metal, No. 1; 1 plug. No. 201, red	single	C 4270
Y1/ZA 27360	<i>D, H.R., double</i> No. 5	<i>Similar to recur., hdgr., D, L.R., double, No. 5 but fitted with high impedance windings</i>	single	C 4270
Y1/ZA 29475	No. 5B	Comprises 1 cord, tel., hdgr., double, No. 3; 2 recvrs., watch, D, H.R.; 1 headband, web, No. 3; 1 neckband, metal, No. 2	single	C 4270
Y1/ZA 29673	No. 5F	Comprises 1 cord, tel., hdgr., double, No. 4; 2 recvrs., watch, D, H.R.; 1 headband, web, No. 3; 1 neckband, metal, No. 2; 1 plug, No. 201, red	single	C 4270
Y1/ZA 17678	<i>D, L.R., double</i> No. 5A	Comprises 1 cord, tel., hdgr., double, No. 3; 2 recvrs., watch, D, L.R., No. 5; 1 headband, web, No. 3; 1 neckband, metal, No. 2; 1 plug, single, No. 9 (Sec. Z1) (I.L. 5576)	single	C 4270

Y1/ZA 22693	No. 5B	Similar to recur., hdgr., D, L.R., double, No. 5, but without plug, single, No. 9 (Sec. Z1) (I.L. 5576)	single	C 4270
Y1/ZA 22715	No. 5C	Comprises 1 cord, tel., head and breast, No. 1 (6-ft.); 2 recur., watch, D, L.R., No. 5; 1 headband, web, No. 3, 1 neckband, metal, No. 2; 1 socket, coupling, No. 3; 1 plug, No. 406 (I.L. 5576)	single	C 4270
Y1/ZA 24789	No. 5D	Comprises 1 cord, tel., hdgr., double, No. 8; 2 recur., watch, D, L.R., No. 5; 1 headband, web, No. 3, 1 neckband, metal, No. 2; 1 plug, single, No. 9A (Sec. Z1) (I.L. 5576)	single	C 4270
Y1/ZA 29474	No. 5F	Comprises 1 cord, tel., hdgr., double, No. 4; 2 recur., watch, D, L.R., No. 5; 1 headband, web, No. 3; 1 neckband, metal, No. 2; 1 plug, No. 201, red	single	C 4270
Y1/ZA 28658	No. 5L	Comprises 1 cord, con., double, no. 17; 1 con., double, No. 18; 2 recur., watch, D, L.R., No. 5; 1 headband, web, No. 3; 1 neckband, metal, No. 2	single	C 4270
Y1/ZA 32580	No. 5N	Comprises 1 cord, head and breast, No. 1; 2 recur., watch, D, L.R., No. 5; 1 headband, web, No. 3; 1 neckband, metal, No. 2; 1 socket coupling, No. 3; 1 plug, No. 406, Mk. 2	single	C 4270
Y1/ZA 34592	No. 5Q	Similar to recur., hdgr., D, L.R., double, No. 5A but with .0004 $\mu$ F capacitor (Sec. Z) in each earpiece watch, D, L.R., No. 5A; 1 headband, web, No. 7; 1 plate, 1.1/4 in. x 3/4 in. x No. 20 S.W.G.; 1 clamp, slide	single	C 4270
Y1/ZA 31000 Y1/YA 9446	D, L.R., No. 5, single I.T.E., double, No. 3	Comprises 1 cord, con., double, No. 18; 1 recur., Comprises 1 cord, con., double, No. 15; 1 headband, web, No. 5; 1 neckband, metal, No. 4; with 6 ft. of 2 core T.R.S. cable terminated in a 6 way Mk. 4 plug	single single	C 4270 C 8181

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 3319	RECEIVER, Headgear - continued No. 10A	G.P.O. patt., 60 ohms; includes 1 diaphragm, No. 25; 1 earpiece, No. 22; 1 headband, No. 6; 1 pad, hdgr., recvr., No. 3; used on Sec. swbd., C.B., W.D., $\frac{10 + 50}{60}$	single	C 4270
Y1/YA 3067	Double	G.P.O. patt.; 2 recvrs., hdgr., No. 10A fitted with headband, No. 12 complete instead of headband, No. 6 and pad, hdgr., recvr., No. 3	single	C 4270
Y1/ZA 32802	Fitted with plug, No. 404	G.P.O. patt.; 60 ohms each	single	C 4270
Y1/5965-99-901-0725	S.I., double, No. 1A	Large rubber earpads fitted with 2 insets, standard receiver, electro-magnetic, No. 2 (Old Cat. No. Y1/YA 9595) (Sec. X1)	single	C 8181
Y1/YA 5637	RECEIVER, Inset Balanced armatures, No. 5	<i>Moving-iron; low resis. inset with plastic case and earpiece; used on tel., hand</i>	single	B 9551

Y1/YA 1302	No. 1.L. (W.D.)	80 ohms.; similar to G.P.O. type, No. 1.L. but with tpl. finish; fitted with diaphragm, No. 12 and earpiece	single	B 1782
	RECEIVER, Watch			
Y1/ZA 5792	C, H.R.	Comprises plastic recvr. case, earpiece and diaphragm; resis. 2,000 ohms.	single	C 4270
Y1/ZA 29349	No. 9	Comprises plastic recvr., case and earpiece; diaphragm; resis. 2,000 ohms.; used on recvr., hdgr., C, H.R., double, No. 9	single	C 4270
Y1/ZA 5796	C, L.R.	Comprises plastic recvr. case and earpiece; diaphragm; resis. 60 ohms.	single	C 4270
Y1/ZA 28231	D, H.R., No. 5	Comprises plastic recvr. case, earpiece and I.T.B.A., No. 5; impedance 8,000 ohms.	single	C 4270
Y1/ZA 14340	D, L.R. No. 5	<i>Comprises 1 I.T.B.A., No. 5; 1 case, recvr., watch, D, L.R., No. 5; 1 earpiece, recvr., watch, D, L.R., No. 5; 1 ring, clamping</i>	single	C 4270
Y1/ZA 31001	No. 5A	<i>Similar to recvr., watch, D, L.R. No. 5 but with modified earpiece</i>	single	C 4270
Y1/ZA 11335	F	Comprises 1 inset, recvr., watch, F; plastic case and cover; cork washer; ear cushion	single	C 4270
Y1/ZA 25220	I.T.E., No. 1	Comprises 1 I.T.E., No. 1, Mk. 2; 1 case, recvr., I.T.E., No. 1; 1 ring, locking, recvr., I.T.E., No. 1; 1 washer, rubber, I.T.E.	single	C 4270
Y1/ZA 17606	J	Comprises 1 inset, recvr., watch, J; 1 cover; 1 earpad; 1 clip	single	C 4270
Y1/YA 3370	RING, Clamping cover, switch	2 in. O.D. x 1.1/4 in. I.D. x 3/32 in. thick; br. with 3 csk. fixing holes .149 in. dia. used on L.S., tel., No. 2, mounted	single	C 4270
Y1/YA 6811	I.T.B.A., No. 5	2.9/32 in. dia. x 19/32 in.; mazac; screwed ring, dia. of threaded portion 2.067 in. x 24 t.p.i., R.H., Whit. form	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5837	RING, Clamping cover, switch - continued No. 1	3.17/32 in. x 3.5/16 in. x 3/16 in.; Al. alloy; centre hole 2.9/32 in. with 3 fixing holes .15 in. dia.; used on mic., hand, powered	single	C 4270
Y1/5965-99-940-1185	RING, Locking, receiver, I.T.E., No. 1	Br. ring threaded on the outside 24 t.p.i. Whit.	single	C 4270, C 8181
Y1/YA 8214	SHROUD, Metal, No. 1	1.1/4 in. x 1/2 in. x 3/8 in.; M.S., No. 26 S.W.G. · semicircular section T plate; fits over cord, con., "T" branch, No. 1; used on mic. and recvr. hdgr. assy., No. 15	single	C 4270
Y1/YA 3210	SOCKET, Coupling No. 2	1.3/8 in. dia. x 2 in. moulded body and gland nut with 2 sockets 5/32 in. I.D. and I socket .196 in. I.D.; used on mic., hand, power, No. 1A and No. 1B	single	C 4270
Y1/YA 2742	No. 3	1.27/32 in. x 1.1/8 in. x 9/16 in.; moulded body with 2 sockets 11/64 in. dia. on 9/16 in. centres; used with con., twin, No. 76 and 76A (Sec. Z1) and various recvr., hdgr.	single	B 3410, B 5585

Y1/YA 4113

No. 3A

1.27/32 in. x 1.1/2 in. x 9/16 in.; moulded body with 2 sockets .17 in. I.D. on 7/16 in. centres; used on tel. attachment, hdgr., double, H, No. 2; transmitter, breast (sound P.), No. 2, Mk. 2; recvr., hdgr., (sound P), No. 2 and 2A

single C 4270

## SPRING

Centre contact  
Micro., No. 7

Y1/ZA 24514

1.7/32 in. x 3/16 in. x 1/16 in.; Ni. Sil.; used, on mic., hand, No. 7

doz. C 4270

Y1/ZA 5371/4

No. 1

1.3/4 in. x .66 in. x 15/64 in.; phos. B.; used on mic., hand, Nos. 3, 4 and 8

single C 4270

Y1/ZA 5406/2

No. 3A

1.1/16 in. x 3/8 in. x 13/32 in.; phos. B.; used on mic., hand, No. 3

single C 4270

## Contact

Capsule case, No. 3A

Y1/ZA 5406/3

1.5/16 in. x 15/16 in. x 1 in.; phos. B.; used on mic., hand, No. 3

single C 4270

Y1/ZA 27793

Double, microphone,

1.9/16 in. x 1/2 in. x 3/8 in.; phos. B. makes contact with inset, microphone, moving coil, No. 2 and pressel switch

doz. C 4270

## Fixed

L.H., micro, No. 7

Y1/ZA 24515

3/4 in. x 3/8 in. x 3/16 in.; Ni. Sil.; pressel switch operated

doz. C 4270

Y1/ZA 24516

R.H., micro, No. 7

3/4 in. x 5/8 in. x 3/16 in.; Ni. Sil.; pressel switch operated

doz. C 4270

Y1/ZA 27791

L.H., microphone, hand,

1 in. x 7/8 in. x 3/8 in.; phos. B.; pressel switch operated

doz. C 4270

Y1/YA 2196/2

Lower

2.1/4 in. x 1.3/4 in. x 3/4 in.; Ni. Sil.; 3/16 in. x .018 in., gold silver contact at one end and at the other end a Br. insert tapped No. 6 B.A.; used on transmitter, breast, No. 1

single C 4270  
single C 4270

## Moving

L.H., micro, No. 7

Y1/ZA 24518

9/16 in. x 17/32 in. x 1/2 in.; Ni. Sil.; pressel switch operated

single C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	SPRING Contact			
Y1/ZA 24519	Moving - continued R.H. micro., No. 7	9/16 in. x 17/32 in. x 1/2 in.; Ni. Sil.; pressel switch operated	single	C 4270
Y1/ZA 27790	R.H., microphone, hand, No. 13	1 in. x 7/8 in. x 3/8 in.; phos. B.; pressel switch operated	single	C 4270
Y1/ZA 27789	Side, microphone, hand, No. 13	11/16 in. x 29/64 in. x .248 in.; phos. B.; makes contact with side of inset, mic., moving coil, No. 2	doz.	C 4270
Y1/ZA 27792	Single, microphone, hand, No. 13	1/2 in. x 3/8 in. x 5/16 in.; phos. B.; pressel switch operated	doz.	C 4270
Y1/ZA 24517	Lever, micro., No. 7	1.3/4 in. x 7/32 in. x 1/32 in. spring steel	single	C 4270
Y1/ZA 5371/6	Microphone, contact, No. 1	1.3/16 in. x 25/32 in. x 1/4 in.; phos. B.; makes contact with side of mic., capsule	doz.	C 4270
Y1/ZA 17538	Microphone, switch No. 1	1.7/8 in. x 7/8 in. x 5/16 in.; Ni. Sil., semi-circular; used on mic., hand, No. 8	doz.	C 4270
Y1/ZA 17539	No. 2	Ni. Sil.; 1 contact; used on mic., hand, No. 8	doz.	C 4270
Y1/ZA 20052	No. 3	1.7/8 in. x 5/8 in. x 5/16 in.; phos. B.; used on mic., hand, Nos. 3 and 4	doz.	C 4270
Y1/ZA 20053	No. 4	1.7/8 in. x 7/8 in. x 5/16 in.; Ni. Sil.; semi-circular; used on mic., hand, No. 4	doz.	C 4270



Y1/ZA 32242	STAND, microphone Floor type, No. 1	Width of base 9 in.; height 3 ft. 4 in.; extended height 6 ft., chromium plated	single	C 4270
Y1/ZA 31703	Hand, No. 1	Steel stand with clamping nut, used to hold mic., hand, No. 19	single	C 4270
Y1/ZA 5139	Moving coil, No. 1	Comprises 1 tube, base, stand, No. 1; 1 tube, centre, stand, No. 1; 1 tube, top, stand, No. 1; 1 nut, brass, locking, No. 1; 3 legs, base, stand, No. 1; 2 screws, special, locking, No. 2	single	C 4270
Y1/ZA 32243	Table type, No. 1	Base 5 in. dia.; height 14 in. with 5 in. flexible chrome tube fitted with 6 point socket for mic.	single	C 4270
Y1/ZC 15674	STIFFENER, No. 1	5/8 in. x 1/4 in. x No. 22 S.W.G.: Ni. Sil. with .12 in. dia. hole; used on jack, mic., No. 2D	single	C 4270
Y1/YA 8218	STIRRUP, Headband, web	Spring steel, No. 13 S.W.G. bent to semi-circular shape 1.5/32 in. rad. and ends bent back to form a loop of 3/32 in. I.D.; used on mic. and recvr., hdgr., assy., No. 15	single	C 4270
Y1/YA 3209	STRAP, Microphone, hand power, No. 1A	Web, drab, 3/4 in., thin, 3 ft. long; with eyelet at each end; used on mic., hand, power, No. 1A	single	C 4270
Y1/ZA 23882	SIRIP, Gauze, 3/4 in., M.C., No. 1	3/4 in. x 10.1/16 in., 100 mesh; used on mic., M.C., No. 1	single	C 4270
Y1/YA 2384	TAG For cord, telephone headgear	1.3/16 in. x 1.1/8 in. x No. 18 S.W.G.; tough and pliable insulating material; secures cord to receiver	single	C 4270
Y1/YA 6807	Strain cord, No. 1	1.1/4 in. x 3/8 in. x No. 18 S.W.G.; plastic sheet; with steel wire hook and strain ring; used on cords, tel., hdgr.	single	C 4270

## SECTION Y1

## CLASS 5965 - HEADSETS, HANDSETS, MICROPHONES AND SPEAKERS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	TELEPHONE ATTACHMENT, Head-gear, double No. 1			
Y1/YA 5814	Mk. 4	Used on tel. sets and swbds., (I.L. 2461)	single	C 4270
Y1/YA 6401	Mk. 5	Used with various sig. apps. (I.L. 2468)	single	B 9551
Y1/YA 8155	Mk. 5/1	Comprises 1 transmitter, breast, No. 1; with mic., capsule, No. 9 or No. 10; 1 recvr., hdgr., D, L.R., double, No. 5N; 1 case, tel. attachment, hdgr., No. 2; used on tel., terminal equipt., No. 1 (I.L. 5464)	single	C 4270
	UNIT Microphone, throat, low level, No. 2 Mk. 1			
Y1/ZA 19692	Complete	For components, see C.I.E.M.E. list E.S. 730	single	C 4270
Y1/ZA 14311	Incomplete	Includes armatures, mic., throat, low level, No. 2 and covers, latex, No. 1, top	single	C 4270
	Mk. 2 Complete			
Y1/ZA 22721	Complete	For components, see C.I.E.M.E. list E.S. 730	single	C 4270
Y1/ZA 21095	Incomplete	Includes armatures, mic., throat, low level, No. 2 and covers, latex, No. 1, top	single	C 4270
Y1/ZA 25311	Receiver, watch, J	For components, see C.I.E.M.E. list E.S. 1017	single	C 4270

CLASS 5970 - ELECTRICAL INSULATORS AND INSULATING MATERIALS

COVER			
	Insulator, No. 16	2.7/8 in. dia. x 15/16 in.; porcelain or composition screw cap	C 4270
Y1/YA 5604	Black		single
Y1/YA 5605	White		single
INSULATOR			
Y1/YA 7951	Battery box, No. 3	4.29/64 in. x 3.13/64 in. x 1.3/4 in.; box-shaped rubber moulding, 3/64 in. thick, with 2 moulded bushes on the side; used on tel. set, J	single C 4270
Y1/YA 2873/2	Battery, No. 2	4.11/16 in. x 3.7/32 in. x 1/32 in.; S.R.B.P. board; fits inside battery box of tel. set, D, Mk. 5	single C 4270
Y1/YA 2873/4	Battery, No. 3	S.R.B.P. board; fits inside battery box of tel. set, D, Mk. 5	doz. C 4270
Y1/YA 2873/3	Battery, No. 4	4.11/16 in. x 1.21/32 in. x 1/32 in.; S.R.B.P. board; fits inside battery box of tel. set, D, Mk. 5	doz. C 4270
	Bobbin	Porcelain or other approved material; with 1/4 in. circular hole; for temporary teleg. or tel. lines	
Y1/YA 0795	No. 1	1 in. dia. x 1 in. high with 1/4 in. groove	doz. 19257, 25123
Y1/YA 0796	No. 2	1.1/4 in. dia. x 1.1/2 in. high, with 3/8 in. groove	doz. 25123
Y1/YA 3624	Wood	Wood bobbin similar to insulator, bobbin, No. 2 except that groove is 1/2 in. from the top instead of 1/4 in. and csk. hole on top of bobbin is not required; gold-size dipped	doz. C 4270
Y1/YA 7698	Bulb holder, No. 3	3.1 in. x 1 in. x .019 in.; black fibre; used on L.S.D.S.R. projector	single C 4270
Y1/YA 7699	Bulb holder, No. 4	2.5 in. x .807 in. x .019 in.; black fibre; used on L.S.D.S.R. projector	single C 4270

## SECTION Y1

## CLASS 5970 - ELECTRICAL INSULATORS AND INSULATING MATERIALS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	INSULATOR - continued			
	Field			
	Bolt			
Y1/YA 2520	Double, J	M.S. 1/2 in. dia. with washer and 2 nuts; for use with cup, Mk. 4/1	single	B 2913
Y1/YA 0800	Single	G.I., 1/2 in. dia. with nut; for use with cups, Mk. 4 or Mk. 4/1	single	16581, B 2913
	Cup			
Y1/YA 0805	Mk. 4	With cap with metal ring; any approved insulating material which can be used as a substitute for ebonite	single	A 2772, B 2913
Y1/YA 0806	Mk. 4/1	With cap; any approved insulating material which can be used as a substitute for ebonite	single	A 2772, B 2913
Y1/YA 5827	Flat, No. 1	.625 in. x .250 in. x .064 in. S.R.B.P.; used on tel., hand, (sound P) No. 2 and tel., hand, No. 6	single	C 4270
Y1/YA 4194	For socket, contact, 5 pr., No. 1	2.23/32 in. x 7/16 in. x 5/16 in. S.R.B.P. part of socket, contact, 5 pr., No. 1; used on frames, D. and P., 10 wire	single	C 4270
Y1/YA 7402	Hanging, No. 2	2.1/4 in. x 1.15/16 in. x 1.1/2 in.; plastic; split ring type of insulator	single	C 4270

Y1/YA 3443	No. 1	3 in. dia. x 4.11/16 in.; G.P.O. patt.; large; white or brown	single	C 4270
Y1/YA 3332	No. 3	2.3/8 in. dia. x 4 in. G.P.O. patt.; small; 2 groove; white, black or brown	single	C 4270
Y1/YA 3444	No. 4	3.1/2 in. dia. x 4.3/4 in.; G.P.O. patt.; terminal, white or brown	single	C 4270
Y1/YA 5643	No. 5	G.P.O. patt.; large; black unbreakable	single	C 8423
Y1/YA 2570	No. 7	3 in. dia. x 4.11/16 in.; G.P.O. patt.; large, 2 groove; white or brown	single	C 4270
Y1/YA 10781	No. 10	G.P.O. patt.; small side knob, white, black or brown	single	C 8423
Y1/YA 3445	No. 14	3.1/2 in. dia. x 5.1/4 in. G.P.O. patt.; terminal and fuze, white body, black cover	single	C 4270
Y1/YA 0794	No. 16	G.P.O. patt.; small, terminal and leading-in; black for general use; white for use with spindle, No. 7	single	C 4270
Y1/YA 11396	No. 17	G.P.O. store; large terminal and lead-in; for 3/4 in. spindle; white; includes cover for insulator No. 17	single	C 9519
*Y1/5970-99-900-0192	Stand off Bakelite, 1.3/32 in. x 3/8 in. wide Sintered al-oxide, unglazed	RR/A506486; used on equipt., radar, No. 7, Mk. 4	single	
*Y1/5970-99-972-6026	1/2 in. x 11/32 in. W. max. O/A. dim.	8 B.A. stud mtg.	single	
*Y1/5970-99-972-9127	55/64 in. x 7/32 in. W. max. O/A. dim.	6 B.A. stud mtg.	single	
Y1/YA 1388	RING, Insulator, No. 1	G.P.O. patt.; rubber; for 5/8 in. insulator spindle	100	C 4270
Y1/ZA 25230	SLEEVE, Rubber, 5/32 in. I.D. x 9/32 in. O.D. x 1 in.	3/8 in. dia. flange	single	C 4270

## SECTION Y1

## CLASS 5975 - ELECTRICAL HARDWARE AND SUPPLIES

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 4361	ARM Iron, No. 6	G.P.O. patt.; tubular, 44 in. long with fittings to grip 3.1/2 in. to 6 in. poles	single	C 4270
Y1/YA 5267	Multi-airline 15 in.	15 in. x 1.3/8 in. x 1.3/8 in., wood	single	C 4270
Y1/YA 0099	30 in., Mk. 2	30 in. x 1.1/2 in. x 1.1/2 in., oak, for use with poles, multi-airline and pole, tele., wood, 16 ft., octagonal, Mk. 1/1	single	A 3845
Y1/YA 6902	33 in.	33 in. x 1.1/2 in. x 1.1/2 in., oak	single	C 4270
Y1/YA 8392	Steel channel, 82 in.	Channel iron 82 in. long; for use on army pole routes	single	C 5687
Y1/YA 2349	Wood No. 6	48 in. x 2.1/2 in. x 2.1/2 in.; G.P.O. patt.; drilled for 5/8 in. spindle, arm and brace bolt	single	C 4270
Y1/YA 2350	No. 8	48 in. x 3 in. x 2.1/2 in., G.P.O. patt.	single	
Y1/YA 3478	No. 13	78 in. x 3 in. x 2.1/2 in., G.P.O. patt.; drilled for 5/8 in. spindle, arm, combiner, and brace bolts	single	
Y1/YA 3329	No. 17	48 in. x 3 in. x 3 in.; G.P.O. patt.; drilled for 3/4 in. spindle, arm and brace bolts	single	
Y1/YA 3479	No. 23	42 in. x 2.1/2 in. x 2.1/2 in.; G.P.O. patt.; drilled for 5/8 in. spindle, arm and brace bolt	single	

Y1/YA 8348	No. 28	36 in. x 3 in. x 2.1/2 in.; G.P.O. patt. type	single	
Y1/YA 5108	4 way, No. 2	48 in. x 2.1/2 in. x 2.1/2 in.; for use with steel pole, drilled for 5/8 in. spindle	single	C 4270
Y1/YA 5849	4 way, No. 3	42 in. x 2.1/2 in. x 2.1/2 in.; for use with steel pole, drilled for 5/8 in. spindle	single	C 4270
Y1/YA 7586	BAG, Waterproof, carbon protector, No. 14	5.3/8 in. x 2.1/4 in.; plastic; for carrying carbon protector, No. 14	single	C 4270
Y1/YA 10698	BOX, Junction, intercom, No. 2	G.P.O. patt.; for use on house exch. systems; 12 in. x 8 in. x 2.1/2 in.	single	C 8423
Y1/YA 11372	BRACE, Bracket	G.P.O. store; for use with axial cable bracket	single	C 9519
Y1/YA 9126	BRACKET Extension	G.P.O. patt.; converter 4 way arms to 8 way. Comprises 2 plates and 2 washers, galv., No. 16	single	C 5687
Y1/YA 3144	No. 2	Double horizontal light, obtuse angle	single	
Y1/YA 3145	No. 5	Angle single	single	
Y1/YA 3953	No. 6	Chimney corner. Includes adjusting device	single	
Y1/YA 8727	No. 7	Pole, tubular. For wood pole	single	
Y1/YA 9123	No. 9	Terminating type, 19 in.	single	
Y1/YA 8962	No. 10	Tubular, for fascias, etc.	single	
Y1/YA 8351	No. 13	Used on overhead lines	single	
Y1/YA 5602	No. 14	Eaves, bracket for walls	single	
Y1/YA 8448	No. 22	For attaching clamps, drop wire to poles and buildings	single	
Y1/YA 9133	BUSH, Cable ring	G.P.O. patt.; for use with drop wires	single	C 5687

## SECTION Y1

## CLASS 5975 - ELECTRICAL HARDWARE AND SUPPLIES - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0427	CARBON PROTECTOR No. 10	G.P.O. patt.; 1.1/4 in. x 3/8 in. edges not bevelled; fitted with fusible plug; groove in back	single	25652, B 5064
Y1/YA 0428	No. 11	G.P.O. patt.; 1.1/4 in. x 3/8 in., edge of face bevelled; no fusible plug; groove in back	single	25652, B 5064
Y1/YA 3096	No. 14, Mk. 1	G.P.O. patt.; 1.1/4 in. x 3/8 in. x 1/4 in.; cellulose varnish insulation over face and bevels; for use on test frames, D. and P., protectors, H.C., and F.2/2	single	B 5064, B 5748
Y1/YA 6693	No. 14, Mk. 2	Similar to No. 14 but material is a composition of cpr. and carb.; moulded to same size as No. 14; insulating varnish over face and bevels	single	C 4270
Y1/YA 0430	CARRIER Cable pack	Hardwood frame, 14 in. sq. fitted with 4 M.S. pillars, M.S. spindle and cross frame; to carry 4 reels, cable, No. 1, Mk. 2 (Sec. Y3); for horse-pack transport, 2 per horse; without reel, cable, No. 1	single	A 2050
Y1/YA 5863	Cable, pack, side	Metal frame with protruding pin at centre and second but smaller frame with protruding pin, the	single	C 4270



		2 connected by riveted on webbing and 2 web straps with sliding buckles; to carry 1 drum, cable, No. 5 or No. 8 (Sec. Y3); for horse-pack transport		
Y1/YA 5862	Cable, pack, top	Metal framework, with 2 web straps and sliding buckles, to take 1 drum, cable, No. 5 or No. 8; (Sec. Y3) or other equip. as desired for horse-pack transport	single	C 4270
Y1/YA 8354	CHAIN, Jack, pole	G.P.O. patt.; used on jack, pole	single	C 4270
	CLAMP			
Y1/YA 5268	Arm, multi-airline, set	Comprises 1 clamp, M.S. 5.1/2 in. x 1.1/2 in. x 1/4 in.; 2 clamping bolts, 6 in. long, threaded 3/8 in. B.S.W.; fitted with 3 washers and 3 hex. nuts	single	C 4270
Y1/YA 6326	Cable, 1 in.	G.P.O. patt.; for anchoring aerial cable not exceeding 1 in. dia.	single	C 4270
Y1/YA 8447	Drop wire, No. 2	G.P.O. patt.; sig. project store	single	C 5687
Y1/YA 6327	Stay	G.P.O. patt.; 3 bolt; for aerial cable suspension wire only	single	C 4270
	CLIP			
Y1/YA 8367	Bonding, No. 1	G.P.O. patt.; used on underground cable jointing	single	C 4270
Y1/YA 9108	No. 7 Pole	1 large and 1 small per set, for poles, teleg., wood, 13 ft.	single	3706, 1576 <sup>1</sup>
Y1/YA 2592	Bolt	Galv. I. 3/8 in. B.S.W. 3.1/8 in. under head, square headed and square shouldered; for clips, pole, small and large	single	
Y1/YA 0450	Large	2 straps and 1 bolt	set	
Y1/YA 2591	Strap	M.I. galv., 4.1/16 in. long	single	
	Lead			
Y1/YA 9135	No. 1	G.P.O. patt.; for securing leads to arms	single	C 5687
Y1/YA 9136	No. 2	G.P.O. patt.; for securing lead and P.C. cable to pole	single	C 5687

## SECTION Y1

## CLASS 5975 - ELECTRICAL HARDWARE AND SUPPLIES - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0451	CLIP Pole - continued Multi-airline	M.I. galv. 2 half clips with square holes; 1 M.S. galv. hex. hd. bolt, nut and washer; for pole, multi-airline and pole, teleg. wood, 16 ft., octagonal	single	25890
Y1/YA 0452 Y1/YA 2590	Small Strap	2 straps and 1 bolt M.I. galv., 3.3/4 in. long	single single	
Y1/YA 3486	CRUTCH, Stay, No. 2	G.P.O. patt.; for 4 way armed poles and 6 way armed "H" poles; includes 3 thimbles, No. 2 (N.I.V.)	single	C 4270
Y1/YA 0535	ELDERPITH	For use by teleg. mechanics	bundle	4590
Y1/YA 3628	FASTENER, Cord, No. 1	G.P.O. patt.; for forked tags; used on various swbds.	100	C 4270
Y1/YA 0684	GUY, Telegraph, pole	White line, 26 ft. long, with eye splice at each end	single	8710, A 6695

Y1/YA 3333	IRON, Terminal, No. 3	G.P.O. patt.; single, for arrs 2.1/2 in. depth	single	C 4270
Y1/YA 0821	JUMPER	2 ft. 9 in. x 2 in.; wt. 27 lb. 10 oz.; steel, octagonal; for poles, teleg, wood	single	5396, C 8635
Y1/YA 11131	JUMPER, Mk. 1/1	2 ft. 9 in. x 2 in.; wt. 27 lb. 10 oz.; steel; with 1 in. hole drilled through the top end to enable a tommy bar to be used	single	C 8635
Y1/YA 1073	MICA, No. 2	1.25 in. x 0.375 in. x 0.004 in.; G.P.O. patt.; used with carbons protector, Nos. 10 and 11 on certain protectors	100	16324, B 5064
Y1/ZA 26641	PANEL, Perforated, M.S., 16.1/2 in. x 13 in.	.0326 in. thick; closely perforated with 5/32 in. dia. hole	single	C 4270
Y1/YA 1112	PEGWOOD	Teleg. mechanics	bundle	4590
Y1/YA 1149	PICKET, Guy, telegraph	15.1/4 oz.; iron; used on teleg. equipt.	single	3312, 25712
Y1/YA 7898	PIN Earth, 6.3/4 in. x 1/2 in. dia.	1/2 in. dia. x 6.1/2 in.; M.S. "L" head with No. 0 B.A. terminal; used on app. C.T. (1 + 1), No. 3 (Sec. Y2)	single	C 4270
Y1/YA 2319	Steel, 7/8 in.	G.P.O., lacquered or tinned, for cleats or clips	lb.	C 4270
Y1/5975-99-943-9506	PLATE Earthing	Steel galv.; 12 in. x 12 in. x 0.08 in. O/A dim.; for telecom. use only; unsuitable for use on power and lighting (Old Cat. No. Y1/YA 9909)	single	
Y1/ZA 27786	Moulded, 1.15/16 in. dia. x 21/32 in.	Plastic	single	C 4270

## SECTION Y1

## CLASS 5975 - ELECTRICAL HARDWARE AND SUPPLIES - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 5751	POST, Picket, multi-airline 2 ft. 6 in.	Wood, octagonal, 2.1/2 in. across the flats; with M.S. wedge shape shoe at end and M.S. ferrule at the other	single	C 4270
Y1/YA 6260	3 ft. 6 in.	Similar to post, picket, multi-airline, 2 ft. 6 in. but 3 ft. 6 in. long	single	C 4270
Y1/YA 6917	Steel, 2 ft. 3 in.		single	C 4270
*Y1/5975-99-901-3020	RACK, Cable, interior	Steel; 6 ft. 4 in. lg. x 6 in. w. x 3 in. h. O/A.	single	
	RING			
	Jumper	G.P.O. patt.		
Y1/YA 7223	No. 1	Int. dimensions 2.1/2 in. dia.	single	C 4270
Y1/YA 3047	No. 3	Int. dimensions 1.1/4 in. dia.	single	C 4270
Y1/YA 7224	No. 4	Int. dimensions 2.1/4 in. x 1.5/8 in.	single	C 4270
Y1/YA 3048	No. 5	Int. dimensions 1.1/4 in. x 1.1/2 in.	single	C 4270
Y1/YA 9222	No. 7	Int. dimensions 2.23/32 in. x 2.5/8 in. sig. project store	single	C 5687
Y1/YA 9223	No. 9	2.1/2 in. dia.	single	C 5687
Y1/YA 7183	No. 10	Int. dimensions 2 in. x 1.1/2 in.	single	C 4270
Y1/YA 5802	No. 12	Int. dimensions 1.13/16 in. dia.	single	C 4270
Y1/YA 7197.	No. 25	Int. dimensions 3.3/8 in. dia.	single	C 4270
Y1/YA 7184	No. 27	Int. dimensions 4.1/8 in. x 2 in.	single	C 4270

*Y1/5975-99-901-0148	ROD, Earthing M.S., galv., 2 ft. x 5 in. x 1 in.	Used on lighting kit 1.1/2 KW.	single	
Y1/5975-99-943-9502	M.S., 3 ft. long x 1.11/32 in. dia. Steel	Old Cat. No. Y1/YA 1155	single	
Y1/5975-99-943-9501	12.3/4 in. x 2.1/4 in. x 1/2 in. O/A. dim	Cone point (Old Cat. No. Y1/YA 1152)	single	
Y1/5975-99-940-2517	2 ft. lg. x 1.1/4 in. w. x 1.1/4 in. h. x 1/8 in. thk.	Used on lighting sets 3 KW. and 10 KW.	single	
Y1/YA 8362 Y1/ZA 25312	SADDLE Galvanized, metal, single 1/4 in., No. 1	G.P.O. patt.; used for overhead lines 15/16 in. x 1/4 in. x 1/4 in.; br.; used on recvr., watch, J	single 100	C 4270 C 4270
Y1/5975-99-940-1515	SPINDLE, Insulator, G.P.O. pattern No. 2	For insulators, No. 14; includes nut and washer (Old Cat. No. Y1/YA 3446)	single	C 4270, C 8424
Y1/5975-99-940-1516	No. 3	Straight 5/8 in.; with woodscrew, for roof ridges, etc. (Old Cat. No. Y1/YA 3691)	single	C 4270, C 8424
Y1/5975-99-940-1517	No. 4	Straight, 5/8 in., small, for wood arms (Old Cat. No. Y1/YA 3147)	single	C 4270, C 8424
Y1/5975-99-940-1518	No. 4A	5/8 in.; for iron arm and bracket (Old Cat. No. Y1/YA 8353)	single	C 4270, C 8424
Y1/5975-99-940-1519	No. 5	Straight, 5/8 in., large, for trunk and junction lines (Old Cat. No. Y1/YA 3148)	single	C 4270, C 8424
Y1/5975-99-940-1520	No. 6	Straight, 3/4 in. terminal, for trunk lines where necessary to terminate on a straight spindle (Old Cat. No. Y1/YA 4251)	single	C 4270, C 8424
Y1/5975-99-940-1521	No. 7A	Double "J" vertical, for leading spur pairs from terminal irons; includes washers, galv., No. 16 (Old Cat. No. Y1/YA 2225)	single	C 4270, C 8424

## SECTION Y1

## CLASS 5975 - ELECTRICAL HARDWARE AND SUPPLIES - continued

Cat No.	Item name or designation	Item description or detail	•	Unit of issue	L. of C. ref.
1	2	3	4	5	
Y1/5975-99-940-1522	SPINDLE, Insulator, G.P.O. pattern - continued No. 8	5/8 in. single "J", for terminating junction, subscriber and trunk lines below 300 lb. per mile (Old Cat. No. Y1/YA 3338)	•	single	C 4270, C 8424
Y1/5975-99-940-1523	No. 10	5/8 in. double "J", 180° (Old Cat. No. Y1/YA 1467)		single	C 4270, C 8424
Y1/5975-99-940-1524	No. 13	5/8 in., "U" cup holder, for inserting crosses on trunk lines (Old Cat. No. Y1/YA 3447)		single	C 4270, C 8424
Y1/5975-99-940-1525	No. 16	Swan neck (Old Cat. No. Y1/YA 5293)		single	C 4270, C 8424
Y1/YA 3339	STEP, Pole	G.P.O. patt., for fixing to wood poles		single	C 4270
Y1/YA 1527	STRAINER, Multi-airline	2 wood bars 1.1/2 in. dia. x 30 in.; each fitted with 3 M.S. galv. eye-bolts and 1 M.S. galv. triangular ring (1 bar fitted with 2 steel galv. stay wires and M.S. galv. hook; 1 bar fitted with 2 M.S. galv. links; 2 M.S. galv. swivels and 2 M.S. galv. snap hooks) and 2 wood bars		single	25890, A 3338
		1.1/2 in. dia. x 18 in. each fitted with 3 M.S. galv. eyebolts; 1 M.S. galv. triangular ring and 2 M.S. galv. snap hooks			

Y1/YA 5854

STRAP, Arm, multi-airline

M.S. galv., 5.1/2 in. x 1.1/2 in. x 1/4 in. Part  
of clamp, arm, multi-airline, set

single C 5130

## CLASS 5977-ELECTRICAL CONTACT BRUSHES AND ELECTRODES

BRUSH

Y1/YA 2881

No. 1

0.1 in. dia. x 0.281 in. long. Carbon, round  
complete with phos. B. helical spring, for use on  
gen. C and gen. No. 26A, W.D.

single B 4389

\*Y1/YA 11304

Minifon recorder

Used on minifon model 54

single

## CLASS 5985-ANTENNAE, WAVEGUIDES, AND RELATED EQUIPMENT

Y1/YA 8355

CHAIR, Ringing

G.P.O. patt.; used when attaching rings to aerial  
cable suspension wire

single C 4270

RING

Y1/YA 2703

Cable

G.P.O. patt.; for suspending aerial cables; galv.

C 4270

Y1/YA 8073

No. 1

2 in.; for 7/12 wire only

single

Y1/WB 2450

No. 2

2 1/2 in.; for 7/10 wire only

single

Y1/YA 8074

No. 3

1.1/2 in.; for 7/14 wire only

single

No. 9

3 in.; for 7/8 wire only

single

## SECTION Y1

## CLASS 5995-CABLE, CORD, AND WIRE ASSEMBLIES; COMMUNICATION EQUIPMENT

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0182	BINDER Cadmium copper, No. 1	12 in. long; 70 lb. cadmium copper; for wire, bronze, 40 lb. (Sec. Y3), or wire, cadmium copper, 40 lb. (Sec. Y3)	100	B 597
Y1/YA 3448	Copper, No. 1	G.P.O. patt.; for 100 lb. wire	100	C 4270
Y1/YA 3449	Copper, No. 2	G.P.O. patt.; for 150 lb. wire	100	C 4270
Y1/YA 5867	Copper, No. 3	G.P.O. patt.; for 200 lb. wire	100	C 4270
Y1/YA 8311	CONNECTOR AND TERMINAL ASSEMBLY, 10 pair, No. 1	2 ft. 7 in. of cable, elec. D3, 5 pair (Sec. Y3) connected to 10 pr. terminal strip	single	C 4270
Y1/ZA 34193	CONNECTOR 2 point, No. 5	6.1/4 in. overall. Cordage, type 2/M black (Sec. Y3); one end terminating in eyelet, the other in 2-way moulded socket; used on tel., hand, No. 14	single	C 4270
Y1/ZA 33338	3 point No. 79	10 ft. of cord, elec., twin, screened, low, .0006 P.V.C. (Sec. Y3); one end connected to plug No. 316 other end to a 3 point socket and handle ass.; used on training set, No. 5A	single	C 4270



Y1/ZA 33313	No. 80	3 ft. 9 in. overall length; cordage, elec., 3 core; one end terminating in 3 point plug which is moulded to cable, other end terminating in eyelet; used on mic. and recvr. hdgr., assy., No. 15	single	C 4270
Y1/ZA 33314	No. 81	6 ft. of cordage, elec., 3 core; one end terminating in 3 point plug which is moulded to cable; used on tel., hand, No. 11	single	C 4270
Y1/ZA 34671	No. 85	9 ft. of cord, elec., U.N., 3 core, .0006 (Sec. Y3); one end terminating in plug, 3 point, No. 7A, other end terminated by a socket, 3 point; used on amp. and playback unit, No. 1	single	C 4270
	5 pair, No. 1	Con.-cable, 15 ft., fitted at each end with a plug, 5 pr. No. 1		B 2912
Y1/YA 2375	Black	Both plugs, 5 pr. No. 1 are black	single	
Y1/YA 2376	Red	Both plugs, 5 pr., No. 1 are red	single	
Y1/YA 2715	Connector-cable 15 ft.	15 ft. of cable, elec., D3, 5 pr (Sec. Y3); with ends prepared to fit plug, 5 pr., No. 1	single	
Y1/YA 2709	5 pair, No. 2	Con.-cable, 15 ft., fitted at each end with a strip, connection, 5 pr., No. 1; for inter-connecting swbds., F. and F., Mk. 1/1 with test frames, 20 pr., Mks. 2 and 3, or 40 pr., Mks. 1 and 2	single	
Y1/YA 2882	Connector-cable, 15 ft.	15 ft. of cable, elec., D3, 5 pr. (Sec. Y3); with both ends prepared to suit strip, con., 5 pr., No. 1	single	B 4959, B 5748
Y1/YA 5568	5 pair, No. 3, black	9 ft. of cable, elec., D3, 5 pr. (Sec. Y3) fitted at one end with plug, 5 pr., No. 1, black, lead at the other end; 4 pr. only; bared and bound; used on wireless set, No. 10 (Sec. Z1)	single	C 4270
Y1/YA 5569	5 pair, No. 3, red	Similar to con. 5 pr., No. 3, black, but fitted with plug, 5 pr., No. 1, red	single	C 4270
Y1/ZA 33875	10 Point No. 10	2 ft. of cord, elec., 8 core, .001 P.V.C. terminating in a plug, 10 point, No. 4; used on training set. No. 5A	single	C 4270

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES; COMMUNICATION EQUIPMENT - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CONNECTOR			
Y1/ZA 34195	10 point - continued No. 11	9.1/2 in. of cable, tencorevin (N.I.V.) terminating in a plug, 10 point, No. 4 (Sec. Z1); used on training set, N o. 4A	single	C 4270
Y1/ZA 22379	26 point No. 1	18.1/4 in. long; screwed breeze socket each end; for connecting pulser to monitor unit on wireless set, No. 10 (Sec. Z1)	single	C 4270
Y1/ZA 22380	No. 2	27.1/4 in. long; with screwed breeze sockets each end; for connecting monitor unit to separator unit on wireless set, No. 10 (Sec. Z1)	single	C 4270
Y1/YA 8102	Battery 5 Point, No. 1	1 ft. 3.1/4 in. of 5 core, 0.0006, V.R. cord with 5 pin plug moulded on; used with amp., field tel., No. 1	single	C 4270
Y1/YA 4661	Black	2.3/8 in. of cord, elec., U.N., single, 0.0048 (Sec. Y3) terminated with tag; used on various tel. sets	single	C 4270
Y1/YA 6761	H.T., No. 1, black	28 in. cord, elec., U.N., single, 0.0006 (Sec. Y3) one end fitted with plug, single, No. 17; used on tel. set, F, high power, No. 1, Mk. 2	single	C 4270

Y1/YA 6760	H.T., No. 1, red	18 in. cord, elec., U.N., single, 0.0006 (Sec. Y3) one end fitted with plug, single, No. 17; used on tel. set, F, high powered, No. 1, Mk. 2	single	C 4270
Y1/YA 6762	H.T., No. 1, yellow	33 in. cord, elec., U.N., single, 0.0006 (Sec. Y3) one end fitted with plug, single, No. 17; used on tel. set, F, high powered, No. 1, Mk. 2	single	C 4270
Y1/YA 6759	L.T., No. 1, black	18 in. cord, elec., U.N. single, 0.0006 (Sec. Y3) one end fitted with plug, single, No. 17; used on tel. set, F, high powered, No. 1, Mk. 2	single	C 4270
Y1/YA 6758	L.T., No. 1, red	15 in. cord, elec., U.N., single, 0.0006 (Sec. Y3) one end fitted with plug, single, No. 17; used on tel. set, F, high powered, No. 1, Mk. 2	single	C 4270
Y1/YA 4660	Red	2.3/8 in. of cord, elec., U.N., single, 0.0048 (Sec. Y3) terminated with tag; used on tel. set, D, Mk. 5	single	C 4270
Y1/YA 6418	Unit, L.S., No. 2	7.1/2 in. of wire, equipt. 14/.0076, 3, C. red or black (Sec. Y3); one end terminating in terminal wire end, No. 1 (Sec. Y3); used on tel. unit, L.S., No. 1	single	C 4270
Y1/ZA 22377	Co-axial No. 10H	4.562 in. long; cable, elec., Uniradio, 1 (Sec. Y3); with sockets, single, No. 11A at each end; connects monitor to separator on wireless set, No. 10 (Sec. Z1)	single	C 4270
Y1/ZA 22378	No. 10J	8.562 in. long; cable, elec., Uniradio, 1 (Sec. Y3); with sockets, single, No. 11A at each end; connects monitor unit to pulser unit on wireless set, No. 10 (Sec. Z1)	single	C 4270
Y1/YA 7084	Coupling, switchboard	4 ft. 6 in. long; 3 core conductor, terminated each end with plug, No. 316, red; used on swbd, position, mag., $\frac{10 + 50}{60}$ No. 1	single	C 4270

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES: COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CONNECTOR - continued			
Y1/YA 6014	Double No. 12	Consists of 1 cord, line con., No. 1 (6 ft.); one end fitted with plug, coupling, No. 4 and socket, coupling, No. 4, the other end finished with loops; used on tel., head and breast (sound P.), complete stations, No. 1	single	C 4270
Y1/YA 6015	No. 13	18 in. of cordage, inst., No. 2/AP (Sec. Y3); one end fitted to black, terminal, No. 18; the other end finished with loop; used on tel., head and breast (sound P.)	single	C 4270
Y1/YA 6909	No. 15	2 ft. 6 in. long; 2 way cong; one end fitted with two 4 B.A. tags and 2 strain cords, the other end stripped back 3/4 in. and soldered; used on swbd., mag., 10 line, W.D.	single	C 4270
Y1/YA 6910	No. 16	3 ft. 2 in. long; twin conductor; one end moulded on to a 2 point plug, the other end fitted with 2 tags and 2 strain cords; used on swbd., mag., 10 line, W.D.	single	C 4270
Y1/YA 7361	No. 17	5 ft. of 3 way cord, terminated at each end by plug, No.-316, Mk. 1, red or black; used on swbd., C.B., multiple, unit type (test equip.)	single	C 4270

Y1/ZA 28661	No. 18	6 ft. 4.1/2 in. of 2 core cable with 2 pin plug moulded on one end and other end with eyelet and cord strain plate; used on recvr., hdgr., D, L.R., double, No. 5L	single	C 4270
Y1/5995-99-940-1186	No. 19	6 ft. long; similar to con., double, No. 18 but without strainplate; used on recvr., hdgr., I.T.E., double, No. 1B (Old Cat. No. Y1/ZA 28662)	single	C 4270, C 8181
Y1/YA 6667	Earth 4 in.	3.1/4 in. of cord, elec., U, single, 0.0048 (Sec. Y3); black; ends terminated by tab, 4 B.A. slot (Sec. Y3); used on test frames, 20 pr., Mk. 3 and 40 pr., Mk. 2	single	C 4270
Y1/YA 6911	No. 2	5 ft. 4 in. of 16/.006 plain cpr. braid, 1/4 in. x .04 in. terminated with 2 B.A. slotted flag tags; used on swbd., mag., 10 line, W.D.	single	C 4270
Y1/ZA 34424	Flexible, 5 point No. 16	8 ft. 9 in. of cord, elec., U.N., 5 core, 0.0006 in. (Sec. Y3); terminated at one end by plug, 5 point, No. 5 and rubber sleeve; other ends bared and bound with B.T.C.; used on tel., hand, moving coil, No. 3	single	C 4270
	Jumper, single No. 1	3 ft. of wire, elec., slip-back, 0.0006, single (Sec. Y3); fitted with 2 plugs, jumper, single, No. 1, black or red; for use with frames, D. and P., 10 wire, Mk. 1/1 sets		B 2172, B 4806
Y1/YA 2726	Black	Both plugs black	single	
Y1/YA 0570	Red	Both plugs red	single	
	Jumper, twin No. 1	3 ft. of wire, elec., slip-back, 0.0006, twin (Sec. Y3); fitted with 2 plugs, jumper, twin, No. 1, black or red; for use with frames, D. and P., 10 wire, Mk. 1/1 sets		B 2172, B 4806

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES: COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 2727 Y1/YA 0571	CONNECTOR Jumper, twin No. 1 - continued Black Red No. 2	Both plugs black Both plugs red 6 ft. 3 in. of twin tinsel cord fitted at each end with a plug, jumper, twin, No. 2; for use with test frames, 20 pr., Mks. 1, 2 and 3; 40 pr., Mks. 1 and 2; 80 pr. and 160 pr.	single single	B 5064, B 5748
Y1/YA 2883 Y1/YA 2884 Y1/YA 3745	Black Red Cord No. 2, TPL	Both plugs black Both plugs red 6 ft. 3 in., twin, braided overall with both ends prepared to fit plug, jumper, twin, No. 2 Similar to No. 2 but cordage to be P.V.C. covered and pin inserts of plugs to be phos. br.	single single single	C 4270
Y1/YA 7864 Y1/YA 7865 Y1/YA 7866	Black Red Cord	Both plugs black Both plugs red 6 ft. 3 in. long	single single single	
Y1/YA 10527	Miniature, 12 point No. 8, 20 ft.	Comprises cable, miniature, No. 12C (Y3/6145-99-910-0032) 1 socket, sealed, M4/Br., free, size 2/0, 12 pole (Z1/ZA 39969); 1 outlet ass., M4/Br., angle, size 2C (Z1/ZA 40379)	single	C 9519

*Y1/YA 11378	No. 8, 35 ft.	Used on truck 3 tons G.S. Bedford R.L., signals, Mk. 2, Signal Centre Medium	single	
Y1/YA 4151	No. 1A	3 ft. of cord, elec., U.N., 3 core, 0.0006 (Sec. Y3) fitted with 1 coupling plug, 3 point, No. 1, Mk. 1 (Sec. X2); and the other end prepared for connection to mic.	single	B 5584, C 4270
Y1/YA 2812	No. 2	6 ft. of cord, elec., U.N., 3 core, 0.0006 (Sec. Y3); fitted with 1 coupling plug, 3 point, No. 1, Mk. 1 (Sec. X2); used with mic. hand, power, No. 1, Mk. 1 and Mk. 2	single	B 5584, C 4270
Y1/ZA 31266	Single No. 147	6 ft. of wire, elec., P.11 (Sec. Y3); fitted at one end with 1 lug, cable, 3/8 in. side slot (Sec. Y3); the other end with 1 No. 2 B.A. spade terminal (Sec. Y3); used on ampfr., port., P.A., No. 1, Mk. 3 and No. 2	single	C 4270
Y1/ZA 31267	No. 148	9 ft. of cord, elec., single, screened, low, 0.0006 (Sec. Y3); one end fitted with plug, single, No. 20 the other end with No. 4 B.A. spade terminal (Sec. Y3); fitted in the con. 9 in. from spade terminal is an attenuator; used on ampfr., port., P.A., No. 1, Mk. 3, kit, No. 1	single	C 4270
Y1/YA 4119	Telephone	3 ft. of wire, elec., Q.11, Mk. 1 (Sec. Y3); with 1 plug, No. 201, black, at one end, the other end looped for connecting to auto. dialling tel. set; used with swbd., U.C., civil line unit	single	B 5750, C 4270
Y1/YA 8146	Test 2 way, No. 1	6 ft. of 2 core cordage fitted at one end with plug, No. 316, red and the other end fitted with 2 tags, 13/32 in., side slot (Sec. Y3); used on rack, tel. terminal, No. 1	single	C 4270

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES: COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CONNECTOR			
Y1/YA 8147	Test - continued 3 way, No. 1	18 in. of 3 core cordage, P.V.C. insulated; fitted at each end with plug, No. 316, red; used with rack, tel. terminal, No. 1	single	C 4270
Y1/YA 7359	No. 4/60, B	8 ft. long, tropically finished cord; one end terminated by 1 red and 1 black plug, No. 222, Mk. 1 engraved "A" and "B", the other end terminated by 1 red and 1 black plug, No. 316, Mk. 1 engraved "external" and "internal"; used on swbd., C.B., multiple, unit type (test equipt.)	single	C 4270
Y1/YA 7360	No. 4/60, E	8 ft. long, tropically finished cord; one end terminated by 1 red and 1 black plug, No. 316, Mk. 1; the other end terminated by a set of clips, test, No. 27, Mk. 1, marked "A" and "B"; used on swbd., C.B., multiple, unit type	single	C 4270
	Test, single No. 1	4 ft. of cordage, inst., No. 1/B; fitted at each end with plug, jumper, single, No. 1; for use with test frames, 20 pr., Mk. 2 and 40 pr., Mk. 1		B 5064, B 5748
Y1/YA 3012	Red	Both plugs red	single	



	No. 2	6 ft. of cordage, inst., No. 1/B; fitted at each end with plug, jumper, single, No. 1; for use with test frames, 20 pr., Mk. 3; 40 pr., Mk. 2; 80 pr. and 160 pr.		B 5064
Y1/YA 3414	Black	Both plugs black	single	
Y1/YA 3602	Red	Both plugs red	single	
	No. 2 "TPL"	Similar to No. 2 but insulation to be P.V.C. and pin inserts of plugs to be phos. B.; for use with test frame, 20 pr., Mk. 3 "TPL" and test frame, 40 pr. Mk. 2 "TPL"		C 4270
Y1/YA 7867	Black	Both plugs black	single	
Y1/YA 7868	Red	Both plugs red	single	
	No. 3	Similar to con., test, single, No. 2, except that length is 2.1/2 ft.		C 4270
Y1/YA 3828	Black	Both plugs black	single	
Y1/YA 3906	Red	Both plugs red	single	
Y1/ZA 26425	Triple, No. 1	3 ft. of 3 core cord with 3 point plug moulded on one end, other end terminating in eyelet; used on mic. and recvr., hdgr. assy., No. 11 and No. 14	single	C 4270
	Twin			
Y1/ZA 10036	No. 76	1 cord, mic., hand, No. 3 fitted with 1 plug, single, No. 10 and 1 socket, coupling, No. 3	single	C 4270
Y1/ZA 10192	No. 76A	1 cord, mic., hand, No. 3A fitted with 1 plug, single, No. 10 and 1 socket, coupling, No. 3	single	C 4270
Y1/YA 7678	No. 283	3 ft. flexible twin cord; one end terminated in loop and the other in tag; used on ampfr., field tel., No. 1	single	C 4270
Y1/ZA 31264	No. 306	30 ft. of cord, elec., U.N., twin, 0.0017 (Sec. Y3 ; ends fitted with No. 4 B.A. spade terminal (Sec. Y3); used on ampfr., port., P.A., No. 1, Mk. 3, kit, No. 2	single	C 4270

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES: COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CONNECTOR			
Y1/ZA 31265	Twin - continued No. 307	30 ft. of cord, elec., U.N., twin, 0.0017 (Sec. Y3); one end fitted with socket, 2 point, No. 5 (Sec. Z1); used on ampfr., port., P.A., No. 1, Mk. 3, kit, No. 2	single	C 4270
Y1/ZA 35210	No. 341	4 ft. 6 in. of cord, elec., U.N., twin, 0.0006 (Sec. Y3); one end terminating in a plug, No. 201, black; used on key and plug assy., No. 21	single	C 4270
	CORD			
Y1/YA 6351	2 core No. 1	Tinsel cord; 3 ft. 6 in. long; one end terminated in No. 6 B.A. lug, the other end bound and tinned; used on wireless, remote control unit, E, Mk. 1 and Mk. 2 (Sec. Z1)	single	C 4270
Y1/YA 5916	No. 2	Tinsel cord; 12 in. long; used on wireless, remote control unit, E, Mk. 1 and Mk. 2 (Sec. Z1)	single	C 4270
Y1/YA 4867	5 core No. 1	Tinsel cord; 9 in. long; used on con., flexible, 5 point, No. 2 (Sec. Z1)	single	C 4270

Y1/YA 6439	No. 2	Tinsel cord; 4 ft. long; used on wireless, remote control unit, E, Mk. 1 and Mk. 2 (Sec. Z1)	single	C 4270
Y1/YA 8235	Connector 3 way, No. 1	3 ft. 9 in. of cordage, inst., 3/M, black; conductor, at one end formed into eyelet to clear No. 8 B.A. screw, other end outer covering removed for 2 in.; used on tel. hand, No. 14	single	C 4270
Y1/ZA 26376	Double No. 14	31 in. of cordage, inst., 2/M; end of conductor formed into eye to clear No. 8 B.A. screw; for use on mic. and recvr., hdgr. assy., No. 11	single	C 4270
Y1/ZA 27859	No. 15	15.1/2 in. of 2 core cord; end of conductor formed into eye to clear No. 8 B.A. screw; for use on recvr., hdgr., I.T.E., double, No. 1	single	C 4270
Y1/ZA 27860	No. 16	6 ft. of 2 core cord; conductor at one end formed into eye to clear No. 8 B.A. screw; used on recvr., hdgr., I.T.E., double, No. 1	single	C 4270
Y1/ZA 28660	No. 17	21.1/2 in. of twin, flat cord, P.V.C. covered; ends of conductor formed into eyes, 1/8 in. dia.; used on recvr., hdgr., D, L.R. double, No. 5L	single	C 4270
Y1/ZA 31002	No. 18	4 ft. 4 in. of cordage, type 2/Q; one end fitted with strain cord 10 in. long and conductor terminated in tag; other end fitted with strain plate, hook and ring; conductor formed into eyelet; used on recvr., hdgr., D, L.R., No. 5, single	single	C 4270
Y1/YA 8020	No. 19	32 in. of cord, elec., U.N., twin, 0.0006 (Sec. Y3) with end terminating in tag; used on ampfr., field tel., No. 1	single	C 4270
Y1/YA 8183	No. 20	7.1/4 in. long; 2 way cord; used on tel., hand, No. 11	single	C 4270
Y1/ZA 24404	Microphone and Receiver, No. 10	27 in. of 2 core cordage; conductor terminated in eyes 1/8 in. dia.; connects recvr. to mic.	single	C 4270

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES; COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of Issue	L. of C. ref.
1	2	3	4	5
	CORD			
Y1/ZA 27861	Connector - continued Quad, No. 1	5 ft. of 4 core cordage; conductor at one end terminated in eye 1/8 in. dia.; covering removed for 1 in. at other end; used on mic., hand, I.T.E., No. 17	single	C 4270
Y1/ZA 33858	"T" Branch, No. 1	17 in. x 3.1/4 in. 5 core cordage; 3 conductors going to right-hand side of "T" and 2 conductors to left-hand side; ends terminating in eyelets to clear No. 8 B.A. screw; used on mic. and recvr., hdgr. assy., No. 15	single	C 4270
Y1/ZA 26806	Triple, No. 2	15.1/2 in. of 3 core cordage; ends of conductor formed into eyes to clear No. 8 B.A. screw; used on recvr., hdgr., I.T.E., No. 1	single	C 4270
Y1/YA 11391	Extensible No. 4/1	G.P.O. store; brown, 21 in. long	single	C 4270
Y1/YA 6017	Headgear, connector,	18.1/2 in. of cordage, inst., No. 2/AP; used on recvr., hdgr. (sound P.), No. 1R	single	C 4270

Instrument	G.P.O. patt.; first figure of No. indicates No. of conductors		
Y1/YA 8833	No. 1/16E, black		single C 5687
Y1/YA 11356	No. 1/34F, black, 48 in.		single C 8635
Y1/YA 11257	No. 1/35F, black, 48 in.		single C 8635
Y1/YA 2470	No. 2/04A, brown, 21 in.		single C 4270
Y1/YA 3706	No. 2/22B, brown, 33 in.		single C 4270
Y1/YA 11260	No. 2/35A, brown, 72 in.	Used with recvr., hdgr., double	single C 8635
Y1/YA 5566	No. 2/58F, black, 48 in.		single C 4270
Y1/YA 7722	No. 2/94B, brown, 54 in.		single C 4270
*Y1/YA 12265	No. 2/94B, green, 54 in.	Used on tel., No. 332, green	single
*Y1/YA 12266	No. 2/94B, ivory, 54 in.	Used on tel., No. 332, ivory	single
*Y1/YA 12264	No. 2/94B, red, 54 in.	Used on tel., No. 332, red	single
Y1/YA 11358	No. 2/117B, brown, 57 in.	Used with recvrs., hdgr., No. 10A	single C 8635
Y1/YA 2526	No. 3/13B, brown, 54 in.		single C 4270
Y1/YA 790B	No. 3/13U, brown, 54 in.	Made similar to G.P.O. store cord, inst., No. 3/13B, brown, 54 in.	single
Y1/YA 2380	No. 3/58E, 2.1/2 in.		single C 4270
Y1/YA 2830	No. 3/61F, black, 24 in.		single C 4270
Y1/YA 3749	No. 3/62B, brown, 54 in.		single C 4270
Y1/YA 7410	No. 3/62B, brown, 72 in.		single C 4270
Y1/YA 6870	No. 3/62B, brown, 120 in.		single C 4270
Y1/YA 7411	No. 3/62B, brown, 180 in.		single C 4270
Y1/YA 3748	No. 3/63A, brown, 42 in.		single C 5687
Y1/YA 7414	No. 3/63A, brown, 54 in.		single C 4270
Y1/YA 2831	No. 3/73L, 60 in.		single B 4104
Y1/YA 7599	No. 3/73L, black, 108 in.		single C 4270

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES; COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CORD			
	Instrument - continued			
Y1/YA 5005	No. 3/74H, black 9.1/2 in.		single	C 4270
Y1/YA 4290	No. 3/77L, 24 in.		single	C 4270
*Y1/YA 12212	No. 3/97L, black, 9.1/2 in.		single	
Y1/YA 7222	No. 4/12A, brown, 48 in.		single	C 4270
Y1/YA 3328	No. 4/36A, brown, 84 in.		single	C 5687
Y1/YA 8832	No. 4/42A, brown, 42 in.		single	C 5687
Y1/YA 2527	No. 4/51H, black, 9.1/2 in.		single	C 4270
Y1/YA 7716	No. 4/54A, brown, 48 in.		single	C 4270
Y1/YA 6874	No. 5/04E, 8 in.		single	C 4270
Y1/YA 5004	No. 5/09E, 3 in.		single	C 4270
Y1/YA 11466	No. 5/22H, black, 9.1/2 in.		single	C 9519
Y1/YA 8831	No. 5/28E		single	C 5687
Y1/YA 8830	No. 8/10E, 8 in.		single	C 5687
Y1/YA 2832	No. 9/11 FS1, black, 60 in.		single	B 4104
Y1/YA 7598	No. 9/11 FS1, 108 in.		single	C 4270

Y1/YA 6898	No. 9/12 FS1, black, 48 in.		single	C 4270
Y1/YA 11249	No. 9/19, H, brown, 54 in.	Used with bell set, No. 44	single	C 8635
Y1/YA 6018	Line connector, No. 1	6 ft. of cordage, inst., No. 2/AP with ends looped; for use with socket coupling, No. 3A and plug, coupling, No. 4	single	C 4270
Y1/ZA 14308	Microphone and receiver No. 5	5 ft. of 4 core cord; for connecting mic., throat and recvr., hdgr.	single	C 4270
Y1/ZA 14309	No. 5A	As No. 5 but fitted with 1 plug, 5 point, No. 5 (Sec. Z1)	single	C 4270
Y1/ZA 17637	No. 9	6 ft. 2 in. of 5 core tinsel cord; for connecting mic. and recvr.; used on mic. and recvr. hdgr. assy., No. 9	single	C 4270
Y1/ZA 24329	No. 10	4 ft. 4 in. of 5 core tinsel cord; for connecting mic. and recvr.; used on mic. and recvr. hdgr. assy., No. 10	single	C 4270
Y1/ZA 5375	Microphone, hand No. 3	4 ft. 2.5/8 in. of 2 core tinsel cord; ends of conductors formed into eyes 1/8 in. dia.; used on con., twin, No. 76	single	C 4270
Y1/ZA 5426	No. 3A	10 ft. 2.5/8 in. of 2 core tinsel cord; ends of conductor formed into eyes 1/8 in. dia.; used on mic., hand, No. 3A and con., twin, No. 76A	single	C 4270
Y1/ZA 10045	No. 3B	As No. 3A but conductor at one end terminating in tag.; used on mic., hand, No. 3B	single	C 4270
Y1/ZA 5444	No. 3C	As No. 3A but 12 ft. 9 in. long	single	C 4270
Y1/ZA 24233	No. 4A, with bush	6 ft. 6 in. of 4 core stranded cpr.; ends of conductor formed into eyes 1/8 in. I.D., fitted with moulded bush; used on mic., hand, No. 4A	single	C 4270

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES: COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CORD			
Y1/ZA 17209	Microphone, hand - continued No. 9	6 ft. 9 in. of cordage 3/A; conductor at one end formed into eyelet to take No. 6 B.A. screw, the other end terminating in No. 4 B.A. tag; fitted with moulded bush; used on mic., hand No. 9	single	C 4270
Y1/ZA 26694	No. 9A	As No. 9 but 10 ft. 9 in. long; used on mic., hand No. 9A	single	C 4270
Y1/ZA 25004	No. 16	As No. 4A with bush, but T.R.S. in lieu of cotton braiding; used on mic., hand, No. 16	single	C 4270
	Microphone, screened			
Y1/ZA 31268	No. 1	45 ft., twin, screened cable (Sec. Y3); one end terminated with 3 No. 2 B.A. spade terminals, the 2nd end with 2 No. 4 B.A. spade terminal used on ampfr., port., P.A., No. 1, Mk. 3 kit, No. 2	single	C 4270
Y1/ZA 17549	No. 2, microphone, throat	4 ft. 6 in. of twin, flat cord with "T" branch; fitted with clamp plate; used on mic., throat, low level, No. 2, Mk. 1 and Mk. 2	single	C 4270
Y1/ZA 21917	No. 2A, microphone, throat	As No. 2, mic., throat but with V.R. insulation; used on mic., throat, low level, No. 2A, Mk. 1 and Mk. 2	single	C 4270



Y1/ZA 27862	No. 2C, microphone, throat	As No. 2, mic., throat, but 16 in. long; used on mic., throat, low level, No. 2C	single	C 4270
Y1/YA 7892	Patching 36 in., No. 1	G.P.O. cord No. 378 red or black (36 in.) fitted with plug, No. 316; used on terminal equip. vehicle, type C	single	C 5687
Y1/YA 7893	48 in., No. 1	G.P.O. cord No. 336 red or black 48 in. long, one end fitted with plug, No. 316 and the other fitted with tag	single	C 5687
Y1/YA 5578	Receiver, headgear, double No. 2	Cordage to Admiralty pattern 2504; length 2 ft. 2 in. to fork and 1 ft. from fork to recvr.; used on recvr., hdgr. (sound P.), No. 2 and No. 2A	single	C 4270
Y1/YA 5874	No. 3	Similar to No. 2 except that recvr. end of cord is made off for fitting to recvr., watch, D, L.R., No. 5	single	C 4270
Y1/YA 6542	Switchboard 13A/2, black	First figure of No. indicates No. of conductors	single	C 5687
Y1/YA 6541	13A/2, red	3 way switchboard cord	single	C 5687
Y1/YA 3535	No. 230 Black	54 in. long for use with swbds., U.C., 10 line	single	B 5064
Y1/YA 3536	Red		single	
Y1/YA 3317	No. 241, red	42 in. long; for use with swbds., teleprinter, 15 and 40 line	single	C 4270
Y1/YA 7473	Fitted with 2 plugs, No. 316	For use with swbds., teleprinter, 15 and 40 line	single	
Y1/YA 2753	No. 242 Black	G.P.O. patt.; 36 in. long	single	24218, B 5064
Y1/YA 0502	Red		single	
Y1/YA 5819	No. 262 With plug, No. 316, black	18 in. long; for use with wireless set, No. 26 (units monitoring, No. 1) (Sec. Z1)	single	C 4270

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES: COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CORD			
	Switchboard			
	No. 262 - continued			
Y1/YA 5820	With plug, No. 316, red		single	
	No. 328	G.P.O. patt.; 72 in. long; to fit plug, No. 310; used on various swbds.		C 4270
Y1/YA 5641	Green		single	
Y1/YA 4010	Neutral		single	
Y1/YA 4009	Red		single	
Y1/YA 8120	No. 335, red	G.P.O. patt.; 72 in. long; used on switchboard, PBX1A (in 35 Group H.Q., R.A.F.)	single	
	No. 336	48 in. long; used on swbds., teleprinter, 15 line and 40 line and swbds., F. and F.		
Y1/YA 1585	Black		single	B 3410
Y1/YA 7896	Green		single	C 4270
Y1/YA 7897	Neutral		single	C 4270
Y1/YA 1586	Red		single	B 3410
Y1/YA 6059	With plug, No. 316 black	Used on swbds., F. and F.	single	C 4270
Y1/YA 6058	With plug, No. 316, red	Used on swbds., F. and F.	single	C 4270

	No. 347	G.P.O. patt.; 24 in. long; suitable for plug, No. 309 or 310		C 4270
Y1/YA 5848	Black		single	
Y1/YA 5847	Red		single.	
	No. 349	G.P.O. patt.; 90 in. long; suitable for plug, No. 309 or with added binding, Nos. 310 and 310B; used on exch., C.B., multiple, W.D., unit type		C 4270
Y1/YA 8160	Black		single	
Y1/YA 8161	Green		single	
Y1/YA 7257	Neutral		single	
Y1/YA 8163	Red	With tr. finish; used on swbds., C.B., multiple, W.D., unit type	single	
	P.V.C.	Tinsel conductors; insulated P.V.C.; used on exch., C.B., multiple, W.D., unit type		C 4270
Y1/YA 8024	Black		single	
Y1/YA 8023	Green		single	
Y1/YA 8021	Neutral		single	
Y1/YA 8022	Red		single	
	W.D.	Not G.P.O. patt.; fitted with special pins; used on swbds., command, 200 line, B unit		C 4270
Y1/YA 3522	Black		single	
Y1/YA 3523	Red		single	
	No. 379	G.P.O. patt.; suitable for plug, No. 309 or with added binding, No. 310 and 310B		C 4270
Y1/YA 9046	Red		single	C 5687
Y1/YA 4035	Red, with 2 plugs, No. 310B, red		single	
Y1/YA 8308	No. 383	G.P.O. patt.; 18 in. long	single	C 4270
	Black			
Y1/YA 6872	No. 384	G.P.O. patt.; 42 in. long		C 4270
Y1/YA 6873	Black		single	
	Red		single	

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES; COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CORD			
	Switchboard - continued			
	No. 386	G.P.O. patt.; 66 in. long		C 4270
Y1/YA 8306	Black		single	
Y1/YA 8313	Green		single	
Y1/YA 8302	Neutral		single	
Y1/YA 8370	Red		single	
Y1/YA 8314	Yellow		single	
	No. 387	G.P.O. patt.		C 8635
Y1/YA 11359	Green		single	
Y1/YA 11360	Red		single	
*Y1/YA 11521	Slate grey		single	
Y1/YA 2731	Switchboard, coupling, No. 1	4 way cord, 20 in. long; end prepared for securing to swbd., and plug, No. 406; used on swbds., F. and F.	single	B 4804
	Telephone, hand			
Y1/YA 0511	No. 1	4 way; 4 ft. long; for use with tel., hand, No. 1, 2 and 3	single	B 1782, B 3410
Y1/YA 3885	No. 1A	As No. 1 except length is 10 ft.; used on tel., hand, No. 2, 2A and 3	single	B 6015
Y1/YA 4951	No. 2	3 way; 4 ft. long; used on tel., hand (sound P.), No. 2	single	C 4270

Y1/YA 5088	No. 3	4 way; 4 ft. long; used on tel., hand, No. 4	single	C 4270
Y1/YA 7667	No. 7	5 way; 9 ft. 2 in. long; includes 1 protector, rubber, No. 1; used on tel., hand, M.C.	single	C 4270
Y1/YA 7959	No. 10	3 way, 4 ft. long; V.R. insulated and T.R.S.; used on tel. set, J	single	C 4270
Y1/YA 3245	Telephone, headgear and breast, No. 1	4 way; 6 ft. to fork; used with recvr., hdgr., C, L.R., Mk. 5; tel. attachment, hdgr., double, Mk. 3; recvr., hdgr., C, L.R., double, No. 6	single	B 3410
	Telephone, headgear, double			
Y1/ZA 2322	No. 2	7 ft. 1.1/4 in. long; 2 core tinsel cord, forked; fitted with strain cord attachment	single	B 5885, C 4270
Y1/ZA 2323	No. 3	As No. 2 but 10 ft. 11.1/4 in. long	single	B 4809, C 4270
Y1/ZA 2049	No. 4	11 ft. 2 in. long; 2 core tinsel cord, forked; fitted with strain cord attachments	single	B 4809, C 4270
Y1/ZA 17541	No. 6	5 ft. 9 in. long; 2 core, forked; used on recvr., hdgr., G, H.R., double, No. 1	single	C 4270
Y1/ZA 24996	No. 8	7 ft. 1.1/2 in. long; 2 core, forked, I.R.S.; fitted with strain plate and plug cover; used on recvr., hdgr., D, L.R., double, No. 5D	single	C 4270
Y1/ZA 29356	No. 12	3 ft. 3.1/4 in.; 2 core, P.V.C., half round; with 1 ft. 9 in. loop; used on recvr., hdgr., C, H.R., double, No. 9A	single	C 4270
Y1/ZA 30004	No. 13	4 ft. long; 2 core, P.V.C., half round; with 1 ft. 9 in. loop at recvr. end; used on recvr., hdgr. C, H.R., double, No. 9	single	C 4270
	Telephone, headgear, single			
Y1/YA 0513	No. 2	2 way, 4 ft. long, fitted with 2 lugs; for use with recvr., hdgr., C, L.R., single, Mk. 2	single	B 1111, B 3410
Y1/YA 2743	No. 3	2 way, 4 ft. long, w/o br. lugs; for use with recvr., hdgr., C, L.R., single, Mk. 4	single	B 3410

## SECTION Y1

## CLASS 5995 - CABLE, CORD, AND WIRE ASSEMBLIES: COMMUNICATION EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	CORD - continued			
Y1/YA 0522	Telephone, transmitter, breast, No. 1	2 way, 8 ft. long; used with tel. attachments, hdgr., A.A., Mk. 3 on transmitter, breast, No. 1	single	B 3410
Y1/YA 6871	Test No. 3/36A	Comprises 1 cord, swbd., No. 378, red (36 in.) and 2 plugs, No. 316, red; used on swbds., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 9053	No. 3/72B	G.P.O. patt.	single	C 5687
Y1/YA 5841	No. 4/153B	G.P.O. patt.; comprises 1 cord, inst., No. 4/41F, black, 153 in.; 1 plug, No. 222, black, engraved "B", 1 plug, No. 222, red, engraved "A"; 1 plug, No. 316, black engraved "INTERNAL"; 1 plug, No. 316, red, engraved "EXTERNAL"	single	C 4270
Y1/YA 5879	No. 5/153A	G.P.O. patt.; comprises 1 cord, inst., No. 5/13F, black, 153 in.; 1 plug, No. 110; 1 plug, No. 222, black, engraved "B"; 1 plug, No. 222, red, engraved "A"; 1 plug, No. 316, black, engraved "INTERNAL"; 1 plug, No. 316, red, engraved "EXTERNAL"; for testing auto. exch.	single	C 4270
	CORD ASSEMBLY, Electrical			
	3 conductors	Tinsel		
	42 in. long - Green	Conductors formed into eyes both ends		
*Y1/5995-99-901-3672	Green	G.P.O. dwg. 62150	single	
*Y1/5995-99-901-3673	Red	G.P.O. dwg. 62150	single	
*Y1/5995-99-901-2504	47 in. long O/A	T.M.C. dwg. No. S44984; used on tel. set (Y1/5805-99-901-2504)	single	

	<b>COVER</b>			
Y1/ZA 17548	Cord, moulded, No. 1	Used on mic., throat, low level, No. 2	single	C 4270
Y1/ZA 21096	Cord, moulded, No. 2	Used on mic., throat, low level, No. 2, Mk. 2	single	C 4270

	<b>LEAD</b>			
Y1/YA, 5184	Battery connection, black	20 in. long; wire, electric, R.5, Mk. 1 (Sec. Y3); end terminating in wire end terminal; used on L.S.D.S.R.	single	C 4270
Y1/YA 5185	Battery connection, red	14.3/8 in. long; wire, electric, R.5, Mk. 1 (Sec. Y3); end terminating in wire end terminal; used on L.S.D.S.R.	single	C 4270

**CLASS 5999 - MISCELLANEOUS ELECTRICAL AND ELECTRONIC COMPONENTS**

	<b>CHUKE</b>			
	R.F.			
Y1/ZA 34470	350 Millihenries, No. 1	61/64 in. dia. x 5/8 in.; plastic bobbin wound with 7,500 turns of No. 44 S.W.G. enam. cpr. wire	single	C 4270
Y1/ZA 34279	No. 215	15/16 in. dia. x 5/8 in.; plastic bobbin wound with 9,400 turns of No. 44 S.W.G. enam. cpr. wire	single	C 4270
	<b>COUNTER</b>	15/16 in. dia.; for labelling electrical ccts.		
Y1/YA 0523	Bone		single	
Y1/YA 0524	Fibre		single	C 4270

**GROUP 61-ELECTRIC WIRE, AND POWER AND DISTRIBUTION EQUIPMENT**

**CLASS 6110-ELECTRICAL CONTROL EQUIPMENT**

Y1/YA 11371	<b>ASSEMBLY</b> , For pillar, distribution	G.P.O. store; P 74, tail 15 ft.; for pillar, distribution, No. 7	single	C 9519
Y1/YA 11259	<b>PILLAR</b> , Distribution, No. 4	G.P.O. patt.; accommodates assy. P74	single	C 8635

## SECTION Y1

## CLASS 6130 - RECTIFYING EQUIPMENT, ELECTRICAL

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L of C. ref.
1	2	3	4	5
Y1/YA 8858	RECTIFIER No. 33B	G.P.O. patt.; metal rectifier, input 110/240 V., 50 c/s., output 30/50 V., 0.025/0.2 amp.; sig. project store	single	C 5687
Y1/YA 9124	No. 38A	G.P.O. patt.; metal rectifier, input 200/250 V., 50 c/s., output 26 V., 0.25/0.5 amp. or 0.75 amp.; used to float charge 12 cell sec. batteries	single	C 5687
Y1/YA 7083	No. 38B (W.D.)	G.P.O. patt.; metal rectifier for floating 12 cell sec. batteries at P.M.B.Xs. etc.; input 200/250 V. at 50 c/s., output 26 V., 1.5A.; used on swbd. position, mag., $\frac{10 + 50}{60}$ , No. 1, complete station	single	C 4270
Y1/YA 8802	No. 38C	G.P.O.; patt.; similar to No. 38A with output of 26 V., 3.0 amp.	single	C 5687
Y1/YA 9344	No. 38D	G.P.O. patt.; metal rectifier for float charging sec. batteries; 26 V., 6 amp. output	single	C 8423
Y1/YA 10703	No. 47A	G.P.O. patt.; input 200/250 V., 50 c/s., output 0.5/1.0 amp. at 24, 40 or 50 V. smoothed	single	C 8423
Y1/YA 9219	No. 47D	G.P.O. patt.; metal rectifier input 200/250 V., 50 c/s., output 4.0/10.0 amps. at 24, 40 or 50 V. smoothed -	single	C 5687



Y1/YA 11370	No. 52C	G.P.O. patt.; metal rectifier with 3 circuits Input Float 140/240 V., 50 c/s.      22.5 V., 2.5/60 amp. Charge 200/250 V., 50 c/s.      24/31 V., 60/40 amp. Trickle charge 200/250 V.,      26 V., 1.5/.03 amp. 50 c/s.      Output	single	C 8635
CLASS 6135-BATTERIES, PRIMARY				
Y1/YA 7745	COVER, Battery, No. 2	Rubber-canvas; for protection of bty.; used with L.S.D.S.R., lightweight	single	C 4270
Y1/YA 5187	LID, Battery compartment,	6.1/2 in. x 3.1/2 in. x 1/4 in.; M.S.; No. 22 W.G.; used on L.S.D.S.R., cases, carrying, No. 4	single	C 4270
CLASS 6140 - BATTERIES, SECONDARY				
Y1/YA 8859	BATTERY UNIT, No. 634	G.P.O. patt.; for supplying power to small P.B.X.	single	C 5687
Y1/YA 2719	BOX Spare battery	6.13/16 in. x 6.5/8 in. x 4.5/8 in. internal dimensions; M.S.; with web cover and web sling; for use with L.S.D.S.R.	single	B 4110
Y1/YA 0196	Spare cell, large	7.1/4 in. x 4.7/8 in. x 4.5/8 in.; C.I., water tight, blacket lined, leather lined lid, or M.S., watertight, felt lined; with 4 compartments for 12 cells, dry, X, Mk. 2 or S, Mk. 1 (Sec. Y3)	single	16646. B 4388
Y1/YA 7942	LID Battery box tel. set, J	3.3 in. x 1.875 in. x .687 in.; stainless steel; includes rubber gasket, label and br. link; used on tel. set, J	single	C 4270

## SECTION Y1

## CLASS 6140 - BATTERIES, SECONDARY - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C ref.
1	2	3	4	5
Y1/YA 5421	LID Battery box - continued tel. set, L	3.5/16 in. x 1.7/8 in. X 1/4 in.; M.S.; No. 22 S.W.G.; part of case for tel. set, L	single	C 4270
CLASS 6145-WIRE AND CABLE, ELECTRICAL				
Y1/YA 8210	CORDAGE, Instrument  2/M	In continuous lengths; for use when made up cords of required lengths are not available. The designation comprises a number denoting the number of insulated conductors, followed by a letter denoting the class of cordage. If no colour follows, the standard colour will be brown. "B" class indicates tinsel conductors, cotton lapped, insulated V.R., braided mercerised cotton and (when more than 1 conductor) braided overall Conductors consist of 55 strands of No. 42 S.W.G. cpr. wire, V.R. insulated and T.R.S. overall	single	B 5064  C 4270, C 8424
Y1/YA 3816	No. 1/B		single	B 5064
Y1/YA 4349	No. 2/AP		single	C 4270
Y1/YA 3817	No. 2/B		single	B 5064
Y1/YA 3818	No. 3/B		single	B 5064
Y1/YA 3819	No. 4/B		single	B 5064

GROUP 62-LIGHTING FIXTURES AND LAMPS

CLASS 6210-INDCOR AND OUTDOOR ELECTRIC LIGHTING FIXTURES

LENS, Indicator light

Glass

Y1/6210-99-901-3214	Amber	G.P.O. cap, lamp, No. 1/1F (Old Cat. No. Y1/YA 8803)	single
Y1/6210-99-901-1249	Green, 0.371 in. dia. O/A.	G.P.O. cap, lamp, No. 1 - 1B; 62941 (Old Cat. No. Y1/YA 8883)	single
Y1/6210-99-901-0732	Green; 0.665 in. dia. O/A.	G.P.O. patt. (Old Cat. No. Y1/YB 02972)	single
Y1/6210-99-901-0729	Red; 0.371 in. dia. O/A.	G.P.O. cap, lamp, No. 1 - 1C; 62941 (Old Cat. No. Y1/YB 02043)	single
Y1/6210-99-901-3210	Red	G.P.O. patt. 62945 cap, lamp, No. 69/1C; for ampfr., aerial wideband; WB31 (Old Cat. No. Y1/YB 02971)	single
Y1/6210-99-901-3450	White, 0.490 in. lg. x 0.371 in. O/A. dim.	G.P.O. cap, lamp, No. 1 - 1A; 62941; used on apps. V.F. telegraph, 6 chan., DX (Old Cat. No. Y1/YB 02044)	single
	Translucent	G.P.O. patt. 406 in dia. (Old Cat. No. Y1/YB 02926)	single
Y1/6210-99-943-5654	Amber, No. 2/1F	(Old Cat. No. Y1/YB 00820)	single
Y1/6210-99-943-5655	Green, No. 2/1B	(Old Cat. No. Y1/YB 00821)	single
Y1/6210-99-943-5656	Red, No. 2/1C		single

LIGHT INDICATOR

	Bracket mounting W/O lens		single
*Y1/6210-99-901-3216	Side clips	Was jack, lamp, No. 25 (Cat. No. Y1/YB 0465)	
*Y1/6210-99-943-7266	Slide type	(Old Cat. No. Y1/YA 3882)	single
	Panel mounting; MES		
*Y1/YA 12194	Green, 1 in. dia.	Used on Amp. mixer type BD.554.B	single
*Y1/YA 12195	Red, 1 in. dia.	Used on Amp. mixer type BD.554.B	single
*Y1/YA 12201	1 in. dia. W/O lens	Used on Port. supply unit type BD.594	single
	Panel mounting. S.B.C.	Used on Project Gwajjn Znuber A77/B	
*Y1/YA 12022	Amber, 1.3/16 in. dia.		single
*Y1/YA 12054	Red, 1.3/16 in. dia.		single

## SECTION Y1

## CLASS 6250-BALLASTS, LAMPHOLDERS AND STARTERS

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 11462 Y1/YA 11461 Y1/YB 02045 Y1/YB 02249 Y1/YA 11037 Y1/YB 00728 Y1/YA 3021 Y1/YA 8289	CAP Lamp No. 2 Chromium plated Green Red White No. 5 No. 69 Blue White Lampholder, No. 1 CASE, Metal, spare bulb,	S.T. and C. type; for use with equip., radar, C.C., No. 1, Mk. 1 Lamp cap 4001-M Lamp cap 4001-J G.P.O. patt.; 0.408 in. dia. overall, 0.350 in. dia. of barrel G.P.O. patt.; tubular for jacks, lamp, Nos. 32, 37 and 39 (N.I.V.) G.P.O. patt.; 0.665 in. dia. overall, 0.536 in. dia. of barrel Comprises threaded metal tube, fitted with pins for bayonet fixing, transparent disc., knurled cap and grub screw 3.11/16 in. x 3.1/8 in. x 1.9/16 in.; for holding 20 bulbs, -6 V.	single single single single single single single single single	C 9519 C 5687, C 7372 C 5687 C 5687, C 8423 C 4270 C 4270

Y1/YA 4714	COVER, Holder, No. 1, spare bulb	4.3/8 in. x 1.1/8 in. x 1 in.; M.S. No. 22 S.W.G.; with knob riveted on at one end; used on cases of control units for tel., L.S., No. 2	single	C 4270
Y1/YA 4713	DISC Insulating, No. 1, lampholder batten	Insulating plate used between chassis and lampholders on tel., L.S., No. 2, control unit	single	C 4270
Y1/YA 3870	Lampholder	Celluloid, 1/2 in. dia.; used on cap, lampholder, No. 1	single	C 4270
Y1/YA 4979	HOLDER Lamp, 4 way, No. 1	Mtg. bar with 4 lamp sockets riveted to it; 1 connecting tag per socket	single	C 4270
Y1/YA 4712	No. 1 spare bulb	Consists of block 4.3/8 in. x 1.1/8 in. x 1/2 in., with 8 holes 3/8 in. dia.; with metal cover	single	C 4270
Y1/YA 1626	LAMPHOLDER	1 in. dia. x 1.3/4 in.; br. and plastic, fitted with bayonet type fixing cap and transparent disc; used on apps., teleg, 2 tone, Mk. 2 (Sec. Y2) and swbds., U.C.	single	B 3011, B 4807
Y1/YA 4758	RING, Securing, lampholder, No. 1	15/16 in. O.D. x 3/4 in. I.D. x 7/64 in.; br.; knurled; threaded 26 t.p.i.	single	C 4270
GROUP 63-ALARM AND SIGNAL SYSTEMS				
CLASS 6350-MISCELLANEOUS ALARM AND SIGNAL SYSTEMS				
Y1/YA 5961	ARMATURE, Buzzer, No. 18	G.P.O. patt.; for buzzer, No. 18	single	C 4270

## SECTION Y1

## CLASS 6350 - MISCELLANEOUS ALARM AND SIGNAL SYSTEMS - continued

Cat No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/6350-99-943-0560	BELL, Electrical 2V., D.C. 3 in. dia. 1.9/16 in. h.	50 ohms + 50 ohms under dome movement without base, used on rack, tel. terminal, No. 1, Mk. 1/1 and Mk. 2 (Old Cat. No. Y1/YA 9788) (Old Cat. No. Y1/YA 9788)	single	
Y1/6350-99-943-0561	2V., D.C. 4 in. dia. 2.1/16 in. h.	50 ohms + 50 ohms replacement for bell battery, No. 13A modified (Old Cat. No. Y1/YA 9736)	single	
Y1/6350-99-943-0566	24V., D.C. 3 in. dia. 1.21 in. h.	1000 ohms used on tel. set L., tel. set N., Mk. 3 (Old Cat. No. Y1/YA 3720)	single	
Y1/6350-99-943-0562	48V., D.C. 4 in. dia. 2.1/16 in. h.	1250 ohms + 1250 ohms; used on exch., CB. multiple (W.D.) (Old Cat. No. Y1/YA 9789)	single	
Y1/6350-99-943-0563	Type 43A	G.P.O. patt.; 24V., D.C. 10 ohms + 10 ohms 6.44 in. lg. 3.25 in. w; 2.56 in. h. (Old Cat. No. Y1/YA 9351)	single	
Y1/6350-99-943-0567	Type 44B	G.P.O. patt.; 24V., D.C. 1000 ohms + 1000 ohms 10.62 in. lg. 5.75 in. w; 3.37 in. h; used on switch board. C.B. multiple (W.D.) (Old Cat. No. Y1/YA 7266)	single	
Y1/6350-99-943-0564	Type 56A	G.P.O. patt.; 4V., D.C. 50 ohms + 50 ohms 5.94 in. lg. 3.25 in. w; 2.39 in. h. used on switch board, tel. 5 position E.S 1653 (Old Cat. No. Y1/YA 0161)	single	
Y1/6350-99-943-0565	Type 56D	G.P.O. patt.; 4V., D.C. 50 ohms + 50 ohms 5.94 in. lg. 3.25 in. w; 2.39 in. h; (Old Cat. No. Y1/YA 9043)	single	
Y1/6350-99-943-0568	Type 56E	G.P.O. patt.; 24V., D.C. 250 ohms + 250 ohms; 5.94 in. lg.; 3.25 in. w; 2.39 in. h. (Old Cat. No. Y1/YA 9164)	single	

Y1/6350-99-943-0569	Type 67A	G.P.O. patt.; 24V., D.C. 500 ohms + 500 ohms (Old Cat. No. Y1/YA 3735)	single	
	<b>BELL GONG</b>			
Y1/YA 0162	No. 2	2.1/2 in. dia.; G.P.O. patt.; high pitch; with eccentric hole	single	B 1782, B 8030
Y1/YA 6404	No. 2A	2.1/2 in. dia.; G.P.O. patt.; low pitch; with eccentric hole	single	B 8030
	<b>BOBBIN</b>			
Y1/YA 2586	X, 1 and 2, for buzzer, I, Mk. 1	2.1/2 in. long x 1 in. sq.; marked X1 and X2 at opposite ends; used on buzzer, I, Mk. 1	single	B 6339, C 4270
Y1/YA 2587	X, 3 and 4, for buzzer, I, Mk. 1	2.1/2 in. long x 1 in. sq.; marked X3 and X4 at opposite ends; used on buzzer, I, Mk. 1	single	B 6339, C 4270
	<b>BUZZER</b>			
Y1/YA 8298	3.5 ohms, No. 1	3 in. x 3 in. x 2.1/8 in. plastic; suitable for bty., xform. or high voltage working	single	C 4270
Y1/YA 7917	F, Mk. 3	Full tropical version of buzzer, F, Mk. 2/2	single	C 4270
Y1/YA 2588	Signalling, training	8.1/2 in. x 4.1/2 in. x 2.1/8 in.; for training purposes; fitted with terminal plate for connecting to recvr., hdgr., or ext. circuits; comprises 1 key, W.T., 8A, No. 2 (Sec. Z1); 1 buzzer; 1 metal bracket for securing bty.; mounted on wood base	single	B 2815
Y1/YA 0222	T, Mk. 1	Polarised type, 6 connections; a self-contained unit (having a pair of bobbins not interchangeable); for use with various tel. app.; fitted with 2 rings, locking, B, and 2 screws, contact, B, Mk. 1 or Mk. 2 (I.L. 11682)	single	B 2342

## SECTION Y1

## CLASS 6350 - MISCELLANEOUS ALARM AND SIGNAL SYSTEMS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	BUZZER - continued			
Y1/6350-99-943-0571	Vibrating, type No. 2	G.P.O. patt.; 2V., D.C.; 10 ohms D.C. resis. coil, 1.5/8 in. lg.; 1.1/2 in. w. (Old Cat. No. Y1/YA 6918)	single	
Y1/6350-99-943-0572	No. 2 mounted	G.P.O. patt.; 2V., D.C., 10 ohms D.C. resis. coil; on plastic base 2.3/4 in. x 1.3/4 in. (Old Cat. No. Y1/YA 7442)	single	
Y1/6350-99-943-0573	No. 18A	G.P.O. patt.; 24V., D.C.; 500 ohms D.C. resis. coil; 3.1/4 in. lg. 3.1/4 in. w. 1.3/4 in. h. (Old Cat. No. Y1/YA 3055)	single	
*Y1/YA 12239	No. 20A	G.P.O. patt.; 3.1/4 in. lg. 3.1/4 in. w. 1.1/2 h.	single	
	BUZZER HOUSING			
Y1/YA 3978	No. 1	For buzzer, T, Mk. 1; includes fixing screws, nuts and washers	single	C 4270
Y1/YA 2257	Telephone, F	Br.; for buzzer, T, used on tel. set, F; complete fixing screws	single	C 4270
Y1/YA 5594	CORE, Coil, No. 2	Soft iron, 2.1/2 in. long, stem tapped 4 B.A.; used on buzzers, T, Mk. 1 and F, Mk. 2	single	C 4270



Y1/YA 5968	COVER Buzzer, No. 18	2.1/2 in. x 2.1/2 in. x 3/4 in. metal cover used on buzzer, No. 18 on swbds., teleprinter, to 15 and 40 line	single	C 4270
Y1/YA 0174/3	GONG, Bell Magneto, "S"	2.31/32 in. dia. x 1.1/4 in. x .080 in. thick; Br. used on tel. set, D, Mk. 5	single	C 4270
Y1/YA 5417	Magneto, "T"	3 in. dia. x 1.3/32 in. x .048 in. thick; Br.; used on bell, magneto, T on tel. set, L and tel. set, H, Mk. 2	single	C 4270
Y1/YA 4797	No. 13A	3 in. dia. x 1 in. x .094 in. thick; used on bell, No. 13A, modified in swbds., U.C.	single	C 4270
Y1/YA 3720/2	HAMMER, Bell, magneto, "T"	1.3/4 in. x 5/16 in. x 5/16 in.; consists of 2 balls, 5/16 in. dia. clinched one each end of a phos. B. spring 1.27/32 in. x 1/4 in. x .0032 in.	single	C 4270
Y1/YA 3176	HOUSING, Buzzer, No. 2	2.7/8 in. x 2.1/2 in. x 1.7/8 in.; Br., No. 20 S.W.G., with 2 bakelised fabric plates, catch spring and bracket; used on app., morse tuition equipt. (Sec. Y2)	single	C 4270
Y1/YA 0225	PLATE, Contact, buzzer, "T", Mk. 1	2.3/4 in. x 2.1/2 in. x 1/16 in.; S.R.B.P.; with 6 contact strips	single	C 4270
Y1/YA 3938	YOKE, B	2.1/4 in. x 1.1/8 in. x 3/16 in.; soft iron (annealed); with 8 holes tapped No. 6 B.A. 1/4 in. deep; used on buzzers, F and T	single	C 4270

## SECTION Y1

## GROUP 66-INSTRUMENTS AND LABORATORY EQUIPMENT

## CLASS 6625-ELECTRICAL AND ELECTRONIC PROPERTIES MEASURING AND TESTING INSTRUMENTS

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
*Y1/6625-99-943-2776	AMMETER	M.C.; 2 in. square flush, 1 mA. (Old Cat. No. Z4/6625-99-943-2776)	single	
Y1/YA 6500	CASE, Test, D 8352	7 in. x 9.1/2 in. x 7 in.; G.P.O. patt.; includes 2 clips, No. 14; 1 coil, induction, No. 12; 1 condenser, M.C., No. 101; 1 gen., No. 4C; 5 keys, No. 212; 5 key-mtgs., V	single	C 4270
Y1/YA 6697	HANDLE, Chest, M.S., No. 2, 4 in. grip	M.S.; used on test frames, 20 pr., Mk. 3 and 40 pr., Mk. 2	single	C 4270
Y1/YA 4679	HOLDER, Testing, No. 1, line unit	Test set for holding line unit (U.C.); for adjusting relays; includes 2 resis., test, 1,960 ohms and 2,960 ohms	single	C 4270
Y1/YA 6701	LID, Case, test frame, 40 pr., Mk. 2	2 ft. 5.1/4 in. x 10.1/2 in.; M.S. plate 16 S.W.G.; edged with M.S. angle 1.1/8 in. x 9/16 in. x 1/8 in. and strengthened by 2 hardwood battens; used on test frame, 40 pr., Mk. 2	single	C 4270
Y1/YA 9465 *Y1/YA 12309	METER No. 100A No. 100D	G.P.O. patt.; 500 ohms for pulse metering Used on outfit REB (5)	single single	C 8181

Y1/YA 11016	No. 103A	G.P.O. patt.; 500 subscribers meter for manual systems, 40V.	single	C 8423
*Y1/YA 12206	POWER UNIT, S.A. 6028	Port. power unit for supplying 200V., A.C. at 100 mA. and for operating test equip. designed for use from A.C. mains operating V.24	single	
*Y1/YA 12205	PROBE, No. 4	For locating and identifying cables	single	
Y1/YA 7208	RACK, Apparatus, test equipment	7 ft. 3 in. x 1 ft. 8.1/2 in. x 1 ft. 6 in.; M.S. channel 3 in. x 1.1/2 in. and angle 4 in. x 4 in. x 3/8 in.; rack for mtg. test equipt.	single	C 4270
	SPRING, Leaf	Spring steel .022 in. thick; used on box, battery test, No. 1		C 4270
Y1/YA 7536	3 in. x 1/2 in. x 1 in. rad.		single	C 4270
Y1/YA 7538	3 in. x 1/2 in. x 1.3/4 in. rad		single	
Y1/YA 7537	3 in. x 1/2 in. x 2 in. rad		single	
Y1/YA 7557	STRIP, Metal, slotted, 5 in. x 1/2 in.	5 in. x 1/2 in. x 1/16 in., with slot 7/32 in.; x 2.17/32 in.; steel; used on testers, junction relay set	single	C 4270
Y1/YA 3746	SUPPORT, Cable Long	M.S. 3/8 in. dia. rod, bent at right angles 4.1/2 in. x 2.9/16 in.; used on test frames, 20 pr., Mk. 3 and 40 pr. Mk. 2	single	C 4270
Y1/YA 3747	Short	M.S. 3/8 in. dia. rod, bent at right angles 4.1/2 in. x 1.5/16 in.; used on test frames, 20 pr., Mk. 3 and 40 pr., Mk. 2	single	C 4270

## SECTION Y1

## CLASS 6625 - ELECTRICAL AND ELECTRONIC PROPERTIES MEASURING AND TESTING INSTRUMENTS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 1688	TABLET, test, E.C.1144	Includes 1 detector, No. 2 special, Mk. 1 (Sec. Y3); key, No. 33; 3 keys, No. 33, NL; mounted in container, the front of which is engraved with instructions; fitted with wood strip, carrying 500 ohms resis. bobbin and terminals; with 1 link wire, without 5 cells, inert, S, Mk. 1 or dry, X, Mk. 2 (Sec. Y3) and 1 bty., 50V. made up locally; used on test frame	single	24851, B 5064
Y1/YA 8044	TESTER Continuity, C.B., exchange	5.1/4 in. x 5.1/2 in. x 6 in.; wooden case with sloping front; fitted with key, buzzer, resistor, 10 ohms; variable resistor, 6 ohms; 5 terminals, inst., slotted, single, No. 4, small (Sec. Y3); fastener, cord, No. 1; for use on exch., C.B., multiple, W.D. unit type	single	C 4270
Y1/YA 9409	G.P.O. type No. 106	G.P.O. patt.; for testing H.Cs. and line fuses in manual exch. over 500 lines and auto. up to 900 lines	single	C 8181
Y1/YA 9408	G.P.O. type No. 790	G.P.O. patt.; direct reading transmission measuring set with a 2 stage negative feedback; for mtg. on rack, apparatus	single	C 8181

Y1/YA 7389	Junction relay set	1 ft. 6.5/16 in. x 1 ft. 1 in. x 1 ft. 6 in. met. C.; with support fitted with G.P.O. shelf jack assy., 16 pt., P.O.62; case fitted with keys, dial, buzzer, relay, condenser, jack, etc.; for testing junction relay sets on exch., C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 7793	No. 23	G.P.O. patt.; lamp for locating faults in manual exch.	single	C 4270
Y1/YA 7348	No. 23A	G.P.O. patt.; lamp for locating faults in auto. exch.	single	C 4270
Y1/YA 9781	No. 43	G.P.O. patt.; clockwork device for testing approx. speed and recording number of pulses dialled of dials, auto. and machines, pulsing; for exch. where the voltage is from 35 to 60	single	C 8181
	TEST FRAME			
Y1/YA 3202	20 pair, Mk. 3	28 in. x 16 in. x 13 in.; port., without test instruments; in wood case, metal frame for line distribution with facilities for connecting lines and instruments to terminals or via strips, connection (IL. 2315)	single	B 5064
Y1/YA 3201	40 pair, Mk. 2	28 in. x 29.1/2 in. x 13 in.; port.; in wood case; consists of two 20 pr., Mk. 3 frames (with fittings) bolted together (IL. 2315)	single	B 5064, C 4270
		CLASS 6645 - TIME MEASURING INSTRUMENTS		
	CLOCK			
Y1/YA 11399	No. 34, mahogany	G.P.O. Drum pattern; double dial, 10 in. dia. with block divisions instead of numerals. For local exchanges, driven by clock, No. 36	single	C 9519

## SECTION Y1

## CLASS 6645 - TIME MEASURING INSTRUMENTS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 11400	CLOCK - continued No. 66A	G.P.O. patt. moulded gold beige, 9 in. dial 1/2 min., pulse driven	single	
*Y1/YA 11686	Wall, 12 in. dia.	Type C.B6/C 400A movement	single	
CLASS 6680 - LIQUID AND GAS FLOW, LIQUID LEVEL, AND MECHANICAL MOTION MEASURING INSTRUMENTS				
*Y1/6680-99-901-0209	COUNTER, Electrical	G.P.O. meter No. 100C	single	
CLASS 6695-COMBINATION AND MISCELLANEOUS INSTRUMENTS				
Y1/YA 8728	DYNAMOMETER, No. 1	G.P.O. patt.; for use when tensioning aerial suspension lines; range 0-20 cwts.	single	C 5687

GROUP 69-TRAINING AIDS AND DEVICES

CLASS 6940-COMMUNICATION TRAINING DEVICES

Y1/YA 8250	ARM, Traverse, cutter, head No. 1	14 in. x 3.1/2 in. x 1.1/2 in.; bronze casting; used with edge drive recorder on training set, No. 5A	single	C 4270
Y1/YA 8224	PANEL, Amplifier, line, No. 1	19 in. x 13.31/32 in. x No. 13 S.W.G. M.S.; mounts 5 ampfrs., line, No. 2; used on training set, No. 4A	single	C 4270
Y1/YA 2178	TRAINING SET, Interference	4.1/2 in. x 3 in. x 2.1/8 in.; to control applied signals (buzzer, etc.) for training operators to read through interference	single	B 1192

GROUP 75-OFFICE SUPPLIES

CLASS 7510-OFFICE SUPPLIES

Y1/YA 1478	FLASK Ink	2.11/16 in. x 2 in. x 1.3/4 in.; tinned plate 25 S.W.G.; fitted with br. cap; used with stamps, army sigs., dating, Mk. 2	single	C 4270
Y1/YA 1475	Ink, filled	Consists of flask, ink filled with approx. 1/8 pint of ink, obliterating; used with stamps, army sigs., dating, Mk. 2	single	
Y1/YA 5931	PAD, Inking, No. 2	4.9/16 in. x 2.9/16 in. x 1.1/16 in.	single	C 4270

## SECTION Y1

## CLASS 7520-OFFICE DEVICES AND ACCESSORIES

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 0187	BOX, Index, field	12 in. x 7.5/8 in. x 5.5/8 in.; wood; with removable partitions; to take cards 6 in. x 4 in. and set of alphabetical guide cards	single	23708, 25268
Y1/YA 8018	FILE, Switchboard, visible index, 6 in. x 3.1/4 in.	Complete visible index for mounting on keyboard of exch, C.B., multiple, W.D., unit type	single	C 4270
Y1/YA 5933	HANDLE, Stamp, dating	4.17/32 in. x 1.1/2 in. dia.; beech, with Br. ferrule and M.S. screw, 5/16 in. dia. B.S.W.; used on stamps, army sigs., dating, Mk. 2	single	C 4270
Y1/YA 5934	PIN Positioning, wheel	Used on stamps, army sigs., dating, Mk. 2	single	C 4270
Y1/YA 5935	Securing, wheel	1/2 in. dia. x 2.5/32 in. long; used on stamps, army sigs., dating, Mk. 2	single	C 4270
Y1/YA 8363	SLIDE-RULE, Stay	G.P.O. patt.; for calculating staying requirements; with case	single	C 4270
Y1/YA 1473	STAMP Army sigs., dating, Mk. 2	Steel, with revolving date and code letter wheel; with inking pad and tray; rubber stamping pad and screwed-capped flask of ink; without stamp "PAID".	single	23622, B 721



Y1/YA'1480	Dating	Units whose code call requires 3 letters in the first half or 3 letters in the second half of the alphabet will demand 1 additional code letter wheel A to M or N to Z. Units will cut a slot in the wooden block to accommodate the additional wheel. (IL. 2525) Consists of body, handle, pin positioning wheel, pin securing wheel and wheels 1 to 6 inc. of stamps, army sigs., dating, Mk. 2	single	C 4270
	WHEEL			
	Type			
Y1/YA 5936	No. 3	Embossed with figures 1, 1, 2, 2, 3, 1, 1, 2, 2, 3 and 2 blanks or hyphens	single	C 4270
Y1/YA 5937	No. 4	Embossed with figures 0 to 9, 2 blanks, and a full stop after each figure	single	
Y1/YA 5938	No. 5	Embossed with Roman figures I to XII and a full stop after each figure	single	
Y1/YA 5939	No. 6	Embossed with figures 3, 4, 4, 5, 5, 6, 6, 7, 7, 8 and 2 blanks	single	

GROUP 76 - BOOKS, MAPS, AND OTHER PUBLICATIONS

CLASS 7610 - BOOKS AND PAMPHLETS

Y1/YA 6766	INSTRUCTIONS, Working Apparatus, cable-laying, No. 8, S.R.D.E.		single	C 4270
Y1/YA 8156	Apparatus, cable-laying, No. 11	S.R.D.E. Pamphlet No. 654A	single	
Y1/ZB 10189	Apparatus, L.S., No. 3		single	

## SECTION Y1

## CLASS 7610 - BOOKS AND PAMPHLETS - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	INSTRUCTIONS, Working - - continued			
Y1/YA 7326	Exchange, C.B., multiple (W.D.) unit type		single	
Y1/YA 7427	Exchange, magneto (W.D.) unit, type, "N" position	S.R.D.E. Pamphlet No. 491A	single	
Y1/YA 7974	Fullerphones, Mk. 4, Mk. 4/1 and Mk. 4/2	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/YA 7856	Fullerphones, Mk. 6	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/YA 8001	Lamp, signalling, daylight, short range, lightweight		single	
Y1/ZB 12983	No. 2, amplifier, port, P.A., No. 1, Mk. 3		single	
Y1/ZA 31785	Recorder with playback, wire, No. 1	S.R.D.E. pamphlet No. 609A	single	
Y1/YA 7735	Switchboards, F. and F.		single	
Y1/YA 7230	Switchboard, magneto, 10 line (W.D.)	S.R.D.E. pamphlet No. 479C	single	
Y1/YA 8175	Switchboard, U.C., 10 line, Mk. 2	S.R.D.E. pamphlet No. 616A	single	

Y1/YA 7424	Telephone, head and breast (S.P.), C/S, No. 2	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/YA 7425	Telephone, head and breast (S.P.), C/S, No. 3	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/YA 7426	Telephone, head and breast (S.P.), C/S, No. 4	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/YA 7918	Telephone, head and breast (S.P.), C/S, No. 5	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/YA 7975	Telephone set, D, Mk. 5	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/YA 7977	Telephone sets, F, Mk. 1, Mk. 1/1 and Mk. 2	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/YA 7976	Telephone set, L	Printed on Manilla card, size 8 in. x 5 in.	single	
Y1/ZB 12915	INSTRUCTION, Working and fitting Apparatus, loudspeaking, No. 9		single	C 4270
Y1/ZB 10977	INSTRUCTIONS, Working, No. 2 Apparatus, loudspeaking, No. 3		single	C 4270
CLASS 7690-MISCELLANEOUS PRINTED MATTER				
Y1/YA 7356	PASTER Diagram Fullerphone, Mk. 4, Modified No. 1		single	C 4270
Y1/YA 6123	No. 1	For boxes, terminal, signal offices, Mk. 2 and Mk. 3	single	
Y1/YA 6990	No. 1 Civil line unit, Mk. 1/1	2.1/4 in. x 2.1/8 in.	single	

## SECTION Y1

## CLASS 7690 - MISCELLANEOUS PRINTED MATTER - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 6192 Y1/YA 7943  Y1/YA 6703 Y1/YA 6704 Y1/YA 8198	PASTER Diagram - continued Switchboard, F. and F. Tel. set, J Instruction Test frame 20 pr., Mk. 3 40 pr., Mk. 2 Modifications record, 3.1/2 in. x 2.1/4 in.	12.1/2 in. x 10 in.; used on swbd., F. and F. units C 5.1/2 in. x 2 in.  11 in. x 7.3/4 in. 1 ft. 6 in. x 8 in. For sticking on outside of packing to record modifications; used on various sig. equipt.	single single  single single single	
Y1/YA 3110	WEB, Non-elastic, No. 2, grey, 18 in.	GROUP 83-TEXTILES, LEATHER, AND FURS  CLASS 8305-TEXTILE FABRICS  G.P.O. patt.; cotton, approx. 1 in. wide; neckband, for B.P. transmitter; used on transmitter, No. 23	yd.	C 4270

CLASS 8310-YARN AND THREAD

	SILK	G.P.O. patt.; for repairing cords		C 8423
Y1/YA 10711	Black		reel	
Y1/YA 10712	Blue		reel	
Y1/YA 10713	Brown		reel	
Y1/YA 10714	Green		reel	
Y1/YA 10716	Red		reel	
Y1/YA 10715	White		reel	

CLASS 8345-FLAGS AND PENNANTS

	APPARATUS, Aerial signalling			
	Ground, indicator	White American cloth; for identification of various formations from the air		21562
Y1/YA 6131	O	Disc; semi-circle; 16 ft. O.D., with 2 ft. wide black border	single	C 4270
	Strip			
Y1/YA 6473	15 ft. x 3 ft.	White American cloth, with loops of cordage at each corner	single	C 4270
Y1/YA 0013	Mk. 1/1	White American cloth; 8 ft. 6 in. x 1 ft. 4 in.; with leather at the centre and ends	single	A 3998

GROUP 84-CLOTHING AND INDIVIDUAL EQUIPMENT

CLASS 8405 - OUTERWEAR MEN'S

Y1/YA 7925	STRAP, Chin, No. 1, Mk. 2	Webbing khaki, 1 in. wide x 15 in., both ends looped, fitted with buckle for adjustment; includes 6 in. insert of 1 in. wide elastic; double ply	single	C 4270
------------	---------------------------	--	--------	--------

## SECTION Y1

## CLASS 8415-CLOTHING, SPECIAL PURPOSE

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
Y1/YA 7621	GLOVES I.R., leather faced, No. 10	G.P.O. patt.; for work in vicinity of power ccts.	pair	C 4270
Y1/YA 7622	I.R., leather faced, No. 12		pair	
CLASS 8465-INDIVIDUAL EQUIPMENT				
Y1/YA 0178	BELT, Reel, cable, No. 2	Leather, with sling and socket; for carrying reel, cable, No. 2, Mk. 2 (Sec. Y3); and tel. set, D	single	14605, 25713
Y1/YA 0445	CLIMBER, Pole Mk. 1	G.P.O. patt. 16 in. x 3 in. inside stem Comprising 2 Mk. 1 climbers, 2 leather pads and 4 straps	single	8778, A 1196 B 5251
Y1/YA 0446	Climber	Steel; without leather pads and straps	single	
Y1/YA 0448	Pad	Leather; with loop, for use with Mk. 1 climbers only	single	
Y1/YA 4115	Mk. 1/1	Comprising 2 Mk. 1/1 climbers; 1 left, 1 right; 2 rubber pads and 4 straps	single	B 5251

Y1/YA 3991	Climber	Steel; with plate; without rubber pads and straps		
Y1/YA 4118	Left	For left leg	single	
Y1/YA 3992	Right	For right leg	single	
	Pads	Rubber; for use with Mk. 1/1 climber only	single	
Y1/YA 6360	CLIMBER, Tree	Comprises M.S. climbing iron, 16 in. x 6 in. x 7/8 in. fitted with knee pad and 2 straps	single	C 4270
Y1/YA 7625	Lightweight	Comprises M.S. stirrup 4.1/2 in. x 5.1/2 in. x 3/4 in.; fitted with straps, single and straps double	single	C 4270
	MEGAPHONE			
Y1/YA 1066	12 in., Mk. 1	Exponential type; A.I., seamless; fitted with handle	single	A 8886, A 9567
Y1/YA 1068	30 in., Mk. 2	Tinned steel, with handle	single	12260, B 4676
Y1/YA 8166	STIRRUP, Climber, tree, lightweight	3/4 in. x 1/4 in. bent to "L" shape 5.1/4 in. x 4.5/16 in.; one end bent to form a loop 1/4 in. x 1.3/8 in. internally; the other end bent to a 2 pronged point and case hardened	single	C 4270
	STRAP			
	Carrying			
Y1/YA 1532	F	Web, 50 in. long with wider shoulder pieces; fitted to carry 1 pin, earth, small; ends fitted with tip, Br., 1 in. and buckle, Br. 1 in.; for carrying various instruments, etc.	single	B 1991
Y1/YA 1533	Fitting, D	Metal plate with "D" attached for coupling straps carrying to insts., etc.; includes 4 No. 6 B.A. csk. hd. screws and 4 special nuts for attaching to wood cases; to be demanded without screws and special nuts when fitting to metal cases	single	B 3410

## SECTION Y1

## CLASS 8465 - INDIVIDUAL EQUIPMENT - continued

Cat. No.	Item name or designation	Item description or detail	Unit of issue	L. of C. ref.
1	2	3	4	5
	STRAP			
Y1/YA 2481	Carrying - continued G	Web, 60 in. long, wider shoulder piece; ends fitted with tip, 1 in.; and buckle, Br., 1 in.; for carrying various sig. apps.	single	B 3253
Y1/8465-99-942-4330 Y1/YA 4080	G, Mk. 1/1 H	Tropicalised version of straps, carrying, web, G Web, 42 in. long x 1 in. wide fitted with two 1 in. Br. hooks and 1 buckle, Br., 1 in. for carrying various insts.	single single	C 4270, C 8424 C 4270
Y1/YA 4352	J	Web, drab, 18 in. x 1 in. fitted with 2 tips, Br. (N.P.D.), 1 in. and 2 buckles, Br. (N.P.D.), 1 in.; used on aerial coupling equipment, aerial units A, and C, Mk. 1, 2 and 2/1 (Sec. Z1)	single	C 4270
Y1/YA 4851	K	Web, 60 in. x 1 in. fitted with tips, Br., 1 in. (N.P.D.) and 2 buckles, 1 in. (N.P.D.); for carrying various sig. apps.	single	B 7413
Y1/YA 7720	Web, No. 3	Web, drab, 48 in. x 3/4 in.; fitted each end with tip, Br., 3/4 in. (N.P.D.); used on L.S.D.S.R., lightweight	single	C 4270
Y1/YA 0449 Y1/YA 8167	Climber, pole Double, climber, tree, lightweight	Leather; 21 in. x 7/8 in. x 1/8 in.; eyeleted 2 chrome leather straps; stitched to metal "D" ring 1.1/4 in. I.D.; 1 strap is 7.3/8 in. x 9/16 in. x 3/32 in. ending in a Br. buckle; the other strap is 11.1/4 in. x 9/16 in. x 3/32 in. with 7 holes	single single	B 5251 C 4270



Y1/YA 7981	Single, climber, tree, lightweight	Chrome leather; 22.1/4 in. x 9/16 in. x 3/32 in. with buckle; used on climber, tree, lightweight	single	C 4270
------------	---------------------------------------	---	--------	--------

GROUP 93-NON-METALLIC FABRICATED MATERIALS

CLASS 9320-RUBBER FABRICATED MATERIALS

Y1/ZA 17553	TAPE, Rubber, No. 1	Used on mic., throat, low level, No. 2; G.P.O. patt.	single	C 4270
-------------	---------------------	--	--------	--------

GROUP 99-MISCELLANEOUS

CLASS 9905-SIGNS, ADVERTISING DISPLAYS, AND IDENTIFICATION PLATES

PLATE, Modification record  
Aluminium

*Y1/9905-99-942-9495	7/8 in. lg. x 5/8 in. w.	Pressure sensitive; used on power unit, mains, No. 1	single	
*Y1/9905-99-901-3500	.875 in. lg. x .625 in. w. x .625 in. thk. x .625 in. thk.	Used on transponder set, M347	single	
*Y1/9905-99-901-3019	1 in. lg. x 5/16 in. w.	Used on radar, F.A., No. 8, Mk. 1	single	
*Y1/YA 12057	1.1/64 in. x 23/32 in. w. x .028 in.	Used on W/S. A40 and CPRC 26	single	
Y1/9905-99-901-3174	1.3/16 in. lg. x 9/16 in. x .004 thk.	Self adhesive (Old Cat. No. Y1/YA 10617); used on W/set B4 <sup>5</sup> /47	single	
*Y1/9905-99-100-4529	1.187 in. x 0.562 in. x x .028 in. thk.	Used on reception set, R 210 (Old Cat. No. Y1/YA 9980)	single	
Y1/9905-99-942-9507	1.5/8 in. lg. x 1 in. x .028 in. thk.	Used on B.I.D. 610 (Old Cat. No. Y1/YA 8197)	single	
Y1/9905-99-901-0238	3.1/2 in. x 2.1/4 in. x .036 in. thk.	(Old Cat. No. Y1/YA 8196)	single	

## SECTION Y1

## APPENDIX A

Items declared obsolete since last amendment to previous edition  
(NOT covered by normal monthly amendment notifications)

Cat. No.	Item name or designation
Y1/YA 5129	ADAPTOR, Spindle, drum, carrying, No. 1
Y1/ZB 0023	AMPLIFIER, Portable, P.A. No. 1, Mk. 1
Y1/YA 0002	APPARATUS, Aerial signalling ground indicator
Y1/YA 0003	A
Y1/YA 0004	B method 1
Y1/YA 0005	C
Y1/YA 0006	D
Y1/YA 0008	E
Y1/YA 0009	G
Y1/YA 0010	H
Y1/YA 3964	J
Y1/YA 3965	K
Y1/YA 6129	L
Y1/YA 6136	M
Y1/YA 6136	APPARATUS, Aerial signalling strip 16 ft. x 6.1/2 ft.
Y1/YA 5282	APPARATUS, Cable Laying No. 8
Y1/YA 0223	ARMATURE, B
Y1/YA 3278	BAND, Brake, No. 3
Y1/YA 0153	BELL, Battery, No. 13A
Y1/YA 2356	BLOCK, Terminal, No. 12
Y1/YA 2585	BOBBIN, Buzzer
Y1/YA 2506	F, Mk. 2
Y1/YA 5600	Signalling training
Y1/YA 0621	BOLT, No. 3
Y1/YA 3930	BOX, No. 1 fullerphone
Y1/YA 0221	BUSH, Split, B
Y1/YA 4139	BUZZER
Y1/YA 7085	F, Mk. 2
Y1/YA 7387	F, Mk. 2/1
Y1/YA 7646	F, Mk. 2/2
Y1/YA 5689	CAPPING, Wood
Y1/YA 3932	CASE, Stowage, trailers, C.L. equipment
Y1/YA 7647	CARRIER
Y1/YA 0625	Armature, B, No. 2
Y1/YA 5065	Screw, contact, B
Y1/YA 2512	CHAIN, Supporting, trailers, C.L. equipment
Y1/YA 7036	CHDKE, No. 1
Y1/YA 5742	COIL, Induction, No. 9
Y1/YA 7666	COLLAR, Spindle, No. 1
	CORD
	Connector telephone
	Instrument, No. 2/35A, brown 96 in.
	Telephone Hand, No. 6

## SECTION Y1

## APPENDIX A - continued

Cat. No.	Item name or designation
	INSTRUCTION, Working
Y1/YA 8041	Cable-laying equipment
Y1/YA 8026	Equipment, multiphone, A.D. 800/1
Y1/YA 8027	Equipment, multiphone, A.D. 1316
Y1/YA 8208	Lamps, signalling, daylight, short range
Y1/YA 8056	Telephone set, J
	INSULATOR
Y1/YA 6869	Field bolts, Mk. 5
Y1/YA 3937	Yokes B
	JACK
Y1/ZA 31087	No. 3
Y1/YA 0817	No. 500A
Y1/YA 7802	No. 8 tpl.
Y1/YA 5821	No. 21
Y1/YA 4493	No. 800 B2
Y1/YA 3053	JACK, Lamp, No. 32
Y1/YA 4860	JAW, Ratchet and tongs, No. 1
Y1/YA 7189	KEEPER, Terminal, black moulded type
	KEY
Y1/YA 5097	Feather
Y1/YA 3515	No. 2 (W.D.)
Y1/YA 7086	No. 7 (W.D.)
	KEYMOUNTING
Y1/YA 5060	PE
Y1/YA 7041	R
Y1/YA 6897	KEY, Signalling, No. 2
	LABEL
Y1/YA 0917	Line, C
Y1/YA 0918	Line, D
Y1/YA 0919	Line, E
Y1/YA 4850	Line, O
Y1/YA 6342	No. 21, White
Y1/YA 0914	No. 115, white
Y1/YA 1043	LAMP, Signalling, yard arm, Mk. 2
Y1/YA 6296	LAMPHOLDER, Special, No. 1
	LEVER, Brake
Y1/YA 5018	Horizontal
Y1/YA 3277	No. 1
Y1/YA 5019	LEVER, Clutch
Y1/YA 3248	LEVER, Crank, No. 2
	LID
Y1/YA 7719	Battery box and signalling key
Y1/YA 5678	No. 2
Y1/YA 8361	LIFTER, Pole, 10 ft.
Y1/YA 4905	LINE, Unit tel. attachments, hdgr., No. 2, Mk. 1
Y1/YA 2771	LINING, Brake, band, No. 1
Y1/YA 3094	LINK, Connecting, No. 1
Y1/ZB 0051	LOUDSPEAKER, Re-entrant, 500 ohms, No. 1
Y1/YA 5145	L.S., tel., No. 2, unmounted

## SECTION Y1

## APPENDIX A - continued

Cat. No.	Item name or designation
Y1/YA 8212 Y1/YA 3131	CORDAGE, Instrument 4M, khaki N. 15/F black.
Y1/YA 5014 Y1/YA 5192 Y1/YA 3935	COVER Brake, gear. Resistance, No. 2 Screw, gland, B
Y1/YA 4875 Y1/YA 7333	DRUM Brake, No. 2 Driving, No. 2
Y1/YA 30863	EAR-CUSHION
Y1/YA 5024 Y1/YA 4889	FRAME, Apparatus, cable-laying, No. 3, Mk. 1 FRAME, Barrow, drum, W.D. Mk. 2
Y1/YA 5646 Y1/YA 5647	FRAME, Fullerphone No. 1 No. 2
Y1/YA 0618 Y1/YA 4138 Y1/YA 6916	FULLERPHONE Mk. 4 Mk. 4/1 Mk. 5
Y1/YA 9961	FUSE, No. 21/25
Y1/YA 5090	GRILL, Loudspeaker, No. 2
Y1/YA 3258 Y1/YA 5619 Y1/YA 5613	GRIP, Handle Cranked Cranked, No. 3 No. 3
Y1/YA 4886 Y1/YA 7329	GUARD CHAIN No. 6 No. 7
Y1/YA 3257 Y1/YA 3264 Y1/YA 3263 Y1/YA 4845 Y1/YA 3111 Y1/YA 7154 Y1/YA 7153	HANDLE Cranked, No. 2 Frame, slotted Frame, unslotted Generator, CN Generator, No. 7 Slotted assembly Unslotted assembly
Y1/YA 3831	HEADBAND, C., No. 3
Y1/YA 5664 Y1/YA 5680	HINGE No. 2 No. 3
Y1/YA 7493 Y1/ZA 5371/1	HOLDER Brake, block, A.C.L., No. 8 Microphone assembly, No. 3
Y1/YA 5648 Y1/YA 4179	HOUSING Buzzer Socket

## SECTION Y1

## APPENDIX A - continued

Cat. No.	Item name or designation
Y1/YA 3941	MAGNET, B
Y1/ZA 25224 Y1/ZA 5414 Y1/ZA 5369/1 Y1/ZA 5369/2	MICROPHONE Hand (ITE), No. 18 Moving coil, No. 1 Respirator, No. 1, case Respirator, No. 1, cover
Y1/ZA 19605	MICROPHONE and Receiver headgear assy. No. 5, Mk. 2
Y1/YA 5697	MOUNTING, Assembly
Y1/YA 2890	MOUNTING, Dial, automatic, No. 13
Y1/YA 4870	NUT, Spec., wheel hub.
Y1/YA 4888 Y1/YA 4871	PACKER Hardwood M.S.
Y1/YA 4872	PAD, Felt
Y1/YA 5649 Y1/YA 7989 Y1/ZA 26634 Y1/ZA 26633 Y1/YA 5650	PANEL Front, No. 30 Front, No. 63 Tag, 9-way, 5.1/4 in. x 1 in., No. 1 Tag, 18-way, 9.1/2 in. x 2 in., No. 1 Top, No. 1
Y1/YA 5651	PILLAR, Choke mounting
Y1/YA 4862 Y1/YA 4877 Y1/YA 3262 Y1/YA 4900	PIN Brake lever Retaining, brake band Shackle, jointed Tapered
Y1/YA 3940 Y1/YA 4873 Y1/YA 4989 Y1/YA 5652 Y1/YA 4878 Y1/YA 5653 Y1/YA 5654 Y1/YA 5655 Y1/YA 8072 Y1/YA 3931 Y1/YA 5688 Y1/YA 4950 Y1/YA 5699 Y1/YA 5666 Y1/YA 5667 Y1/YA 7990 Y1/YA 5083 Y1/YA 5687 Y1/YA 4861 Y1/YA 4860 Y1/YA 2905 Y1/YA 5682 Y1/YA 5706 Y1/YA 5703 Y1/YA 5668 Y1/YA 5669 Y1/YA 5683 Y1/YA 5072 Y1/YA 5657	PLATE Armature, B Axle bearing, No. 1 Axle bearing, No. 2 Base, No. 8 Bearing, brake lever Clamping, No. 7 Connection, No. 10 Connector, protecting Contract, buzzers F, Mk. 2/2 Cover B, No. 1 Cover B, No. 2 Designation, D Designation, No. 3 Diagram, fullerphone, Mk. 4 Diagram, fullerphone, Mk. 4/1 Diagram, fullerphone, Mk. 5 Escutcheon, No. 48 (W.D.) Escutcheon, No. 50 (W.D.) Fixing, frame, handle, slotted Fixing, frame, handle, unslotted Instruction, No. 2 Instruction, No. 4 fullerphone Instruction, No. 28 Insulating, terminal, No. 8 Locking, No. 5 Locking, No. 6 Locking, No. 7 Mounting, condenser, No. 1 Mounting, No. 19

## SECTION Y1

## APPENDIX A - continued

Cat. No.	Item name or designation
	PLATE - continued
Y1/YA 5704	Panel, front, No. 1
Y1/YA 5670	Retaining, headgear
Y1/YA 4470	Terminal, line, fullerphone
	PLUNGER
Y1/YA 2515	Drum, air line
Y1/YA 4893	Spindle
Y1/YA 0042	POUCH, Leather, No. 3
	RAIL
Y1/YA 7978	Guard, L.H., No. 1
Y1/YA 7916	Guard, L.H. trailers, 10 cwt., G.S., Mk. 2
Y1/YA 7915	Guard, R.H. trailers, 10 cwt., G.S., Mk. 2
	RECEIVER, Headgear
Y1/ZA 29234	C.H.R. double, No. 9A
Y1/ZA 18207	C.H.R. double No. 20
Y1/ZA 18206	C.L.R. double, No. 3
Y1/YA 1281	C.L.R. single, Mk. 4
Y1/ZA 30314	D.H.R. double, No. 5H
Y1/ZA 15037	D.L.R. double, No. 5
Y1/YA 9498	D.L.R. double, No. 5R
Y1/YA 8309	S.P. No. 2C
Y1/YA 0227	REED, Contact B
	RELAY
Y1/YA 7724	H.S., No. 5
Y1/YA 7396	No. 3000 Type (W.D.) C.R.
Y1/YA 7397	No. 3000 Type (W.D.) C.S.
	RING
Y1/YA 0226	Locking B
Y1/YA 8111	Ring
	SACK
Y1/YA 5821	No. 21
Y1/YA 0817	No. 500A
	SCREW
Y1/YA 4114	Contact, B, Mk. 2
Y1/YA 7166	Contact, B, Mk. 2/1
Y1/YA 3934	Gland, B
Y1/YA 5069	Set, special, B.S.F., steel, 5/16 x 13/16
Y1/YA 5915	Special, B.A., brass
Y1/YA 1428	SHUTTER, Sig., folding
	SOCKET
Y1/YA 0180	Belt, reel cable, No. 2
Y1/YA 2729	Contact, 5 pair, No. 1 1/5
Y1/YA 2730	Contact, 5 pair, No. 1 6/10
Y1/YA 1439	Coupling, No. 1
Y1/YA 4348	Plain, carrier
Y1/YA 4895	Spare spindle
Y1/YA 4347	Spring-loaded carrier, spare spindle
Y1/YA 3268	SPANNER, Box, D.E.
Y1/YA 4879	SPINDLE, Sprocket driving
	SPRING
Y1/YA 0229	Armature, B
Y1/YA 5013	Catch.
Y1/YA 0622	No. 5
Y1/YA 5658	Plate, contact
Y1/YA 2516	Plunger, drum, air line

## SECTION Y1

## APPENDIX A - continued

Cat. No.	Item name or designation
Y1/YA 3272	SPROCKET, Driving
Y1/YA 4896	STAY, Body
Y1/YA 4897	Diagonal
	Vertical
Y1/YA 5106	STEP, Pole, No. 2 (for iron poles)
	STRAP
Y1/ZA 26640	Carrying, No. 14
Y1/YA 7648	Safety, trailers, C.L. equipment
Y1/YA 7651	Securing, ladders and poles, trailers, G.S., Mk. 2
Y1/YA 7653	Securing, ladders and poles, trailers, light cargo
Y1/YA 7980	Securing, web, 1.1/2 in. x 24 in.; No. 1
Y1/YA 6899	Shoulder, type B
Y1/YA 7644	Strengthening, trailers, G.S., Mk. 2
	STRIP
Y1/YA 7496	Connection, No. 97
Y1/YA 3936	Insulating, B.
Y1/YA 6329	Rawhide
Y1/YA 7190	Terminal assy. "K"
Y1/YA 7191	Terminal assy. "L"
Y1/YA 0632	SWITCH, On and off, No. 1
Y1/YA 4923	SWITCH, Press button, S.P., No. 1A
Y1/YA 4920	SWITCHBOARD, U.C., civil line units, Mk. 1/1
Y1/YA 3929	TAG, Armature, B
Y1/YA 3933	TAG, Screw, contact, B
Y1/YA 4904	TELEPHONE, Attachment, headgear, double, No. 2, Mk. 1
Y1/YA 3835	TELEPHONE, Hand, No. 2A
Y1/YA 7590	TELEPHONE, Hand (S.P.) No. 2A
Y1/YA 7412	TELEPHONE, No. 164, black
Y1/YA 4159	TELEPHONE, Loudspeaking, No. 2 switch reply
Y1/YA 4925	TELEPHONE UNIT, Loudspeaking, No. 1
Y1/YA 9782	TESTER, No. 86
	TRANSFORMER, Microphone
Y1/YA 5052	"B"
Y1/YA 5053	"C"
Y1/YA 7846	UNISELECTOR, No. 50, modified
Y1/YA 7200	UNIT, Resistance, 30 amp., 0.1 ohm.
	WASHER
Y1/YA 5071	M.S.
Y1/YA 5080	Packing, No. 3
Y1/YA 4986	Sealing

## Section Y1

## INDEX TO CATALOGUE NUMBERS

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/FV 23432	196	Y1/YA 0477	163	Y1/YA 0924	75
Y1/HH 0700	47			Y1/YA 0925	75
Y1/HH 0701	47			Y1/YA 0931	47
				Y1/YA 0934	47
				Y1/YA 0942	153
		Y1/YA 0502	269	Y1/YA 0948	158
		Y1/YA 0511	272	Y1/YA 0953	157
Y1/WB 2450	251	Y1/YA 0513	273	Y1/YA 0961	160
		Y1/YA 0522	274	Y1/YA 0962	160
		Y1/YA 0523	275	Y1/YA 0966	152
		Y1/YA 0524	275		
		Y1/YA 0529	207		
Y1/YA 0013	297	Y1/YA 0532	207		
Y1/YA 0041	26	Y1/YA 0535	246	Y1/YA 1000	153
Y1/YA 0043	27	Y1/YA 0570	257	Y1/YA 1001	153
Y1/YA 0044	28	Y1/YA 0571	258	Y1/YA 1002	153
Y1/YA 0053	18			Y1/YA 1009	153
Y1/YA 0058	21			Y1/YA 1011	154
Y1/YA 0059	21			Y1/YA 1012	160
Y1/YA 0060	21	Y1/YA 0629	162	Y1/YA 1014	159
Y1/YA 0061	21	Y1/YA 0630	73	Y1/YA 1015	160
Y1/YA 0062	22	Y1/YA 0659	35	Y1/YA 1057	76
Y1/YA 0064	27	Y1/YA 0662	63	Y1/YA 1061	33
Y1/YA 0067	30	Y1/YA 0664	64	Y1/YA 1063	33
Y1/YA 0099	242	Y1/YA 0665	65	Y1/YA 1064	33
		Y1/YA 0684	246	Y1/YA 1066	299
		Y1/YA 0686	32	Y1/YA 1068	299
		Y1/YA 0687	32	Y1/YA 1073	247
Y1/YA 0125	17	Y1/YA 0688	32	Y1/YA 1084	161
Y1/YA 0133	32	Y1/YA 0689	32		
Y1/YA 0154	51				
Y1/YA 0162	283			Y1/YA 1112	247
Y1/YA 0166	51			Y1/YA 1149	247
Y1/YA 0174/3	285	Y1/YA 0712	154	Y1/YA 1158	85
Y1/YA 0176	32	Y1/YA 0778	67	Y1/YA 1182/1	174
Y1/YA 0177	32	Y1/YA 0780	214	Y1/YA 1185	48
Y1/YA 0178	298	Y1/YA 0794	241		
Y1/YA 0182	252	Y1/YA 0795	239		
Y1/YA 0187	292	Y1/YA 0796	239		
Y1/YA 0196	277				
				Y1/YA 1201	48
				Y1/YA 1244	94
Y1/YA 0222	283	Y1/YA 0800	240	Y1/YA 1246	95
Y1/YA 0225	285	Y1/YA 0805	240	Y1/YA 1247	95
Y1/YA 0228	37	Y1/YA 0806	240	Y1/YA 1248	96
		Y1/YA 0814	176		
		Y1/YA 0821	247		
		Y1/YA 0846	69		
		Y1/YA 0857	68		
Y1/YA 0427	244	Y1/YA 0862	72	Y1/YA 1302	233
Y1/YA 0428	244	Y1/YA 0871	72	Y1/YA 1388	241
Y1/YA 0430	244			Y1/YA 1389	14
Y1/YA 0445	298			Y1/YA 1390	14
Y1/YA 0446	298			Y1/YA 1391	14
Y1/YA 0448	298			Y1/YA 1395	14
Y1/YA 0449	300	Y1/YA 0907	71	Y1/YA 1396	14
Y1/YA 0450	245	Y1/YA 0915	75	Y1/YA 1397	14
Y1/YA 0451	246	Y1/YA 0916	75	Y1/YA 1398	15
Y1/YA 0452	246	Y1/YA 0920	75	Y1/YA 1399	15
Y1/YA 0459	55	Y1/YA 0921	75		
Y1/YA 0464	200	Y1/YA 0922	75		
Y1/YA 0467	201	Y1/YA 0923	75		



## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 2599	165	Y1/YA 2814	224	Y1/YA 3110	296
		Y1/YA 2815	215	Y1/YA 3119	70
		Y1/YA 2816	225	Y1/YA 3121	70
		Y1/YA 2830	265	Y1/YA 3127	77
		Y1/YA 2831	265	Y1/YA 3132	107
Y1/YA 2636/3	65	Y1/YA 2832	266	Y1/YA 3133	209
		Y1/YA 2856	226	Y1/YA 3144	243
		Y1/YA 2857	207	Y1/YA 3145	243
		Y1/YA 2858	69	Y1/YA 3149	121
		Y1/YA 2860	199	Y1/YA 3154	59
Y1/YA 2703	251	Y1/YA 2861	201	Y1/YA 3172	89
Y1/YA 2707	56	Y1/YA 2862	199	Y1/YA 3176	285
Y1/YA 2709	253	Y1/YA 2863	202	Y1/YA 3177	57
Y1/YA 2710	18	Y1/YA 2873	55	Y1/YA 3190	52
Y1/YA 2711	18	Y1/YA 2873/2	239		
Y1/YA 2715	253	Y1/YA 2873/3	239		
Y1/YA 2717	182	Y1/YA 2873/4	239		
Y1/YA 2718	182	Y1/YA 2873/5	87		
Y1/YA 2719	277	Y1/YA 2873/6	87	Y1/YA 3201	289
Y1/YA 2722	85	Y1/YA 2873/7	90	Y1/YA 3202	289
Y1/YA 2723	187	Y1/YA 2874	93	Y1/YA 3204	169
Y1/YA 2724	181	Y1/YA 2875	106	Y1/YA 3206	209
Y1/YA 2725	181	Y1/YA 2876	166	Y1/YA 3207	213
Y1/YA 2726	257	Y1/YA 2878	63	Y1/YA 3209	237
Y1/YA 2727	258	Y1/YA 2881	251	Y1/YA 3210	234
Y1/YA 2731	272	Y1/YA 2882	253	Y1/YA 3212	181
Y1/YA 2732	109	Y1/YA 2883	258	Y1/YA 3221	129
Y1/YA 2739	176	Y1/YA 2884	258	Y1/YA 3230	84
Y1/YA 2740	99	Y1/YA 2886	119	Y1/YA 3232	39
Y1/YA 2741	79	Y1/YA 2889	59	Y1/YA 3233	177
Y1/YA 2742	234			Y1/YA 3234	155
Y1/YA 2743	273			Y1/YA 3236	80
Y1/YA 2753	269			Y1/YA 3245	273
Y1/YA 2754	182			Y1/YA 3255	99
Y1/YA 2767	155	Y1/YA 2922	182	Y1/YA 3236	99
Y1/YA 2768	155	Y1/YA 2923	182	Y1/YA 3259	29
Y1/YA 2772	13	Y1/YA 2939	85	Y1/YA 3265	27
Y1/YA 2773	187	Y1/YA 2954	159	Y1/YA 3266	27
Y1/YA 2774	187	Y1/YA 2957	187	Y1/YA 3269	26
Y1/YA 2776	156	Y1/YA 2958	102	Y1/YA 3270	29
Y1/YA 2777	159			Y1/YA 3271	30
Y1/YA 2778	126			Y1/YA 3273	79
Y1/YA 2779	159			Y1/YA 3285	178
Y1/YA 2790	155			Y1/YA 3289	177
Y1/YA 2792	156	Y1/YA 3000	73	Y1/YA 3293	183
Y1/YA 2793	156	Y1/YA 3011	69		
Y1/YA 2794	156	Y1/YA 3012	260		
Y1/YA 2796	133	Y1/YA 3020	56		
Y1/YA 2797	219	Y1/YA 3021	280		
Y1/YA 2798	203	Y1/YA 3022	104	Y1/YA 3306	105
Y1/YA 2799	128	Y1/YA 3045	103	Y1/YA 3317	269
		Y1/YA 3046	103	Y1/YA 3319	232
		Y1/YA 3047	248	Y1/YA 3328	266
		Y1/YA 3048	248	Y1/YA 3329	242
		Y1/YA 3052	175	Y1/YA 3330	35
		Y1/YA 3054	177	Y1/YA 3331	36
Y1/YA 2800	203	Y1/YA 3062	172	Y1/YA 3332	241
Y1/YA 2801	51	Y1/YA 3063	53	Y1/YA 3333	247
Y1/YA 2803	133	Y1/YA 3064	17	Y1/YA 3334	47
Y1/YA 2804	219	Y1/YA 3067	232	Y1/YA 3336	97
Y1/YA 2804/1	214	Y1/YA 3068	121	Y1/YA 3339	250
Y1/YA 2810	224	Y1/YA 3096	244	Y1/YA 3347	17
Y1/YA 2810/1	213			Y1/YA 3364	78
Y1/YA 2812	259			Y1/YA 3366	203
Y1/YA 2813	224				

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 1400	15	Y1/YA 1705	55	Y1/YA 2308	221
Y1/YA 1401	15			Y1/YA 2309	225
Y1/YA 1402	15			Y1/YA 2319	247
Y1/YA 1403	15			Y1/YA 2328	27
Y1/YA 1404	15			Y1/YA 2343	18
Y1/YA 1405	15	Y1/YA 1853	118	Y1/YA 2347	187
Y1/YA 1406	15	Y1/YA 1853/5	77	Y1/YA 2349	242
Y1/YA 1407	15	Y1/YA 1853/6	79	Y1/YA 2350	242
Y1/YA 1413	37	Y1/YA 1853/7	81	Y1/YA 2351	186
Y1/YA 1414	37	Y1/YA 1860	72	Y1/YA 2352	186
Y1/YA 1468	34	Y1/YA 1867	52	Y1/YA 2353	186
Y1/YA 1473	292	Y1/YA 1872	105	Y1/YA 2354	185
Y1/YA 1475	291	Y1/YA 1876	176	Y1/YA 2358	35
Y1/YA 1478	291	Y1/YA 1877	93	Y1/YA 2369	55
Y1/YA 1480	293	Y1/YA 1881	169	Y1/YA 2370	200
Y1/YA 1487	161	Y1/YA 1881/1	166	Y1/YA 2373	163
Y1/YA 1489	154	Y1/YA 1882	169	Y1/YA 2374	163
Y1/YA 1495	155	Y1/YA 1885	52	Y1/YA 2375	253
Y1/YA 1496	157	Y1/YA 1886	99	Y1/YA 2376	253
Y1/YA 1497	157	Y1/YA 1887	101	Y1/YA 2380	265
		Y1/YA 1896	69	Y1/YA 2384	237
		Y1/YA 1897	80	Y1/YA 2386	36
		Y1/YA 1898	113	Y1/YA 2387	35
		Y1/YA 1899	114		
Y1/YA 1505	161			Y1/YA 2462	69
Y1/YA 1514	34			Y1/YA 2470	265
Y1/YA 1515	34	Y1/YA 2051	177	Y1/YA 2481	300
Y1/YA 1516	34				
Y1/YA 1517	34				
Y1/YA 1518	34				
Y1/YA 1519	34				
Y1/YA 1522	34				
Y1/YA 1524	34				
Y1/YA 1525	34	Y1/YA 2101	189		
Y1/YA 1526	34	Y1/YA 2173	120	Y1/YA 2511	19
Y1/YA 1527	250	Y1/YA 2174	120	Y1/YA 2513	18
Y1/YA 1532	299	Y1/YA 2175	61	Y1/YA 2517	29
Y1/YA 1533	299	Y1/YA 2176	35	Y1/YA 2520	240
Y1/YA 1534	104	Y1/YA 2177	35	Y1/YA 2526	265
Y1/YA 1549	59	Y1/YA 2178	291	Y1/YA 2527	266
Y1/YA 1558	121	Y1/YA 2185	204	Y1/YA 2540	180
Y1/YA 1585	270	Y1/YA 2194	121	Y1/YA 2541	180
Y1/YA 1586	270	Y1/YA 2196	120	Y1/YA 2548	19
Y1/YA 1596	163	Y1/YA 2196/1	100	Y1/YA 2549	19
Y1/YA 1597	109	Y1/YA 2196/2	235	Y1/YA 2551	19
Y1/YA 1598	109	Y1/YA 2196/4	99	Y1/YA 2552	19
		Y1/YA 2196/5	228	Y1/YA 2553	19
		Y1/YA 2196/7	180	Y1/YA 2554	19
				Y1/YA 2555	19
Y1/YA 1600	109			Y1/YA 2556	20
Y1/YA 1601	109			Y1/YA 2557	20
Y1/YA 1626	281	Y1/YA 2209	125	Y1/YA 2558	20
Y1/YA 1640	39	Y1/YA 2216	72	Y1/YA 2559	20
Y1/YA 1686	111	Y1/YA 2230	107	Y1/YA 2562	125
Y1/YA 1688	288	Y1/YA 2257	284	Y1/YA 2563	125
Y1/YA 1697	111	Y1/YA 2271	101	Y1/YA 2570	241
Y1/YA 1699	111	Y1/YA 2273	63	Y1/YA 2586	283
		Y1/YA 2274	63	Y1/YA 2587	283
		Y1/YA 2275	63	Y1/YA 2588	283
		Y1/YA 2278	63	Y1/YA 2590	246
		Y1/YA 2279	65	Y1/YA 2591	245
Y1/YA 1700	111	Y1/YA 2280	211	Y1/YA 2592	245
Y1/YA 1701	111	Y1/YA 2282	176	Y1/YA 2597	164
				Y1/YA 2598	164

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 3367	204	Y1/YA 3720/2	285	Y1/YA 4113	235
Y1/YA 3369	167	Y1/YA 3731	178	Y1/YA 4115	298
Y1/YA 3370	233	Y1/YA 3745	258	Y1/YA 4118	299
Y1/YA 3371	202	Y1/YA 3746	287	Y1/YA 4119	259
Y1/YA 3372	101	Y1/YA 3747	287	Y1/YA 4126	105
		Y1/YA 3748	265	Y1/YA 4146	157
		Y1/YA 3749	265	Y1/YA 4147	158
		Y1/YA 3776	196	Y1/YA 4151	259
		Y1/YA 3777	169	Y1/YA 4154	224
Y1/YA 3414	261	Y1/YA 3788	173	Y1/YA 4158	133
Y1/YA 3420	54			Y1/YA 4168	78
Y1/YA 3441	97			Y1/YA 4169	79
Y1/YA 3443	241			Y1/YA 4170	79
Y1/YA 3444	241			Y1/YA 4171	79
Y1/YA 3445	241	Y1/YA 3804	201	Y1/YA 4174	240
Y1/YA 3448	252	Y1/YA 3806	120	Y1/YA 4198	60
Y1/YA 3449	252	Y1/YA 3807	49		
Y1/YA 3450	88	Y1/YA 3816	278		
Y1/YA 3455	36	Y1/YA 3817	278		
Y1/YA 3456	35	Y1/YA 3818	278		
Y1/YA 3478	242	Y1/YA 3819	278	Y1/YA 4220	77
Y1/YA 3479	242	Y1/YA 3828	261	Y1/YA 4221	75
Y1/YA 3485	97	Y1/YA 3833	71	Y1/YA 4225	90
Y1/YA 3486	246	Y1/YA 3870	281	Y1/YA 4252	112
Y1/YA 3492	83	Y1/YA 3874	203	Y1/YA 4259	209
Y1/YA 3493	84	Y1/YA 3885	272	Y1/YA 4290	266
Y1/YA 3494	84				
Y1/YA 3502	183	Y1/YA 3901	198	Y1/YA 4339	200
Y1/YA 3505	59	Y1/YA 3906	261	Y1/YA 4349	278
Y1/YA 3506	164	Y1/YA 3920	117	Y1/YA 4352	300
Y1/YA 3522	271	Y1/YA 3923	39	Y1/YA 4358	169
Y1/YA 3523	271	Y1/YA 3928	53	Y1/YA 4361	242
Y1/YA 3526	177	Y1/YA 3938	285		
Y1/YA 3529	178	Y1/YA 3945	18		
Y1/YA 3535	269	Y1/YA 3948	68		
Y1/YA 3536	269	Y1/YA 3953	243		
Y1/YA 3553	186	Y1/YA 3977	177	Y1/YA 4417	117
Y1/YA 3582	99	Y1/YA 3978	284	Y1/YA 4418	117
		Y1/YA 3981	177	Y1/YA 4424	78
		Y1/YA 3991	299	Y1/YA 4425	57
		Y1/YA 3992	299		
		Y1/YA 3994	199		
Y1/YA 3602	261	Y1/YA 3999	55		
Y1/YA 3624	239			Y1/YA 4606	208
Y1/YA 3628	246			Y1/YA 4619	56
Y1/YA 3629	67			Y1/YA 4620	207
Y1/YA 3649	183	Y1/YA 4000	61	Y1/YA 4621	58
Y1/YA 3650	183	Y1/YA 4002	33	Y1/YA 4624	80
Y1/YA 3654	64	Y1/YA 4006	121	Y1/YA 4652	107
Y1/YA 3658	77	Y1/YA 4009	270	Y1/YA 4653	209
Y1/YA 3662	172	Y1/YA 4010	270	Y1/YA 4660	255
		Y1/YA 4014	81	Y1/YA 4661	254
		Y1/YA 4016	54	Y1/YA 4662	207
		Y1/YA 4035	271	Y1/YA 4663	78
		Y1/YA 4080	300	Y1/YA 4664	83
Y1/YA 3706	265	Y1/YA 4083	104	Y1/YA 4665	85
Y1/YA 3712	36	Y1/YA 4090	117	Y1/YA 4667	41
Y1/YA 3714	54			Y1/YA 4672	172
Y1/YA 3717	119			Y1/YA 4674	201
Y1/YA 3719	65			Y1/YA 4675	65

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 4679	286	Y1/YA 5000	211	Y1/YA 5203	159
Y1/YA 4682	117	Y1/YA 5001	227	Y1/YA 5218	157
Y1/YA 4686	201	Y1/YA 5004	266	Y1/YA 5231	158
		Y1/YA 5005	266	Y1/YA 5232	155
		Y1/YA 5011	42	Y1/YA 5239	158
		Y1/YA 5017	24	Y1/YA 5240	160
		Y1/YA 5020	22	Y1/YA 5241	159
Y1/YA 4705	130	Y1/YA 5021	22	Y1/YA 5244	16
Y1/YA 4706	131	Y1/YA 5022	40	Y1/YA 5251	47
Y1/YA 4709	131	Y1/YA 5023	29	Y1/YA 5257	242
Y1/YA 4710	130	Y1/YA 5028	31	Y1/YA 5268	245
Y1/YA 4711	216	Y1/YA 5037	42	Y1/YA 5274	23
Y1/YA 4712	281	Y1/YA 5040	25	Y1/YA 5275	215
Y1/YA 4713	281	Y1/YA 5054	215	Y1/YA 5290	21
Y1/YA 4714	281	Y1/YA 5055	165	Y1/YA 5291	36
Y1/YA 4757	175	Y1/YA 5068	23	Y1/YA 5297	57
Y1/YA 4758	281	Y1/YA 5070	112		
Y1/YA 4773	109	Y1/YA 5088	273	Y1/YA 5309	174
Y1/YA 4774	109	Y1/YA 5093	55	Y1/YA 5311	168
Y1/YA 4777	109	Y1/YA 5094	93	Y1/YA 5351	101
Y1/YA 4778	182	Y1/YA 5095	170	Y1/YA 5361	188
Y1/YA 4779	76	Y1/YA 5098	227	Y1/YA 5379	41
Y1/YA 4780	82	Y1/YA 5099	227		
Y1/YA 4781	83				
Y1/YA 4782	83				
Y1/YA 4792	173				
Y1/YA 4797	285				
		Y1/YA 5101	51		
		Y1/YA 5108	243	Y1/YA 5413	102
		Y1/YA 5112	74	Y1/YA 5417	285
		Y1/YA 5123	77	Y1/YA 5418	73
Y1/YA 4816	40	Y1/YA 5130	202	Y1/YA 5421	278
Y1/YA 4820	167	Y1/YA 5131	65	Y1/YA 5436	191
Y1/YA 4821	85	Y1/YA 5132	79	Y1/YA 5442	68
Y1/YA 4823	37	Y1/YA 5133	86	Y1/YA 5447	77
Y1/YA 4824	37	Y1/YA 5134	50	Y1/YA 5449	87
Y1/YA 4841	119	Y1/YA 5135	209	Y1/YA 5450	87
Y1/YA 4843	169	Y1/YA 5138	67	Y1/YA 5451	91
Y1/YA 4844	52	Y1/YA 5139	44	Y1/YA 5456	89
Y1/YA 4848	133	Y1/YA 5141	39	Y1/YA 5465	89
Y1/YA 4849	117	Y1/YA 5143	92	Y1/YA 5479	64
Y1/YA 4851	300	Y1/YA 5150	57	Y1/YA 5499	90
Y1/YA 4864	95	Y1/YA 5151	66		
Y1/YA 4865	119	Y1/YA 5153	188		
Y1/YA 4867	262	Y1/YA 5155	85		
		Y1/YA 5156	87		
		Y1/YA 5157	87		
		Y1/YA 5158	88	Y1/YA 5502	38
		Y1/YA 5159	90	Y1/YA 5503	39
Y1/YA 4901	43	Y1/YA 5160	90	Y1/YA 5541	41
Y1/YA 4907	159	Y1/YA 5161	93	Y1/YA 5566	265
Y1/YA 4926	219	Y1/YA 5162	93	Y1/YA 5568	253
Y1/YA 4927	114	Y1/YA 5176	158	Y1/YA 5569	253
Y1/YA 4928	134	Y1/YA 5184	275	Y1/YA 5572	40
Y1/YA 4929	68	Y1/YA 5185	275	Y1/YA 5578	269
Y1/YA 4930	133	Y1/YA 5186	157	Y1/YA 5581	208
Y1/YA 4946	83	Y1/YA 5187	277	Y1/YA 5585	167
Y1/YA 4951	272	Y1/YA 5188	126	Y1/YA 5589	227
Y1/YA 4952	164	Y1/YA 5189	157	Y1/YA 5592	131
Y1/YA 4977	191	Y1/YA 5191	158	Y1/YA 5593	81
Y1/YA 4978	202	Y1/YA 5193	157	Y1/YA 5594	284
Y1/YA 4979	281	Y1/YA 5194	157	Y1/YA 5599	35
Y1/YA 4985	43				
Y1/YA 4987	44				

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 5602	243	Y1/YA 5897	23	Y1/YA 6047	73
Y1/YA 5604	239	Y1/YA 5898	23	Y1/YA 6048	74
Y1/YA 5605	239	Y1/YA 5899	25	Y1/YA 6049	74
Y1/YA 5607	39			Y1/YA 6050	74
Y1/YA 5637	232			Y1/YA 6051	73
Y1/YA 5639	33			Y1/YA 6052	73
Y1/YA 5640	33			Y1/YA 6053	74
Y1/YA 5641	270	Y1/YA 5914	96	Y1/YA 6054	87
Y1/YA 5643	241	Y1/YA 5916	262	Y1/YA 6056	71
Y1/YA 5681	76	Y1/YA 5919	22	Y1/YA 6057	71
		Y1/YA 5920	25	Y1/YA 6058	270
		Y1/YA 5921	28	Y1/YA 6059	270
		Y1/YA 5922	30	Y1/YA 6061	74
		Y1/YA 5923	31	Y1/YA 6062	74
Y1/YA 5700	86	Y1/YA 5924	31	Y1/YA 6063	73
Y1/YA 5715	58	Y1/YA 5925	31	Y1/YA 6064	73
Y1/YA 5716	60	Y1/YA 5926	31	Y1/YA 6065	39
Y1/YA 5717	63	Y1/YA 5927	31	Y1/YA 6068	96
Y1/YA 5719	66	Y1/YA 5928	31	Y1/YA 6069	66
Y1/YA 5723	69	Y1/YA 5931	291	Y1/YA 6086	13
Y1/YA 5724	63	Y1/YA 5933	292	Y1/YA 6088	19
Y1/YA 5726	77	Y1/YA 5934	292	Y1/YA 6089	19
Y1/YA 5735	203	Y1/YA 5935	292	Y1/YA 6090	19
Y1/YA 5751	248	Y1/YA 5936	293	Y1/YA 6091	23
Y1/YA 5777	129	Y1/YA 5937	293	Y1/YA 6092	24
Y1/YA 5778	213	Y1/YA 5938	293	Y1/YA 6095	26
Y1/YA 5784	190	Y1/YA 5939	293	Y1/YA 6096	27
Y1/YA 5794	200	Y1/YA 5940	94	Y1/YA 6097	27
Y1/YA 5796	215	Y1/YA 5950	38	Y1/YA 6098	28
Y1/YA 5799	68	Y1/YA 5952	180	Y1/YA 6099	29
		Y1/YA 5953	93		
		Y1/YA 5961	281		
		Y1/YA 5968	285		
		Y1/YA 5982	80		
Y1/YA 5802	248	Y1/YA 5998	57	Y1/YA 6100	30
Y1/YA 5807	16	Y1/YA 5999	67	Y1/YA 6102	18
Y1/YA 5814	238			Y1/YA 6107	27
Y1/YA 5817	178			Y1/YA 6115	186
Y1/YA 5818	68			Y1/YA 6122	188
Y1/YA 5819	269			Y1/YA 6123	295
Y1/YA 5820	270	Y1/YA 6003	16	Y1/YA 6124	188
Y1/YA 5827	240	Y1/YA 6006	124	Y1/YA 6125	42
Y1/YA 5829	92	Y1/YA 6007	110	Y1/YA 6126	42
Y1/YA 5832	65	Y1/YA 6014	256	Y1/YA 6127	107
Y1/YA 5833	81	Y1/YA 6015	256	Y1/YA 6131	297
Y1/YA 5837	234	Y1/YA 6017	264	Y1/YA 6142	19
Y1/YA 5841	274	Y1/YA 6018	267	Y1/YA 6149	184
Y1/YA 5847	271	Y1/YA 6020	64	Y1/YA 6150	181
Y1/YA 5848	271	Y1/YA 6023	37	Y1/YA 6152	170
Y1/YA 5849	243	Y1/YA 6026	90	Y1/YA 6153	100
Y1/YA 5854	251	Y1/YA 6029	92	Y1/YA 6154	100
Y1/YA 5855	203	Y1/YA 6030	41	Y1/YA 6157	25
Y1/YA 5858	20	Y1/YA 6031	58	Y1/YA 6158	25
Y1/YA 5862	245	Y1/YA 6032	88	Y1/YA 6160	21
Y1/YA 5863	244	Y1/YA 6033	88	Y1/YA 6164	91
Y1/YA 5866	111	Y1/YA 6034	66	Y1/YA 6170	59
Y1/YA 5867	252	Y1/YA 6036	99	Y1/YA 6171	59
Y1/YA 5869	79	Y1/YA 6038	89	Y1/YA 6172	59
Y1/YA 5874	269	Y1/YA 6040	66	Y1/YA 6173	88
Y1/YA 5877	121	Y1/YA 6041	88	Y1/YA 6174	91
Y1/YA 5879	274	Y1/YA 6043	66	Y1/YA 6175	41
Y1/YA 5891	19	Y1/YA 6044	73	Y1/YA 6192	296
Y1/YA 5894	21	Y1/YA 6045	73	Y1/YA 6193	51
Y1/YA 5896	23	Y1/YA 6046	74		

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 6205	57	Y1/YA 6450	114	Y1/YA 6766	293
Y1/YA 6206	174	Y1/YA 6451	114		
Y1/YA 6207	174	Y1/YA 6456	80		
Y1/YA 6210	60	Y1/YA 6460	123		
Y1/YA 6211	66	Y1/YA 6473	297		
Y1/YA 6213	176	Y1/YA 6499	165	Y1/YA 6806	215
Y1/YA 6214	81			Y1/YA 6807	237
Y1/YA 6217	85			Y1/YA 6809	65
Y1/YA 6221	89			Y1/YA 6811	233
Y1/YA 6222	91			Y1/YA 6861	97
Y1/YA 6223	91	Y1/YA 6500	286	Y1/YA 6866	51
Y1/YA 6224	92	Y1/YA 6528	28	Y1/YA 6867	101
Y1/YA 6227	99	Y1/YA 6541	269	Y1/YA 6870	265
Y1/YA 6228	101	Y1/YA 6542	269	Y1/YA 6871	274
Y1/YA 6229	106	Y1/YA 6562	63	Y1/YA 6872	271
Y1/YA 6230	106			Y1/YA 6873	271
Y1/YA 6238	76			Y1/YA 6874	266
Y1/YA 6240	91			Y1/YA 6875	166
Y1/YA 6241	92			Y1/YA 6877	178
Y1/YA 6244	119	Y1/YA 6655	47	Y1/YA 6878	215
Y1/YA 6260	248	Y1/YA 6667	257	Y1/YA 6879	165
		Y1/YA 6675	41	Y1/YA 6898	267
		Y1/YA 6680	102		
		Y1/YA 6681	105		
		Y1/YA 6685	189		
		Y1/YA 6686	122		
Y1/YA 6306	157	Y1/YA 6690	82	Y1/YA 6900	17
Y1/YA 6324	36	Y1/YA 6691	87	Y1/YA 6902	242
Y1/YA 6326	245	Y1/YA 6693	244	Y1/YA 6908	44
Y1/YA 6327	245	Y1/YA 6697	286	Y1/YA 6909	256
Y1/YA 6335	174			Y1/YA 6910	256
Y1/YA 6337	70			Y1/YA 6911	257
Y1/YA 6339	70			Y1/YA 6917	248
Y1/YA 6345	104			Y1/YA 6919	37
Y1/YA 6347	215	Y1/YA 6701	286	Y1/YA 6928	17
Y1/YA 6349	78	Y1/YA 6703	296	Y1/YA 6929	25
Y1/YA 6351	262	Y1/YA 6704	296	Y1/YA 6937	25
Y1/YA 6354	24	Y1/YA 6706	37	Y1/YA 6938	25
Y1/YA 6355	20	Y1/YA 6707	42	Y1/YA 6940	77
Y1/YA 6357	29	Y1/YA 6708	37	Y1/YA 6941	22
Y1/YA 6360	299	Y1/YA 6709	38	Y1/YA 6951	170
Y1/YA 6362	37	Y1/YA 6725	62	Y1/YA 6989	119
Y1/YA 6371	118	Y1/YA 6726	62	Y1/YA 6990	295
Y1/YA 6375	165	Y1/YA 6728	95		
Y1/YA 6394	214	Y1/YA 6729	94		
		Y1/YA 6730	199		
		Y1/YA 6731	95		
		Y1/YA 6733	110	Y1/YA 7019	197
		Y1/YA 6738	112	Y1/YA 7020	197
Y1/YA 6401	238	Y1/YA 6739	181	Y1/YA 7021	197
Y1/YA 6404	283	Y1/YA 6742	87	Y1/YA 7022	197
Y1/YA 6408	129	Y1/YA 6743	81	Y1/YA 7023	197
Y1/YA 6410	129	Y1/YA 6748	84	Y1/YA 7024	197
Y1/YA 6418	255	Y1/YA 6752	65	Y1/YA 7025	197
Y1/YA 6419	129	Y1/YA 6754	93	Y1/YA 7026	197
Y1/YA 6423	76	Y1/YA 6755	66	Y1/YA 7027	197
Y1/YA 6436	36	Y1/YA 6756	85	Y1/YA 7028	197
Y1/YA 6437	111	Y1/YA 6757	93	Y1/YA 7029	197
Y1/YA 6439	263	Y1/YA 6758	255	Y1/YA 7030	197
Y1/YA 6442	41	Y1/YA 6759	255	Y1/YA 7031	197
Y1/YA 6444	216	Y1/YA 6760	255	Y1/YA 7032	197
Y1/YA 6445	130	Y1/YA 6761	254	Y1/YA 7033	197
Y1/YA 6448	132	Y1/YA 6762	255	Y1/YA 7034	196
Y1/YA 6449	134	Y1/YA 6763	184	Y1/YA 7035	196

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 7037	16	Y1/YA 7261	67	Y1/YA 7414	265
Y1/YA 7044	87	Y1/YA 7262	67	Y1/YA 7422	59
Y1/YA 7083	276	Y1/YA 7268	168	Y1/YA 7424	295
Y1/YA 7084	255	Y1/YA 7270	101	Y1/YA 7425	295
				Y1/YA 7426	295
				Y1/YA 7427	294
				Y1/YA 7428	121
				Y1/YA 7429	75
Y1/YA 7130	178	Y1/YA 7311	165	Y1/YA 7431	40
Y1/YA 7131	191	Y1/YA 7312	166	Y1/YA 7432	81
Y1/YA 7132	69	Y1/YA 7317	203	Y1/YA 7433	39
Y1/YA 7133	70	Y1/YA 7318	183	Y1/YA 7434	176
Y1/YA 7134	94	Y1/YA 7319	105	Y1/YA 7435	214
Y1/YA 7136	176	Y1/YA 7320	177	Y1/YA 7436	107
Y1/YA 7137	200	Y1/YA 7323	168	Y1/YA 7437	83
Y1/YA 7139	70	Y1/YA 7326	294	Y1/YA 7439	45
Y1/YA 7141	78	Y1/YA 7332	168	Y1/YA 7440	39
Y1/YA 7142	200	Y1/YA 7334	91	Y1/YA 7441	39
Y1/YA 7159	167	Y1/YA 7335	197	Y1/YA 7443	99
Y1/YA 7161	167	Y1/YA 7339	75	Y1/YA 7444	90
Y1/YA 7163	167	Y1/YA 7341	50	Y1/YA 7445	87
Y1/YA 7164	167	Y1/YA 7342	50	Y1/YA 7449	91
Y1/YA 7183	248	Y1/YA 7343	14	Y1/YA 7450	197
Y1/YA 7184	248	Y1/YA 7344	175	Y1/YA 7452	196
Y1/YA 7195	103	Y1/YA 7345	33	Y1/YA 7454	156
Y1/YA 7186	103	Y1/YA 7346	33	Y1/YA 7458	21
Y1/YA 7187	103	Y1/YA 7348	289	Y1/YA 7459	25
Y1/YA 7188	103	Y1/YA 7350	133	Y1/YA 7460	28
Y1/YA 7193	78	Y1/YA 7351	133	Y1/YA 7461	30
Y1/YA 7194	56	Y1/YA 7352	219	Y1/YA 7462	42
Y1/YA 7195	78	Y1/YA 7355	33	Y1/YA 7463	42
Y1/YA 7197	248	Y1/YA 7356	295	Y1/YA 7465	20
Y1/YA 7198	75	Y1/YA 7359	260	Y1/YA 7467	214
		Y1/YA 7360	260	Y1/YA 7470	71
		Y1/YA 7361	256	Y1/YA 7472	36
		Y1/YA 7365	177	Y1/YA 7473	269
		Y1/YA 7368	61	Y1/YA 7474	50
		Y1/YA 7369	95	Y1/YA 7475	17
Y1/YA 7201	106	Y1/YA 7370	108	Y1/YA 7476	96
Y1/YA 7202	175	Y1/YA 7374	78	Y1/YA 7479	97
Y1/YA 7206	123	Y1/YA 7375	177	Y1/YA 7480	44
Y1/YA 7207	123	Y1/YA 7376	177	Y1/YA 7481	44
Y1/YA 7208	287	Y1/YA 7379	61	Y1/YA 7482	97
Y1/YA 7212	71	Y1/YA 7380	61	Y1/YA 7483	67
Y1/YA 7213	71	Y1/YA 7381	95	Y1/YA 7486	97
Y1/YA 7215	71	Y1/YA 7383	175	Y1/YA 7487	120
Y1/YA 7217	71	Y1/YA 7384	79	Y1/YA 7492	19
Y1/YA 7219	71	Y1/YA 7389	289	Y1/YA 7495	104
Y1/YA 7220	71	Y1/YA 7390	53	Y1/YA 7497	58
Y1/YA 7222	266	Y1/YA 7391	83		
Y1/YA 7223	248	Y1/YA 7392	95		
Y1/YA 7224	248	Y1/YA 7398	108		
Y1/YA 7230	294			Y1/YA 7500	172
Y1/YA 7232	105			Y1/YA 7502	197
Y1/YA 7234	57			Y1/YA 7503	197
Y1/YA 7235	57			Y1/YA 7506	192
Y1/YA 7236	57	Y1/YA 7402	240	Y1/YA 7507	198
Y1/YA 7252	71	Y1/YA 7403	165	Y1/YA 7508	198
Y1/YA 7253	57	Y1/YA 7404	23	Y1/YA 7509	198
Y1/YA 7254	57	Y1/YA 7407	112	Y1/YA 7510	198
Y1/YA 7255	57	Y1/YA 7408	111	Y1/YA 7511	198
Y1/YA 7256	191	Y1/YA 7409	52	Y1/YA 7511	198
Y1/YA 7257	271	Y1/YA 7410	265	Y1/YA 7514	196
Y1/YA 7258	81	Y1/YA 7411	265	Y1/YA 7515	198

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 5602	243	Y1/YA 5897	23	Y1/YA 6047	73
Y1/YA 5604	239	Y1/YA 5898	23	Y1/YA 6048	74
Y1/YA 5605	239	Y1/YA 5899	25	Y1/YA 6049	74
Y1/YA 5607	39			Y1/YA 6050	74
Y1/YA 5637	232			Y1/YA 6051	73
Y1/YA 5639	33			Y1/YA 6052	73
Y1/YA 5640	33			Y1/YA 6053	74
Y1/YA 5641	270	Y1/YA 5914	96	Y1/YA 6054	87
Y1/YA 5643	241	Y1/YA 5916	262	Y1/YA 6056	71
Y1/YA 5681	76	Y1/YA 5919	22	Y1/YA 6057	71
		Y1/YA 5920	25	Y1/YA 6058	270
		Y1/YA 5921	28	Y1/YA 6059	270
		Y1/YA 5922	30	Y1/YA 6061	74
		Y1/YA 5923	31	Y1/YA 6062	74
Y1/YA 5700	86	Y1/YA 5924	31	Y1/YA 6063	73
Y1/YA 5715	58	Y1/YA 5925	31	Y1/YA 6064	73
Y1/YA 5716	60	Y1/YA 5926	31	Y1/YA 6065	39
Y1/YA 5717	63	Y1/YA 5927	31	Y1/YA 6068	96
Y1/YA 5719	66	Y1/YA 5928	31	Y1/YA 6069	66
Y1/YA 5723	69	Y1/YA 5931	291	Y1/YA 6086	13
Y1/YA 5724	63	Y1/YA 5933	292	Y1/YA 6088	19
Y1/YA 5726	77	Y1/YA 5934	292	Y1/YA 6089	19
Y1/YA 5735	203	Y1/YA 5935	292	Y1/YA 6090	19
Y1/YA 5751	248	Y1/YA 5936	293	Y1/YA 6091	23
Y1/YA 5777	129	Y1/YA 5937	293	Y1/YA 6092	24
Y1/YA 5778	213	Y1/YA 5938	293	Y1/YA 6095	26
Y1/YA 5784	190	Y1/YA 5939	293	Y1/YA 6096	27
Y1/YA 5794	200	Y1/YA 5940	94	Y1/YA 6097	27
Y1/YA 5796	215	Y1/YA 5950	38	Y1/YA 6098	28
Y1/YA 5799	68	Y1/YA 5952	180	Y1/YA 6099	29
		Y1/YA 5953	93		
		Y1/YA 5961	281		
		Y1/YA 5968	285		
		Y1/YA 5982	80		
Y1/YA 5802	248	Y1/YA 5998	57	Y1/YA 6100	30
Y1/YA 5807	16	Y1/YA 5999	67	Y1/YA 6102	18
Y1/YA 5814	238			Y1/YA 6107	27
Y1/YA 5817	178			Y1/YA 6115	186
Y1/YA 5818	68			Y1/YA 6122	188
Y1/YA 5819	269			Y1/YA 6123	295
Y1/YA 5820	270	Y1/YA 6003	16	Y1/YA 6124	188
Y1/YA 5827	240	Y1/YA 6006	124	Y1/YA 6125	42
Y1/YA 5829	92	Y1/YA 6007	110	Y1/YA 6126	42
Y1/YA 5832	65	Y1/YA 6014	256	Y1/YA 6127	107
Y1/YA 5833	81	Y1/YA 6015	256	Y1/YA 6131	297
Y1/YA 5837	234	Y1/YA 6017	264	Y1/YA 6142	19
Y1/YA 5841	274	Y1/YA 6018	267	Y1/YA 6149	184
Y1/YA 5847	271	Y1/YA 6020	64	Y1/YA 6150	181
Y1/YA 5848	271	Y1/YA 6023	37	Y1/YA 6152	170
Y1/YA 5849	243	Y1/YA 6026	90	Y1/YA 6153	100
Y1/YA 5854	251	Y1/YA 6029	92	Y1/YA 6154	100
Y1/YA 5855	203	Y1/YA 6030	41	Y1/YA 6157	25
Y1/YA 5858	20	Y1/YA 6031	58	Y1/YA 6158	25
Y1/YA 5862	245	Y1/YA 6032	88	Y1/YA 6160	21
Y1/YA 5863	244	Y1/YA 6033	88	Y1/YA 6164	91
Y1/YA 5866	111	Y1/YA 6034	66	Y1/YA 6170	59
Y1/YA 5867	252	Y1/YA 6036	99	Y1/YA 6171	59
Y1/YA 5869	79	Y1/YA 6038	89	Y1/YA 6172	59
Y1/YA 5874	269	Y1/YA 6040	66	Y1/YA 6173	88
Y1/YA 5877	121	Y1/YA 6041	88	Y1/YA 6174	91
Y1/YA 5879	274	Y1/YA 6043	66	Y1/YA 6175	41
Y1/YA 5891	19	Y1/YA 6044	73	Y1/YA 6192	296
Y1/YA 5894	21	Y1/YA 6045	73	Y1/YA 6193	51
Y1/YA 5896	23	Y1/YA 6046	74		



## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 7517	198	Y1/YA 7670	82	Y1/YA 7860	29
Y1/YA 7532	17	Y1/YA 7674	166	Y1/YA 7861	21
Y1/YA 7535	41	Y1/YA 7678	261	Y1/YA 7862	29
Y1/YA 7536	287	Y1/YA 7682	17	Y1/YA 7863	31
Y1/YA 7537	287	Y1/YA 7684	165	Y1/YA 7864	258
Y1/YA 7538	287	Y1/YA 7686	200	Y1/YA 7865	258
Y1/YA 7539	38	Y1/YA 7688	201	Y1/YA 7866	258
Y1/YA 7540	60	Y1/YA 7689	79	Y1/YA 7867	261
Y1/YA 7541	38	Y1/YA 7691	96	Y1/YA 7868	261
Y1/YA 7542	57	Y1/YA 7692	179	Y1/YA 7873	221
Y1/YA 7543	66	Y1/YA 7693	169	Y1/YA 7875	65
Y1/YA 7544	104	Y1/YA 7695	153	Y1/YA 7885	124
Y1/YA 7549	71	Y1/YA 7698	239	Y1/YA 7887	81
Y1/YA 7550	89	Y1/YA 7699	239	Y1/YA 7890	78
Y1/YA 7551	40			Y1/YA 7892	269
Y1/YA 7552	88			Y1/YA 7893	269
Y1/YA 7553	89			Y1/YA 7894	98
Y1/YA 7554	105			Y1/YA 7895	98
Y1/YA 7555	40	Y1/YA 7700	153	Y1/YA 7896	270
Y1/YA 7556	57	Y1/YA 7703	162	Y1/YA 7897	270
Y1/YA 7557	287	Y1/YA 7704	159	Y1/YA 7898	247
Y1/YA 7558	105	Y1/YA 7705	45		
Y1/YA 7559	105	Y1/YA 7706	45		
Y1/YA 7560	105	Y1/YA 7710	157		
Y1/YA 7561	86	Y1/YA 7712	159		
Y1/YA 7562	86	Y1/YA 7713	159	Y1/YA 7905	64
Y1/YA 7563	87	Y1/YA 7714	211	Y1/YA 7908	265
Y1/YA 7564	87	Y1/YA 7715	227	Y1/YA 7911	122
Y1/YA 7565	86	Y1/YA 7716	266	Y1/YA 7917	283
Y1/YA 7566	87	Y1/YA 7717	63	Y1/YA 7918	295
Y1/YA 7567	86	Y1/YA 7720	300	Y1/YA 7923	203
Y1/YA 7568	86	Y1/YA 7722	265	Y1/YA 7924	211
Y1/YA 7571	165	Y1/YA 7723	190	Y1/YA 7925	297
Y1/YA 7574	40	Y1/YA 7728	74	Y1/YA 7928	114
Y1/YA 7575	102	Y1/YA 7730	98	Y1/YA 7931	56
Y1/YA 7578	177	Y1/YA 7733	41	Y1/YA 7932	125
Y1/YA 7580	196	Y1/YA 7735	294	Y1/YA 7935	51
Y1/YA 7581	196	Y1/YA 7745	277	Y1/YA 7939	55
Y1/YA 7586	243	Y1/YA 7782	60	Y1/YA 7940	62
Y1/YA 7587	173	Y1/YA 7786	50	Y1/YA 7941	45
Y1/YA 7588	215	Y1/YA 7793	289	Y1/YA 7942	277
Y1/YA 7589	57			Y1/YA 7943	296
Y1/YA 7594	56			Y1/YA 7944	89
Y1/YA 7598	266			Y1/YA 7945	89
Y1/YA 7599	265			Y1/YA 7946	93
		Y1/YA 7818	30	Y1/YA 7949	38
		Y1/YA 7820	25	Y1/YA 7950	38
		Y1/YA 7821	26	Y1/YA 7951	239
		Y1/YA 7822	25	Y1/YA 7952	43
Y1/YA 7619	24	Y1/YA 7823	26	Y1/YA 7953	43
Y1/YA 7621	298	Y1/YA 7824	24	Y1/YA 7954	170
Y1/YA 7622	298	Y1/YA 7825	24	Y1/YA 7955	87
Y1/YA 7623	49	Y1/YA 7826	24	Y1/YA 7959	273
Y1/YA 7624	47	Y1/YA 7827	24	Y1/YA 7960	65
Y1/YA 7625	299	Y1/YA 7829	18	Y1/YA 7961	100
Y1/YA 7630	153	Y1/YA 7830	31	Y1/YA 7962	101
Y1/YA 7631	153	Y1/YA 7832	17	Y1/YA 7967	69
Y1/YA 7633	154	Y1/YA 7833	23	Y1/YA 7972	46
Y1/YA 7663	92	Y1/YA 7834	17	Y1/YA 7973	46
Y1/YA 7664	53	Y1/YA 7835	28	Y1/YA 7974	294
Y1/YA 7665	121	Y1/YA 7836	27	Y1/YA 7975	295
Y1/YA 7667	273	Y1/YA 7844	155	Y1/YA 7976	295
Y1/YA 7668	33	Y1/YA 7856	294	Y1/YA 7977	295

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 7517	198	Y1/YA 7670	82	Y1/YA 7860	29
Y1/YA 7532	17	Y1/YA 7674	166	Y1/YA 7861	21
Y1/YA 7535	41	Y1/YA 7678	261	Y1/YA 7862	29
Y1/YA 7536	287	Y1/YA 7682	17	Y1/YA 7863	31
Y1/YA 7537	287	Y1/YA 7684	165	Y1/YA 7864	258
Y1/YA 7538	287	Y1/YA 7686	200	Y1/YA 7865	258
Y1/YA 7539	38	Y1/YA 7688	201	Y1/YA 7866	258
Y1/YA 7540	60	Y1/YA 7689	79	Y1/YA 7867	261
Y1/YA 7541	38	Y1/YA 7691	96	Y1/YA 7868	261
Y1/YA 7542	57	Y1/YA 7692	179	Y1/YA 7873	221
Y1/YA 7543	66	Y1/YA 7693	169	Y1/YA 7875	65
Y1/YA 7544	104	Y1/YA 7695	153	Y1/YA 7885	124
Y1/YA 7549	71	Y1/YA 7698	239	Y1/YA 7887	81
Y1/YA 7550	89	Y1/YA 7699	239	Y1/YA 7890	78
Y1/YA 7551	40			Y1/YA 7892	269
Y1/YA 7552	88			Y1/YA 7893	269
Y1/YA 7553	89			Y1/YA 7894	98
Y1/YA 7554	105			Y1/YA 7895	98
Y1/YA 7555	40	Y1/YA 7700	153	Y1/YA 7896	270
Y1/YA 7556	57	Y1/YA 7703	162	Y1/YA 7897	270
Y1/YA 7557	287	Y1/YA 7704	159	Y1/YA 7898	247
Y1/YA 7558	105	Y1/YA 7705	45		
Y1/YA 7559	105	Y1/YA 7706	45		
Y1/YA 7560	105	Y1/YA 7710	157		
Y1/YA 7561	86	Y1/YA 7712	159		
Y1/YA 7562	86	Y1/YA 7713	159	Y1/YA 7905	64
Y1/YA 7563	87	Y1/YA 7714	211	Y1/YA 7908	265
Y1/YA 7564	87	Y1/YA 7715	227	Y1/YA 7911	122
Y1/YA 7565	86	Y1/YA 7716	266	Y1/YA 7917	283
Y1/YA 7566	87	Y1/YA 7717	63	Y1/YA 7918	295
Y1/YA 7567	86	Y1/YA 7720	300	Y1/YA 7923	203
Y1/YA 7568	86	Y1/YA 7722	265	Y1/YA 7924	211
Y1/YA 7571	165	Y1/YA 7723	190	Y1/YA 7925	297
Y1/YA 7574	40	Y1/YA 7728	74	Y1/YA 7928	114
Y1/YA 7575	102	Y1/YA 7730	98	Y1/YA 7931	56
Y1/YA 7578	177	Y1/YA 7733	41	Y1/YA 7932	125
Y1/YA 7580	196	Y1/YA 7735	294	Y1/YA 7935	51
Y1/YA 7581	196	Y1/YA 7745	277	Y1/YA 7939	55
Y1/YA 7586	243	Y1/YA 7782	60	Y1/YA 7940	62
Y1/YA 7587	173	Y1/YA 7786	50	Y1/YA 7941	45
Y1/YA 7588	215	Y1/YA 7793	289	Y1/YA 7942	277
Y1/YA 7589	57			Y1/YA 7943	296
Y1/YA 7594	56			Y1/YA 7944	89
Y1/YA 7598	266			Y1/YA 7945	89
Y1/YA 7599	265			Y1/YA 7946	93
		Y1/YA 7818	30	Y1/YA 7949	38
		Y1/YA 7820	25	Y1/YA 7950	38
		Y1/YA 7821	26	Y1/YA 7951	239
		Y1/YA 7822	25	Y1/YA 7952	43
Y1/YA 7619	24	Y1/YA 7823	26	Y1/YA 7953	43
Y1/YA 7621	298	Y1/YA 7824	24	Y1/YA 7954	170
Y1/YA 7622	298	Y1/YA 7825	24	Y1/YA 7955	87
Y1/YA 7623	49	Y1/YA 7826	24	Y1/YA 7959	273
Y1/YA 7624	47	Y1/YA 7827	24	Y1/YA 7960	65
Y1/YA 7625	299	Y1/YA 7829	18	Y1/YA 7961	100
Y1/YA 7630	153	Y1/YA 7830	31	Y1/YA 7962	101
Y1/YA 7631	153	Y1/YA 7832	17	Y1/YA 7967	69
Y1/YA 7633	154	Y1/YA 7833	23	Y1/YA 7972	46
Y1/YA 7663	92	Y1/YA 7834	17	Y1/YA 7973	46
Y1/YA 7664	53	Y1/YA 7835	28	Y1/YA 7974	294
Y1/YA 7665	121	Y1/YA 7836	27	Y1/YA 7975	295
Y1/YA 7667	273	Y1/YA 7844	155	Y1/YA 7976	295
Y1/YA 7668	33	Y1/YA 7856	294	Y1/YA 7977	295

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 7981	301	Y1/YA 8135	131	Y1/YA 8289	280
Y1/YA 7982	221	Y1/YA 8146	259	Y1/YA 8290	164
Y1/YA 7985	195	Y1/YA 8147	260	Y1/YA 8292	45
Y1/YA 7986	211	Y1/YA 8148	184	Y1/YA 8293	86
Y1/YA 7991	89	Y1/YA 8149	115	Y1/YA 8294	86
		Y1/YA 8150	122	Y1/YA 8295	53
		Y1/YA 8152	70	Y1/YA 8296	39
		Y1/YA 8153	103	Y1/YA 8297	51
		Y1/YA 8154	55	Y1/YA 8298	283
		Y1/YA 8155	238		
Y1/YA 8001	294	Y1/YA 8156	293		
Y1/YA 8018	292	Y1/YA 8159	152		
Y1/YA 8019	198	Y1/YA 8160	271		
Y1/YA 8020	263	Y1/YA 8161	271	Y1/YA 8300	198
Y1/YA 8021	271	Y1/YA 8163	271	Y1/YA 8302	272
Y1/YA 8022	271	Y1/YA 8166	299	Y1/YA 8305	53
Y1/YA 8023	271	Y1/YA 8167	300	Y1/YA 8306	272
Y1/YA 8024	271	Y1/YA 8175	294	Y1/YA 8307	198
Y1/YA 8029	87	Y1/YA 8179	143	Y1/YA 8308	271
Y1/YA 8032	119	Y1/YA 8181	62	Y1/YA 8310	125
Y1/YA 8044	288	Y1/YA 8183	263	Y1/YA 8311	252
Y1/YA 8053	51	Y1/YA 8185	205	Y1/YA 8313	272
Y1/YA 8061	67	Y1/YA 8186	106	Y1/YA 8314	272
Y1/YA 8054	68	Y1/YA 8188	61	Y1/YA 8315	174
Y1/YA 8065	58	Y1/YA 8195	121	Y1/YA 8337	191
Y1/YA 8073	251	Y1/YA 8198	296	Y1/YA 8338	191
Y1/YA 8074	251			Y1/YA 8339	197
Y1/YA 8079	115			Y1/YA 8341	197
Y1/YA 8083	125			Y1/YA 8343	75
Y1/YA 8089	82			Y1/YA 8344	75
Y1/YA 8090	123	Y1/YA 8204	70	Y1/YA 8345	75
Y1/YA 8091	77	Y1/YA 8205	203	Y1/YA 8346	118
Y1/YA 8092	124	Y1/YA 8210	278	Y1/YA 8348	243
Y1/YA 8093	123	Y1/YA 8214	234	Y1/YA 8349	36
Y1/YA 8094	102	Y1/YA 8215	205	Y1/YA 8350	122
Y1/YA 8095	103	Y1/YA 8217	209	Y1/YA 8351	243
Y1/YA 8097	94	Y1/YA 8218	237	Y1/YA 8352	53
Y1/YA 8098	82	Y1/YA 8220	227	Y1/YA 8354	245
Y1/YA 8099	45	Y1/YA 8224	291	Y1/YA 8355	251
		Y1/YA 8232	115	Y1/YA 8356	164
		Y1/YA 8235	263	Y1/YA 8357	60
		Y1/YA 8236	76	Y1/YA 8358	22
		Y1/YA 8237	98	Y1/YA 8359	32
Y1/YA 8102	254	Y1/YA 8238	102	Y1/YA 8360	32
Y1/YA 8103	64	Y1/YA 8246	198	Y1/YA 8362	249
Y1/YA 8104	80	Y1/YA 8248	137	Y1/YA 8363	292
Y1/YA 8105	80	Y1/YA 8250	291	Y1/YA 8364	33
Y1/YA 8106	82	Y1/YA 8254	38	Y1/YA 8365	75
Y1/YA 8107	85	Y1/YA 8256	134	Y1/YA 8366	32
Y1/YA 8108	85	Y1/YA 8263	68	Y1/YA 8367	245
Y1/YA 8109	89	Y1/YA 8264	102	Y1/YA 8368	99
Y1/YA 8112	96	Y1/YA 8267	184	Y1/YA 8370	272
Y1/YA 8113	41	Y1/YA 8268	135	Y1/YA 8392	242
Y1/YA 8114	41	Y1/YA 8272	64		
Y1/YA 8115	202	Y1/YA 8274	135		
Y1/YA 8116	203	Y1/YA 8275	41		
Y1/YA 8118	43	Y1/YA 8277	179		
Y1/YA 8120	270	Y1/YA 8278	44		
Y1/YA 8121	763	Y1/YA 8279	167	Y1/YA 8439	217
Y1/YA 8123	221	Y1/YA 8280	207	Y1/YA 8447	245
Y1/YA 8125	177	Y1/YA 8281	85	Y1/YA 8448	243
Y1/YA 8126	69	Y1/YA 8282	121	Y1/YA 8473	61
Y1/YA 8129	163	Y1/YA 8284	135	Y1/YA 8481	217
Y1/YA 8130	183	Y1/YA 8285	72	Y1/YA 8488	186
Y1/YA 8132	197	Y1/YA 8288	53	Y1/YA 8498	64

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 8499	177	Y1/YA 9057	55	Y1/YA 9310	116
		Y1/YA 9059	113	Y1/YA 9311	116
				Y1/YA 9317	75
Y1/YA 8502	217			Y1/YA 9322	52
Y1/YA 8515	217	Y1/YA 9104	62	Y1/YA 9325	113
Y1/YA 8585	52	Y1/YA 9107	62	Y1/YA 9333	127
Y1/YA 8586	177	Y1/YA 9108	245	Y1/YA 9344	276
Y1/YA 8588	113	Y1/YA 9109	67	Y1/YA 9361	112
Y1/YA 8599	223	Y1/YA 9118	55	Y1/YA 9389	111
		Y1/YA 9123	243		
		Y1/YA 9124	276		
		Y1/YA 9126	243	Y1/YA 9408	288
		Y1/YA 9127	35	Y1/YA 9409	288
Y1/YA 8637	55	Y1/YA 9128	35	Y1/YA 9430	117
Y1/YA 8665	95	Y1/YA 9129	35	Y1/YA 9446	231
Y1/YA 8667	143	Y1/YA 9130	36	Y1/YA 9465	286
Y1/YA 8674	58	Y1/YA 9131	36	Y1/YA 9466	50
		Y1/YA 9132	36	Y1/YA 9467	50
		Y1/YA 9133	243	Y1/YA 9494	112
		Y1/YA 9135	245		
		Y1/YA 9136	245		
Y1/YA 8727	243	Y1/YA 9144	187		
Y1/YA 8728	290	Y1/YA 9146	187		
Y1/YA 8739	217	Y1/YA 9147	187	Y1/YA 9500	143
Y1/YA 8782	229	Y1/YA 9163	165	Y1/YA 9558	115
Y1/YA 8791	126	Y1/YA 9166	51	Y1/YA 9559	115
		Y1/YA 9192	165	Y1/YA 9560	116
				Y1/YA 9561	116
				Y1/YA 9562	116
Y1/YA 8802	276			Y1/YA 9639	165
Y1/YA 8830	266	Y1/YA 9205	178	Y1/YA 9670	50
Y1/YA 8831	266	Y1/YA 9206	178	Y1/YA 9695	17
Y1/YA 8832	266	Y1/YA 9207	178		
Y1/YA 8833	265	Y1/YA 9214	84		
Y1/YA 8835	59	Y1/YA 9219	276		
Y1/YA 8839	174	Y1/YA 9222	248	Y1/YA 9764	187
Y1/YA 8840	174	Y1/YA 9223	248	Y1/YA 9770	83
Y1/YA 8841	174	Y1/YA 9226	98	Y1/YA 9781	289
Y1/YA 8846	118	Y1/YA 9229	112	Y1/YA 9792	130
Y1/YA 8847	113	Y1/YA 9230	112		
Y1/YA 8850	178	Y1/YA 9231	112		
Y1/YA 8851	177	Y1/YA 9232	113	Y1/YA 10002	112
Y1/YA 8855	55	Y1/YA 9237	134	Y1/YA 10207	51
Y1/YA 8858	276	Y1/YA 9238	134	Y1/YA 10249	166
Y1/YA 8859	277	Y1/YA 9252	47		
Y1/YA 8884	83	Y1/YA 9259	84		
Y1/YA 8886	83	Y1/YA 9260	84		
Y1/YA 8887	84	Y1/YA 9278	113		
		Y1/YA 9279	113		
		Y1/YA 9280	113		
		Y1/YA 9281	165	Y1/YA 10413	116
		Y1/YA 9282	165		
Y1/YA 8962	243	Y1/YA 9283	165		
		Y1/YA 9285	110		
				Y1/YA 10515	125
Y1/YA 9046	271			Y1/YA 10516	125
Y1/YA 9049	84	Y1/YA 9305	115	Y1/YA 10527	258
Y1/YA 9053	274	Y1/YA 9306	116	Y1/YA 10559	219
Y1/YA 9056	55	Y1/YA 9309	116		

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 10612	161	Y1/YA 11195	137	Y1/YA 11397	215
Y1/YA 10631	53			Y1/YA 11398	54
Y1/YA 10651	59			Y1/YA 11399	289
Y1/YA 10652	59				
Y1/YA 10692	112	Y1/YA 11247	52		
Y1/YA 10698	243	Y1/YA 11249	267		
		Y1/YA 11251	72	Y1/YA 11400	290
		Y1/YA 11252	72	Y1/YA 11433	104
Y1/YA 10703	276	Y1/YA 11253	72	Y1/YA 11434	104
Y1/YA 10705	81	Y1/YA 11257	265	Y1/YA 11439	208
Y1/YA 10711	297	Y1/YA 11259	275	Y1/YA 11448	131
Y1/YA 10712	297	Y1/YA 11260	265	Y1/YA 11449	220
Y1/YA 10713	297	Y1/YA 11280	113	Y1/YA 11450	224
Y1/YA 10714	297			Y1/YA 11451	222
Y1/YA 10715	297			Y1/YA 11461	280
Y1/YA 10716	297			Y1/YA 11462	280
Y1/YA 10762	53	Y1/YA 11303	127	Y1/YA 11465	50
Y1/YA 10763	52	Y1/YA 11304	251	Y1/YA 11466	266
Y1/YA 10764	53	Y1/YA 11305	136	Y1/YA 11472	115
Y1/YA 10765	53	Y1/YA 11306	163		
Y1/YA 10781	241	Y1/YA 11307	137		
		Y1/YA 11308	137		
		Y1/YA 11309	46	Y1/YA 11521	272
		Y1/YA 11311	139	Y1/YA 11545	145
		Y1/YA 11312	139		
Y1/YA 10831	72	Y1/YA 11314	144		
Y1/YA 10838	63	Y1/YA 11316	37		
Y1/YA 10839	56	Y1/YA 11317	37		
Y1/YA 10881	54	Y1/YA 11318	37	Y1/YA 11669	114
Y1/YA 10882	54	Y1/YA 11320	37	Y1/YA 11672	115
Y1/YA 10886	118	Y1/YA 11321	33	Y1/YA 11686	290
Y1/YA 10887	200	Y1/YA 11322	33		
		Y1/YA 11323	149		
		Y1/YA 11324	147		
		Y1/YA 11326	203		
		Y1/YA 11327	203	Y1/YA 11784	145
Y1/YA 10953	72	Y1/YA 11328	140		
Y1/YA 10969	108	Y1/YA 11329	135		
Y1/YA 10976	36	Y1/YA 11330	136		
Y1/YA 10977	36	Y1/YA 11331	135		
Y1/YA 10978	36	Y1/YA 11332	167	Y1/YA 11801	209
Y1/YA 10980	36	Y1/YA 11333	225	Y1/YA 11802	209
Y1/YA 10982	36	Y1/YA 11334	182	Y1/YA 11803	209
		Y1/YA 11336	148		
		Y1/YA 11338	125		
		Y1/YA 11341	36		
		Y1/YA 11352	113		
Y1/YA 11008	84	Y1/YA 11356	265	Y1/YA 11974	79
Y1/YA 11010	200	Y1/YA 11358	265	Y1/YA 11997	149
Y1/YA 11016	287	Y1/YA 11359	272	Y1/YA 11998	135
Y1/YA 11037	280	Y1/YA 11360	272		
Y1/YA 11048	224	Y1/YA 11364	199		
Y1/YA 11082	71	Y1/YA 11366	199		
Y1/YA 11083	72	Y1/YA 11368	144		
Y1/YA 11084	73	Y1/YA 11369	105	Y1/YA 12004	64
		Y1/YA 11370	277	Y1/YA 12009	147
		Y1/YA 11371	275	Y1/YA 12011	201
		Y1/YA 11372	243	Y1/YA 12012	202
		Y1/YA 11378	259	Y1/YA 12013	226
Y1/YA 11131	247	Y1/YA 11390	177	Y1/YA 12019	143
Y1/YA 11186	128	Y1/YA 11391	264	Y1/YA 12022	279
Y1/YA 11191	135	Y1/YA 11396	241	Y1/YA 12037	222

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/YA 12054	279	Y1/YA 12122	132	Y1/YA 12444	225
Y1/YA 12055	169	Y1/YA 12123	132		
Y1/YA 12056	145	Y1/YA 12124	146		
Y1/YA 12057	301	Y1/YA 12125	169		
Y1/YA 12060	147	Y1/YA 12126	162		
Y1/YA 12061	147	Y1/YA 12127	61	Y1/YA 12527	149
Y1/YA 12062	162	Y1/YA 12128	204	Y1/YA 12580	16
Y1/YA 12063	139	Y1/YA 12129	225	Y1/YA 12590	225
Y1/YA 12064	140	Y1/YA 12130	59	Y1/YA 12592	67
Y1/YA 12065	140	Y1/YA 12131	226		
Y1/YA 12066	151	Y1/YA 12132	225		
Y1/YA 12067	135	Y1/YA 12133	104		
Y1/YA 12068	135	Y1/YA 12134	105		
Y1/YA 12069	135	Y1/YA 12135	92	Y1/YA 12606	193
Y1/YA 12070	167	Y1/YA 12136	92	Y1/YA 12618	145
Y1/YA 12071	163	Y1/YA 12137	143		
Y1/YA 12072	163	Y1/YA 12141	221		
Y1/YA 12073	163	Y1/YA 12142	58		
Y1/YA 12074	163	Y1/YA 12145	221		
Y1/YA 12075	163	Y1/YA 12181	73	Y1/YA 12907	191
Y1/YA 12076	163	Y1/YA 12194	279	Y1/YA 12909	217
Y1/YA 12077	163	Y1/YA 12195	279		
Y1/YA 12078	137				
Y1/YA 12079	137				
Y1/YA 12080	206				
Y1/YA 12081	206			Y1/YB 00728	280
Y1/YA 12082	206	Y1/YA 12201	279		
Y1/YA 12083	137	Y1/YA 12205	287		
Y1/YA 12084	138	Y1/YA 12206	287		
Y1/YA 12085	209	Y1/YA 12207	97		
Y1/YA 12086	138	Y1/YA 12208	132	Y1/YB 00933	69
Y1/YA 12087	139	Y1/YA 12209	81		
Y1/YA 12088	139	Y1/YA 12212	266		
Y1/YA 12089	139	Y1/YA 12235	46		
Y1/YA 12090	139	Y1/YA 12236	46		
Y1/YA 12091	139	Y1/YA 12238	46	Y1/YB 01457	84
Y1/YA 12092	140	Y1/YA 12239	284		
Y1/YA 12093	140	Y1/YA 12260	149		
Y1/YA 12094	140	Y1/YA 12261	174		
Y1/YA 12096	225	Y1/YA 12262	112		
Y1/YA 12097	225	Y1/YA 12263	79	Y1/YB 02045	280
Y1/YA 12098	140	Y1/YA 12264	265		
Y1/YA 12099	141	Y1/YA 12265	265		
		Y1/YA 12266	265		
		Y1/YA 12267	54		
		Y1/YA 12268	54	Y1/YB 02249	280
Y1/YA 12100	141				
Y1/YA 12101	141				
Y1/YA 12102	83				
Y1/YA 12103	143	Y1/YA 12309	286	Y1/YB 03461	72
Y1/YA 12104	143	Y1/YA 12310	51		
Y1/YA 12105	146	Y1/YA 12361	147		
Y1/YA 12106	147	Y1/YA 12362	196		
Y1/YA 12107	162	Y1/YA 12363	196		
Y1/YA 12108	162	Y1/YA 12365	196	Y1/YB 04605	70
Y1/YA 12109	162	Y1/YA 12375	127		
Y1/YA 12110	162				
Y1/YA 12111	162				
Y1/YA 12112	162				
Y1/YA 12113	162				
Y1/YA 12114	37	Y1/YA 12429	127	Y1/YC 00646	54
Y1/YA 12115	37	Y1/YA 12430	128		
Y1/YA 12120	37	Y1/YA 12431	128	Y1/YC 00758	187

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/ZA 0820	205	Y1/ZA 5406/1	213	Y1/ZA 12841	223
		Y1/ZA 5406/2	235		
		Y1/ZA 5406/3	235		
		Y1/ZA 5406/4	100		
		Y1/ZA 5418	223		
Y1/ZA 1043	199	Y1/ZA 5418/1	213	Y1/ZA 13343	173
		Y1/ZA 5426	267		
		Y1/ZA 5427	209		
		Y1/ZA 5428	222		
		Y1/ZA 5428/2	213		
Y1/ZA 2049	273	Y1/ZA 5444	267	Y1/ZA 13587	175
		Y1/ZA 5470	222		
		Y1/ZA 5470/1	213		
Y1/ZA 2322	273			Y1/ZA 13859	223
Y1/ZA 2323	273				
		Y1/ZA 5792	233		
		Y1/ZA 5796	233		
Y1/ZA 2902	223			Y1/ZA 14289	207
				Y1/ZA 14293	228
		Y1/ZA 5807	209		
Y1/ZA 3193	195			Y1/ZA 14308	267
				Y1/ZA 14309	267
		Y1/ZA 10036	261	Y1/ZA 14311	238
		Y1/ZA 10041	207	Y1/ZA 14340	233
		Y1/ZA 10042	216		
Y1/ZA 4165	43	Y1/ZA 10043	80		
		Y1/ZA 10044	228		
		Y1/ZA 10045	267	Y1/ZA 15129	92
Y1/ZA 4353	175				
Y1/ZA 4355	175				
Y1/ZA 4389	179	Y1/ZA 10109	195		
Y1/ZA 4390	179	Y1/ZA 10192	261	Y1/ZA 15843	220
Y1/ZA 4393	175			Y1/ZA 15849	206
Y1/ZA 4394	175				
		Y1/ZA 11335	233		
		Y1/ZA 11382	208	Y1/ZA 16209	199
Y1/ZA 5139	237	Y1/ZA 11383	215		
				Y1/ZA 16938	179
Y1/ZA 5313	223	Y1/ZA 11411	179		
Y1/ZA 5369	225				
Y1/ZA 5371	222				
Y1/ZA 5371/3	213				
Y1/ZA 5371/4	235			Y1/ZA 17204	213
Y1/ZA 5371/6	236	Y1/ZA 12354	226	Y1/ZA 17205	213
Y1/ZA 5374	222	Y1/ZA 12598	37	Y1/ZA 17208	223
Y1/ZA 5375	267			Y1/ZA 17209	268
		Y1/ZA 12651	173		
Y1/ZA 5406	222	Y1/ZA 12672	226	Y1/ZA 17330	204

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/ZA 17537	213	Y1/ZA 21095	238	Y1/ZA 23878	132
Y1/ZA 17538	236	Y1/ZA 21096	275	Y1/ZA 23879	210
Y1/ZA 17539	236			Y1/ZA 23880	210
Y1/ZA 17541	273			Y1/ZA 23881	210
Y1/ZA 17545	204			Y1/ZA 23882	237
Y1/ZA 17546	206			Y1/ZA 23883	43
Y1/ZA 17547	206	Y1/ZA 21270	223	Y1/ZA 23884	44
Y1/ZA 17548	275				
Y1/ZA 17549	268				
Y1/ZA 17550	227				
Y1/ZA 17551	227				
Y1/ZA 17552	204	Y1/ZA 21514	220	Y1/ZA 24233	267
Y1/ZA 17553	301			Y1/ZA 24234	206
		Y1/ZA 21858	197		
Y1/ZA 17602	215			Y1/ZA 24329	267
Y1/ZA 17604	220				
Y1/ZA 17605	223				
Y1/ZA 17606	233				
Y1/ZA 17637	267	Y1/ZA 21917	268		
Y1/ZA 17678	230			Y1/ZA 24404	263
		Y1/ZA 22377	255		
Y1/ZA 18203	230	Y1/ZA 22378	255	Y1/ZA 24509	207
Y1/ZA 18204	230	Y1/ZA 22379	254	Y1/ZA 24510	210
Y1/ZA 18205	229	Y1/ZA 22380	254	Y1/ZA 24512	227
				Y1/ZA 24513	227
				Y1/ZA 24514	235
				Y1/ZA 24515	235
Y1/ZA 18577	228	Y1/ZA 22497	55	Y1/ZA 24516	235
Y1/ZA 18578	229			Y1/ZA 24517	236
Y1/ZA 18579	229			Y1/ZA 24518	235
Y1/ZA 18580	229			Y1/ZA 24519	236
Y1/ZA 18581	229			Y1/ZA 24594	149
Y1/ZA 18582	229	Y1/ZA 22693	231		
				Y1/ZA 24789	231
Y1/ZA 19010	55	Y1/ZA 22715	231	Y1/ZA 24791	223
Y1/ZA 19011	209	Y1/ZA 22721	238		
				Y1/ZA 24996	273
Y1/ZA 19692	238	Y1/ZA 22963	130		
Y1/ZA 19693	140	Y1/ZA 22966	139		
				Y1/ZA 25004	268
Y1/ZA 20050	90	Y1/ZA 23540	132		
Y1/ZA 20051	91	Y1/ZA 23546	227		
Y1/ZA 20052	236	Y1/ZA 23547	216	Y1/ZA 25219	229
Y1/ZA 20053	236			Y1/ZA 25220	233
				Y1/ZA 25221	220
				Y1/ZA 25223	205
				Y1/ZA 25229	43
		Y1/ZA 23877	255	Y1/ZA 25230	241



## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/ZA 25311	238	Y1/ZA 27661	221	Y1/ZA 29474	231
Y1/ZA 25312	249			Y1/ZA 29475	230
Y1/ZA 25313	227				
Y1/ZA 25314	205				
Y1/ZA 25367	45	Y1/ZA 27786	247		
Y1/ZA 25382	175	Y1/ZA 27788	206	Y1/ZA 29643	128
		Y1/ZA 27789	236	Y1/ZA 29673	230
		Y1/ZA 27790	236		
Y1/ZA 26270	130	Y1/ZA 27791	235		
		Y1/ZA 27792	236		
		Y1/ZA 27793	235		
Y1/ZA 26329	205	Y1/ZA 27794	216	Y1/ZA 29837	209
Y1/ZA 26376	263	Y1/ZA 27795	205	Y1/ZA 29857	138
				Y1/ZA 29858	138
		Y1/ZA 27859	263		
		Y1/ZA 27860	263	Y1/ZA 30004	273
		Y1/ZA 27861	264	Y1/ZA 30023	135
Y1/ZA 26425	261	Y1/ZA 27862	269		
Y1/ZA 26426	92	Y1/ZA 27863	225		
Y1/ZA 26438	169	Y1/ZA 27864	225		
Y1/ZA 26439	169			Y1/ZA 30398	149
				Y1/ZA 30399	149
		Y1/ZA 28231	233		
Y1/ZA 26519	220				
Y1/ZA 26582	132			Y1/ZA 30400	149
		Y1/ZA 28336	59		
Y1/ZA 26635	131			Y1/ZA 30506	141
Y1/ZA 26636	131			Y1/ZA 30507	141
Y1/ZA 26637	131			Y1/ZA 30585	139
Y1/ZA 26638	131	Y1/ZA 28658	231		
Y1/ZA 26639	131	Y1/ZA 28660	263		
Y1/ZA 26641	247	Y1/ZA 28661	257		
Y1/ZA 26642	129			Y1/ZA 30662	199
Y1/ZA 26643	131				
Y1/ZA 26694	268	Y1/ZA 28968	115		
Y1/ZA 26695	223			Y1/ZA 30758	129
Y1/ZA 26700	128				
Y1/ZA 26797	223	Y1/ZA 29026	113		
				Y1/ZA 31000	231
				Y1/ZA 31001	233
Y1/ZA 26806	264	Y1/ZA 29349	233	Y1/ZA 31002	263
		Y1/ZA 29351	205	Y1/ZA 31075	144
		Y1/ZA 29352	206		
		Y1/ZA 29353	206		
Y1/ZA 27360	230	Y1/ZA 29356	273		
				Y1/ZA 31264	261
				Y1/ZA 31265	262
				Y1/ZA 31266	259

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/ZA 31267	259	Y1/ZA 31873	173	Y1/ZA 34424	257
Y1/ZA 31268	268			Y1/ZA 34470	275
Y1/ZA 31287	225			Y1/ZA 34592	231
				Y1/ZA 34671	253
		Y1/ZA 31913	137		
Y1/ZA 31640	152	Y1/ZA 31960	151		
Y1/ZA 31641	151			Y1/ZA 35210	262
Y1/ZA 31643	148				
Y1/ZA 31644	139				
Y1/ZA 31645	137	Y1/ZA 32242	237		
Y1/ZA 31646	151	Y1/ZA 32243	237		
Y1/ZA 31647	151			Y1/ZA/BF 28831	141
Y1/ZA 31648	151				
Y1/ZA 31650	142				
Y1/ZA 31651	138			Y1/ZB 0109	127
Y1/ZA 31652	137	Y1/ZA 32580	231		
Y1/ZA 31653	146				
Y1/ZA 31654	148			Y1/ZB 0478	50
Y1/ZA 31655	148				
Y1/ZA 31656	148				
Y1/ZA 31657	139	Y1/ZA 32802	232		
Y1/ZA 31658	142	Y1/ZA 32829	150	Y1/ZB 0574	217
Y1/ZA 31660	148	Y1/ZA 32832	135	Y1/ZB 0575	217
Y1/ZA 31661	143	Y1/ZA 32833	147		
Y1/ZA 31662	142	Y1/ZA 32835	142		
Y1/ZA 31663	135				
Y1/ZA 31664	151				
Y1/ZA 31665	152				
Y1/ZA 31666	149				
Y1/ZA 31667	147	Y1/ZA 32986	223		
Y1/ZA 31668	148	Y1/ZA 32998	221		
Y1/ZA 31669	149				
Y1/ZA 31670	138			Y1/ZB 10189	293
Y1/ZA 31671	141				
Y1/ZA 31672	146				
Y1/ZA 31673	141	Y1/ZA 33313	253		
Y1/ZA 31674	141	Y1/ZA 33314	253		
Y1/ZA 31676	136	Y1/ZA 33338	252	Y1/ZB 10262	207
Y1/ZA 31677	138				
Y1/ZA 31678	140				
Y1/ZA 31679	151				
Y1/ZA 31680	146	Y1/ZA 33500	213	Y1/ZB 10706	217
Y1/ZA 31702	162				
Y1/ZA 31703	237	Y1/ZA 33858	264	Y1/ZB 10977	295
Y1/ZA 31704	223	Y1/ZA 33875	253		
Y1/ZA 31744	137				
Y1/ZA 31745	147				
Y1/ZA 31785	294				
Y1/ZA 31788	147			Y1/ZB 11017	127
Y1/ZA 31789	147	Y1/ZA 34167	221		
Y1/ZA 31794	136	Y1/ZA 34193	252		
Y1/ZA 31795	142	Y1/ZA 34195	254		
Y1/ZA 31796	142			Y1/ZB 11178	219
Y1/ZA 31872	179	Y1/ZA 34279	275		

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/ZB 11310	214	Y1/ZB M94 0004	223	Y1/5510-99-942-7774	49
Y1/ZB 11311	214	Y1/ZB M94 0005	126	Y1/5510-99-942-7775	49
Y1/ZB 11312	214	Y1/ZB M94 0006	153	Y1/5510-99-942-7776	49
Y1/ZB 11318	219	Y1/ZB M94 0008	45	Y1/5510-99-942-7777	49
		Y1/ZB M94 0009	45	Y1/5510-99-942-7781	49
		Y1/ZB M94 0016	209	Y1/5510-99-942-7935	48
		Y1/ZB M94 0017	214	Y1/5510-99-942-7936	48
		Y1/ZB M94 0018	214	Y1/5510-99-942-7937	48
Y1/ZB 11566	127	Y1/ZB M94 0020	228	Y1/5510-99-942-7938	48
		Y1/ZB M94 0021	228	Y1/5510-99-942-7939	48
				Y1/5510-99-942-7940	48
Y1/ZB 11681	127				
		Y1/ZC 15668	185	Y1/5805-99-100-1865	63
		Y1/ZC 15669	185	Y1/5805-99-901-2497	119
		Y1/ZC 15674	237	Y1/5805-99-901-3003	119
Y1/ZB 12617	218			Y1/5805-99-943-0570	96
				Y1/5805-99-949-2570	118
		Y1/3130-99-942-1744	13	Y1/5820-99-943-6987	126
Y1/ZB 12745	218			Y1/5835-99-901-0051	139
				Y1/5835-99-901-2090	146
				Y1/5835-99-901-2114	144
				Y1/5835-99-901-2115	145
		Y1/3895-99-901-1033	15	Y1/5835-99-901-2137	136
Y1/ZB 12834	218	Y1/3895-99-901-2162	15	Y1/5835-99-901-2138	150
Y1/ZB 12855	217	Y1/3895-99-901-3232	15	Y1/5835-99-901-2139	150
Y1/ZB 12871	218	Y1/3895-99-901-3901	15	Y1/5835-99-942-1756	146
				Y1/5835-99-942-1757	150
				Y1/5835-99-943-6981	151
				Y1/5835-99-943-8232	137
				Y1/5835-99-943-8235	145
		Y1/5120-99-901-1229	33	Y1/5835-99-943-9128	136
Y1/ZB 12914	126	Y1/5120-99-901-3232	33	Y1/5835-99-943-9129	136
Y1/ZB 12915	295				
Y1/ZB 12916	134				
Y1/ZB 12917	219				
Y1/ZB 12918	205				
Y1/ZB 12979	210	Y1/5307-99-901-2150	43	Y1/5920-99-901-2113	165
Y1/ZB 12980	228	Y1/5330-99-943-9359	45	Y1/5920-99-901-2535	164
Y1/ZB 12982	132	Y1/5330-99-943-9360	45	Y1/5930-99-012-0146	171
Y1/ZB 12983	294	Y1/5340-99-120-0363	46	Y1/5930-99-012-0180	171
		Y1/5340-99-901-2415	46	Y1/5930-99-901-0650	171
		Y1/5340-99-901-2416	46	Y1/5930-99-901-2488	167
		Y1/5340-99-943-8227	46	Y1/5930-99-901-3171	167
				Y1/5930-99-901-3172	167
Y1/ZB 13029	218			Y1/5930-99-911-4130	171
Y1/ZB 13037	217			Y1/5930-99-932-5790	171
				Y1/5930-99-932-5791	171
				Y1/5930-99-940-1848	171
		Y1/5510-99-942-7761	48	Y1/5930-99-940-1855	171
		Y1/5510-99-942-7762	48	Y1/5930-99-940-1861	171
		Y1/5510-99-942-7763	49	Y1/5930-99-940-1864	171
Y1/ZB 13185	218	Y1/5510-99-942-7764	49	Y1/5930-99-940-1867	171
		Y1/5510-99-942-7765	49	Y1/5930-99-940-1870	171
		Y1/5510-99-942-7766	49	Y1/5930-99-940-1872	171
		Y1/5510-99-942-7767	49	Y1/5930-99-940-1879	171
		Y1/5510-99-942-7768	49	Y1/5930-99-940-1887	168
Y1/ZB 13438	218	Y1/5510-99-942-7769	49	Y1/5930-99-940-1888	168
		Y1/5510-99-942-7770	49	Y1/5930-99-940-1892	168
		Y1/5510-99-942-7771	49	Y1/5930-99-940-1921	168
		Y1/5510-99-942-7772	49	Y1/5930-99-940-3564	171
		Y1/5510-99-942-7773	49	Y1/5930-99-940-9357	171

## Section Y1

## INDEX TO CATALOGUE NUMBERS - continued

Cat. No.	Page	Cat. No.	Page	Cat. No.	Page
Y1/5935-99-100-1955	179	Y1/5945-99-011-9144	195	Y1/5965-99-901-0725	232
Y1/5935-99-100-3995	185	Y1/5945-99-100-2793	199	Y1/5965-99-901-1184	226
Y1/5935-99-100-6741	181	Y1/5945-99-100-7359	194	Y1/5965-99-901-1502	213
Y1/5935-99-901-0161	183	Y1/5945-99-580-0469	192	Y1/5965-99-901-1503	211
Y1/5935-99-901-0198	181	Y1/5945-99-901-0256	199	Y1/5965-99-901-2007	212
Y1/5935-99-901-2491	185	Y1/5945-99-901-0260	195	Y1/5965-99-901-2048	210
Y1/5935-99-901-2534	173	Y1/5945-99-901-0264	194	Y1/5965-99-901-2219	218
Y1/5935-99-901-2960	181	Y1/5945-99-901-0388	194	Y1/5965-99-901-2324	212
Y1/5935-99-901-3057	184	Y1/5945-99-901-0389	192	Y1/5965-99-901-2503	208
Y1/5935-99-901-3058	185	Y1/5945-99-901-0449	194	Y1/5965-99-901-3112	210
Y1/5935-99-901-3059	185	Y1/5945-99-901-0450	194	Y1/5965-99-901-3290	211
Y1/5935-99-901-3060	185	Y1/5945-99-901-0542	192		
Y1/5935-99-901-3061	184	Y1/5945-99-901-0610	195	Y1/5965-99-940-0046	212
Y1/5935-99-901-3062	185	Y1/5945-99-901-0628	195	Y1/5965-99-940-1178	205
Y1/5935-99-901-3122	185	Y1/5945-99-901-0629	192	Y1/5965-99-940-1179	207
Y1/5935-99-911-4121	185	Y1/5945-99-901-0889	195	Y1/5965-99-940-1180	207
Y1/5935-99-914-5028	185			Y1/5965-99-940-1181	211
Y1/5935-99-914-7189	185			Y1/5965-99-940-1182	216
Y1/5935-99-932-6349	179			Y1/5965-99-940-1183	227
		Y1/5945-99-901-2005	191	Y1/5965-99-940-1185	234
Y1/5935-99-940-1756	181	Y1/5945-99-901-2322	193	Y1/5965-99-940-1185	213
Y1/5935-99-940-1758	183	Y1/5945-99-901-2487	193	Y1/5965-99-943-9279	217
Y1/5935-99-940-1759	183	Y1/5945-99-901-3221	195	Y1/5965-99-943-9280	217
Y1/5935-99-940-1760	183	Y1/5945-99-901-3224	193	Y1/5965-99-972-9307	217
Y1/5935-99-940-1761	183	Y1/5945-99-901-3225	193		
Y1/5935-99-940-1764	183	Y1/5945-99-901-3226	193		
Y1/5935-99-940-1765	183	Y1/5945-99-901-3227	194		
Y1/5935-99-940-1766	181	Y1/5945-99-901-3288	193	Y1/5970-99-900-0192	241
Y1/5935-99-940-1769	181	Y1/5945-99-901-3289	194	Y1/5970-99-972-6026	241
Y1/5935-99-940-1771	179	Y1/5945-99-901-3356	193	Y1/5970-99-972-9127	241
Y1/5935-99-940-1772	179	Y1/5945-99-901-3357	192		
Y1/5935-99-940-1777	178	Y1/5945-99-901-3358	192	Y1/5975-99-940-1515	249
Y1/5935-99-940-1779	178	Y1/5945-99-901-3359	192	Y1/5975-99-940-1516	249
Y1/5935-99-940-1780	178	Y1/5945-99-901-3417	193	Y1/5975-99-940-1517	249
Y1/5935-99-940-1781	179	Y1/5945-99-901-3418	193	Y1/5975-99-940-1518	249
Y1/5935-99-940-1782	179	Y1/5945-99-901-3421	199	Y1/5975-99-940-1519	249
Y1/5935-99-940-1783	179	Y1/5945-99-901-3615	192	Y1/5975-99-940-1520	249
Y1/5935-99-940-1785	178			Y1/5975-99-940-1521	249
Y1/5935-99-940-1832	181			Y1/5975-99-940-1522	250
Y1/5935-99-943-6969	179	Y1/5945-99-901-3720	191	Y1/5975-99-940-1523	250
Y1/5935-99-972-8553	179	Y1/5945-99-911-4074	195	Y1/5975-99-940-1524	250
Y1/5935-99-972-9652	179	Y1/5945-99-932-0971	196	Y1/5975-99-940-1525	250
Y1/5935-99-972-9795	185	Y1/5945-99-932-1732	195	Y1/5975-99-940-2504	274
		Y1/5945-99-933-0516	193	Y1/5975-99-940-2517	249
Y1/5940-99-900-3936	189	Y1/5945-99-940-1965	195	Y1/5975-99-943-9501	249
Y1/5940-99-901-2014	189	Y1/5945-99-943-8811	195	Y1/5975-99-943-9502	249
Y1/5940-99-901-2959	189	Y1/5945-99-943-9131	193	Y1/5975-99-943-9506	247
Y1/5940-99-901-2983	189	Y1/5945-99-999-4741	191		
Y1/5940-99-901-3144	189			Y1/5995-99-901-3672	274
Y1/5940-99-901-3145	189	Y1/5950-99-100-1810	201	Y1/5995-99-901-3673	274
Y1/5940-99-901-3147	189			Y1/5995-99-940-1186	257
Y1/5940-99-901-3148	189				
Y1/5940-99-901-3149	190			Y1/6210-99-901-0729	279
Y1/5940-99-943-3565	190			Y1/6210-99-901-0732	279
Y1/5940-99-943-8586	186	Y1/5965-99-901-0201	205	Y1/6210-99-901-1249	279
Y1/5940-99-943-8587	186	Y1/5965-99-901-0202	226	Y1/6210-99-901-3210	279
		Y1/5965-99-901-0204	226	Y1/6210-99-901-3214	279
				Y1/6210-99-901-3450	279
				Y1/6210-99-943-5654	279